

DOCUPRINT N2825 NETWORK LASER PRINTER

If you're looking for unparalleled paper-handling flexibility, fastest-in-class print speed, and stellar image quality, take a look at the DocuPrint N2825 network laser printer from Xerox.

The N2825 can meet virtually all your printing needs. It handles a wide range of paper sizes, from postcard to 11 x 17 in., and runs labels, card stocks, and envelopes effortlessly. And, thanks to a high-performance controller, you'll enjoy significant speed and resolution advantages over other printers. Count on a quick 28 pages per minute, with a crisp 1200 dpi Image Quality at rated speed.

With the N2825, you get more printer for less. Fully network ready with 10/100Base-TX Ethernet, 32 MB of printer memory, true Adobe PostScript 3, PCL6 emulation, and a long list of Workset convenience features, all standard, at a very competitive price. Customize it to suit your workgroup's exact needs with extra input and output trays, and automatic duplexing.



The DocuPrint N2825 is part of the DocuPrint N Series family of network laser printers. For more information on our DocuPrint N Series printers, see your Xerox reseller or visit www.xerox.com/officeprinting

performance advantage

True 1200 x 1200 dpi delivers razor-sharp text and photo-quality images.

Print speed of 28 pages per minute. Fast "first-print-out" time of 10 seconds ensures that even pages with graphics, photos or charts are printed at a quick pace.

Plenty of memory is built-in for handling complex jobs and multiple set applications. Features like *Send Once*, *RIP Once*, *Print Many*, and job pipelining, minimize network traffic and streamline your work-flow. And for very large jobs, standard Automatic Tray Switching and Load While Run features enable nonstop printing.

Advanced graphics features like Edge-to-Edge Printing, Booklet Printing, and the ability to print up to 11 x 17 in. page size, let you produce professional-looking newsletters and brochures.



DocuPrint N2825 is shown with standard 500 sheet tray, a 500 sheet ledger-size feeder, a 2,000 sheet letter-size feeder, and 500 sheet offset catch tray.

overall printer value

The N2825 comes network ready out of the box, with 10/100Base-TX Ethernet, USB, true Adobe PostScript 3 and PCL6 emulations, with support for all popular client environments.

The hard disk (standard on the DX configuration) can store fonts, forms and macros, enables *Secure* and *Proof Print* features, and guarantees uninterrupted printing and collation of large multi-set jobs.

The N2825's built-in reliability is backed with a standard on-site warranty and the unmatched Xerox Total Satisfaction Guarantee.



productivity features

The N2825 is packed with over 20 WorkSet convenience and productivity features including *MailInX Remote Printing*, *Secure Print*, *Proof Print*, *Booklet Printing*, *Edge-to-Edge Printing*, *Automatic Separator Sheets*, and *Fax Friendly Black*.

Xerox pioneered the Embedded Web Server, which offers you more ways to manage printers on your network using your favorite web browser. *MailInX* e-mail alerts can be automatically sent to system administrators who can correct problems before they impact productivity. *PrinterMap* enables proactive management, usage tracking and automatic reporting of all SNMP-based printers regardless of vendor.

flexible paper handling

The N2825 boasts excellent reliability on all media types, handling paper weights from from 17 lb bond to 110 lb cardstock (64 to 200 gsm). To improve printing quality on different stocks, the N2825 enables variable fusing temperatures.

Multiple input and output options give you maximum printing flexibility:

The N2825 comes standard with a 150 sheet multipurpose bypass feeder, a 500 sheet input tray, and a 500 sheet output tray. Add one or two 500 sheet paper feeders (in letter or ledger sizes). Broaden your input and output capabilities with a 2,000 sheet feeder, and 500 sheet offset catch tray.

For exceptionally fast two-sided printing, add an automatic duplex module (standard on DT and DX configurations).

XEROX
NETWORK PRINTERS

DocuPrint N2825 NETWORK LASER PRINTER SPECIFICATIONS



N2825N



N2825DT








N2825DX

CONFIGURATIONS

Print speed	28 pages per minute (ppm) simplex, 23 images per minute (ipm) duplex		
First page out	10 seconds		
Processor/PDL	PowerPC 200 MHz RISC processor, Adobe PostScript 3, PCL6 and PCL5e emulations		
Memory Standard / Maximum	32 MB / 192 MB RAM	32 MB / 192 MB RAM	64 MB / 192 MB RAM
Print resolution	True 1200 x 1200 dpi, 1200 dpi Image Quality, 600 dpi, Xerox Image Enhancement, Xerox Quad Dot Technology		
Standard network/connectivity	10/100Base-TX Ethernet, Bi-directional parallel, USB, (Token Ring, Serial, 10Base2 optional)		
Automatic 2-sided printing	Optional	Standard	Standard
Paper input capability	500 sheet tray 150 sheet bypass feeder	500 sheet tray 150 sheet bypass feeder additional 500 sheet feeder (ledger)	500 sheet tray 150 sheet bypass feeder 2 additional 500 sheet feeders (ledger)
Paper output capability	500 sheet face down	500 sheet face down	500 sheet face down
Monthly duty cycle	Up to 130,000 pages/month		
Additional features			Internal hard disk
Warranty	One year on-site warranty, Xerox Total Satisfaction Guarantee		

SPECIFICATIONS

 <p>Network/Software</p> <p>Printer management CentreWare Printer Management for Microsoft NT, Microsoft Management Console, Novell, UNIX, Tivoli NetView, CA Unicenter TNG, and HP OpenView, Xerox PrinterMap, Certifications: Adobe, SolarisReady, PrintXchange, Microsoft. SAP R/3, Tivoli, Unicenter, SNMP-standard MIBs and Xerox extended MIBs</p> <p>Font capabilities 35 Resident Adobe Type 1 fonts, 101 Downloadable Adobe soft fonts, 10 Microsoft TrueType fonts, 35 Intellifonts, 1 PCL Bitmap font</p> <p>Printer drivers Windows 3.1, 95/98, NT 4.0, 2000, NetWare 3.x, 4.x, 5.x, OS/2 and OS/2 WARP, UNIX (Sun Solaris, HP-UX, IBM AIX, SGI, DEC, SCO RedHat Linux), Mac System 7.0, OS 8.0+</p> <p>Languages Genuine Adobe® PostScript® 3™, PCL5e and PCL6 emulations with automatic sensing and switching.</p>
 <p>Paper handling</p> <p>Paper input</p> <p><i>Standard</i> 500-sheet tray: 17 lb bond to 110 lb cardstock (64-200gsm), letter, statement, executive, custom sizes, or 75 envelopes (monarch, com-10, C5/DL, custom sizes)</p> <p><i>Standard</i> 150-sheet multipurpose bypass feeder: 17 lb bond to 110 lb cardstock (64-200gsm), statement to ledger, custom sizes, up to 10 envelopes (monarch, com-10, C5/DL)</p> <p>Duplex Module (standard on DT and DX): 17 to 28 lb bond (64-105gsm), statement to ledger</p> <p>500 sheet feeder (one or two may be added with choice of Letter tray or Ledger tray)</p> <p>2,000 sheet feeder: Letter size (can be used with one 500 sheet feeder)</p> <p>Paper output</p> <p><i>Standard</i> 500 sheets face down</p> <p><i>Optional</i> Offset catch tray – 500 sheets face down with job and copy offset</p>

 <p>WorkSet special features</p> <p>Convenience features: MailiNX – emails jobs to printer and sends alerts and status via email, Edge-to-Edge Printing, Proof Print®, Secure Print®, Draft Mode/Toner Saver, Separator Sheets, Cover Sheets, Auto Tray Select, N-Up Printing, Non-Standard Paper Sizes, Print Anyway, Smart Ja Diagnostics, Load While Run, Booklet Printing, Fax Friendly Black, Variable Fuser Temperature (*needs hard disk)</p> <p>Print productivity features: <i>Send Once, RIP Once, and Print Many</i> capability (RAM or hard disk), Job Pipelining to process multiple jobs concurrently</p> <p>Productivity tools for the IT manager: Web-based Printer Administration via Embedded Web Server, <i>MailiNX</i> e-mail alerts, PrinterMap, IPP support</p>
 <p>Operating</p> <p>Dimensions width: 19.3in/490mm, height: 15.6in/395mm, depth: 18.1in/460mm, weight: 60lb/27kg</p> <p>Environmental Temperature: 5° to 35°C / 41° to 95°F, Relative Humidity: 15% to 85% (noncondensing), Noise Level: 35 dB(A) standby, 50 dB(A) running (ISO 7779, DIN EN 27779)</p> <p>Electrical Sleep mode, Energy Star Compliant, two models: 110-127 VAC, 50/60 Hz; 220-240 VAC 50/60 Hz</p> <p>Regulatory FCC Part 15 Subpart B, UL listed to UL 1950, UL Certified to CSA—C22.2 No. 950-M93, FDA 21 CFR Sub J, CE Mark applicable to directives 73/23/EEC and 89/336/EEC, TUV - GS Mark, IEC 950 Second Edition (EN 60950, EN 60825)</p>
 <p>Customer support</p> <p>1-year On-site Warranty, online web technical support and telephone support. The DocuPrint N2825 printer is backed by the Xerox Total Satisfaction Guarantee.</p>

SUPPLIES

Consumables	
Toner Cartridge (17K yield at 5% coverage)	113R00443
Maintenance Kit 110V (200K yield)	109R00481
Feed Roller Kit For 2000 sheet feeder (200K life)	108R00335
Options	
500 sheet Feeder (Legal/Ledger) (Letter)	097S02371 097S02372
2,000 sheet Feeder (Letter)	097S02374
Duplex Module	097S02373
500 sheet Offset Catch Tray	097S02375
500 sheet Replacement Tray (Legal/Ledger) (Letter)	109R00484 109R00485
Token Ring Interface Card	097S02363
Ethernet 10Base2 Interface Card	097S02362
RS232-C Serial Interface Card	097S02361
Internal Hard Disk	097S02364
16-MB DIMM	097S02356
32-MB DIMM	097S02357
64-MB DIMM	097S02358
8-MB Flash DIMM	097S02360
SAP Bar Code Flash DIMM Kit	097S04409
SAP Bar Code Media Kit	097S04410
For media offerings, see our web site: www.xerox.com	

For the location of your nearest Xerox reseller, or for more information, visit our Web site or call: United States and Canada 1-877-362-6567 Europe (UK) +44 870 241 0921, other regions see your local Xerox or Fuji/Xerox representative.



www.xerox.com/officeprinting

XEROX®, The Document Company®, CentreWare®, DocuPrint®, PrinterMap®, WorkSet®, and N2825 are trademarks of XEROX CORPORATION. Solaris™ Ready, the Solaris™ Ready logo, SunOS™, and Solaris™ are trademarks of Sun Microsystems Inc. in the US and other countries. As an ENERGY STAR® Partner, Xerox has determined that this product meets the ENERGY STAR® guidelines for energy efficiency. Other product and/or company names used herein are trademarks of their respective owners. Product appearance and/or specifications subject to change without notice. 3/01 BT 282D5-01UB

THE DOCUMENT COMPANY
XEROX