

Xerox® Phaser® 3250

A4 Black and White Printer

Compact, business-ready productivity

This powerful little printer is ready to support a single user or a small work group with fast, automatic two-sided printing, office-friendly convenience and outstanding overall value.



More performance for less

- Get work done fast, with a print speed of up to 28 ppm and a first-page-out time less than 8.5 seconds.
- Automatic two-sided printing saves valuable time and paper.
- A network configuration – with both Windows, Mac and Linux compatibility – is truly business-ready.
- The 400 MHz processor ensures all jobs print quickly and accurately, even when they're loaded with graphics.

Convenience, flexibility


- A surprisingly small footprint makes it easy to position within quick reach.
- Standard 32 MB memory can expand to 160 MB for enhanced performance when your workload demands it.
- Add a second 250-sheet paper tray for a total capacity of 500 sheets.
- Print on custom sizes and a wide range of media, from transparencies and card stock, to envelopes and postcards.
- Power Save and Toner Save modes help you spend less on electricity and consumables.

Always impressive results

- 600 x 600 dpi print resolution (up to 1200 x 1200 enhanced image quality) adds visual impact to important jobs.
- Adobe® PostScript® 3™ compatibility and PCL® 6 emulation ensure your print jobs are always accurate.
- A 30,000-page monthly duty cycle handles big print volumes with ease.
- Outstanding Xerox quality, reliability and performance are backed by Xerox Service and Support with a standard one-year on-site warranty with optional service extensions.



364 x 370 x 239 mm



Xerox® Phaser® 3250

Black and white printer



Phaser® 3250DN	
Speed	Up to 28 ppm
Duty Cycle	Up to 30,000 pages / month
Paper Handling	Bypass Tray: 1 sheet; Custom sizes: 76 x 127 mm to 216 x 356 mm
	Tray 1: 250 sheets; Sizes: A6 – A4
Paper input	Standard
	Optional
	Tray 2: 250 sheets; Sizes: A6 – A4
Paper output	150 sheets
Automatic two-sided output	Standard
Print	
First-page-out-time	As fast as 8.5 seconds
Resolution	600 x 600 dpi (up to 1200 x 1200 enhanced image quality)
Processor	400 MHz
Memory (std/max)	32 MB / 160 MB
Connectivity	10/100Base-TX Ethernet, USB 2.0
Language support	PostScript® 3™ compatibility, PCL® 6 and 5e emulations, IBM ProPrinter emulation, Epson emulation, GDI
Print features	Watermarks, Poster printing, N-up, Fit to page, Scaling, Overlays, Booklets, Reduce/enlarge, Toner saver, Custom-size pages
Warranty	One-year on-site warranty. Plus optional service extensions available.

Device Management

Printer Setting Utility for Windows, CentreWare® Internet Services, SNMP 1-2, EtherTalk, HTTP, TCP/IP

Print Drivers

Windows® 2000/XP/7/Server 2003/2008/Vista, Mac OS®X version 10.3-10.5, Various Linux® OS including SUSE™ 8.2-9.2, Red Hat® 8-9, Fedora™ Core 1-4, Mandrake 9.2-10.1

Font Support

1 bitmap, 45 scaleable, 136 PostScript® fonts

Media Handling

Multipurpose Tray: 60 – 163 gsm
Media types: Plain paper, envelopes, transparencies, labels, card stock
Tray 1 and Tray 2 (optional): 60 – 105 gsm
Media types: Plain paper
Two sided printing: 75 – 90 gsm

Operating Environment

Temperature: Storage: 0° to 35° C
Operating: 10° to 32° C
Humidity: 20 % to 80 %
Sound pressure levels:
Printing: 54 dB(A)
Standby: 29 dB(A)
Warm-up time (from sleep mode): Less than 15 seconds

Electrical

Power: 220–240 VAC, 50/60 Hz
Power consumption: Standby: 70 W
Printing: 400 W
Power save: 11 W

Dimensions (WxDxH)

364 x 370 x 239 mm
Weight: 11.9 kg
Optional 250-sheet Tray 2: 364 x 400 x 86 mm
Weight: 3.67 kg
Package Dimensions (WxDxH): 562 x 472 x 344 mm

Certifications

Listed UL 60950/CSA C22.2 No. 60950, CE Mark applicable to Directives 2006/95/EC and 2004/108/EC

What Comes In The Box

- Phaser 3250 Printer
- Print Cartridge (2,000 print capacity¹)
- Software and Documentation CD (with User Manual, Quick Installation Guide, Warranty Statement, Registration Card)
- Power cord
- USB cable



Phaser 3250 shown with optional Tray 2

Supplies

Standard-Capacity Print Cartridge ¹ :	
3,500 std. pages	106R01373
High-Capacity Print Cartridge ¹ :	
5,000 std. pages	106R01374

¹ Average standard pages. Declared Yield in accordance with ISO/IEC 19752. Yield will vary based on image, area coverage and print mode.

Options

250-sheet Tray	098N02194
128 MB Phaser Memory	098N02195

Supplies Recycling Programme

Consumables for the Phaser 3250 are part of the Xerox Green World Alliance Supplies Recycling Programme. For more information, please visit the Green World Alliance website at www.xerox.com/gwa



For more information, visit us at www.xerox.com/office.

