

**XEROX**®

Technology | Document Management | Consulting Services

black-and-white laser printer

# The compact printer that makes a big impression



**Call today.** For more information, call **1-877-362-6567** or visit us at **www.xerox.com/office**



		Phaser 5335
<b>Speed</b>		Up to 35 ppm
<b>Duty Cycle</b>		100,000 pages / month
<b>Paper Handling</b>		
Paper input	Standard	<b>Tray 1 (MPT):</b> 150 sheets; Custom sizes: 3 x 5.8 in. to 11.7 x 17 in. / 75 x 148 mm to 297 x 431 mm
		<b>Tray 2:</b> 550 sheets; Custom sizes: 3 x 5.8 in. to 11.7 x 17 in. / 75 x 148 mm to 297 x 431.8 mm
	Optional	<b>Tray 3 – 5:</b> 550 sheets; Custom sizes: 3 x 5.8 in. to 11.7 x 17 in. / 75 x 148 mm to 297 x 431.8 mm (up to three can be added)
Paper output		250 sheets
Two-sided output		Optional
<b>Print</b>		
First-page-out time		As fast as 9.5 seconds
Resolution (max)		1200 x 1200 dpi
Processor		400 MHz
Memory (std / max)		64 MB / 576 MB
Connectivity		10/100Base-TX Ethernet, Parallel, USB 2.0
Page Description Languages		Adobe® PostScript® 3™, PCL® 5e emulation, PCL 6 emulation, ESC / P
Print features	Standard	Custom-size pages, Banner-size (11.7 x 35.4 in. / 297 x 900 mm), Booklet printing, Poster printing, Edge-to-edge printing, Scaling, Watermarks, Covers, Separators, N-up, Load-while-run, Job accounting
	Optional	Hard Drive Kit (minimum 40 GB): Secure/Proof Print, Hard disk collation, Extended font storage, limited PDF-direct printing
<b>Warranty</b>		One-year on-site warranty, Xerox Total Satisfaction Guarantee

**Device Management**

CentreWare® IS Embedded Web Server

**Print Drivers**

Windows® 2000/XP/2003 Server, NT 4.0, Vista, Mac OS® X version 10.3.9 or higher, Red Hat® Enterprise Linux WS version 4, Turbolinux 10F, SUSE Linux 9.3 Professional, SUSE Linux 10.1

**Font Capability**

PostScript® fonts: 136; PCL® fonts: 81

**Media Handling**

Trays 1–5: 60–216 gsm  
Two-sided output: 60–190 gsm  
Media types: Plain paper, envelopes, labels, transparencies, card stock

**Operating Environment**

Temperature: 41° to 90°F / 5° to 32°C  
Humidity: 15% to 85%  
Sound power: Printing: 7.1 B, Standby: 5.3 B  
Warm-up time (from power save): 16 seconds or less, FPOT from power save: as fast as 10 seconds

**Electrical**

Power: 220–240 VAC, 50/60 Hz  
Power consumption: Printing: 470 W or less, Standby: 105 W, Power save: 5 W

**Dimensions (WxDxH)**

18.1 x 19.9 x 14.8 in. / 459 x 506 x 375.3 mm  
Weight w/ consumables: 52.2 lb. / 23.5 kg  
Weight w/o consumables: 47.3 lb. / 21.3 kg

**Certifications**

FDA/CDRH – Class 1 Laser Product, CE marked, Low Voltage Directive 73/23/EEC, EN 60950-1, 1st Edition, EN 60825-1 – Class 1 Laser Product, EMC Directive 89/336/EEC, EN 55022, Class B, EN 55024, RoHS Directive 2002/95/EC, WEEE Directive 2002/96/EC

**Supplies**

Print Cartridge: 10,000 pages<sup>1</sup> 113R00737

**Routine Maintenance Items**

Maintenance Kit, 220V: 100,000 pages<sup>2</sup> 108R00772

**Options**

Hard Drive Kit 098S05006  
Duplex Module 097S03871  
550-Sheet Feeder 097S03870  
256 MB Phaser Memory 098S05021  
512 MB Phaser Memory 098S05022  
Multi-Protocol Network Card 098S05007  
Wireless LAN 220 V 097S03741



<sup>1</sup>Average standard pages. Declared Yield in accordance with ISO/IEC 19752. Yield will vary based on image, area coverage and print mode.

<sup>2</sup>Approximate pages. Declared Yield based on letter-/A4-size 20 lb. (75 gsm) pages. Yield will vary based on media type, size, weight, orientation, and usage patterns.

