

Xerox<sup>®</sup> Phaser<sup>®</sup> 6360 Color Laser Printer Office color performance redefined



# Phaser® 6360 Color Laser Printer

**Setting the standard** for high-performance color laser printers, the Xerox Phaser 6360 leads the industry with best-in-class print speed and exceptional color performance. Easy to operate and engineered to meet the exacting demands of high-volume office environments, the Phaser 6360 laser printer isn't just an obvious choice — it's the only choice.

# Unrivaled performance

In the race for print speed supremacy, the Phaser 6360 printer sets the pace.

- Get unparalleled, professional-quality color at a blazing print speed of up to 42 ppm — so fast, jobs you used to outsource can be printed in-house.
- Stay efficient in a busy environment with a first-page-out time as fast as 9 seconds.
- Print resolution of 2400 dpi and Adobe®
   PostScript® 3™ page description language
   combine to give your work vibrant, true-to-life
   colors and crisp text and image definition.
- As the industry's only letter-size color printer with α built-in 1 GHz processor, the Phaser 6360 has the muscle to handle even the most complex print jobs.
- The Phaser 6360DN, DT and DX configurations feature standard onboard duplexing for fast, automatic, two-sided printing.

# **Printing simplified**

With ultra-fast setup and seamless operation, the Phaser 6360 printer delivers unbeatable ease-of-use.

- User-friendly installation software gets the Phaser 6360 out of the box and running smoothly on your network in minutes.
- PhaserSMART® online troubleshooting saves you time by providing 24/7 access to the Xerox Knowledge Base system.
- Check print job status from the comfort of your chair with Xerox CentreWare® IS Embedded Web Server which works seamlessly with your browser.
- The built-in PrintingScout® function tracks print jobs and provides immediate print-issue alerts and timely correction suggestions.
- Smart Trays alleviate guesswork by showing all available media types and sizes at print time.
- Convenient email alerts notify network administrators of common hang-ups, such as low toner levels, to help maintain an uninterrupted workflow.

# **Built for sharing**

High-capacity paper volumes, powerful performance features and seamless network integration make the Phaser 6360 the ultimate multiuser printing solution.

- A maximum paper input of 2,350 pages and high-capacity toner cartridges keep the Phaser 6360 poised to handle a steady stream of print jobs.
- **Up to 5 paper trays** allow the Phaser 6360 to easily adapt to the size of your office.
- 100,000-page-per-month duty cycle provides reliable operation for high-demand office environments.
- A variety of printing possibilities from booklet to banner to a full range of custom sizes lets your creativity run wild.
- Administrators can easily collect, organize and analyze print job accounting data from multiple printers via the Usage Analysis Tool.



Spectacular results. Bring everyday office print jobs to life with attention-grabbing color quality.

## Phaser® 6360 Quick Facts

- Print up to 42 ppm color and black-and-white
- 2400 x 600 dpi
- 1 GHz processor
- 100,000 pages/month duty cycle
- 256 MB memory, expandable to 1 GB



WxDxH: 6360N/DN 17.2 x 22.8 x 20.2 in. 429 x 580 x 513 mm





Real-time paper and supply-level status lets you take action before the printer runs out.



Fast, automatic two-sided printing is standard on all configurations except 6360N.



150-sheet multipurpose tray (standard) supports a wide range of media, from executive to banner, card stock to envelopes.



550-sheet tray (standard) allows you to add a full ream of paper.



An optional 550-sheet paper feeder provides added convenience and no-hassle media loading.



Add the 1,100-sheet, high-capacity feeder and turn the Phaser 6360 into a convenient floor-standing printer with a total paper capacity of 2,350 sheets.









# Phaser® 6360 Printer Configurations

## Phaser 6360N

- 2-Tray, 700-sheet capacity
- 10/100Base-TX Ethernet and USB connectivity
- 256 MB memory (expandable to 1 GB)

## Phaser 6360DN

## 6360N model plus:

• Automatic two-sided output

## Phaser 6360DT

## 6360DN model plus:

- Additional 550-sheet feeder for 1,250-sheet capacity
- 512 MB memory (expandable to 1 GB)

## Phaser 6360DX

## 6360DN model plus:

- Additional 1,100-sheet feeder for 1,800-sheet capacity
- 512 MB memory (expandable to 1 GB)
- Productivity Kit (includes 40 GB Hard Drive)

## **Options**

- Productivity Kit (includes 40 GB Hard Drive)
- 550 and 1,100-sheet feeders
- Additional memory

3

4

# Phaser® 6360

# Color Laser Printer









|                                     |          | Phaser 6360N  | Phaser 6360DN | Phaser 6360DT | Phaser 6360DX   |
|-------------------------------------|----------|---|---------------|---------------|---|
| Speed                               |          | Up to 42 ppm color / 42 ppm black-and-white   |               |               |   |
| Duty Cycle                          |          | 100,000 pages / month*  |               |               |   |
| Paper Handling Paper input Standard |          | <b>Tray 1 (MPT):</b> 150 sheets; Selectable sizes: 3.5 x 5.5 in. to 8.5 x 36 in. / 89 x 140 mm to 216 x 914 mm                              |               |               |   |
|                                     |          | Tray 2: 550 sheets; Selectable sizes: Up to Legal / A4  |               |               |   |
|                                     | Optional |   |               | Standard      | Optional  |
|                                     |          | Additional 1100-sheet Feeder  |               |               | Standard  |
| Paper output                        | Standard | 250 sheets  |               |               |   |
| Automatic two-sided printing        |          | Optional  | Standard      |               |   |
| <b>Print</b> First-page-out-time    |          | As fast as 9 seconds color  |               |               |   |
| Resolution (max)                    |          | 2400 x 600 dpi  |               |               |   |
| Processor                           |          | 1 GHz   |               |               |   |
| Memory (std / max)                  |          | 256 MB / 1 GB   |               | 512 MB / 1 GB |   |
| Connectivity                        |          | 10/100Base-TX Ethernet, USB 2.0, IPv6**   |               |               |   |
| Page description languages          |          | Adobe® PostScript® 3™, PCL® 5c emulation  |               |               |   |
| Print features                      |          | Booklet printing, Mirror image, Scaling, Watermarks, Custom-size pages, Run Black, Covers, Separators, RAM collation, Remote Printing, N-up |               |               |   |
| Productivity kit                    |          |   | Optional      |               | Hard drive: Secure/Proof/Personal/<br>Shared Saved/Personal Saved Print,<br>Print With, Hard disk collation,<br>PDF-direct print, Extended<br>font/form storage |
| Security                            |          | 802.1x, IPsec, SMNP v3, Secure Print and Hard Drive Overwrite (requires Productivity Kit)   |               |               | it)   |
| Warranty                            |          | One-year on-site warranty, Xerox Total Satisfaction Guarantee   |               |               |   |

## Device Management

CentreWare<sup>®</sup> IS Embedded Web Server, CentreWare Web, Xerox NDPS Gateway, Xerox Usage Analysis Tool, Xerox Support Centre, Configuration card, PrintingScout™, MaiLinX email alerts, PhaserSMART®

## Print Drivers

Windows® XP/2003 Server, Vista™, Mac OS® version 10.3 and above, Novell NetWare® 5.x/6.5 (NPDS only), Linux Red Hat®, Fedora™ Core 5, Suse™ Linux 10.0, UNIX: Sun Solaris™ 9/10, IBM AIX® 5.1, HP/UX® 11.0/11i, Xerox Walk-Up® Printer Drivers with Windows

# Font Capability

PostScript® Fonts: 139; PCL® Fonts: 81

# Media Handling

Tray 1 (MPT): 17-40 lb. bond to 50-80 lb. cover / 65-216 gsm; Trays 2-5: 17-40 lb. bond to 50-60 lb. cover / 65-163 gsm; Two-sided output: 17-60 lb. bond / 65-163 gsm; Media types: Plain paper, glossy, envelopes, labels, transparencies, card stock

## Color Standards

PANTONE® Color approved solid-color simulations, Adobe® PostScript® device-independent color, CIE International color standards, Color options, ICC Profile, Apple ColorSync®

## Operating Environment

Temperature: Storage:  $32^{\circ}$  to  $95^{\circ}$  F /  $0^{\circ}$  to  $35^{\circ}$  C, Operating:  $50^{\circ}$  to  $90^{\circ}$ F /  $10^{\circ}$  to  $32^{\circ}$ C; Humidity:  $15^{\circ}$ % to  $85^{\circ}$ ; Sound pressure levels: Printing: 58.0 dB(A), Standby: 34.4 dB(A); Sound power levels: Printing: 7.26 B, Standby: 5.0 B; Warm-up time (from sleep mode): 49 seconds

## Electrical

Power: 110–127 VAC, 50/60 Hz or 220–240 VAC, 50/60 Hz; Power consumption: 110–127 VAC: Standby: less than 105 W, Printing: less than 750 W, Power save: less than 20 W, 220–240 VAC: Standby: less than 95 W, Printing: less than 750 W, Power save: less than 22 W, 6360DN/DT/DX: ENERGY STAR® qualified

## Dimensions (WxDxH)

6360N/DN: 17.2 x 22.8 x 20.2 in. /429 x 580 x 513 mm; 6360DT: 17.2 x 22.8 x 25.4 in. /429 x 580 x 643 mm; 6360DX: 22.5 x 27.5 x 33.8 in. /572 x 698 x 854 mm; Weight: 6360N/DN: 77.4 lb. / 35.2 kg, 360DT: 92.4 lb. / 42 kg, 6360DX: 123.6 lb. / 56.2 kg

## Certifications

FCC Part 15, Class A, Listed UL 60950-1/CSA 60950-1-03, CE Mark applicable to Directives 73/23/EEC, 89/336/EEC, and 1999/5/EC, Section 508 ADA

## Supplies

 Standard-capacity toner cartridge:

 Black: 9,000 pages¹
 106R01217

 Cyan: 5,000 pages¹
 106R01214

 Magenta: 5,000 pages¹
 106R01215

 Yellow: 5,000 pages¹
 106R01216

 High-capacity toner cartridge:
 Black: 18,000 pages¹
 106R01221

 Cyan: 12,000 pages¹
 106R01218

# Routine Maintenance Items

Magenta: 12,000 pages1

Yellow: 12,000 pages1

 Imaging unit: 35,000 pages²
 108R00645

 110V Fuser: 100,000 pages³
 115R00055

 220V Fuser: 100,000 pages³
 115R00056

 Transfer roller: 35,000 pages
 108R00646

## Options

 N to DN Upgrade
 097503791

 Productivity kit
 097503747

 550-sheet feeder
 097503378

 1100-sheet feeder
 097503379

 Phaser memory
 -256 MB

 097503381
 097503381

-512 MB 097503382 Wireless network adapter 097S03740























Average standard pages. Declared Yield based on 5% area coverage on letter/A4-size page. Yield will vary based on image, area coverage and print mode.



106R01219

106R01220

<sup>&</sup>lt;sup>2</sup> Approximate pages. Declared yield based on an average job size of 4 AA-/letter-size pages. Yield will vary depending on job run length and media size and orientation.
<sup>3</sup> Approximate pages. Declared yield based on A4-/letter-size 20 lb. / 75 gsm pages. Yield will vary depending on media type, size, weight, orientation and usage patterns.

<sup>© 2010</sup> Xerox Corporation. All rights reserved. XEROX®, CentreWare®, Phoser®, PhaserSMART®, PrintingScout® and the sphere of connectivity design are trademarks of Xerox Corporation in the U.S. and/or other countries. All other trademarks are the property of their respective manufacturers. PANTONE Colors generated may not match PANTONE-identified standards. Consult current PANTONE publications for accurate color. PANTONE and other Pantone, Inc. trademarks are the property of Pantone, Inc. PCL® is a registered trademark of Hewlett-Packard. As an Energy Star partner, Xerox Corporation has determined that these products (Phaser 6360DN / DT / DX) meet the Energy Star guidelines for energy efficiency. Energy Star and the Energy Star mark are registered U.S. marks. The information in this brochure is subject to change without notice. 2/10 610P727150F