

Xerox[®] Phaser[®] 7800 Color Printer



Phaser 7800DN A full-featured color printer with automatic 2-sided printing and 620-sheet paper capacity.



Phaser 7800DX All of the features of the 7800DN plus a High Capacity Tandem Tray, for a total paper capacity of 3,140 sheets.



Phaser 7800GX Paper capacity of 2,180 sheets and includes PhaserCal® and PhaserMatch 5.0 with PhaserMeter® Color Measurement Device powered by X-Rite.

	Phaser 7800DN	Phaser 7800DX	Phaser 7800GX	
Output Speed - Color and I	Output Speed - Color and Black and White			
One-sided	Up to 45 ppm 8.5 x 11 in. / A4 (210 x 297 mm) Up to 26 ppm 8.5 x 14 in. Up to 22 ppm 11 x 17 in. / A3 (297 x 432 mm)			
Automatic Two-sided	Up to 45 ppm 8.5 x 11 in. / A4 (210 x 297 mm) Up to 17 ppm 8.5 x 14 in. Up to 15 ppm 11 x 17 in. / A3 (297 x 432 mm)			
Paper Handling - Input	Paper Handling - Input			
Tray 1 (Standard on all cor	nfigurations)			
Capacity ¹	100 sheets			
Sizes	Custom Sizes: 3.5 x 3.9 in. to 12.6 x 48 in. / 88 x 99 mm to 320 x 1,219 mm			
Weights	Single-sided printing: 20 lb. bond to 130 lb. cover / 75 to 350 gsm Automatic two-sided printing: 20 lb. bond to 98 lb. cover / 75 to 256 gsm Automatic two-sided printing with Extra Heavy Duty Media Kit (optional): 20 lb. bond to 110 lb. cover / 75 to 300 gsm			
Media Types	Plain paper Card stock Prepunched Letterhead Recycled Pre-printed Transparencies Labels	Envelopes Custom Lightweight card Heavyweight card Extra heavyweigh Lightweight glossy Glossy card stock Heavyweight glos Extra heavyweigh	stock : card stock v card stock sy card stock	
Tray 2 (Standard on all configurations)				
Capacity ¹	520 sheets			
Sizes	Sizes: 5.5 x 7.2 in. to 11.7 x 17 in. / 140 x 182 mm to 297 x 432 mm			
Weights	20 lb. bond to 98 lb. cover / 75 to 256 gsm			

Media Types	Plain paper Card stock Prepunched Letterhead Recycled Pre-printed Custom Lightweight card stock Lightweight glossy card stock Glossy card stock	
Capacity ¹	1,560 sheets	
Sizes	Sizes: 5.5 x 7.2 in. to 13 x 18 in. / 140 x 182 mm to 330 x 457.2 mm	
Weights	20 lb. bond to 98 lb. cover / 75 to 256 gsm	
Media Types	Plain paper Card stock Prepunched Letterhead Recycled Pre-printed Custom Lightweight card stock Lightweight glossy card stock Glossy card stock	
High-Capacity Tandem	Tray (Standard on 7800DX)	
Capacity ¹	2,520 sheets	
Sizes	Sizes: 5.5 x 7.2 in. to 13 x 18 in. / 140 x 182 mm to 330 x 457.2 mm	
Weights	16 lb. bond to 32 lb. bond / 60 to 122 gsm	
Media Types	Plain paper Card stock Prepunched Letterhead Recycled Pre-printed Custom Lightweight card stock Lightweight glossy card stock Glossy card stock	
Paper Capacity		
Standard Capacity ¹	7800DN: 620 sheets 7800GX: 2,180 sheets 7800DX: 3,140 sheets	

Paper Output / Finishing				
Output Trays (Standard)				
Dual Offset Catch Tray	250 sheets each tray ¹			
Office Finisher LX (Optiono	11) ²			
Capacity ¹	Stacking Tray: 2,000 sheets unstapled or 1,000 sheets single stapled or 750 sheets dual stapled (8.5 x 11 in. / A4)			
Sizes	8.5 x 7.2 in. to 11.7 x 17 in. / 210 x 182 mm to 297 x 432 mm			
Weights	Cover: 20 lb. bond to 98 lb. cover / 75 to 256 gsm (1 cover maximum) Text: 20 lb. to 28 lb. bond / 75 to 105 gsm			
Multiposition Stapling	50 sheets of 24 lb. bond / 90 gsm			
Hole Punch (Optional)	North AmericaEurope2-3 Hole Punch2-4 Hole Punch			
Booklet Maker for Office Fi	inisher LX (Score/Crease, Saddle-stitch Staple) (Optional)			
Capacity ¹	40 booklets (2-15 sheets per booklet – 20 lb. bond / 75 gsm	or less		
Sizes	8.5 x 11 in. to 11.7 x 17 in. / 210 x 279.4 mm to 297 x 432 r	nm		
Weights	20 lb. bond to 98 lb. cover / 75 to 256 gsm			
Saddle-stitch Stapling	2-15 sheets / 8-60 page booklet			
Score / Crease	1-15 sheets / unstapled			
Professional Finisher (Optio	Professional Finisher (Optional) ²			
Capacity ¹	Top Tray: 500 sheets of 8.5 x 11 in. / A4 (unstapled) Stacking Stapling Tray: - 1,500 sheets of 8.5 x 11 in. / 11 x 17 in. / A4 / A3 / SRA3 unstapled or - 200 stapled sets of 8.5 x 11 in. / A4 or - 100 stapled sets of 11 x 17 in. / A3 / SRA3			
Sizes	7.2 x 7.2 in. to 13 x 18 in. / 182 x 182 mm to 330.2 x 457.2	mm		
Weights	20 lb. bond to 130 lb. cover / 75 to 350 gsm			
Stapling	Single and multiposition stapling Auto stapling (50 sheets maximum) – 24 lb. / 90 gsm Letter, Legal, Tabloid / A4, A3, B4 and B5 sizes supported			
Hole Punch (Standard)	North America 2-3 Hole Punch	Europe 2-4 Hole Punch 4 Hole Swedish Punch (Optional)		
Booklet Maker	Saddle-stitch 2 to 15 sheets – Cover: 20 lb. bond to 98 lb. cover / 75 to 256 gsm (1 cover maximum) – Text: 20 lb. to 28 lb. bond / 75 to 105 gsm V-fold up to 15 sheets Letter, Legal, Tabloid / A4, A3, SRA3 sizes supported			
Print				
First-page-out Time	As fast as 9 seconds color / 9 seconds black-and-white			
Print Resolution	Enhanced: 1200 x 2400 x 1 dpi Photo Mode: 600 x 600 x 8 dpi Standard: 1200 x 600 x 1 dpi			
Maximum Print Area	11.69 x 18.74 in. / 297 x 476 mm			
Memory (Std/max)	2 GB			

Hard Drive	160 GB minimum	160 GB minimum		
Processor	1.33 GHz			
Language Support	Adobe [®] Postscript [®] 3 [™] PCL [®] 5c PCL [®] 6 Adobe PDF-Direct version 1.6			
Connectivity	Ethernet 10/100/1000Base-T USB 2.0 Optional external wireless 802.11 b, g, n			
Printing Features	Print AroundWatermarks (Windows driver only)Color By WordsXerox® PhaserSMART®PDF DirectPrint submission toolsSmart duplexExtended font storageRun BlackScalingSecure and Personal PrintSeparation pagesBooklet printingN-upSmart traysInternet Printing Protocol (IPP)Sample setJob pipeliningPersonal saved printBi-directional driverCustom sized pagesLayout/watermarksCollationForm/font storage			
Supported Operating Systems	Windows® XP (SP3 and above), Server 2003, Server 2008, Vista, 7 Mac OS® 10.5 and higher Oracle® Solaris® 9, 10 Fedora Core® 12-15 HP-UX® 11iv2 IBM® AIX® 5, SUSE® 11.x			
Print Drivers	Windows: PostScript, PCL5, PCL6 Macintosh, UNIX and Linux: PostScript Xerox [®] Global Print Driver [®] Xerox [®] Mobile Express Driver [®]			
Font Capability	139 PostScript [®] fonts 93 PCL [®] fonts			
Color Standards	PANTONE® calibrated solid-color simulations Adobe® PostScript® device-independent color CIE International color standards Support for ICC, ICM and Apple® ColorSync color management systems Xerox® PhaserMatch® 5.0 Xerox® PhaserCal®			
Xerox [®] Mobile Express Driver [®]	Makes it easy for mobile users to find, use and manage Xerox [®] and non-Xerox [®] devices in every new location. Plug into a new network, and Xerox [®] Mobile Express Driver automatically discovers available printers and provides status and capability information. Save a list of "favorite" printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT. • Printers are automatically discovered • Printer list can be managed based on location • Gives Bi-directional feedback device status, supplies, queue management			
Xerox® Global Print Driver®	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox [®] and non-Xerox [®] devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management. • Printers are automatically discovered • Printer list can be managed based on location • Gives Bi-directional feedback device status, supplies, queue management			

Accounting		
Accounting Control		
	Job Accounting Usage Analysis Tool	
Xerox® MeterAssistant®	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time. Device Direct or via Smart eSolutions Client for Windows or via Xerox® CentreWare® Web.	
Xerox [®] SuppliesAssistant [®]	Automatically orders supplies for Xerox output devices based on actual usage, eliminating the need to manually manage supplies inventory. Device Direct or via Smart eSolutions Client for Windows or via CentreWare Web.	
Security		
Security Features	Secure HTTPS (SSL/TLS) IPsec Optional removeable hard drive 802.1X authentication IPv6 SNMP v3 Image overwrite Configurable disk overwrite Port control IP filtering FIPS 140-2	
Device Management		
Xerox® PhaserCal® (Standa	rd)	
	PhaserCal is the color calibration application within PhaserMatch 5.0. Color laser printers should be periodically calibrated to eliminate changes in printed colors caused by environmental conditions and normal wear and tear on the printer's consumables. PhaserCal can account for these changes and maintain consistent print output. PhaserCal can control and communicate with the Xerox® PhaserMeter® color measurement device (standard on 7800GX), connected to your computer, resulting in highly accurate color calibration for your Phaser 7800 color printer.	
Xerox® PhaserMatch® 5.0 w (Standard on 7800GX, Opti	vith Xerox® PhaserMeter Color Measurement Device powered by X-Rite ional on 7800DN, DX)	
	PhaserMatch 5.0 color management and calibration software adds another level of color control and helps maintain color accuracy. It brings stability to the process – delivering consistent, predictable and reproducible color matching. Includes the PhaserMeter all-in-one color measurement device powered by X-Rite, which captures colors and helps calibrate your monitors and Phaser 7800 printer.	
Xerox [®] CentreWare [®] Web		
	 A Web-based server application for network administrators that permits web browser-based device management from any workstation, whether running Windows or UNIX or any other operating system Works with any SNMP-managed printer from any manufacturer Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management 	
Xerox [®] CentreWare Interne	at Services - Integrated Device Web Page	
Device Status	Web server embedded • Tray status/contents • Consumables status	
Print Queue Viewing	Complete job print queue management – hold, release, promote and delete	
Job Submission	Print-ready files (PS, PCL, TIFF, PDF) Output feature selection	

Device Administration	Allows simple, remote installation setting of configuration options and management of the device			
Browsers	Microsoft® Internet Explorer 7 Firefox® version 4 and above			
Xerox [®] Mobile Solutions				
Xerox® PrintBack	PrintBack takes the capabilities of the printer you already use, and extends them beyond your computer and out to your Apple iOS- or Android-based mobile device. When you're working offsite or away from your desk and receive an important document via your mobile device, simply use PrintBack to print it with your default printer back at your office or desk. Plus, it supports the most common office file types (Microsoft® Office documents, PDF, etc.) with uncompromised print quality.			
Xerox [®] Mobile Express Driver [®]	The Xerox [®] Mobile Express Driver is a single, universal printer driver that can be downloaded to a PC and used to print to virtually any PostScript device on the network, including printers made by other manufacturers. Instead of downloading individual printer drivers for each product in each office, users can download the single, simple, Mobile Express Driver.			
Device Specifications				
Duty Cycle				
	Up to 225,000 pages per month ³			
Recommended Monthly P	Recommended Monthly Print Volume			
	Up to 30,000 pages per month ⁴	Up to 30,000 pages per month ⁴		
Power Consumption	Power Consumption			
	115V, 50/60 Hz	230V, 50/60 Hz		
Printing (average operations)	844 watts	760 watts		
Ready	86 watts	86 watts		
Power saver	53 watts	56 watts		
Sleep	5.3 watts	6.3 wattss		
Warm up (from sleep)	As fast as 40 seconds			
Warm up (from power on)	As fast as 180 seconds			
Operating Temperature Range	50° to 90° F (10° to 32° C)			
Relative Humidity (noncondensing)	15% to 85%			
Operating Altitude	Up to 2,500 meters			
Sound Pressure Levels				
Printing	52 dB(A)			
Standby	21 dB(A)			
Sound Power Levels				
Printing	6.81 B(A)			
Standby	3.80 B(A)			

Dimensions and Weights (Unpackaged)	Width	Depth	Height	Weight
7800DN	25.3 in. / 641 mm	27.5 in. / 699 mm	22.8 in. / 578 mm	178.6 lbs / 81 kg
7800GX	25.3 in. / 641 mm	27.5 in. / 699 mm	37.5 in. / 953 mm	255.7 lbs / 116 kg
7800DX	25.3 in. / 641 mm	27.5 in. / 699 mm	37.5 in. / 953 mm	275.6 lbs / 125 kg
7800DN with Office Finisher LX	65.6 in. / 1,667 mm	27.5 in. / 699 mm	37.1 in. / 942 mm	240.2 lbs / 109 kg
7800DN with Office Finisher LX with Booklet Maker	65.6 in. / 1,667 mm	27.5 in. / 699 mm	41.6 in. / 1,057 mm	260.4 lbs / 118.1 kg
7800DN with Professional Finisher	75.7 in. / 1,923 mm	27.5 in. / 699 mm	41.9 in. / 1,065 mm	378.1 lbs / 171.5 kg
Dimensions and Weights (packaged)	Width	Depth	Height	Weight
7800DN	30.3 in. / 770 mm	33.4 in. / 848 mm	27 in. / 686 mm	232 lbs / 105.2 kg
7800GX	30.3 in. / 770 mm	33.4 in. / 848 mm	45 in. / 1,143 mm	324 lbs / 147 kg
7800DX	30.3 in. / 770 mm	33.4 in. / 848 mm	45 in. / 1,143 mm	324 lbs / 147 kg
Office Finisher LX	39 in. / 991 mm	27.4 in. / 697 mm	25.7 in. / 654 mm	79.2 lbs / 36 kg
Office Finisher LX Booklet Maker	30 in. / 762 mm	19.7 in. / 500 mm	17.2 in. / 437 mm	28.7 lbs / 13.1 kg
Professional Finisher	30.1 in. / 765 mm	45.7 in. / 1,161 mm	48.9 in. / 1,241 mm	264 lbs / 120 kg
Certifications				
	Certified to UL 60950-1/CSA 60950-1-07, 2nd Edition FCC Part 15, Class A Low Voltage Directive 2006/95/EC EN 60950-1, 2nd Edition EMC Directive 2004/108/EC EN 55022, Class A EN 55024 RoHS Directive 2002/95/EC Section 508 Compliant ENERGY STAR® Qualified			
What Comes in the Box				
	Phaser 7800 Starter Toner Cartridges – One of each (Cyan, Magenta, Yellow: 6,000 print capacity; Black: 24,000 print capacity) Quick Use Guide Software and Documentation CD (with Drivers, User Manual, System Admin. Guide and Warranty Statement) Power cord			

Supplies and Options	Description	Order Number
Standard-Capacity Toner Cartridges	Cyan: 6,000 pages ⁵	106R01563
	Magenta: 6,000 pages⁵	106R01564
	Yellow: 6,000 pages⁵	106R01565
High-Capacity Toner	Black: 24,000 pages ⁵	106R01569
Cartridges	Cyan: 17,200 pages ⁵	106R01566
	Magenta: 17,200 pages⁵	106R01567
	Yellow: 17,200 pages ⁵	106R01568
Staple cartridges	Staple Refills for Office Finisher LX	008R12941
	Staple Refills for Professional Finisher	008R12897
Routine Maintenance	Imaging Unit: Up to 145,000 pages ⁶	106R01582
Items	Waste Cartridge: Up to 20,000 pages ⁶	108R00982
	Suction Filter: Up to 120,000 pages ⁶	108R01037
	IBT Cleaner: Up to 160,000 pages ⁶	108R01036
Options	Office Finisher LX ⁷	097S04166
	Booklet Maker for Office Finisher LX	497K03850
	2/3-hole Punch for Office Finisher LX	497K03860
	Professional Finisher ⁷	097S04167
	3 Tray Module	097S04159
	High Capacity Tandem Tray	097S04160
	Cabinet Stand	097S04552
	Extra Heavy Duty Media Kit	097504341
	PhaserMatch® 5.0 (includes PhaserMeter® powered by X-Rite)	097504276
	Wireless Network Adapter – North American power converter – Euro power converter – UK power converter	097S03740 097S03741 097S03742

¹ Paper capacities are based on 20 lb. / 75 gsm stock; capacities will vary with different weight stocks.

² Finishers require installation of either a 3 Tray Module or High Capacity Tandem Tray.

³ Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

⁴ Range reflects the number of pages per month the product can regularly print while maintaining optimal performance (considering factors including supplies replenishment and reliability over the expected product life).

⁵ Average standard pages. Declared Yield in accordance with ISO/IEC 19798. Yield will vary based on image, area coverage and print mode.

⁶ Average standard pages. Yield will vary depending on job run length, media size and orientation.

⁷ Finishers require installation of either a 3 Tray Module or High Capacity Tandem Tray.



©2015 Xerox Corporation. All rights reserved. Contents of this publication may not be reproduced in any form without permission of Xerox Corporation. Xerox®, Xerox and Design®, CentreWare®, Global Print Driver®, Mobile Express Driver®, Phaser®, PhaserCalØ, PhaserMatch®, PhaserMeter® and PhaserSMART® are trademarks of Xerox Corporation in the United States and/or other countries. As an ENERGY STAR® partner, Xerox Corporation has determined that this product meets the ENERGY STAR guidelines for energy efficiency. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. The information in this document is subject to change without notice. Updated 2/15 78XSS-01UE

