Xerox® AltaLink® Multifunction Printer



B8045/B8055/B8065/B8075/B8090



AltaLink® B8000 Series Multifunction Printers are built on Xerox® ConnectKey® Technology. For more information, go to www.ConnectKey.com.

System Specification	AltaLink® B8045	AltaLink® B8055	AltaLink® B8065	AltaLink® B8075	AltaLink® B8090	
Simplex Speed						
A4 (LEF)	45 ppm	55 ppm	65 ppm	75 ppm	90 ppm	
A4 to B4 (SEF)	36 ppm	36 ppm	49 ppm	49 ppm	54 ppm	
A3 (A3 SEF)	31 ppm	31 ppm	42 ppm	42 ppm	47 ppm	
(Bypass Tray will reduce speed by 10 to 20%)						
Auto Duplex Speed A4 (LEF)	Up to 55 ppm (32.5 sheets)	Up to 55 ppm (32.5 sheets)	Up to 70.6 ppm (35.3 sheets)	Up to 77 ppm (38.5 sheets)	Up to 87 ppm (43 sheets)	
Monthly Duty Cycle ¹	Up to 175,000 pages/month	Up to 200,000 pages / month	Up to 250,000 pages/month	Upto 300,000 pages/month	Up to 400,000 pages/month	
Recommended Average Monthly Print Volume ²	15,000 to 75,000 pages	20,000 to 100,000 pages	25,000 to 110,000 pages	30,000 to 125,000 pages	50,000 to 150,000 pages	
Hard Drive / Processor / Memory	Minimum 250 GB HDD / 1.8 GHz Quad-Core / 4 GB system memory					
Connectivity	Ethernet 10/100/1000 Base-	T, High-speed USB 2.0 direct pr	int, Wi-Fi Direct with optional >	Kerox®USB Wireless Adapter, N	FC Tap-to-Pair	
Controller Features	Unified Address Book, Remot	e Control Panel, Configuration	Cloning, Online Support			
Copy and Print						
Copy and Print Resolution	Copy: Up to 600 x 600 dpi; Pr	rint: Up to 1200 x 1200, 256 sh	ades of gray			
First-Print-Out Time (Ready to print from warmed-up state)	As fast as 3.9 seconds		As fast as 4.9 seconds			
First-Copy-Out Time (Ready to copy from warmed-up state)	the Duplex Automatic Document Feeder the Platen / 7.2 seconds from the Duplex Automatic				As fast as 4.9 seconds from the Platen / 8.7 seconds from the Duplex Automatic Document Feeder	
Page Description Language	Adobe®PostScript® 3™, Adobe®PDF version 1.7, PCL® 5c / PCL 6, XML Paper Specification (XPS®) (Optional)					
Print Features	Print from USB, Encrypted Secure Print, Xerox® Earth Smart Driver Settings, Job Identification, Booklet Layout, Store and Recall Driver Settings, Bi-directional Real-time Status, Scaling, Job Monitoring, Application Defaults, Two-sided Printing (as default), Hold All Jobs					
Mobile (Optional)						
Mobile Printing	Xerox®Workplace Suite and X	Xerox® Workplace Suite and Xerox® Workplace Cloud				
Mobile Printing Connectivity	Apple®AirPrint®, Mopria®Cert	ified, Mopria® Print Service Pluç	g-in for Android™, @PrintByXero	ox, Xerox®Print Service Plug-in f	or Android™	

Mobile (Optional)						
Mobile Apps and Xerox App Gallery Xerox® Workplace Suite	Xerox App Gallery: Cloud Connector Apps: Print and Scan to/from: Salesforce, Google Drive®, Microsoft®OneDrive®, Microsoft Office 365™, DropBox™ and Box® Productivity Apps: Xerox®Easy Translator Service Device Management Apps: QR Code Scan Apps: Xerox® Scanning App for DocuShare® See the full list of apps available in the XeroxApp Gallery at www.xerox.com/AppGallery.					
and Xerox® Workplace Cloud	while enabling worker produ	ıctivity and mobility throu	igh α set of robust workflows		ective control over their print fleet, omer flexibility by offering these d) of this solution.	
Scan						
Standard Features		Scan, Searchable PDF, Sing		rmats: PDF, PDF/A, XPS, JPEG, T F, Encrypted / Password Protecto	IFF; Convenience Features: ed PDF, Linearised PDF / PDF/A,	
Optional Features	ConnectKey® for DocuShare®	, other solutions available	hrough various Xerox Busines	s Innovation Partners, www.off	ice.xerox.com/Software-Solutions	
Fax						
Standard Features	Internet Fax, Fax Build Job, N	letwork Server Fax Enabler	nent			
Optional Features	Fax Forward to Email or SMB	, Walk-up Fax (one-line an	d two-line options, includes LA	N Fax)		
Security						
Standard Features	compliant), SSL, SHA-256 Ha	sh Message Authentication et Orchestrator, Secure Em	, Common Criteria Certificatio	n (ISO 15408), Encrypted Secu	S 256-bit Encryption (FIPS 140-2 re Print, Secure Fax, Secure Scan, Controls, User Permissions, Cisco®	
Optional Features	McAfee Integrity Control, Sm	nart Card Enablement Kit (CAC/PIV/.NET), Xerox® Integra	ted RFID Card Reader		
Accounting						
Standard Features	Xerox®Standard Accounting	(Copy, Print, Scan, Fax, Em	ail), Network Accounting Enab	lement		
Optional Features	Equitrac Express®, Equitrac O	ffice®, YSoft®SafeQ®, othe	network accounting solutions	s available through various Xero	x Business Innovation Partners	
Device Specification						
Control Panel Languages			talian, German, International n, Romanian, Catalan, Arabic	Spanish, Dutch, Brazilian Portug	guese, Swedish, Norwegian, Danish,	
Accessories						
Optional	High Capacity Feeder (HCF) Envelope Tray (Replaces Tray Office Finisher (optional with Office Finisher with Booklet I Hole Punch for Office Finishe High Volume Finisher (B806: High Volume Finisher with Bo Convenience Stapler (may re Smart Card Enablement Kit Walk up Fax (one- or two-line Wi-Fi Direct with Optional Xe McAfee® Integrity Control En XPS Print Option Kit Keyboard Kit (Wired/USB) Integrated RFID Card Reade Foreign Device Interface	B8045/B8055/B8065/B80 Maker (optional with B804 or (B8045/B8055/B8065/B 6/B8075, required for B805 boklet Maker (optional with quire Work Surface) e options, includes LAN Fax rox® USB Wireless Adapter ablement Kit	5/B8055/B8065/B8075 only) 3075 only) (0) n B8065/B8075/B8090)			
Foreign Device Interface (FDI)	Also known as Auxiliary Acce	ss Device, this is an interfa	ce to third party access contro	l devices, such as coin machines	s and card readers.	
Electrical Requirements	AltαLink® B8045	AltaLink® B8055	AltaLink® B8065	AltαLink® B8075	AltαLink® B8090	
Europe	Voltage: 220-240 VAC +/- 10 % Frequency: 50/60 Hz +/- 5 % 10 A					
Power Consumption	AltaLink® B8045	AltaLink® B8055	AltaLink® B8065	AltaLink® B8075	AltαLink® B8090	
Running (Average)	1,150 watts	1,250 watts	1,550 watts	1,600 watts	1,650 watts	
Standby Mode	45 watts	45 watts	310 watts	310 watts	310 watts	
Low Power Mode	4 watts		'	•	,	
	<4 watts (Default time to sleep = 1 minutes)					

Power Consumption	AltaLink® B8045	AltaLink® B8055	AltaLink® B8065	AltaLink® B8075	AltaLink® B8090	
Boot Time (from Power On	As fast as 120 seconds					
to Services Home Screen)	<28 seconds					
Recovery from Sleep mode	20 Seconds					
Operating Environment						
Required Temperature Range	10 to 32° C					
Required Reletive Humidity	15% to 85%					
Sound Power Levels	Operating: 7.1 B(A); Standby	5.0 B(A)	Operating: 7.2 B(A); Standby	5.0 B(A)	Operating: 7.3 B(A); Standby 5.0 B(A)	
Sound Pressure Levels	Operating 56 dB(A), Standby	35 dB(A)	Operating 57 dB(A), Standby	35 dB(A)	Operating 58 dB(A), Standby 35 dB(A)	
Dimensions and Weight						
Base Configuration with OCT	Width: 850 mm Depth: 665 mm Height: 1,150 mm Weight: 113 kg					
With Office Finisher (B8045/B8055/B8065/B8075 only)	Width: 1,470 mm Depth: 665 mm Height: 1,150 mm Weight: 142.5 kg					
With Office Finisher with Booklet Maker (B8045/B8055/B8065/ B8075 only)	Width: 1,530 mm Depth: 665 mm Height: 1,150 mm Weight: 158.5 kg					
With High Volume Finisher and High Capacity Feeder (B8065/B8075/B8090 only)	Depth: 665 mm					
With High Volume Finisher with Booklet Maker and High Capacity Feeder (B8065/B8075/B8090 only)	Width: 2,485 mm Depth: 665 mm Height: 1,150 mm Weight: 196.5 kg					
High Capacity Feeder	Width: 1,995 mm Depth: 510 mm Height: 510 mm Weight: 30 kg					
Work Surface (Does not add to overall width if combined with High Capacity Feeder)	Width: 285 mm					
System Certification/Regula	atory Compliance					
Certifications	To view the latest list of certif	ications, go to www.xerox.com	m/OfficeCertifications.			
Paper Handling	AltaLink® B8045	AltaLink® B8055	AltaLink® B8065	AltaLink® B8075	AltaLink® B8090	
Single-Pass Duplex Automa	tic Document Feeder (DADF)					
Capacity ³	200 sheets					
Speed	Up to 140 images per minute (ipm) colour (simplex) Up to 200 ipm black and white (duplex)					
Paper Sizes Sensed	125 x 138 mm to 297 x 432 mm					
Weights	50 to 160 gsm					
Bypass Tray						
Capacity ³	100 sheets					
Sizes	Custom Sizes: A6 x A3					
Weights	60 to 216 gsm					

Bypass Tray	
Media Types	Bond
	Card Stock
	Envelopes Usla Division of the Control of the Contr
	Hole Punched Index
	Labels
	Letterhead Plain
	Preprinted
	Recycled
	Transparencies
Trays 1 and 2	
Capacity ³	500 sheets each
Sizes	Custom Sizes: A5 to A3
Weights	60 to 200 gsm
Media Types	Bond Card Stock
	Glossy
	Hole Punched
	Index Labels
	Labels Letterhead
	Lightweight Cardstock
	Plain Preprinted
	Recycled
	Transparencies (Tray 2 only)
High Capacity Tandem T	ray
Capacity ³	Tray 3: 1,600 sheets
	Tray 4: 2,000 sheets each
Sizes	Standard Sizes A4
Weights Media Types	60 to 216 gsm Bond
Media Types	Card Stock
	Glossy
	Hole Punched Index
	Letterhead
	Lightweight Cardstock
	Plain Preprinted
	Recycled
Envelope Tray (Optional	- Replaces Tray 2)
Capacity ³	Up to 50 envelopes
Sizes	Monarch, DL, C5
Weights	75 to 90 gsm
High Capacity Feeder (H	·
Capacity ³	3,300 sheets
Sizes	A4 LEF
Weights	60 to 216 gsm
Media Types	Bond
	Card Stock
	Hole Punched Index
	Letterhead
	Plain
	Preprinted Recycled
Total Capacity	
Device Total Capacity ³	8,000 sheets
_ ss . star capacity	Telest miner

Finishing	AltaLink® B8045 AltaLink® B8055 AltaLink® B8065 AltaLink® B8075 AltaLink® B8090					
	Optional with B8045/B8055/B8065/B8075) (Required when finisher not attached)					
Capacity	Up to 400 sheets of 80 gsm					
	ional with B8045/B8055/B8065/B8075 only)					
Top Tray Capacity	250 sheets unstapled of 80 qsm					
Stacking Tray Capacity	2,000 sheets unstapled of 80 gsm or 1,000 sheets single stapled or 750 sheets dual stapled (A4) (Degradation of stacking quality may occur with more than 50 stapled sets.)					
Top Tray Sizes	A6 to A3					
Stacking Tray Sizes	A5 to A3					
Weights	60 to 216 gsm					
Multiposition Stapling	80 gsm					
Hole Punch (Optional) Europe	2-4 Hole Punch					
Office Finisher with Booklet	et Maker (Optional with B8045/B8055/B8065/B8075 only)					
Top Tray Capacity	250 sheets unstapled of 80 gsm					
Stacking Tray Capacity	2,000 sheets unstapled of 80 gsm or 1,000 sheets single stapled or 750 sheets dual stapled (A4) (Degradation of stacking quality may occur with more than 50 stapled sets)					
Top Tray Sizes	A6 to A3					
Stacking Tray Sizes	A5 to A3					
Weights	60 to 216 gsm					
Multiposition Stapling	80 gsm					
Hole Punch (Optional)						
Europe	2-4 Hole Punch					
Booklet Making Capacity ³	40 booklets (2-15 sheets per booklet – 80 gsm or less)					
Booklet Making Sizes	A4 SEF B4 SEF A3 SEF					
Saddle-Stitch Stapling	2-15 sheets / 8-60 page booklet 60 to 90 gsm					
Folding (unstapled)	1-5 sheets / unstapled					
High Volume Finisher (HVF	F) (OCT) (Optional with B8065/B8075, required for B8090)					
Top Tray Capacity ³	250 sheets					
Stacking Tray Capacity ³	3,000 sheets					
Sizes	A6 to A3 / 105 x 148 mm to 297 x 420 mm					
Weights	60 to 216 gsm					
Stapling ³	100 sheets Single (any corner), dual, front, rear, SEF and 4-stitch					
Hole Punch (Optional) Europe	2-hole punch 4-hole punch and 4-hole "Swedish" punch					
High Volume Finisher with Booklet Maker (Optional with B8065/B8075, required for B8090)						
Top Tray Capacity ³	250 sheets					
Stacking Tray Capacity ³	3,000 sheets					
Sizes	A6 to A3 / 105 x 148 mm to 297 x 420 mm					
Weights	60 to 216 gsm					
Stapling ³	100 sheets Single (any corner), dual, front, rear, SEF and 4-stitch					
Hole Punch (Optional) Europe	2-hole punch 4-hole punch and 4-hole "Swedish" punch					

High Volume Finisher with	Booklet Maker (Optional wi	th B8065/B8075/B8090)				
Booklet Making Capacity ³	Tray stop up: 30 booklets (1 Tray stop down: Unlimited	Tray stop up: 30 booklets (1-15 sheets per booklet) Tray stop down: Unlimited				
Booklet Making Sizes	A4 / 210 x 297 mm 216 x 356 mm A3 / 297 x 420 mm					
Booklet Maker Weights	60 to 216 gsm					
Saddle-Stitch Stapling ³	Saddle-Stitch (2-15 sheets /	8-60 page booklet)				
Folding	V-folding (1-5 sheets / unsto	ıpled)				
Convenience Stapler (May I	Require Work Surface)					
Capacity ³	50-sheet stapling 5,000 staples Requires separate power ou	tlet				
Сору	AltaLink® B8045	AltaLink® B8055	AltaLink® B8065	AltαLink® B8075	AltαLink® B8090	
First-Copy-Out Time	As fast as 3.8 seconds from the Duplex Automatic Docu	the Platen / 7.4 seconds from ment Feeder	As fast as 3.3 seconds from the Platen / 7.2 seconds from the Duplex Automatic Document Feeder	As fast as 2.9 seconds from the Platen / 6.9 seconds from the Duplex Automatic Document Feeder	As fast as 4.9 seconds from the Platen / 8.7 seconds from the Duplex Automatic Document Feeder	
Sides (input: output)	1-1, 1-2, 2-2, 2-1					
Quantity	1 to 9,999					
Resolution(max)	Up to 600 x 600 dpi					
Reduction/Enlargement	Variable zoom from 25% to	400% in 1% increments.				
Concurrency	Program-ahead to allow job	to be initiated while initial job i	s processed (Copy, Print, Fax an	ıd Scan)		
Copy Features	Annotation and Bates™ stamping (with colour capability and font size adjustment) Authentication for Services Auto Paper Select Auto Reduction & Enlargement to fit selected paper size Auto Tray Switching Automatic 2-sided / Duplex Booklet Creation (requires finishing option) Build Job: (Enables page-level programming and also lets you proof each section or delete last section as the job is built) Collation Covers (Front only, front and back, back only, printed inside and out: Blank or Printed) Dividers (blank) Edge Erase Features Help (Intuitive text and graphic descriptions) ID Card Copy Image Quality Adjustments Image Shift (with Auto Center option) Invert Image (negative or mirror image) Large Job Interrupt Multi-up (up to 15 columns by 15 rows) Sample Set Save Job Settings Stapling (requires optional Finisher) Transparencies					
Xerox®Copier Assistant®	Xerox® Copier Assistant® Software provides a PC-based alternative to the user interface touchscreen. Used in conjunction with a customer-supplied PC attached via the USB port, this software supports text-to-speech, screen magnification and easy PC keyboard access to basic and advanced copy features. Section 508-compliant. For more information or to download Xerox® Copier Assistant for free, visit www.xerox.com.					
Print	AltaLink® B8045	AltαLink® B8055	AltaLink® B8065	AltaLink® B8075	AltαLink® B8090	
First-Page-Out Time	As fast as 3.9 seconds As fast as 4.9 seconds					
Resolution	Up to 1200 x 1200, 256 shades of gray					

Print	AltαLink® B8045	AltaLink® B8055	AltαLink® B8065	AltαLink® B8075	AltaLink® B8090		
Print Features	Duplex Printing Default Job Identification (Print I LAN Fax (requires option Job Monitoring (Client or Watermark (predefined of N-up (up to 16 pages per Booklet Layout Finishing (requires a finis Fit to New Paper Size Paper Selection by Attrib Print Around Enable / Dis Sample Set Saved Job Secure Print with Timed I Skip Blank Pages Special Pages (exception Store and Recall Driver Sc Stored Jobs Deletion	tatus c) solution, Standard, Toner Sar ID or Banner, Print ID in mar al Fax Kit) c Local User Interface) and custom) r sheet) ther option) ute able Deletion page programming: covers, ettings (Grox® Earth Smart Settings,	gins on first page only or all positive pages only or all positive pages only or all positive pages on the pages of the pa	ages) and Print ID, Smart Sample Set	, Hold All Jobs)		
Print from USB	Allows walk-up printing f Supports direct printing f	rom Type A USB port on fror from computer via Type B U DF, JPEG, TXT, PS, XPS4, PCL	SB port				
Operating Systems	Windows 7 (32- and 64-bit) Windows 8 (32- and 64-bit) Windows 8.1 (32- and 64-bit) Windows 10 (32- and 64-bit) Windows 10 S (32- and 64-bit) Windows Server 2008 SP2 (32- and 64-bit) Windows Server 2008 R2 (64-bit) Windows Server 2012 (64-bit) Windows Server 2012 (64-bit) Windows Server 2012 (64-bit) Windows Server 2016 (64-bit) Windows Server 2016 (64-bit) Windows Server 2016 (64-bit) Windows Server 2019 (64-bit) Undows Server 2019 (64-bit) Windows Server 2019 (64-bit)						
Network Protocols	Fedora Core® TCP/IP: HTTP/HTTPS, Int ThinPrint® Airprint® Mopria® Google Cloud Print Bonjour® IPv6 Secure FTP Most protocols not in use	<u>-</u>	LPD, Raw Socket Printing/Port	9100, IPv4/IPv6, WSD			
Administrative Protocols			HCP Autonet, NTP, TLS, SMB,	SMTP/POP3, WSD, LDAP, Multico	ast DNS		
Font Capability	PCL: 93 scalable fonts, lir	ne printer and bitmap font (i	ncluding Cyrillic font support)	PostScript 3: 173 Type 1 fonts, 2	2 Multiple Master fonts		
Xerox® Mobile Express Driver®	Driver automatically disc	overs available printers and		information. Save a list of "favo	o a new network, and Mobile Express prite" printers for each location, store		
Xerox®Global Print Driver®	consistent, easy-to-use ir	iterface for end-users, reduc	ing the number of support call	s, and simplifying print services	3		
Xerox [®] Pull Print Driver	Makes it easy for IT managers to qualify, deploy and manage all print devices using a single driver in a Pull Print environment. Uses a single queue and single driver. The Xerox® Pull Print Driver extends convenience across a broad range of printing assets. IT administrators no longer need to manage and configure multiple drivers. Used in conjunction with Equitrac Office®, Ysoft® SafeQ®, Pharos® and others.						
Unified Address Book for Fo	for Fax, Internet Fax, Email and Scan to						
Features	Maximum contacts: 5,00 Contacts: Supports 1 or r						
Scan	AltaLink® B8045	AltaLink® B8055	AltaLink® B8065	AltαLink® B8075	AltaLink® B8090		
Concurrency	Scan while the system is concurrent jobs)	printing, copying, or while it	is transferring scan to network	or fax jobs (priority is for return	of scanned originals and printing		
Input Speed	Up to 140 images per mi Up to 200 ipm (duplex) b	inute (ipm) (simplex) colour plack and white					
Resolution	72 x 72 dpi to 600 x 600	dpi					
Bit Depth	1-bit (black and white), 8	-bit (greyscale), 24-bit (color	ur)				

Scan	AltaLink® B8045	AltaLink® B8055	AltaLink® B8065	AltaLink® B8075	AltαLink® B8090				
Maximum Scan Area	A3								
Scan Template Management		Support 250 scan templates Create Xerox® CentreWare® IS scan templates and share via device cloning to other multifunction printers Confirmation sheet options							
Network Filing Protocol	sFTP, FTP, SMB, HTTP, HT	TPS							
File Compression	Searchable PDF/OCR and	MH, G4 MMR compression - sing PDF/A-1b (MRC, JPEG, G3 MH, G	4 MMR, JBIG 2 Huffman, JBIG A	Arithmetic Compression, Deflate (f Ining apps) Linearised PDF / PDF/					
Document Management Fields (Metadata)	1 to 6 user programmab field name, default valu	Network Scan to File Templates ble metadata fields per network e and other configurations d on user interface for variable	scan to file templates and unlin	nited fields within the template –	Metadata field consists of				
Scan Features	Mixed Size Originals Scan Build Job Compression Quality / File Size Control Original Type (Photo and Text, Photo, Text, Map, Newspaper / Magazine) Auto Background and Shadow Suppression Size for Size (for mixed size originals) TWAIN Support / WIA 2.0 Support Bound Originals Edge Erase Reduction/Enlargement 1-Touch Scan buttons (up to 10)								
Scan to Email (Standard)									
Scan Features	Email signatures (6 lines Scan to Email S/MIME E Email signing (requires S Auto send to self	ncryption	mail message body (user config	gurable), email CentreWare IS cor	firmation sheetoptions				
Directory Access	Address list via LDAP (Win	dows Active Directory, Exchang	e, Notes, Domino) Downloadec	l address list (comma-separated f	ile format)				
Scan to (Standard)									
Features	Scan to USB Scan to Network Folder (uses Unified Address Book entries) Scan to Home Scan to Network Scan to Email Scan to PC/Server Client (SMB or FTP) Scan to Mailbox Scan to Secure FTP and HTTPS								
Workflow Scanning (Option	Workflow Scanning (Optional)								
Scanning Software	Autostore v7 eCopy ShareScan v5.2 eCopy ScanStation v5.2								
Scanning Apps and Xerox App Gallery	Scan to/from: Dropbox™, 0 www.xerox.com/AppGal		rive [®] , Microsoft Office 365™ αn	d Box [®] See the full list of apps avo	ailable in the App Gallery:				

Security	AltaLink® B8045	AltaLink® B8055	AltaLink® B8065	AltaLink® B8075	AltaLink® B8090
Xerox® Integrated RFID Card Reader E1.0 (Optional kit) Fax Network Server Fax Featur Compatibility Maximum Scan Area Send Features	Expanded Authentication Network authentication Local Authentication Smart Card authentic Secure Data Digitally signed Email Encrypted Scan to Enercypted ond authe Secure Print (up to 10 Immediate Image Orline 1978, SF1 Expanded Authorization SA access based on note of the configuration Watched Scan to USB Enable Print from USB Enable Print from USB Port Enable Audit Log Enable Print Immediate Job Oven Scheduled Image Oven McAfee® Advanced Secure Network Acce Configuration Watched Scan to USB Enable Print from USB Enable Print Immediate Job Oven Scheduled Image Oven McAfee® Advanced Secure Network Accees Scan to USB Enable Print Immediate Job Oven Scheduled Image Oven McAfee® Advanced Secure Network Immediate Job Oven Scheduled Image Oven McAfee® Embedded Common Criteria Certiful Cisco® Identity Services Full system Common Control Integrated Support for morinters panel. AltaLink® B8045	(internal database) cation – 144k CAC / PIV Card I (when using Smart Card au nail I Protected PDF (when using ntication to SMTP server for O digit PIN or Network Authe verwrite / Securely delete job Overwrite (Scheduled, Manuc cryption TP, SNMPv3 n tetwork credentials er per service uired to access Print and Prin ss og (Monitor and remediate 8 pisable e / Disable e / Disable e e / Disable e everite Enable / Disable erwrite Enable / Disable erurity (Embedded Control) S v1.0, v1.2, SNMPv3, HTTPs ontrol (whitelisting), McAfee fication ISO 15408 (certifice Engine (ISE) compatible riteria certified by NIAP und ost industry security cards pro AltaLink® B8055 rious Xerox Business Innovat	device services via Kerberos (Ld Support (2048 bit certificate athentication) Email and Network Scan Tem Scan to Email entication) so using approved algorithms all), includes sanitation of unuse at Features (e.g., time restriction) at Features (e.g., time restriction) at Security settings) Enable / Disable (802.1X, Device Security, SFT Integrity Control (optional), Plan INAP HCD_PP v1.0) er HD Protection Profile for Hooviding additional security with AltaLink® B8065	Port disablement including USB pardcopy Devices v1.0 (HCD-PP v1	Orts, Audit Log, Hide Print Job Names
Sena reactives	Add to Send List (200 nu	mbers maximum)	AT A Colored to the colored	11 13	
Print Fax Features			al Type (photo, text or photo	and text)	
Transmission Resolution	One- or Two-sided Printin	<u> </u>			
Transmission resolution	Superfine: 400 x 200 dpi Fine: 200 x 200 dpi Standard: 200 x 100 dpi	(Scan at 600 x 600 dpi)			
Internet Fax Features					
Compatibility			internet fax machines or ema t via email from remote Interr	il clients (SMTP) net Fax machines or email clients	S
Directory Access	Utilises the Unified Addre				
Send/Receive	Send: Multi-page TIFF, P Receive: TIFF, MTIFF, PD	DF, PDF/A _' F, PDF/A, PS, Text, PCL, PRN,	JPEG		
Resolution	72 x 72 dpi to 600 x 600	dpi, Bit Depth: 1-bit (black-a	ind-white)		
Network Protocols	SMTP (send), POP3 (rece	ive)			
Compliance	ITU-T T.37 compliant				
Walk-up Fax Features					
Compatibility	ITU (CCITT) Group 3				
Speed / Modems	One or Two V.34 modem utilising T38 (optional)	s: 33,600 bps. Less than 4 se	econds per page transmission	time ATA analog terminal adapt	ter
Compression / Speed	MH/G3, MR/G3, MMR/SG	i3, JBIG/SG3			
Resolution	Walkup Send: Standard: 200 x 100 dpi Fine: 200 x 200 dpi Supe Receive: Accepts all sizes				

Fax Send Features	LAN Fax (fax from print driver) Auto Fax Transmission Reduction Page-by-page Job Status at the Machine Delay Start, Build Job, Favorites Automatic Memory Resend Automatic Cover Sheets PSTN Fax Batch Send (up to memory capacity) Device Address Book (up to 1,000 contacts)
Fax Receive Features	One- or Two-sided Printing Stapled or Unstapled Receive Print Mode – Manual (size, margin, stock, header) / Auto Output Tray Selection Up to 200 Password Protected Mailboxes Secure Receive Receive Timestamp Auto Answer Delay 1-Touch Convenience
Fax Forward	Forward to Email or SMB Location Fax Forward on Receive Only
Fax Reports	Activity, Dial Directory, Group Directory, Transmission Confirmation, Pending Fax, Options Report, On Demand Overwrite Report, Mailbox Report, Broadcast Report
Directory Access	Utilises the Unified Address Book Group fax available
Auto Redial	Up to 14 attempts (per country requirements) 1 to 25 minute intervals
Auto Resend	Up to 5 attempts
Device Management	
Management Support	SNMP Version 1. SNMP Version 2c and SNMP Version 3 trap over TCP/IP and IP MIB access (IETF-MIBII RFC 1213), Host Resources MIB RFC 2790 Printer MIB RFC 3805, PWG Imaging System Power MIB, Fleet Orchestrator, Configuration Watchdog
Xerox® CentreWare® Web	A web-based server application for network administrators that permits web browser-based device management from any workstation, whether running Windows or UNIX or any other operating system • Works with any SNMP-managed printer from any manufacturer • Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management. • Windows® 2008 x86 and x64 and R2x64 • Windows® 10 • Windows® Server® 2012 and 2012 R2 • Auto-detect Xerox Device Manager server and download configurations files for touchless remote install
Xerox® Device Manager	Xerox® Device Manager collects and manages the data that drives fact-based decisions for your enterprise device management environment. It is a single tool to install print queues and configure, manage, monitor and report on both networked and locally connected devices – regardless of vendor – across your enterprise. Xerox® Device Manager provides: • Device monitoring and troubleshooting • Extensive reporting and discovery of new devices • Usage collection, chargeback and billing capabilities
Fleet Orchestrator	Fleet Orchestrator feature offers the ability to create a group of devices that share information with each other via a secure peer-to-peer connection. The following data can be shared: software update files, clone files, 1-Touch App files
Novell NDPS/NEPS	Server gateway application: centralised management tool.
Xerox® Device Types for SAP Environment	Xerox, together with SAP through our Gold-level membership in the SAP Printer Vendor Program, provides seamless connectivity between SAP systems and your Xerox® printers and multifunction printers. And as an SAP customer you benefit from having SAP-certified Xerox® device types available right from SAP's online delivery model. SAP-certified device types for Xerox® printers and multifunction printers are available to download. www.office.xerox.com/Software-Solutions
Xerox® Device Types for SAP R/3 Intelligent Barcode Utility (optional)	Provides built-in process intelligence that allows the printing of barcodes on any appropriately configured PostScript printer in specific versions of SAP environment and within Latin-1 (ISO8859-1) SAP system code pages only. Used in conjunction with Xerox® PostScript Device Types for SAP environment and Xerox® Font Center Barcode Fonts. Information available at www.office.xerox.com/Software-Solutions
Xerox® Barcode Pro PS (optional)	Enables intelligent PostScript printing on Xerox® multifunction printers by storing Xerox® software, as well as, the barcode fonts on the printer hard disk. Enables the printing of barcodes from any application (SAP client or mainframe) that supports PostScript printing. Information available at www.office.xerox.com/Software-Solutions
Xerox®Embedded Web Ser	ver - Integrated Device Web Page
Device Status	Web server embedded in Network Controller: • Tray status/contents • Consumables status • Alerts Remote Control Panel
Job Submission	Print ready files: PS, PCL, TIFF, PDF, JPG, XPS (requires XPS Print Kit), TXT, PRN Output feature selection (2-sided, output colour, collate, orientation, staple, hole punch, folding, output destination) Delivery options (Immediate, sample set, delay and secure, Save job or reprint)
Device Administration	Allows simple, remote installation setting of configuration options and management of the device. Fleet Orchestrator offers the ability to create a group of devices that securely share information with each other. Sharing is done via a secure connection between devices allowing a new communication model where devices have the ability to "talk" to each other and pass information/data back and forth. Data that can be shared consists of software upgrade files, clone files, and 1-Touch Apps.

Browsers	Internet Explorer 10.x, 11.x Safari 10.x, 11.x, 12.x Mozilla Firefox 45.x and higher Opera 25.x and higher Chrome 48.x and higher Edge 40.x and higher				
Support	Install print / scan drivers and online support available via web po	ige			
Languages Supported	International English, International French, Italian, German, Inte Russian, Simplified Chinese, Korean, Japanese, Arabic	rnational Spanish, Dutch, Brazilian Portuguese, Swedish, N	Norwegian, Danish, Finnish,		
Remote Services					
Xerox® Automatic Meter Readings (AMR)	Automates the process of collecting and submitting meter reads time-consuming end-user involvement and ensures that meter re	for tracking and billing of Xerox®device usage. Eliminates ads are submitted to Xerox on time.	the need for		
Xerox® Automatic Supplies Replenishment (ASR)	Automatically orders supplies for Xerox® output devices based on	actual usage, eliminating the need to manually manage	supplies inventory.		
Accounting					
Xerox®Standard Accoun	ting (Standard)				
Tracking	Copy, Print, Fax, Scan and Email usage				
Accounting	Up to 2,497 User Accounts (User ID) Up to 500 General Accounts (Client) Up to 498 Group accounts (Department)				
Features	Administrator can manage the feature via the Web User Interf Administrator has the ability to import or export user accounts,		industry standard CSV file.		
Accounting Options – Ne	etwork Accounting Enablement (Allows central server to manage	all accounting)			
	Enhanced network accounting with up-to-the-minute data on h Comprehensive management and enterprise scale tracking and Numerous solutions are available through Xerox Alliance Partne Security enhancements with the addition of HTTPS protocol su Device requests account authentication from third party server Accept Authentication Login at control panel and pass to third Interface with third party accounting terminal for accounting u	I reporting of device usage of copy, print, scan and server ers. For details visit www.xerox.com pport enabling larger databases of users and accounts party Networking Account	fax		
Supplies	Description	Quantity	Part Number		
Supplies					
Toner Cartridge (Sold)	Includes 2 Toner Cartridges	100,000 pages (50,000 pages each) ⁴	006R01683		
Toner Cartridge (Metered)	Includes 2 Toner Cartridges	100,000 pages (50,000 pages each) ⁴	006R01604		
Staple Cartridges	Cartridges Office Finisher with Booklet Maker – saddle-stitch stapling (B8045/B8055/B8065/B8075 only) 2,000 per cartridge (8,000 staples)				
	HVF and HVF with Booklet Maker (B8065/B8075/B8090 only) • Complete Cartridge Refill Cartridge	5,000 per cartridge 5,000 per cartridge (15,000 staples)	008R12912 008R12898		
	HVF with Booklet Maker – Saddle-Stitch Stapling (B8065/B8075/B8090 only)	2,000 per cartridge (16,000 staples)	008R12897		
	Convenience Stapler (may require Work Surface), Office Finisher • Complete Cartridge • Refill Cartridge	5,000 per cartridge 5,000 per cartridge (15,000 staples)	008R12964 008R12941		
Drum Cartridge		Up to 200,000 ^s	013R00675		

Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

² Expected regular monthly throughput; ¹ Paper capacities are based on 75 gsm stock; capacities will vary with different weight stocks; ⁴ Average standard pages. Declared in accordance with ISO/IEC 19752. Yield will vary based on media size, image area, coverage, Print Mode, media orientation and usage patterns; ⁵ 200,000 yield will vary depending on job length, media size/orientation and machine speeds

Return spent imaging supplies through the Xerox Green World Alliance collection/reuse/recycling programme. For more information, visit www.xerox.com/About-Xerox/Recycling.



