



Simply superb colour printing





Call today. For more information or detailed product specifications, call **00 800 9000 9090**. Or visit us at **www.xerox.com/office**

EFI® Fiery® Network Colour Server on the Xerox DocuColor 240/250

With the EFI Fiery network colour server on your Xerox DocuColor 240/250 printer-copier, you can count on world-class colour and superior workflow. Here are some of the features and benefits you'll enjoy:

- ColorWise® provides outstanding colour management tools for producing precise, accurate colour from all applications, platforms and formats
- Command WorkStation® 4.4 makes it easy to programme, monitor and manage workflows
- Variable data printing capabilities enable you to customise your output to a specific audience with varying text, photos and graphics
- EFI Fiery Scan allows you to convert hard copy documents into digital data that you can print, integrate into another document, email or convert into multiple file formats
- Fiery Driver 2.5 based booklet creation for in-line Saddle Stapling, Perfect and Gang-Up for off-line finishing

PRINTER-COPIER SUPPORTED

- DocuColor 240/250

PROCESSOR

- Intel® Celeron® 2.8 GHz (minimum)

MEMORY

- 512 MB

HARD DISK DRIVE

- 80 GB

CONTROLLER OPERATING SYSTEM

- Linux

NETWORK CONNECTIVITY

- Ethernet 10/100/1000 Base-T Autosensing

PAGE DESCRIPTION LANGUAGES

- Adobe® PostScript® 3™ (v3016)
- PCL 6C (emulation)

PRINT SPECIFICATIONS

Print resolution

- 2400 x 2400 dpi

Pages per minute

- DocuColor 250 – Up to 50 ppm colour, 65 ppm black and white
- DocuColor 240 – Up to 40 ppm colour, 55 ppm black and white

First-print-out time

- As fast as 7.8 seconds colour, 4.3 seconds black and white

SCAN RESOLUTION

- 200 x 200 dpi, 300 x 300 dpi, 400 x 400 dpi, 600 x 600 dpi

MAXIMUM IMAGE SIZE

Print

- Maximum Area – 323 x 480 mm
- Maximum Guaranteed – 317 x 480 mm

Scan

- Maximum Area – 297 x 432 mm
- Maximum Guaranteed – 297 x 432 mm

PRINT DRIVERS

Fiery Driver 2.5 (Bi-Directional) support for:

- Windows® 2000
- Windows® XP
- Windows® 2003 Server
- Mac OS® 9.2 / 10.2.3 and later

DRIVER CERTIFICATION

- WHQL Certified

FIERY UTILITIES

(enabled on PC and Apple Operating systems)

- Command WorkStation 4.4
- EFI ColorWise
- Fiery Downloader
- Fiery WebTools
- Fiery Remote Scan
- FreeForm for Variable Data Printing
- Spot-On Colour
- Auto Trapping

CALIBRATION

- ColorCal® (standard)
- X-Rite® DTP 32 Series II Densitometer (optional)
- Also supports X-Rite DTP41/34 and ES1000

DOCUMENT MANAGEMENT

- RIP while print
- Continuous Print
- Face-up and Face-down printing
- Fiery Scan and Scan-to-Job templates
- Fiery Driver 2.5 based booklet creation

STANDARD COLOUR PROFILES

- SWOP-Coated
- ISO-coated
- ISO-uncoated
- DIC
- Euroscale
- TOYO Offset Coated 2.0

FONTS

- 136 Adobe fonts
- 80 PCL 6C (emulation) fonts

OPTIONS

- X-Rite DTP 32 Series II Densitometer (optional)
- Secure Disk Erase
- EFI Profiler Kit
- Impose 2.5
- 512 MB memory upgrade

SECURITY

- Secure Disk Erase
- Scan to mailbox / Job template password

POWER REQUIREMENTS

- Controller power supplied by the DocuColor 240/250 engine. No additional power service is required. 220 – 240v – 10 Amp

Novell



Adobe® PostScript® 3™

