

XEROX[®]

DocuColor[®] 240 / 250



Technology | Document Management | Consulting Services

EFI[®] Splash[®] Workflow Software

High speed.
Precision color.





Splash RPX-i Workflow Software on the Xerox DocuColor 240 / 250

Adding the Splash RPX-i software turns the already sophisticated DocuColor 240/250 printer-copier into the ultimate toolkit for the graphic arts professional. Employ color management, document management and production features that will satisfy the precision printing needs of the most demanding creative assignment.

- ColorCal offers a closed-loop calibration system using a simple yet effective scan-and-print interface.
- Color Tuner lets the user edit the output color of RIPped pages before printing all copies of the job. Color Tuner can be used to make minimal corrections not provided by color profile selection and calibration and to make significant corrections to color content.
- Hot Folders allow users to create multiple drop folders and apply a specific set of job options to any Postscript, TIFF, EPS, PDF, or DCS 2.0 files placed in the folder. Users can create unlimited numbers of Hot Folders.
- Save time, eliminate waste, and reduce costs with Job Pre-Flighting, which gives DocuColor 240 / 250 printer-copier users the power to review jobs for errors before their projects hit paper.
- Standard Splash production features include Schedule Job (to automate workflow) and SetBuilder (group documents and print them with one set of commands).
- Users can choose from two configurations: direct connect Splash to the EFI Bustled Controller (turning the DocuColor 240 / 250 into a dedicated Splash system) or network connect (run the DocuColor 240/250 as a Splash or as an EFI Fiery Network Color Server – the choice is yours).

Call today. For more information or detailed product specifications, call **1-800-ASK-XEROX**. Or visit us at www.xerox.com/office

PRINTER/COPIER SUPPORTED

- Xerox DocuColor 240 / 250 with EFI Bustled Controller

PRINT SPECIFICATIONS

Print resolution

- 2400 x 2400 dpi for all supported page sizes

Scan resolution

- Up to 600 x 600 dpi

PAGE DESCRIPTION LANGUAGES

- Adobe® PostScript® 3™
- PDF Native
- Compatible with PDF-X, CT/LW, PSD

COLOR MANAGEMENT

Monitor matching, Mixed TIFF/EPS, Spot color workflow, Color Sync 2.6 compatible, Mixed RGB/CMYK, Press (SWOP, Euroscale, SNAP, TOYO, DCI Simulation, Import RGB, CMYK, and Output Profiles).

CALIBRATION

Color sets, ColorCal, Random patches, Calibration for unique stocks, expert mode, AutoGrey.

MAXIMUM PRINTING AREA

Supports full bleed printing on oversized media

Paper Size	Maximum Printable Area
13 x 18 in. (SRA3)	12.4 x 18.7 in. (317 x 480 mm)

EASE OF USE

Graphic user interface

Previews of RIPped jobs, Customizable status windows, Drag and drop management, Full job recovery, Active queue job management.

CUSTOM DRIVER

Provides application-independent color management.

DOCUMENT MANAGEMENT

Collation, Reverse order printing, Continual print, RIPwhile-receive, DCS 2.0, EPS, PDF, PostScript 1.4, TIFF, and TIFF-IT, PDF-X, CT/LW, PSD direct print, remote job manipulation via Apple personal Web server are all supported.

Hot Folders for Mac, Secure Printing, Set Builder, Imposition, Secure Access, Print Information.

PREPRESS FEATURES

Preflight, Progressives, Custom CMYK profiles, Userdefinable screening, Control strip, Auto-trapping (application independent), Dynamic edge smoothing, Custom page size, Separations, Spot color separations, Screen DMax, Selectable copier screening, Spot Color Editor, Color Tuner.

FONTS

- 136 Adobe fonts plus two multi-master fonts included.

NETWORK CONNECTIVITY

- Ethernet 10/100/1000 Base-T

NETWORKING PROTOCOLS

- TCP/IP
- AppleTalk™
- Novell 5.1 and 6.0 (NDPS and Unix Printing Services)
- Unix and Windows

SUPPORTED DOCUCOLOR 240 / 250 OPTIONS

- All DocuColor 240 / 250 options are supported

PRINT DRIVERS

- Macintosh OS X™
- Macintosh OS 9®
- Windows 2000®
- Windows 2003®
- Windows XP®

MINIMUM COMPATIBLE HOSTS FOR SPLASH RPX-i WORKFLOW SOFTWARE

- G5 PowerPC or Intel (iMac is not supported)
- Built-in Ethernet connection (direct connect requires 2 Ethernet ports on the Mac)
- Macintosh OS 10.4.3 or later
- 60 GB minimum hard drive
- 1024 x 768 dpi resolution monitor
- Combo (DVD-R/CD-RW) or SuperDrive (DVD-RW/CD-RW) drive
- 1 GB minimum host memory



Adobe® PostScript® 3™

© 2006 Xerox Corporation. All rights reserved. Xerox® and DocuColor® are registered trademarks of Xerox Corporation in the United States and other countries. Adobe® and PostScript® 3™ are trademarks or registered trademarks of Adobe, Inc. Intel® and Celeron® are registered trademarks of Intel Corporation. EFI®, Fiery®, ColorCal®, ColorWise®, Command WorkStation® and Spot-On® are registered trademarks of Electronics for Imaging, Inc. X-Rite® is a registered trademark of X-Rite, Incorporated. Windows® is a registered trademark of Microsoft Corporation. Mac OS® is a registered trademark of Apple Computer, Inc. As an ENERGY STAR® partner, Xerox Corporation has determined that these products meet the ENERGY STAR guidelines for energy efficiency. The ENERGY STAR name and logo are registered U.S. trademarks. The information in this brochure is subject to change without notice.

3/07 610P725920B

D50BR-07UC