XEROX

ISO/IEC 19752 Yield Test Report

USE GENUINE XEROX SUPPLIES MADE FOR EACH OTHER

Phaser 3500 Toner Cartridge (Standard Capacity)

Declaration of Yield:

Published Cartridge Yield: 6,000 standard pages
Declared yield value in accordance with ISO/IEC 19752

Average:	6,499
Standard Deviation:	4
90% Lower Confidence:	6,497

	Start	**End**
Date Tested:	25-May-2005	5-Aug-2005

Number of Cartridges used in testing:	9
Number of Cartridges used in calculations:	9
Type of Cartridge:	All-in-one
Shake Procedure Used?	Yes
Print mode:	Continuous (500pages/job)
Number of engines used in testing:	3
Media Used:	Samsung Premium (75gsm)
Paper Weight:	75gsm
Paper Size:	A4
Paper feed orientation:	Short edge feed (SEF)
Computer Model:	M5950 (Samsung)
Driver Version:	0.61 (PCL6. Phaser 3500)
Operating System:	Win_XP
Application Software:	Adobe Acrobat Professional 6.01
Test Page Version:	Version 4.0
Power (off/on) everyday?	Yes

Cartridge Serial Number	Printer Serial Number	Temperature (°C) Avg.	Max	Min	Humidity (%RH) Avg.	Max	Min	Cartridge Yield	Included in calc.
520010	PRS-LV-012	24.5	25.0	24.0	45	47	42	6,500	y
520008	PRS-LV-014	24.5	25.0	24.0	45	47	42	6,500	y
520001	PRS-HV-008	24.5	25.0	24.0	48	50	45	6,500	y
KRE1JC9603398FDJ78Y6UO003	PRS-LV-012	25.0	26.0	24.0	45	47	42	6,501	y
KRE1JC9603398FDJ78Y7PS005	PRS-LV-014	25.0	26.0	23.0	45	47	42	6,501	y
KRE1JC9603398FDJ78Y7PS003	PRS-HV-008	25.0	26.0	23.0	45	47	42	6,501	y
KRE1JC9603398FDJ78Y7PS004	PRS-LV-012	24.5	25.0	23.0	48	50	45	6,501	y
KRE1JC9603398FDJ78Y7PS001	PRS-LV-014	24.5	25.0	23.0	48	50	45	6,501	y
KRE1JC9603398FDJ78Y7PS002	PRS-HV-008	24.5	25.0	23.0	48	50	45	6,490	y

Comments: