



# ISO/IEC 19752 Yield Test Report



## Phaser 4500 Toner Cartridge (Standard Capacity)

Declaration of Yield:

**Published Cartridge Yield: 10,000 standard pages**  
**Declared yield value in accordance with ISO/IEC 19752**

Average: 10,313  
 Standard Deviation: 365  
 90% Lower Confidence: 10,087

**Date Tested:**                      **Start**                      **End**  
    18-May-2007                      1-Jun-2007

Number of Cartridges used in testing: 9  
 Number of Cartridges used in calculations: 9  
 Type of Cartridge: Standard Capacity Cartridge  
 Shake Procedure Used? yes  
 Print mode: Continuous (500pages/job)  
 Number of engines used in testing: 3  
 Media Used: Xerox 4200  
 Paper Weight: 20lb  
 Paper Size: A4  
 Paper feed orientation: Long Edge Feed (LEF)  
 Computer Model: Dell PC 1.2GHz  
 Driver Version: Xerox  
 Operating System: Windows XP  
 Application Software: Adobe Acrobat Professional 7.0.1  
 Test Page Version: ISO/IEC 19752:2004  
 Power (off/on) everyday? No

Cartridge Serial Number	Printer Serial Number	Temperature (°C)			Humidity (%RH)			Cartridge Yield	Included in calc.
		Avg.	Max	Min	Avg.	Max	Min		
CN-084K-10799-71R 2000000131	XWO3541	22.6	25.0	22.0	50.0	51.0	50.0	10,215	y
CN-084K-10799-71R 2000000108	XWO3541	22.5	22.8	22.3	50.0	51.0	49.0	10,640	y
CN-084K-10799-71R 2000000135	XWO3541	22.6	22.8	22.4	50.0	51.0	50.0	10,303	y
CN-084K-10799-71R 2000000119	XW03751	22.5	22.8	22.0	50.0	50.0	50.0	10,482	y
CN-084K-10799-71R 2000000146	XW03751	22.7	22.8	22.5	50.0	50.0	50.0	10,625	y
CN-084K-10799-71R 2000000147	XW03751	22.6	22.8	22.4	50.0	50.0	50.0	10,131	y
CN-084K-10799-71R 2000000137	XW03613	22.5	22.8	22.0	50.0	50.0	49.0	10,457	y
CN-084K-10799-71R 2000000138	XW03613	22.7	22.8	22.5	50.0	51.0	49.0	10,504	y
CN-084K-10799-71R 2000000139	XW03613	22.6	22.8	22.4	50.0	51.0	50.0	9,458	y

Comments: