

Xerox Phaser 8560W Solid Ink Yield

Declaration of Yield:

Published CMY Ink Stick Yield:	1,300 standard pages
Published K Ink Stick Yield:	1,300 standard pages
Average Composite CMY Ink Yield:	1,317 standard pages
Average K Ink Yield:	1,331 standard pages
Declared yield value in accordance with ISO/IEC 24711	

Published Ink Yield:	
3 Pack Yield (CMY)	3,900 standard pages
3 Pack Yield (K)	3,900 standard pages
Declared yield value in accordance with ISO/IEC 24711	

90% Lower Confidence
 Cyan: 1,331 Standard Pages
 Magenta: 1,384 Standard Pages
 Yellow: 1,244 Standard Pages
 Black: 1,331 Standard Pages

Date Tested: **Start** **End**
 21-Feb-2007 23-Feb-2007

Number of Ink Sticks used in testing: C=9, M=9, Y=9, K=9
 Number of Ink Sticks used in calculations: C=9, M=9, Y=9, K=9
 Type of Ink: Phaser 8560W Solid Ink
 Print mode: Continuous (500pages/job)
 Number of engines used in testing: 3
 Media Used: Xerox 4200
 Paper Weight: 20lb
 Paper Size: Letter
 Paper feed orientation: Short Edge Feed (SEF)
 Computer Model: Dell Latitude C640 4M 2.0GHz
 Driver Version: Walk Up Driver 2.0
 Operating System: Windows XP
 Application Software: Adobe Acrobat Professional 7.0.7
 Test Page Version: ISO/IEC 24712 FCD Test Suite
 Power (off/on) everyday? No

Printer #1: PP2-20

	Ink	Serial Number	Temperature (°C)			Humidity (%RH)			Ink Yield	Included in calc.
			Avg.	Max	Min	Avg.	Max	Min		
1st Set	C	na	22.0	23.0	22.0	46.0	47.0	45.0	1451	y
	M	na	22.0	23.0	22.0	46.0	47.0	45.0	1435	y
	Y	na	22.0	23.0	22.0	46.0	47.0	45.0	1300	y
	K	na	22.0	23.0	22.0	46.0	47.0	45.0	1420	y
2nd Set	C	na	22.0	22.0	22.0	46.0	48.0	46.0	1285	y
	M	na	22.0	22.0	22.0	46.0	48.0	46.0	1415	y
	Y	na	22.0	22.0	22.0	46.0	48.0	46.0	1265	y
	K	na	22.0	22.0	22.0	46.0	48.0	46.0	1372	y
3rd Set	C	na	22.0	23.0	22.0	47.0	48.0	45.0	1426	y
	M	na	22.0	23.0	22.0	47.0	48.0	45.0	1410	y
	Y	na	22.0	23.0	22.0	47.0	48.0	45.0	1200	y
	K	na	22.0	23.0	22.0	47.0	48.0	45.0	1339	y

Printer #2: PP2-14

	Ink	Serial Number	Temperature (°C)			Humidity (%RH)			Ink Yield	Included in calc.
			Avg.	Max	Min	Avg.	Max	Min		
1st Set	C	na	22.0	23.0	22.0	46.0	47.0	45.0	1392	y
	M	na	22.0	23.0	22.0	46.0	47.0	45.0	1298	y
	Y	na	22.0	23.0	22.0	46.0	47.0	45.0	1270	y
	K	na	22.0	23.0	22.0	46.0	47.0	45.0	1335	y
2nd Set	C	na	22.0	22.0	22.0	46.0	48.0	46.0	1361	y
	M	na	22.0	22.0	22.0	46.0	48.0	46.0	1463	y
	Y	na	22.0	22.0	22.0	46.0	48.0	46.0	1265	y
	K	na	22.0	22.0	22.0	46.0	48.0	46.0	1340	y
3rd Set	C	na	22.0	23.0	22.0	47.0	48.0	45.0	1360	y
	M	na	22.0	23.0	22.0	47.0	48.0	45.0	1424	y
	Y	na	22.0	23.0	22.0	47.0	48.0	45.0	1270	y
	K	na	22.0	23.0	22.0	47.0	48.0	45.0	1378	y

Printer #3: PP2-13

	Ink	Serial Number	Temperature (°C)			Humidity (%RH)			Ink Yield	Included in calc.
			Avg.	Max	Min	Avg.	Max	Min		
1st Set	C	na	22.0	23.0	22.0	46.0	47.0	45.0	1425	y
	M	na	22.0	23.0	22.0	46.0	47.0	45.0	1515	y
	Y	na	22.0	23.0	22.0	46.0	47.0	45.0	1257	y
	K	na	22.0	23.0	22.0	46.0	47.0	45.0	1453	y
2nd Set	C	na	22.0	22.0	22.0	46.0	48.0	46.0	1238	y
	M	na	22.0	22.0	22.0	46.0	48.0	46.0	1372	y
	Y	na	22.0	22.0	22.0	46.0	48.0	46.0	1253	y
	K	na	22.0	22.0	22.0	46.0	48.0	46.0	1252	y
3rd Set	C	na	22.0	23.0	22.0	47.0	48.0	45.0	1486	y
	M	na	22.0	23.0	22.0	47.0	48.0	45.0	1475	y
	Y	na	22.0	23.0	22.0	47.0	48.0	45.0	1266	y
	K	na	22.0	23.0	22.0	47.0	48.0	45.0	1430	y