



**Colour**

**Detailed Specifications**



*WorkCentre Pro 32 Colour.*



*WorkCentre Pro 40 Colour shown with High-Capacity Feeder and Office Finisher Options.*

	<b>WorkCentre® Pro 32 Colour Advanced Multifunction System</b>	<b>WorkCentre® Pro 40 Colour Advanced Multifunction System</b>
--	--	--

**OUTPUT SPEED – printing and copying**

	<b>Black and white</b>	<b>Colour</b>	<b>Black and white</b>	<b>Colour</b>
	32 images per minute (ipm) A4	16 ipm A4	40 ipm A4	22 ipm A4
	20 ipm B4	11 ipm B4	24 ipm B4	13 ipm B4
	17 ipm A3	9 ipm A3	20 ipm A3	11 ipm A3

**WorkCentre® Pro 32 Colour/40 Colour**

**NETWORK PRINTING – Smart Network Controller**

<b>Processor</b>	Intel® Celeron® 733 MHZ
<b>Memory</b>	128 MB RAM (256 MB max)
<b>System Disk</b>	18 GB minimum
<b>Printer Languages (auto switching)</b>	PostScript® 3 emulation TIFF PCL® 5c emulation PDF LCDS, SCS, XES and IPDS through third-party transforms

**NETWORK PRINTING – resolution, printing via CentreWare® software**

PostScript emulation: 600 x 600 dpi: 1200 x 1200 dpi  
PCL emulation: 600 x 600 dpi





## WorkCentre® Pro 32/40 Colour Advanced Multifunction Systems

## NETWORK PRINTING – printing features\*

Secure print  
 Delay print (specific time)  
 Sample set  
 Booklet creation  
 Cover selection  
 Paper selection by attribute  
 N-up  
 Output tray selection  
 Watermark  
 Fit to new paper size  
 Transparency interleave  
 Banner sheet enable/disable  
 Image quality  
 Store and recall driver settings

## PRINT PROTOCOLS AND NETWORKS

**Physical**

Ethernet 100BaseT/10BaseT, 10Base2, 10Base5 via adapter  
 USB printer port (optional)  
 Wireless Ethernet (IEEE 802.11b) via third-party adapters

**Operating Systems**

Microsoft® Windows® 95, 98, Me® (Millennium), NT® 4.0, 2000, XP®  
 Novell® NetWare® 4.x, 5.x, 6  
 Mac OS® 8.x, 9.x, OS X  
 Solaris® 2.5.1, 2.6 and higher  
 HP-UX® 10.2, 11.x  
 IBM AIX® 4.2 and higher  
 Linux® Intel®  
 – Red Hat®  
 – Caldera®  
 – Mandrake™ (LPRNG printing infrastructure)  
 – Corel® (i386)  
 – TurboLinux® (i386)  
 – SuSE® (i386)  
 Linux Power PC®  
 – TurboLinux Server 6.0.2

**Network Protocols**

TCP/IP: Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, NetBIOS, HTTP  
 NetWare: Bindery and NDS IPX/SPX, NDPS®/NEPS (with Server Gateway)  
 AppleTalk®: EtherTalk®  
 Microsoft Windows Networking over IP and NetBEUI

\*Note: Not all features are available in every driver.



## WorkCentre® Pro 32/40 Colour Advanced Multifunction Systems

## PRINT PROTOCOLS AND NETWORKS

**Administration Protocols** DHCP, BOOTP, SNMP, WINS, DDNS, SLP® v2, HTTP, RARP, DHCP Autonet

**Fonts** PostScript 3: 136 PostScript standard fonts  
PCL: 80 scalable fonts, line printer and bitmap format line printer fonts  
Font Management Utility for downloading additional fonts

<b>Print Drivers</b>	<b>Environment</b>	<b>PCL5c</b>	<b>PostScript</b>
	Windows 95/98/Me	Bidirectional (enhanced*)	Bidirectional (enhanced*)
	Windows NT 4.0	Bidirectional with user-selectable interface (standard** and enhanced)	Bidirectional with user-selectable interface (standard** and enhanced)
	Windows 2000/XP (WHQL certified)	Bidirectional with user-selectable interface (standard and enhanced)	Bidirectional with user-selectable interface (standard and enhanced)
	Macintosh® System 8.x, 9.x, OS X	N/A	Generic PPD
	Macintosh® System 9.x	N/A	Bidirectional via AppleTalk
<b>Print Submission Tools</b>	<b>Environment</b>	<b>PostScript</b>	<b>PCL</b>
	Solaris 2.5.1, 2.6 and higher; IBM AIX 4.2 and higher; LPRNG printing infrastructure; Linux Intel and Linux Power PC	Submission Tool with full feature set (includes administration, GUI/TTY print driver and software installation)	Submission Tool only
	TIFF/PDF: Supported in Windows 95/98/Me/NT 4.0/2000/XP	Submission Tool for any TIFF or PDF file	

\*Enhanced: Xerox custom graphical user interface.

\*\* Standard: Driver based on Microsoft tree-structure user interface (includes Xerox features and functionality).



## WorkCentre® Pro 32/40 Colour Advanced Multifunction Systems

## CENTREWARE® INTERNET SERVICES – integrated device Web page

<b>Device Status</b>	Web server embedded on SMart network controller – Tray status/contents – Consumables status
<b>Print Queue Viewing</b>	Complete job print queue management – hold, release, promote and delete
<b>Job Submission</b>	Print-ready files (PS, PCL, TIFF, PDF) Output feature selection
<b>Device Administration</b>	Allows simple, remote installation setting of configuration options and management of the device
<b>Browsers</b>	Windows XP, 2000/NT 4.0/Me/98/95: Netscape Navigator® 6.x, Microsoft Internet Explorer 5.x/6.x Macintosh 9.x/OS X: Netscape Navigator 6.x Linux: Netscape® Navigator 6.x

## NETWORK SCANNING (optional\*)

<b>Capability</b>	Colour Scanning, Black and White Scanning
<b>Concurrency</b>	Scan while the system is printing copy or network print jobs, or while it is transferring scan to network or fax jobs
<b>Input Speed</b>	Scan at rated speed (32 ipm black and white/22 ipm colour) (A4 long edge feed [LEF])
<b>Resolutions</b>	600 x 600 dpi 400 x 400 dpi 300 x 300 dpi 200 x 200 dpi Bit depth: 1 bit (black and white), 8 bit (greyscale), 24 bit (colour)
<b>Maximum Scan Area</b>	297 x 432 mm
<b>Authentication</b>	Optional secure device login with network user name and password Supports Kerberos (Windows 2000/UNIX), SMB (Windows NT 4.0/Windows 2000), and Novell NetWare 4.x/5.x/6.x Optional PIN-based guest login
<b>Network Protocol</b>	Novell (NCP via IPX/SPX) FTP via TCP/IP Microsoft SMB
<b>File Formats</b>	TIFF 6.0 with G3 MH, G4 MMR, or JPEG compression (single page or multiple pages) PDF with G3 MH, G4 MMR, JPEG or MRC compression JFIF with JPEG compression
<b>Document Management Fields</b>	One to six user-programmable metadata fields per scan job Customised fields viewed on user interface Variable data entered using virtual keyboard

Continued

\*Also available as standard on some configurations.



## WorkCentre® Pro 32/40 Colour Advanced Multifunction Systems

NETWORK SCANNING (optional) *Continued*

<b>Scan Destinations</b>	<p>Scan to network server</p> <p>Scan to remote e-mail destinations via direct SMTP addresses</p> <p>Scan to e-mail via optional CentreWare® Scanning Services using MAPI 32-bit compliant e-mail client</p> <p>Scan to application (workflow, Electronic Document Management System)</p> <p>Scan to Microsoft Exchange Public Folders</p> <p>Scan to PC Desktop™ (Standard and Deluxe editions)</p> <p>Scan to Windows XP Client via WIA (Windows Image Acquisition)</p>
<b>Network Scanning With E-Mail</b>	<p>Scan to network directory</p> <p>Scan to e-mail distribution</p> <p>Scan to Xerox or third-party applications</p> <p>Scan to Windows XP Client (requires WIA driver, downloadable from <a href="http://www.xerox.com/office">www.xerox.com/office</a>)</p>
<b>Scanning Software Options</b>	<p>Scan to PC Desktop Standard – everything in Network Scanning With E-Mail, plus:</p> <ul style="list-style-type: none"> <li>– Xerox CentreWare® Scanning Services (template-based scanning to desktops or e-mail for repetitive tasks)</li> <li>– ScanSoft® PaperPort® SE 1.0 – image viewing and file management software</li> <li>– ScanSoft OmniPage® SE 1.0 – OCR and file format conversion software</li> </ul> <p>Scan to PC Desktop Deluxe – everything in Network Scanning With E-Mail, plus:</p> <ul style="list-style-type: none"> <li>– Xerox CentreWare® Scanning Services (template-based scanning to desktops or e-mail for repetitive tasks)</li> <li>– ScanSoft PaperPort Deluxe 8.0 – advanced image viewing and file management/sharing software</li> <li>– ScanSoft OmniPage Pro* 11.0 – advanced OCR and file format conversion software</li> </ul>

## E-MAIL (included with Network Scanning Option)

<b>Capability</b>	<p>Colour scanning</p> <p>Direct document e-mail from device</p> <p>Manual address entry or directory (Exchange/Notes/LDAP) address searching</p>
<b>Resolutions</b>	<p>600 x 600 dpi</p> <p>400 x 400 dpi</p> <p>300 x 300 dpi</p> <p>200 x 200 dpi</p> <p>Bit Depth: 1 bit (black and white), 8 bit (greyscale), 24 bit (colour)</p>
<b>Maximum Scan Area</b>	297 x 432 mm
<b>Network Protocol</b>	SMTP, MIME encoded
<b>Authentication</b>	<p>Optional secure device login with network user name and password</p> <p>Supports Kerberos (Windows 2000/UNIX), SMB (Windows NT 4.0/Windows 2000), and Novell NetWare 4.x/5.x/6.x</p> <p>Optional PIN-based guest login</p>
<b>Directory Access</b>	<p>Corporate address list via LDAPv3 (Exchange/Notes)</p> <p>Downloaded address list (comma-separated file format)</p>
<b>File Formats</b>	<p>TIFF 6.0 with G3 MH, G4 MMR, or JPEG compression (single page or multiple pages)</p> <p>PDF with G3 MH, G4 MMR, JPEG or MRC compression</p> <p>JFIF with JPEG compression</p>

\*Advanced optical character recognition (OCR) software



## WorkCentre® Pro 32/40 Colour Advanced Multifunction Systems

**COPYING**

<b>Document Scanner</b>	Duplex Automatic Document Feeder with 50-sheet capacity
<b>Sides (input:output)</b>	1:1, 1:2, 2:2 and 2:1
<b>Quantity</b>	1 to 9,999
<b>Resolution</b>	600 x 600 dpi
<b>Concurrency</b>	Concurrent scanning and printing
<b>Digital Imaging</b>	<ul style="list-style-type: none"> <li>AutoIQ automatic digital image quality control</li> <li>Auto rotation 180° or 270° when needed</li> <li>Image shift</li> <li>Edge erase</li> <li>Auto centring</li> <li>Original type selection (photo/text, photo, text, map, inkjet, highlighted)</li> <li>Lighter/darker</li> <li>Background suppression</li> <li>Contrast</li> <li>Sharpness</li> <li>Screening</li> <li>Negative image</li> <li>Mirror image</li> </ul>
<b>Copy Pre-collation Memory</b>	256 MB plus 18 GB hard disk drive
<b>Reduction/Enlargement</b>	<ul style="list-style-type: none"> <li>Variable zoom from 25% to 400% in 1% increments</li> <li>Anamorphic zoom</li> <li>Six user-programmable percentages</li> </ul>
<b>Special Features</b>	<ul style="list-style-type: none"> <li>Auto colour detection</li> <li>Auto paper select</li> <li>Auto reduction/enlargement to fit selected paper size</li> <li>Auto registration</li> <li>Auto tray switching</li> <li>Automatic job recovery</li> <li>Booklet creation</li> <li>N-up – up to six columns by six rows</li> <li>Transparency dividers</li> <li>Covers insertion (front only, front and back, back only; blank or printed)</li> <li>Build Job (produce multiple sets from stored job segments)</li> <li>Store and recall job programming</li> <li>Job interrupt</li> <li>Bound document copying</li> <li>Sample set</li> <li>Mixed-size originals</li> <li>Context-sensitive help screens</li> </ul>

Continued



## WorkCentre® Pro 32/40 Colour Advanced Multifunction Systems

**COPYING** *Continued*

<b>Foreign Device Interface (optional)</b>	Interface to third-party access control devices, coin machines and card readers Supports a variety of vending stations available through the Xerox Custom Application Service
--	--

**INTERNET FAX (optional)**

<b>Capability</b>	<b>Ability to send documents in colour</b> Direct document transmission to remote Internet Fax machines or e-mail clients (SMTP) Reception and automatic printout of documents in colour and black and white sent via e-mail from remote Internet Fax machines or e-mail clients
-------------------	--

<b>Maximum Scan Area</b>	297 x 432 mm
--------------------------	--------------

<b>Authentication</b>	Optional secure device login with network user name and password Supports Kerberos (Windows 2000/UNIX), SMB (Windows NT 4.0/Windows 2000), and Novell NetWare 4.x/5.x/6.x Optional PIN-based guest login
-----------------------	--

<b>Address Directory</b>	Corporate address list via LDAPv3
--------------------------	-----------------------------------

<b>Access</b>	Downloaded address list (comma-separated file format)
---------------	---

<b>File Formats</b>	TIFF-FX Profiles S, F with G3 MH, GM MMR, or JPEG compression PDF with G3 MH, G4 MMR, JPEG or MRC compression
---------------------	--

<b>Resolutions</b>	600 x 600 dpi 400 x 400 dpi 300 x 300 dpi 200 x 200 dpi Bit Depth: 1 bit (black and white), 8 bit (greyscale), 24 bit (colour)
--------------------	--

<b>Network Protocols</b>	SMTP POP3 (RFC 1939)
--------------------------	-------------------------

<b>Compliance</b>	ITU-T T.37 compliant
-------------------	----------------------

**NETWORK FAX SERVER INTEGRATION (optional)**

<b>Fax Send Features</b>	One- or two-sided scanning Phone number entry Add to send list (50 numbers maximum) Delay send (specific time) Resolution selection (fine, standard) Image quality selection (normal, text, halftone photo, photo, background suppression, seven levels of contrast, seven levels of sharpness)
--------------------------	--

*Continued*



## WorkCentre® Pro 32/40 Colour Advanced Multifunction Systems

NETWORK FAX SERVER INTEGRATION (optional) *Continued*

<b><i>Fax Print Features</i></b>	One- or two-sided printing Quantity Staple on/off Collate on/off Finisher output tray selection (top tray or main tray) Secure print on/off
<b><i>Authentication</i></b>	Optional secure device login with network user name and password Supports Kerberos (Windows 2000/UNIX), SMB (Windows NT 4.0/Windows 2000), and Novell NetWare 4.x/5.x/6.x Optional PIN-based guest login
<b><i>Fax Vendors</i></b>	Multiple vendors, certified by the Xerox Business Partners Program For details, visit <a href="http://www.xerox.com">www.xerox.com</a>

## DEVICE MANAGEMENT

<b><i>Management Support</i></b>	SNMP Version 1 and SNMP Version 2c trap MIB access (IETF-MIB II RFC 1213), Host Resources MIB RFC 2790, Printer MIB RFC 1759 v. 2
<b><i>CentreWare Network Services</i></b>	Device Discovery wizard (available at <a href="http://www.xerox.com">www.xerox.com</a> ) Device Administration wizard (available at <a href="http://www.xerox.com">www.xerox.com</a> ) Font Management Utility
<b><i>Xerox CentreWare Web</i></b>	A Web-based server application for network administrators that permits Web browser-based device management from any workstation, whether running Windows or UNIX or any other operating system Works with any SNMP-managed printer from any manufacturer Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management Requires Windows XP or 2000 (Professional or Advanced Server) and Internet Explorer 5.01 or higher
<b><i>Novell NDPS/NEPS (gateway for WorkCentre Pro)</i></b>	Server gateway application: Centralised management tool provides streamlined installations via printer agents, automated printer driver installation and downloads, printer and job configuration, configurable event notification
<b><i>Xerox CentreWare® for Unicenter TNG®</i></b>	Provides added identification to the general discovery performed by Unicenter TNG and the ability to see the device under a Unicenter TNG Business Process View Provides full integration with event management and the choice to integrate with problem management and advanced Help Desk
<b><i>Xerox CentreWare® for Tivoli® NetView®</i></b>	Provides for the identification of Xerox N-Series printers and WorkCentre Pro multifunction devices in the general discovery performed by Tivoli NetView Provides the ability to see the discovered Xerox printers/devices in a Xerox Printers Set in addition to the Printers SmartSet Provides full integration with the NetView and Event Browser and Tivoli Enterprise Console (TEC)

*Continued*



## WorkCentre® Pro 32/40 Colour Advanced Multifunction Systems

DEVICE MANAGEMENT *Continued*

<b>Xerox CentreWare® MC for Microsoft Management Console (MMC)</b>	CentreWare MC Snap-in supports printer discovery and management via a Microsoft Management Console (MMC) link to an embedded Web server in NT and Windows 2000 environments. It is a general-purpose management display framework for hosting administrative tools
<b>Xerox CentreWare® for HP® OpenView®</b>	Provides for the identification of Xerox N-Series printers and WorkCentre Pro multifunction devices in the general discovery performed by HP OpenView Provides the ability to see the current status of discovered Xerox printers/devices under a Xerox PrinterMap and IP Map via colour-coded icons Provides traps and message updates to the OpenView alarm browser and the ability to launch CentreWare Internet Services for device management directly from OpenView
<b>Xerox Plug and Print 2000</b>	Plug and Print 2000 (PnP2000) is an administrative service program that simplifies enterprise-wide printer installs and relocations for Windows 2000 environments. The product discovers devices, automatically installs devices, enables sharing printers to users, and provides install reports – all through a user-friendly interface
<b>Xerox Device Types for SAP R/3 Environment</b>	Simplifies printing in SAP R/3 environments by providing users of SAP R/3 v4.6C, 4.x and 3.x ERP applications with enhanced WorkCentre Pro printing functionality (PostScript and PCL): – Simplex or duplex printing – Finishing – single or dual stapling – Tray pull location from any tray – Print security via PIN ID capability at the WorkCentre Pro
<b>Xerox SAP R/3 Intelligent Barcode Utility</b>	Provides built-in process intelligence that allows the printing of barcodes on any appropriately configured PostScript printer on the SAP R/3 4.x (or higher) network. Used in conjunction with Xerox Device Types for SAP R/3 Environment and Xerox Font Center Barcode Fonts. Utility automatically calculates checksum, placement of start/stop characters, and encoding of data string

## PAPER HANDLING – Duplex Automatic Document Feeder

<b>Capacity*</b>	50 sheets
<b>Speed</b>	32 ipm A4 long edge feed (LEF)
<b>Paper Sizes Sensed</b>	A5 long edge feed (LEF) or short edge feed (SEF) A4 LEF or SEF B4 SEF A3 SEF B5 SEF
<b>Weights</b>	50 to 120 gsm

\*Paper capacities are based on 20 lb/75 gsm stock; capacities will vary with different weight stocks.



## Colour

## WorkCentre® Pro 32/40 Colour Advanced Multifunction Systems

## PAPER HANDLING – Bypass Tray

<b>Capacity*</b>	100 sheets
<b>Sizes</b>	A6 to SRA3
<b>Weights</b>	60 to 220 gsm
<b>Types</b>	Letterhead Bond Preprinted forms Hole-punched Recycled paper Transparencies Custom (user defined) Lightweight Heavyweight Envelopes

## PAPER HANDLING – Front-Loading Paper Tray (standard)

<b>Tray 1</b>	520 sheets
<b>Sizes</b>	User adjustable from A5 to A3
<b>Weights</b>	64 to 105 gsm
<b>Types</b>	Letterhead Bond Preprinted forms Hole-punched Recycled paper Transparencies Custom (user defined)

\*Paper capacities are based on 20 lb/75 gsm stock; capacities will vary with different weight stocks.



## WorkCentre® Pro 32/40 Colour Advanced Multifunction Systems

## PAPER HANDLING – INPUT TRAY OPTIONS – One Tray with Stand Option

<b>Tray 2</b>	520 sheets
<b>Sizes</b>	User adjustable from A5 to A3
<b>Weights</b>	64 to 105 gsm
<b>Types</b>	Letterhead Bond Preprinted forms Hole-punched Recycled paper Custom (user defined)
<b>Total Capacity</b>	1,140 sheets (Includes Tray 1, Tray 2 and Bypass Tray)

## PAPER HANDLING – INPUT TRAY OPTIONS – Three Tray Option (Tray One and Two plus Two-Tray Module)

<b>Tray 2 – Tray 4</b>	520 sheets
<b>Sizes</b>	User adjustable from A5 to A3
<b>Weights</b>	64 to 105 gsm
<b>Types</b>	Letterhead Bond Preprinted forms Hole-punched Recycled paper Custom (user defined)
<b>Total Capacity</b>	2,180 sheets (Includes Tray 1, Tray 2, Trays 3-4 and Bypass Tray)

## PAPER HANDLING – INPUT TRAY OPTIONS – High-Capacity Feeder Option

<b>Tray 2</b>	520 sheets
<b>Sizes</b>	User adjustable from A5 to A3
<b>Tray 3 and Tray 4</b>	2,000 sheets
<b>Sizes</b>	B5, A4
<b>Weights</b>	64 to 105 gsm
<b>Types</b>	Letterhead Bond Preprinted forms Hole-punched Recycled paper Custom (user defined)
<b>Total Capacity</b>	3,140 sheets (Includes Tray 1, Tray 2, High-Capacity Feeder and Bypass Tray)



## WorkCentre® Pro 32/40 Colour Advanced Multifunction Systems

## PAPER HANDLING – Convenience Stapler Option

**Capacity\*** Up to 50 sheets (5,000 staples per cartridge)

## OUTPUT – Centre Tray

**Stacking Tray** 400 sheets (200 sheets with finisher option)

**Sizes** A6 to SRA3

## OUTPUT OPTIONS – Office Finisher (50-sheet stapling)

**Stacking Tray** 1,000 sheets

**Sizes** B5 to A3

**Weights** 60 to 105 gsm

**Stapling** Single (any corner) and dual  
Auto stapling (50 sheets maximum)  
A3, A4, B4 and B5 sizes supported

## ACCOUNTING

**Accounting with  
Third-Party Server  
Applications (optional)** Up-to-the-minute data on how the WorkCentre Pro system is being used; comprehensive usage tracking and reporting; print, scan, copy and fax  
Multiple accounting vendors, certified by the Xerox Business Partner Program. For details, visit [www.xerox.com](http://www.xerox.com)

**Internal Auditron** Tracks and limits black and colour copy usage; supports up to 2,000 user accounts or 300 general accounts  
Auditron report printout  
Note: Option to upload/download account and usage data via direct connection using Microsoft® Windows-based software.

## WorkCentre® Pro 32 Colour/40 Colour

## BASIC CONFIGURATIONS\*\*

Network Multifunction System with network controller, stand, Duplex Automatic Document Feeder, two paper trays and centre output tray

\*Paper capacities are based on 75 gsm stock; capacities will vary with different weight stocks.  
\*\*Features, configurations and options may vary by location.



Colour

WorkCentre® Pro 32/40 Colour Advanced Multifunction Systems

ACCESSORY OPTIONS

- 128 MB Network Controller Memory
- Office Finisher (50-sheet stapling)
- Foreign Device Interface
- Network Accounting Enablement
- Network Scanning With E-Mail\*\*
- Network Server/Internet Fax
- Image Overwrite Security
- Scan to PC Desktop Client Software (Standard or Deluxe)
- USB Port Printing
- Convenience Stapler

ELECTRICAL REQUIREMENTS

220–240 V Nominal, 50 Hz, 10A

	WorkCentre® Pro 32 Colour	WorkCentre® Pro 40 Colour
<b>POWER CONSUMPTION</b>		
<i>Running</i>	< 672 watts	< 672 watts
<i>Standby</i>	< 240 watts	< 240 watts
<i>Low-Power Mode</i>	< 173 watts	< 204 watts
<i>Sleep Mode</i>	< 80 watts	< 80 watts
<i>Warm-up</i>	3 minutes (maximum)	3 minutes (maximum)
<i>Low-Power Recovery</i>	30 seconds (maximum)	30 seconds (maximum)

WorkCentre® Pro 32 Colour/40 Colour

ENVIRONMENTAL CONSIDERATIONS

<i>Required Temperature Range</i>	10° to 32° C
<i>Required Relative Humidity</i>	10% to 85%
<i>Heat Emission</i>	2,285 BTU/Hr running 720 BTU/Hr standby
<i>Noise Emission</i>	35.1 dB(A) standby 55.2 dB(A) running 59.4 dB(A) impulse

\*\* Also available as standard on some configurations.



Colour

United Kingdom  
Tel: 0870 241 3245

Eire  
Tel: 0818 300015

WorkCentre® Pro 32/40 Colour Advanced Multifunction Systems

DIMENSIONS AND WEIGHT

	<i>Width</i>	<i>Depth</i>	<i>Height</i>	<i>Weight</i>
<b>Fully Configured</b>	1,346 mm	636 mm	1,116 mm	274 kg

SPACE REQUIREMENTS

	<i>Width</i>	<i>Depth</i>	<i>Height</i>
<b>Basic Configuration Without Finisher</b>	1,461 mm	1,755 mm	1,600 mm
<b>Basic Configuration With Finisher</b>	1,908 mm	1,755 mm	1,600 mm

CERTIFICATIONS

89/336/EEC  
UL Listed (UL 1950, Third Edition)  
CB Certified (IEC 60950/EN 60950)  
73/23/EEC  
WHQL  
Novell NetWare

SUPPLIES

<i>Description</i>	<i>Order Number</i>	<i>No. per Box</i>
Black Toner	6R1122	1
Cyan Toner	6R1123	1
Magenta Toner	6R1124	1
Yellow Toner	6R1125	1
Drum Cartridge	13R579	1
Fuser Cartridge	8R1295	1
Waste Toner Container	8R12903	1
Staples (convenience stapler)	8R7644	4



**XEROX**  
Worldwide Partner

© 2003 XEROX CORPORATION. All rights reserved. XEROX®, The Document Company®, the digital X®, WorkCentre® Pro, CentreWare® and Copier Assistant are trademarks of XEROX CORPORATION. In support of Xerox's environmental leadership goals, these models may contain some recycled components that are reconditioned. Other marks are trademarks or registered trademarks of the companies with which they are associated. Whilst this information is correct at the time of going to press, Xerox Europe reserves the right to change specifications of the equipment described herein without notice.

09/03

P32FS-01EB