## Xerox

## Xerox<sup>®</sup> VersaLink<sup>®</sup> B400 Printer

VersaLink<sup>®</sup> B400 Printers are built on Xerox<sup>®</sup> ConnectKey<sup>®</sup> Technology. For more information, go to **www.Connectkey.co.uk**.



SYSTEM SPECIFICATIONS	VERSALINK <sup>®</sup> B400	
<b>One-sided Speed<sup>1</sup></b> 216 x 279 mm A4/210 x 297 mm 216 x 356 mm	Up to 47 ppm black-and-white Up to 45 ppm black-and-white Up to 38 ppm black-and-white	
<b>Two-sided Speed<sup>1</sup></b> 216 x 279 mm A4/210 x 297 mm 216 x 356 mm	Up to 29 ppm black-and-white Up to 28 ppm black-and-white Up to 25 ppm black-and-white	
Monthly Duty Cycle <sup>2</sup>	Up to 150,000 pages/month	
Recommended Average Monthly Print Volume <sup>3</sup>	Up to 15,000 pages	
Processor	1.5 GHz ARM Dual Core	
Memory	2 GB	
Connectivity	Ethernet 10/100/1000 Base-T, High-speed USB 3.0, Wi-Fi 802.11n and Wi-Fi Direct with optional Wi-Fi Kit (concurrent wired and wireless connections supported), NFC Tap-to-Pair	
Controller Features	Configuration Cloning, Xerox Extensible Interface Platform®, Xerox® App Gallery App, Xerox® Standard Accounting Tool, Network Accounting Enabled, Role Based Permissions, Convenience Authentication Enabled, Online Support	
User Interface Languages	English, French, Italian, German, Spanish, Brazilian Portuguese, Russian, Dutch, Swedish, Danish, Finnish, Norwegian, Greek, Turkish, Polish, Czech, Hungarian, Romanian, Catalan, Ukrainian, Croatian	

## Xerox<sup>®</sup> VersaLink<sup>®</sup> B400 Printer

DEVICE SPECIFICATIONS					
ELECTRICAL REQUIREMENTS					
North America		Voltage: 110-127 VAC Frequency: 50/60 Hz 11 A			
Europe and Other Geographies	Voltage: 220-240 V Frequency: 50/60 F				
POWER CONSUMPTION					
Continuous Printing <sup>4</sup>	565 watts or less				
Ready (Standby) <sup>4</sup>	46 watts or less				
Energy Saver (Sleep Mode) <sup>4</sup>	4 watts or less				
OPERATING ENVIRONMENT					
Required Temperature Range (Storage)	0 to 35 °C	0 to 35 °C			
Required Temperature Range (Operating)	10 to 32 °C	10 to 32 °C			
Required Relative Humidity	10% to 85%				
<b>Sound Power Levels</b> Operating Standby	7.5 B(A) or less 5.3 B(A) or less				
<b>Sound Pressure Levels</b> Operating Standby	56 dB(a) or less 30 dB(a) or less				
Boot Time (from Off to UI Ready)	As fast as 60 seconds				
Warm-up Time (from Sleep to UI Ready)	As fast as 5 seconds				
DIMENSIONS AND WEIGHT (UNPACKAGED)	WIDTH	WIDTH DEPTH H		HEIGHT	WEIGHT
VersaLink <sup>®</sup> B400	459 mm	426 m	ım	339 mm	14 kg
550-sheet Paper Tray	393 mm	393 m	ım	94 mm	3.2 kg
DIMENSIONS AND WEIGHT (PACKAGED)	WIDTH	DEPT	Н	HEIGHT	WEIGHT
VersaLink® B400	540 mm	588 m	ım	480 mm	17.35 kg
550-sheet Paper Tray	498 mm	504 m	ım	234 mm	4.4 kg
SYSTEM CERTIFICATION/REGUL	ATORY COMPLIANCE	E			
Certifications	To view the latest list of certifications, go to www.xerox.com/OfficeCertifications.				
PRINT					
First-Print-Out Time	As fast as 4.7 seconds				
Print Resolution	Up to 1200 x 1200 dpi (enhanced)				
Page Description Languages	PCL <sup>®</sup> 5e, 6 PDF XPS	PDF JPEG Adobe® Po		HP-GL Adobe® PostScript® 3™	
Maximum Print Area	4 mm from edge of paper				
	······································				

Print Features	Application Defaults Banner Pages Enable/Disable Bi-directional Real-time Status Booklet Layout Draft Mode Fit to New Paper Size Job Identification (Print ID or Banner, Print ID in margins on first page only or all pages) Job Monitoring (Client or Local User Interface) N-up Page Layout (up to 16 pages per sheet) Paper Selection by Attribute Personal Print Print Around Enable/Disable Print from USB Sample Set Saved Job Scaling Secure Print Skip Blank Pages Special Pages (exception page programming: covers, inserts, exceptions pages) Store and Recall Driver Settings Stored Jobs Deletion Two-sided Printing Watermark (predefined and custom) Xerox® Earth Smart Driver Settings	
Print from USB	Allows walk-up printing from Type A USB port Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TIFF, XPS, PDF/A	
Operating Systems	Windows® 7, 8, 8.1, 10 Windows Server 2008 SP2, Server 2008 R2 SP1, Server 2012, Server 2012 R2, Server 2016 macOS® 10.11, 10.12, 10.13 Citrix® Redhat® Enterprise Linux® Fedora Core IBM® AIX® HP-UX® Oracle® Solaris SUSE® SAP® Note: For information about supported versions for the above operating systems, please visit our	
Fonts	Drivers & Downloads page and specify your device at www.support.xerox.com         PostScript fonts: 136         PCL fonts: 83	
Xerox <sup>®</sup> Global Print Driver <sup>®</sup>	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox devices from a single driver. It provides a consistent, easy-to-use interface for End users, reducing the number of support calls and simplifying print services management.	
Xerox <sup>®</sup> Pull Print Driver	Makes it easy for IT managers to qualify, deploy and manage all print devices using a single driver in a Pull Print environment. Uses a single queue and single driver. The Xerox® Pull Print Driver extends convenience across a broad range of printing assets. IT administrators no longer need to manage and configure multiple drivers. Used in conjunction with Equitrac Office®, Ysoft® SafeQ®, Pharos® and others.	

SOFTWARE SOLUTIONS			
Xerox® ConnectKey® Apps (Found at the Xerox App Gallery)	Increase user productivity by simplifying and shortening everyday tasks. Unlike traditional software, ConnectKey® Apps do not require a dedicated server, PC or IT resource. Instead, simply download these lightweight, serverless ConnectKey® Apps to the ConnectKey® Technology-enabled device.		
MOBILE SOLUTIONS AND MOBILE	E DEVICE APPS		
Apple <sup>®</sup> AirPrint <sup>®</sup>	Print email, photos and important office documents directly from an Apple iPhone® or iPad®, with no drivers to install and no cables to connect. With AirPrint, an iPhone or iPad automatically locates and connects to the AirPrint-enabled device over the office Wi-Fi network.		
Mopria® Certified	ConnectKey® Technology-enabled MFPs are Mopria® certified. Mopria® certification ensures you can print wirelessly from your Mopria® supported (Android) smart phone, tablet and other mobile devices instantly and easily.		
Xerox <sup>®</sup> @printbyXerox App	@printbyXerox App is a free service that allows secure printing from any email-enabled device (computer, phone, tablet, iOS, Android <sup>™</sup> , Google <sup>®</sup> Chromebook <sup>™</sup> and more) to a Xerox <sup>®</sup> Printer or multifunction printer using a single email address with no IT intervention. No training is needed. End users simply send attachments to the email address, and release them at the multifunction printer panel.		
Xerox® Print Services plug-in for Android™ (Free at Google Play™ Store)	The Xerox <sup>®</sup> Print Services plug-in for Android devices streamlines mobile printing without third-party apps or additional print drivers. You can easily print photos, web pages and documents when your mobile device is connected to multifunction printers using a wireless network. A robust print option set includes two-sided printing, stapling and secure code release. A free download is available from the Google Play <sup>™</sup> store.		
Xerox® Easy Assist App	The Xerox <sup>®</sup> Easy Assist app simplifies installation, monitoring and management of your printer or MFP right from your mobile phone. It provides easy access to self-support services and real-time monitoring of printer performance. And, Xerox <sup>®</sup> Smart Start Software takes the guess work out of setup by automating the installation of the latest software for your printer or MFP on your computer – all without IT support – allowing you to be up and running quickly.		
Xerox® Workplace Suite and Xerox® Workplace Cloud	Xerox <sup>®</sup> Workplace Suite is a modular set of workflows designed to save customers time and money by providing effective control over their print fleet, while enabling worker productivity and mobility through a set of robust workflows. Xerox enables ultimate customer flexibility by offering these capabilities in both an on-premises server version (Workplace Suite) and a cloud-based version (Workplace Cloud) of this solution.		
SECURITY			
Security Features	Access controls AES 256-bit Encryption Audit Log Certificate path validation Certificate Revocation List (CRL)/Status Protocol (OCSP) Cisco® Identity Services Engine (ISE) Integration Detection of External Program Falsification (XCP Plug-in) Domain Filtering FIPS 140-2 Firmware Verification IP Address Filtering IPsec Network Authentication Port Filtering Pre-installed Self-Signed Certificates Role Based Permissions Secure print Security certificate management Smart Card Enablement (CAC/PIV/.NET) SNMPv3 Status Protocol (OCSP) TLS 1.3/SSL Trusted Platform Module (TPM)		

## Xerox<sup>®</sup> VersaLink<sup>®</sup> B400 Printer

ACCOUNTING				
		UNTING (STANDARD)		
Tracking	Print usage			
Accounting	Xerox® Standard Accounting Tool Up to 1,000 User Accounts without SSD Up to 9,999 User Accounts with SSD Up to 500 General Accounts			
	Network Accounting (Job-Based Accounting) Up to 1,000 User IDs; Up to 1,000 Account IDs without SSD Up to 60,000 User IDs; Up to 60,000 Account IDs with SSD Up to 14,000 Accounting Records (transactions)			
Features	Administrator can mana	ige the feature via the Embedded \	Web Server.	
ACCOUNTING OPTIONS	- NETWORK ACCOUNTING (ALLC	WS CENTRAL SERVER TO MAN	AGE ALL ACCOUNTING)	
	<ul> <li>Comprehensive mana</li> <li>Numerous solutions at visit www.xerox.co.uk</li> <li>Security enhancement</li> <li>Device requests accounts</li> <li>Accept Authentication</li> </ul>	gement and enterprise scale tracki re available through Xerox Alliance ts include simultaneous support for	Partners. For details HTTP/HTTPS protocols server, enabling larger databases of third-party Networking Account	
PAPER HANDLING		·		
BYPASS TRAY				
Capacity <sup>5</sup>	150 sheets	150 sheets		
Sizes	Custom sizes: 76.2 x 127	Custom sizes: 76.2 x 127 mm to 216 x 356 mm		
<b>Weights</b> One-sided: Two-sided:	60 to 220 gsm 60 to 163 gsm			
Media Types	Bond Plain Paper Cardstock Custom	Envelopes Hole-Punched Labels Letterhead	Lightweight Cardstock Pre-Printed Recycled	
TRAY 1			I	
Capacity <sup>5</sup>	550 sheets	550 sheets		
Sizes	Custom Sizes: 76.2 x 127 mm to 216 x 356 mm			
<b>Weights</b> One-sided: Two-sided:	60 to 220 gsm 60 to 163 gsm			
Media Types	Bond Plain Paper Cardstock Custom	Hole-Punched Labels Letterhead	Lightweight Cardstock Pre-Printed Recycled	
OPTIONAL TRAY 2				
Capacity <sup>5</sup>	550 sheets	550 sheets		
Sizes	Custom sizes: 139.7 x 210 mm to 216 x 356 mm			

<b>Weights</b> One-sided: Two-sided:	60 to 220 gsm 60 to 163 gsm		
Media Types	Bond Plain Paper Cardstock Custom	Hole-Punched Labels Letterhead	Lightweight Cardstock Pre-Printed Recycled
TOTAL CAPACITY <sup>5</sup>	1		
Device Standard Capacity <sup>5</sup>	700 sheets		
Device Total Capacity <sup>5</sup>	2,350 sheets		
PAPER OUTPUT	1		
Output Capacity <sup>5</sup>	250 sheets		
Automatic Two-sided Printing	Standard		
DEVICE MANAGEMENT			
Network Protocols	TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD LDAP Bonjour®/AirPrint® Most protocols not in use can be disabled		
Administrative Protocols	DHCP, SNMP, WINS, HTTP, HTTPS, TLS 1.3, SNTP, MDNS		
REMOTE CONTROL PANEL	1		
	<ul> <li>Enables faster, more convenient technical support and user training</li> <li>IT administrators and authorised users can control the device remotely from a web page on any device</li> <li>Remote user experience is identical to performing tasks directly at the device</li> </ul>		
XEROX <sup>®</sup> CENTREWARE <sup>®</sup> WEB			
	<ul> <li>A web-based server application for network administrators that permits web browser-based device management from any workstation, whether running Windows, UNIX or any other operating system</li> <li>Works with any SNMP-managed printer from any manufacturer</li> <li>Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management</li> </ul>		
EMBEDDED WEB SERVER – INTEG	RATED DEVICE WEB PA	AGE	
Device Status	<ul> <li>Tray Status/Contents</li> <li>Consumables Status</li> <li>Billing/Usage</li> <li>Quick Links</li> <li>Online Support</li> </ul>		
Print Queue Viewing	Job print queue management – view and delete		
Job Submission	Print-ready files (PS, PCL, PDF, XPS, JPEG)		
Device Administration	Allows simple, remote installation setting of configuration options and management of the device		
Browsers	Microsoft® Internet Explorer® Microsoft Edge™ Mozilla™ Firefox® Apple® Safari® Google Chrome™		

REMOTE SERVICES			
Automated Meter Readings (AMR)	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® Device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.		
Automatic Supplies Replenishment (ASR)	Automatically orders supplies for Xerox <sup>®</sup> output devices based on actual usage, eliminating the need to manually manage supplies inventory.		
WHAT COMES IN THE BOX			
	VersaLink <sup>®</sup> B400 Printer Standard Capacity Toner Cartridge: 5,900 p Software and Documentation CD (Safety, R and Warranty Statement) Installation Guide Quick Use Guides Power Cord	print capacity <sup>6</sup> Regulatory, Recycling and Disposal Guides, Print Drivers	
SUPPLIES AND ACCESSORIES	QUANTITY	PART NUMBER	
SUPPLIES			
Standard Capacity Toner Cartridges	5,900 standard pages <sup>6</sup>	106R03580	
High Capacity Toner Cartridges	13,900 standard pages <sup>6</sup>	106R03582	
Extra-High Capacity Toner Cartridges	24,600 standard pages <sup>6</sup>	106R03584	
Drum Cartridge	65,000 standard pages <sup>7</sup>	101R00554	
ACCESSORIES/OPTIONS			
550-sheet Paper Tray		497K13620	
Productivity Kit with 16 GB Solid State Drive		097504913	
Stand		497K13660	
Wireless Network Adapter Kit497K16750		497K16750	

<sup>1</sup> Declared print speed in accordance with ISO/IEC 24734.
<sup>2</sup> Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

<sup>3</sup> Recommended average throughput is not a minimum, but is intended to cover a range of volumes for different environments. <sup>4</sup> Power states defined per EVERGY STAR® Programme requirements for Imaging Equipment. <sup>5</sup> Paper capacities are based on 75 gsm stock; capacities will vary with different weight stocks. <sup>6</sup> Average standard pages. Declared Yield in accordance with ISO/IEC19752. Yield will vary based on image, area coverage and print mode. <sup>7</sup> Approximate pages. Declared yield will vary depending on job run length, media size/orientation and machine speed. For more information visit: https://www.office.xerox.com/latest/SUPGL-01.pdf.

Return spent imaging supplies through the Xerox Green World Alliance collection/reuse/recycling programme. For more information, visit www.xerox.co.uk/recycling.

For more information, visit us at www.xerox.co.uk/office.

Configurations vary by geography.

© 2022 Xerox Corporation. All rights reserved. Xerox®, CentreWare®, ConnectKey®, Global Print Driver®, VersaLink® and Xerox Extensible Interface Platform® are trademarks of Xerox Corporation in the United States and/or other countries. The information in this brochure is subject to change without notice. 06/22 TSK-3322 BR26410 VB4SS-01EI

