

# Xerox<sup>®</sup> VersaLink<sup>®</sup> Colour Multifunction Printer

#### C7020/C7025/C7030

VersaLink C7000 Series Colour Multifunction Printers are built on Xerox® ConnectKey® Technology. For more information, go to www.connectkey.com.



| System Specifications                                      | VersaLink C7020   | VersaLink C7025                              | VersaLink C7030                              |
|--|---|--|--|
|  | Versaemik ez ded  | Versuelink e7 023                            | Versuelink e7 050                            |
| <b>One-Sided Speed</b><br>8.5 x 11 in. / A4 / 210 x 297 mm | Up to 20 ppm (pages per minute) long edge feed (LEF)  Up to 25 ppm (LEF)  Up to 30 ppm (LEF)  |  | Up to 30 ppm (LEF)                           |
| 8.5 x 14 in. / 216 x 356 mm                                | Up to 16 ppm 8.5 x 14 in. /<br>216 x 356 mm   | Up to 19 ppm 8.5 x 14 in. /<br>216 x 356 mm  | Up to 23 ppm 8.5 x 14 in. /<br>216 x 356 mm  |
| 11 x 17 in. / A3 / 297 x 420 mm                            | Up to 11 ppm 11 x 17 in. / A3 / 297 x 420 mm  | Up to 14 ppm 11 x 17 in. / A3 / 297 x 420 mm | Up to 17 ppm 11 x 17 in. / A3 / 297 x 420 mm |
| Monthly Duty Cycle <sup>1</sup>                            | Up to 87,000 pages / month <sup>1</sup>   | Up to 107,000 pages / month <sup>1</sup>     | Up to 129,000 pages / month <sup>1</sup>     |
| Recommended Average<br>Monthly Print Volume <sup>2</sup>   | Up to 5,500 pages   | Up to 6,250 pages                            | Up to 7,000 pages                            |
| Hard Drive   | 320 GB HDD (Optional)   |  |  |
| Processor  | 1.05 GHz Dual-Core  |  |  |
| Memory   | 4 GB  |  |  |
| Connectivity   | Ethernet 10/100/1000 Base-T, High-speed USB 3.0, Wi-Fi 802.11n/g/b/a and Wi-Fi Direct with optional Wi-Fi Kit (concurrent wired and wireless connections supported), NFC Tap-to-Pair  |  |  |
| Controller Features  | Unified Address Book, Configuration Cloning, Scan Preview, Fax Preview, Xerox Extensible Interface Platform®, Xerox App Gallery, Xerox® Standard Accounting, Role Based Permissions, Convenience Authentication Enabled, Online Support |  |  |
| Device Specifications                                      |   |  |  |
| Electrical Requirements                                    |   |  |  |
| North America  | Voltage : 110-127V -10 % / +6 %<br>Frequency: 50/60 Hz +/-3 % , 12A   |  |  |
| Europe   | Voltage : 220-240V +/- 10 %<br>Frequency: 50 Hz +/- 3 % , 8A  |  |  |

| Power Consumption  |  |                                |                   |       |                                      |
|--|--|--------------------------------|-------------------|-------|--------------------------------------|
| Printing <sup>5</sup>  | For 110V: 20 ppm = 0.9 kWh; 25 ppm = 1.1 kWh; 30 ppm = 1.5 kWh<br>For 220V: 20 ppm = 0.9 kWh; 25 ppm = 1.1 kWh; 30 ppm = 1.5 kWh   |                                |                   |       |                                      |
| Standby Mode <sup>5</sup>  | 110V: 80 Watts or less<br>220V: 80 Watts or less   | 110V: 80 Watt<br>220V: 80 Watt |                   |       | 94 Watts or less<br>94 Watts or less |
| Sleep Mode <sup>5</sup>  | 110V: 1.0 watts or less<br>220V: 1.4 watts or less   | ·                              |                   |       |                                      |
| Operating Environment  |  |                                |                   |       |                                      |
| Required Temperature Range<br>(Storage)  | 32° to 95° F (0° to 35° C  | )                              |                   |       |                                      |
| Required Temperature Range<br>(Operating)  | 50 to 90° F (10 to 32° C   | )                              |                   |       |                                      |
| Required Relative Humidity   | 10% to 85%   |                                |                   |       |                                      |
| Sound Power Levels   | Printing: 6.70 B(A) or less  • 20 ppm = 6.45 B(A); 25 ppm = 6.50 B(A); 30 ppm = 6.70 B(A)  Standby: 4.10 B(A) or less  • 20 ppm = 4.10 B(A); 25 ppm = 4.10 B(A); 30 ppm = 4.10 B(A)  Full System (including finisher and HCF)  Printing: 20 ppm = 7.07 B(A); 25 ppm = 7.22 B(A); 30 ppm = 7.37 B(A)  Standby: 20 ppm = 4.10 B(A); 25 ppm = 4.10 B(A); 30 ppm = 4.10 B(A) |                                |                   |       |                                      |
| Sound Pressure Levels  | Printing: 52.0 dB(A)  • 20 ppm = 49.5 dB(A); 25 ppm = 50.0 dB(A); 30 ppm = 52.0 dB(A)  Standby: 26.0 dB(A)  • 20 ppm = 26.0 dB(A); 25 ppm = 26.0 dB(A); 30 ppm = 26.0 dB(A)  Full System (including finisher and HCF)  Printing: 20 ppm = 55.5 dB(A); 25 ppm = 57.0 dB(A); 30 ppm = 58.5 dB(A)  Standby: 20 ppm = 26.0 dB(A); 25 ppm = 26.0 dB(A); 30 ppm = 26.0 dB(A)   |                                |                   |       |                                      |
| Boot Time (from Off to UI Ready)   | As fast as 98 seconds  |                                |                   |       |                                      |
| Warm-up Time (from Sleep to UI<br>Ready)   | As fast as 12 seconds  |                                |                   |       |                                      |
| Dimensions and Weight<br>(Unpackaged)  | Width  | Depth                          | Height            |       | Weight                               |
| Base Unit  | 23.23 in. / 590 mm   | 26.41 in. / 670.8 mm           | 30.23 in. / 767.9 | mm    | 152.12 lbs. / 69.0 kg                |
| Base Unit with Single Tray with Stand Module                                       | 24.24 in. / 615.7 mm   | 26.41 in. / 670.8 mm           | 44.04 in. / 1118  | .6 mm | 203.49 lbs. / 92.3 kg                |
| Base Unit with High Capacity<br>Tandem Tray Module                                 | 24.24 in. / 615.7 mm   | 26.41 in. / 670.8 mm           | 44.04 in. / 1118  | .6 mm | 234.79 lbs. / 106.5 kg               |
| Base Unit with Three Tray<br>Module  | 24.24 in. / 615.7 mm   | 26.41 in. / 670.8 mm           | 44.04 in. / 1118  | .6 mm | 212.75 lbs. / 96.5 kg                |
| Base Unit with Three Tray<br>Module and Office Finisher LX<br>(with Booklet Maker) | 47.0 in. / 1194.0 mm   | 26.8 in. / 681.8 mm            | 44.04 in. / 1118  | .6 mm | 296.3 lbs. / 134.4 kg                |
| Certifications   |  |                                |                   |       |                                      |
|  |  |                                |                   |       |                                      |

To view the latest list of certifications, go to www.xerox.com/OfficeCertifications.

| Print                      |                               |                               |                               |
|----------------------------|-------------------------------|-------------------------------|-------------------------------|
| First-print-out Time       | As fast as 9.4 seconds Colour | As fast as 9.4 seconds Colour | As fast as 7.3 seconds Colour |
|                            | As fast as 7.2 seconds Black  | As fast as 7.1 seconds Black  | As fast as 5.6 seconds Black  |
| Print Resolution           | Up to 1200 x 2400 dpi         |                               |                               |
| Page Description Languages | PCL® 5e, 6<br>PDF<br>XPS      |                               |                               |

|                         | TIFF<br>JPEG  |   |  |  |
|-------------------------|---|---|--|--|
|                         | HP-GL<br>Adobe® PostScript® 3™ (Optional)   |   |  |  |
| Maximum Print Area      | 4 mm from lead edge of paper, 2 mm from Side and Trail edges of paper   |   |  |  |
| Print Features          | Application Defaults Bi-directional Real-time Status Booklet Creation Draft Mode Job Identification Job Monitoring Personal Print Print from USB Sample Set Saved Job Scaling Secure Print Skip Blank Pages Store and Recall Driver Settings Two-sided Printing (as default) Xerox® Earth Smart Driver Settin | Bi-directional Real-time Status Booklet Creation Draft Mode Job Identification Job Monitoring Personal Print Print from USB Sample Set Saved Job Scaling Secure Print Skip Blank Pages Store and Recall Driver Settings |  |  |
| Print from USB          | Supports direct printing from co  | Allows walk-up printing from Type A USB port<br>Supports direct printing from computer via Type B USB port<br>Supported file formats: PDF, JPEG, TIFF, XPS  |  |  |
| Operating Systems       | Windows®, 7, 8, 10, Server 2000 Mac OS® version 10.10, 10.11, 8 Citrix Redhat® Enterprise Linux® IBM® AIX® 7.2 HP-UX® 11iv3 Oracle® Solaris 11.3 Fedora Core 24 SUSE® 13.2  | Redhat® Enterprise Linux® IBM® AIX® 7.2 HP-UX® 11iv3 Oracle® Solaris 11.3 Fedora Core 24  |  |  |
| Fonts                   | PostScript fonts: 136<br>PCL fonts: 83  |   |  |  |
| Сору                    |   |   |  |  |
| Document Scanner        | 110-sheet Duplex Automatic Do   | ocument Feeder (DADF)   |  |  |
| Document Scanner Size   |   | Platen: Up to 13.1 x 17.2 in. / 332.0 x 437 mm<br>DADF: Up to 11.7 x 17 in. / 297 x 431.8 mm  |  |  |
| Simplex Copy Speed      | Up to 20 cpm (copies per minute) 8.5 x 11 in. Up to 20 cpm A4 (210 x 297 mm)  | Up to 25 cpm (copies per<br>minute) 8.5 x 11 in.<br>Up to 25 cpm A4 (210 x 297<br>mm)   | Up to 30 cpm (copies per minute) 8.5 x 11 in. Up to 30 cpm A4 (210 x 297 mm) |  |
| Duplex Copy Speed       | Up to 17 cpm (copies per minute) 8.5 x 11 in. Up to 17 cpm A4 (210 x 297 mm)  | Up to 18 cpm (copies per minute) 8.5 x 11 in. Up to 18 cpm A4 (210 x 297 mm)  | Up to 18 cpm (copies per minute) 8.5 x 11 in. Up to 18 cpm A4 (210 x 297 mm) |  |
| First-copy-out Time     | As fast as 9.0 seconds Colour   |   |  |  |
|                         | As fast as 6.9 seconds Black As fast as 5.8 seconds Black   |   |  |  |
| Sides (input:output)    | 1:1, 1:2, 2:2 and 2:1   | 1:1, 1:2, 2:2 and 2:1   |  |  |
| Quantity                | 1 to 999  |   |  |  |
| Resolution (max.)       | Up to 600 x 600 dpi   |   |  |  |
| Reduction / Enlargement | Variable zoom from 25% to 400% in 1% increments   |   |  |  |
| Concurrency             | Concurrent scanning and printir   | Concurrent scanning and printing  |  |  |
| Copy Features           |   | Automatic Background Suppression<br>Book Copying with Center Erase  |  |  |

|   | Booklet Creation (requires HDD) Annotations (Page Numbers, Comments, Date Stamp, Bates Stamp) (requires HDD) Collation Darkness Control Edge Erase ID Card Copy N-up Reduce / Enlarge 25% to 400% Image Shift Original Type Sample Copy Sharpness   |
|---|---|
| Scan  |   |
| Capability  | Black and white and colour scanning   |
| Concurrency   | Scan while the system is printing copy or network print jobs, or while it is transferring scan to network or fax jobs   |
| Simplex Input Speed   | Black and white: Scan up to 55 ipm – 8.5 x 11 in. / A4 (210 x 297 mm)<br>Colour: Scan up to 55 ipm – 8.5 x 11 in. / 55 ipm A4 (210 x 297 mm)  |
| Duplex Input Speed  | Black and white: Scan up to 26 ipm – 8.5 x 11 in. / A4 (210 x 297 mm)<br>Colour: Scan up to 26 ipm – 8.5 x 11 in. / 26 ipm A4 (210 x 297 mm)  |
| Resolution  | Optical – 600 x 600 dpi   |
| Bit Depth   | 24-bit colour / 8-bit grayscale   |
| Maximum Scan Area   | Platen: Up to 13.1 x 17.2 in. / 332 x 437 mm<br>Document Feeder: 11.7 x 17 in. / 297 x 431.8 mm   |
| Network Filing Protocols  | FTP<br>SMTP<br>SMB  |
| File Formats  | JPG TIFF (single and multi-page) XPS (single and multi-page) PDF (single and multi-page) Searchable PDF Password-protected PDF Linearised PDF (set via embedded web server) and PDF/A   |
| Scan Driver Compatibility<br>(Network Only)   | WIA<br>TWAIN  |
| Supported Scan Destinations   | Scan to Home<br>Scan to USB<br>Scan to Email<br>Scan to Network (Browse FTP or Browse SMB)  |
| Network Scanning – Software Sol   | utions  |
| Xerox <sup>®</sup> ConnectKey <sup>®</sup> Apps<br>(Found at the Xerox <sup>®</sup> App<br>Gallery) | Increase user productivity by simplifying and shortening everyday tasks. Unlike traditional software, ConnectKey Apps do not require a dedicated server, PC or IT resource. Instead, simply download these lightweight, serverless ConnectKey Apps to the ConnectKey-enabled multifunction printer. |
| PSTN One-line or Three-line Fax (   | Optional)   |
| Fax <sup>3</sup>  |   |
| Fax Speed   | 33.6 Kbps   |
| Resolution  | Up to 600 x 600 dpi resolution  |
| Compression   | MH, MR, MMR, JBIG   |
| Fax Features  | Walk-up Fax, includes LAN Fax, Direct Fax, Fax Forward to Email<br>Fax dialing via Unified Address Book (up to 2,000 contacts)  |

| Fax over IP (Optional)  |  |
|---|--|
| Compliance  | T.38 compliant IP / SIP  |
| Resolution  | Up to 600 x 600 dpi resolution   |
| Compression   | MH, MR, MMR, JBIG  |
| Fax Features  | Walk-up Fax, includes LAN Fax, Direct Fax, Fax Forward to Email<br>Fax dialing via Unified Address Book (up to 2,000 contacts)   |
| Mobile Solutions and Mobile Devi  | ce Apps  |
| Xerox <sup>®</sup> Mobile Express Driver <sup>®</sup>   | Makes it easy for mobile users to find, use and manage Xerox® and non-Xerox® devices in every new location. Plug into a new network, and Mobile Express Driver automatically discovers available printers and provides status and capability information. Save a list of "favourite" printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT.  |
| Xerox® Global Print Driver®   | A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox® devices from a single driver. It provides a consistent, easy-to-use interface for endusers, reducing the number of support calls, and simplifying print services management.  |
| Apple <sup>®</sup> AirPrint <sup>®</sup>  | Print email, photos and important office documents directly from an Apple iPhone® or iPad® with no drivers to install and no cables to connect. With AirPrint, an iPhone or iPad automatically locates and connects to the AirPrint-enabled device over the office Wi-Fi network.  |
| Google Cloud Print™   | Google Cloud Print connects print devices to the web, enabling users to print the applications they use every day from smartphones, tablets, Chromebook™ notebook computers and any other webconnected device.   |
| Xerox <sup>®</sup> Print Service Plug-in for<br>Android™ (Free αt Google Play™<br>Store)          | The Xerox® Print Service Plug-in for Android KitKat (4.4 or greater) devices streamlines mobile printing without third-party apps or additional print drivers. You can easily print photos, Web pages and documents when your mobile device is connected to multifunction printers using a wireless network. A robust print option set includes two-sided printing, stapling and secure code release. A free download is available from the Google Play™ store.                        |
| Xerox® Mobile Link App (Free at<br>Google Play™<br>Store and Apple® App Store)                    | The Xerox® Mobile Link App allows you to scan, email and fax from your phone or tablet by connecting with our multifunction printers and send data to and print data from cloud storage. It is easy to create Mobile Link One-Touch Workflows between a mobile device and a multifunction printer. Using a manual address or QR code identification for pairing, automatic device discovery makes it easy to find and pair a mobile device with a nearby Xerox® multifunction printer. |
| Xerox® Print Management<br>and Mobility Suite, Xerox®<br>Print Management and<br>Mobility Service | Xerox® Print Management and Mobility Suite is a modular set of workflows designed to save customers time and money by providing effective control over their print fleet, while enabling worker productivity and mobility through a set of robust workflows. Xerox enables ultimate customer flexibility by offering these capabilities in both an on-premises server version and with a cloud based-version of this solution.   |

| Security                        |  |  |
|---------------------------------|--|--|
| Standard Security Features      | Firmware Verification Security Certificate Management Automatic Self-Signed Certificate Creation Certificate Revocation List (CRL)/Online Certificate Status Protocol (OCSP) Certificate Path Validation Immediate Disk Overwrite (requires HDD) AES 256-bit Encryption FIPS 140-2 TLS/SSL SNMPv3 Smart Card Enablement (CAC/PIV/.NET) Detection of external programme falsification (XCP Plug-in) Network Authentication Access Controls Role Based Permissions Domain Filtering IP Address Filtering Port Filtering Audit Log Secure Email Secure Fax Secure Print Secure Scan   |  |
| Accounting                      |  |  |
| Xerox® Standard Accounting (Sta | ndard)   |  |
| Tracking                        | Copy, Print, Fax, Scan and Email usage   |  |
| Accounting                      | Xerox® Standard Accounting Tool Up to 9,999 User Accounts with HDD installed Up to 1,000 User Accounts without HDD installed  Network Accounting (Job Based Accounting) Up to 60,000 User IDs; Up to 60,000 Account IDs with HDD installed Up to 1,000 User IDs; Up to 1,000 Account IDs without HDD installed Up to 14,000 accounting records (transactions)  |  |
| Features                        | Administrator can manage the feature via the Embedded Web Server or local user interface on device   |  |
| Accounting Options – Network Ac | counting Enablement (Standard) (Allows central server to manage all accounting)  |  |
|                                 | <ul> <li>Enhanced network accounting with up to the minute data on how the system is being used</li> <li>Comprehensive management and enterprise scale tracking and reporting of device usage of copy, print, scan and fax</li> <li>Numerous solutions are available through Xerox Alliance Partners. For details visit www.xerox.com</li> <li>Security enhancements includes support for HTTPS protocol</li> <li>Device requests account authentication from third party server enabling larger databases of users and accounts</li> <li>Accept Authentication Login at control panel and pass to third party Networking Account</li> </ul> |  |
| Paper Handling                  |  |  |
| Document Feeder (Standard)      |  |  |
| Capacity <sup>4</sup>           | Duplex Automatic Document Feeder (DADF): 110 sheets  |  |
| Sizes                           | Custom sizes: Duplex: 4.92 x 4.33 in. to 11.69 x 17 in. / 125 x 110 mm to 297 x 431.8 mm;<br>Simplex: 4.92 x 3.35 in. to 11.69 x 17 in. / 125 x 85 mm to 297 x 431.8 mm  |  |
| Weights                         | Simplex: 11 lb. bond to 34 lb. bond / 38 –128 gsm<br>Duplex: 13 lb. bond to 34 lb. bond / 50 –128 gsm  |  |
| Bypass Tray (Standard)          |  |  |
| Capacity <sup>4</sup>           | 100 sheets   |  |
| Sizes                           | Custom sizes: 3.5 x 3.87 in. to 11.69 x 17 in. / 88.9 x 98.4 mm to 297 x 431.8 mm  |  |
| Weights                         | 16 lb. bond to 80 lb. cover / 60 to 216 gsm  |  |

| Types   | Bond Plain Paper Cardstock Custom Envelopes Hole Punched Labels Heavyweight Labels Letterhead Lightweight Cardstock Lightweight Glossy Cardstock Lightweight Glossy Cardstock Reload Pre-Printed Recycled    |
|---|--|
| Tray 1 (Standard)   |  |
| Capacity <sup>4</sup>                                       | 520 sheets   |
| Sizes   | Custom sizes: 5.5 x 7.17 in. to 11.69 x 17 in. / 139.7 x 182.0 mm to 297.0 x 431.8 mm  |
| Weights   | 16 lb. bond to 95 lb. cover / 60 to 256 gsm  |
| Types   | Bond Plain Paper Cardstock Custom Hole Punched Labels Heavyweight Labels Extra Heavyweight Labels Letterhead Lightweight Glossy Cardstock Lightweight Glossy Cardstock Reload Heavyweight Cardstock Recycled |
| Choose 1 of the 4 Additional Pape                           | er Handling Options:   |
| Option 1 – Single Tray (Tray 2)<br>(Does not include stand) |  |
| Capacity <sup>4</sup>                                       | 520 sheets   |
| Sizes   | Custom sizes: 5.5 x 7.17 in. to 11.69 x 17 in. / 139.7 x 182.0 mm to 297.0 x 431.8 mm  |
| Weights   | 16 lb. bond to 95 lb. cover / 60 to 256 gsm  |
| Types   | Bond Plain Paper Cardstock Custom Hole Punched Labels Heavyweight Labels Extra Heavyweight Labels Letterhead Lightweight Glossy Cardstock Lightweight Glossy Cardstock Reload Heavyweight Cardstock Recycled |
| Option 2 – Single Tray Module (Tr                           | ay 2) with Stand   |
| Capacity <sup>4</sup>                                       | 520 sheets   |
| Sizes   | Custom sizes: 5.5 x 7.17 in. to 11.69 x 17 in. / 139.7 x 182.0 mm to 297.0 x 431.8 mm  |
| Weights   | 16 lb. bond to 95 lb. cover / 60 to 256 gsm  |
| Types   | Bond<br>Plain Paper  |

|  | Cardstock   |  |
|--|---|--|
|  | Custom<br>Hole Punched<br>Labels  |  |
|  | Heavyweight Labels Extra Heavyweight Labels Letterhead Lightweight Cardstock Lightweight Glossy Cardstock Lightweight Glossy Cardstock Lightweight Glossy Cardstock Reload Heavyweight Cardstock Pre-Printed Recycled                       |  |
| Option 3 – Three Tray Stand Mod            | lule (Optional)   |  |
| Capacity <sup>4</sup>                      | Tray 2: 520 sheets<br>Tray 3: 520 sheets<br>Tray 4: 520 sheets  |  |
| Sizes                                      | Custom sizes: 5.5 x 7.17 in. to 11.69 x 17 in. / 139.7 x 182.0 mm to 297.0 x 431.8 mm   |  |
| Weights                                    | 16 lb. bond to 95 lb. cover / 60 to 256 gsm   |  |
| Types                                      | Bond Plain Paper Cardstock Custom Hole Punched Labels Heavyweight Labels Extra Heavyweight Labels Letterhead Lightweight Cardstock Lightweight Glossy Cardstock Lightweight Glossy Cardstock Reload Heavyweight Cardstock Recycled          |  |
| Option 4 – High Capacity Tanden            | n Tray Stand Module (Optional)  |  |
| Capacity <sup>4</sup>                      | Tray 2: 520 sheets Tray 3: 870 sheets Tray 4: 1,130 sheets  |  |
| Sizes                                      | Tray 2: Custom sizes: 5.5 x 7.17 in. to 11.69 x 17 in. / 139.7 x 182.0 mm to 297.0 x 431.8 mm<br>Tray 3: Standard Sizes: 8.5 x 11 in. and 7.25 x 10.5 in. / A4 or B5<br>Tray 4: Standard Sizes: 8.5 x 11 in. and 7.25 x 10.5 in. / A4 or B5 |  |
| Weights                                    | 16 lb. bond to 95 lb. cover / 60 to 256 gsm   |  |
| Types                                      | Bond Plain Paper Cardstock Custom Hole Punched Labels Heavyweight Labels Extra Heavyweight Labels Letterhead Lightweight Cardstock Lightweight Glossy Cardstock Lightweight Glossy Cardstock Reload Heavyweight Cardstock Recycled          |  |
| Envelope Tray – Replaces Tray 1 (Optional) |   |  |
| Capacity <sup>4</sup>                      | Up to 60 envelopes  |  |
|  |   |  |

| Sizes   | #10 commercial, Monarch, DL, C5<br>Custom sizes: 3.9 x 5.8 in. to 6.4 x 9.5 in. / 98 x 148 mm to 162 x 241 mm  |  |
|---|--|--|
| Weights   | 20 lb. bond to 25 lb. bond / 75 to 90 gsm  |  |
| High Capacity Feeder (Optional – requires either one of options 2, 3 or 4 above)  |  |  |
| Capacity <sup>4</sup>   | 2,000 sheets   |  |
| Sizes   | Standard Sizes: 8.5 x 11 in. and 7.25 x 10.5 in. / A4 or B5  |  |
| Weights   | 16 lb. bond to 80 lb. cover / 60 to 216 gsm  |  |
| Total Capacity  |  |  |
| Base Unit Capacity <sup>4</sup>   | 620 sheets   |  |
| Single Tray Module Capacity <sup>4</sup>  | 1,140 sheets   |  |
| Single Tray Module with Stand<br>Capacity <sup>4</sup>  | 1,140 sheets (3,140 sheets with optional High Capacity Feeder)   |  |
| Three Tray Module Capacity <sup>4</sup>   | 2,180 sheets (4,180 sheets with optional High Capacity Feeder)   |  |
| High-Capacity Tandem Tray<br>Capacity <sup>4</sup>  | 3,140 sheets (5,140 sheets with optional High Capacity Feeder)   |  |
| Finishing   |  |  |
| Centre Output Tray (Optional – no   | ot compatible with other Finishing options)  |  |
| Dual Catch Trays <sup>4</sup>   | 250 sheets each; Lower tray offsets  |  |
| Integrated Office Finisher (Option  | nal)   |  |
| Stacking Tray   | 500 sheets of 20 lb. bond / 80 gsm – 8.5 x 11 in. / A4 or 250 sheets of 20 lb. bond / 80 gsm – 11 x 17 in. / A3  |  |
| Sizes   | 3.5 x 3.9 in. to 11.7 x 17 in. / 89 x 98 mm to 297 x 432 mm  |  |
| Weights   | 16 lb. bond to 80 lb. cover / 60 to 220 gsm  |  |
| Stapling  | Single Auto stapling: 50 sheets maximum: Letter / A4 / B5-size sheets (less than 90 gsm or (2) 220 gsm covers) 30 sheets maximum: Legal / Tabloid / A3 / B4-size sheets (less than 90 gsm or (2) 220 gsm covers) |  |
| Office Finisher LX (Optional) (Requ   | uires one of the above paper handling options 2, 3 or 4)   |  |
| Capacity <sup>4</sup>   | Stacking Tray: 2,000 sheets unstapled or 1,000 sheets single stapled or 750 sheets dual stapled (8.5 x 11 in. / A4) (dual stapling only with optional booklet maker)   |  |
| Sizes   | 8.3 x 7.2 in. to 11.7 x 17 in. / 210 x 182 mm to 297 x 432 mm  |  |
| Weights   | 16 lb. bond to 80 lb. cover / 60 to 220 gsm  |  |
| Multiposition Stapling  | 50 sheets of 24 lb. bond / 90 gsm  |  |
| Hole Punch (Optional)<br>North America:<br>Europe:  | 2-3 Hole Punch<br>2-4 Hole Punch   |  |
| Booklet Maker for Office Finisher LX (Score/Crease, Saddle-stitch Staple) (Optional) (Requires one of the above paper handling options 2, 3 or 4) |  |  |
| Capacity <sup>4</sup>   | 40 booklets (2-15 sheets per booklet – 20 lb. / 80 gsm or less)  |  |
| Sizes   | Letter – 8.5 x 11 in. / A4 SEF Legal – 8.5 x 14 in. / B4 SEF Ledger – 11 x 17 in. / A3 SEF   |  |
| Saddle-stitch Stapling  | 2-15 sheets / 8-60 page booklet 16 lb. bond to 24 lb. bond / 60 to 90 gsm  |  |
| Score / Crease  | 1-15 sheets / unstapled  |  |
|   |  |  |

| Convenience Stapler (Optional – I     | Requires Work Surface)   |
|---------------------------------------|--|
| Capacity <sup>4</sup>                 | 50-sheet stapling<br>5,000 staples<br>Requires a separate outlet   |
| Device Management                     |  |
| Network Protocols                     | TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD LDAP Bonjour® / AirPrint™ FTP Most protocols not in use can be disabled   |
| Administrative Protocols              | DHCP, SNMP, WINS, HTTP, HTTPS, TLS, SNTP, MDNS   |
| Xerox® CentreWare® Web                |  |
|                                       | <ul> <li>A Web-based server application for network administrators that permits web browser-based device management from any workstation, whether running Windows or UNIX or any other operating system</li> <li>Works with any SNMP-managed printer from any manufacturer</li> <li>Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management</li> </ul> |
| Embedded Web Server – Integrat        | ed Device Web Page   |
| Device Status                         | Web server embedded  Tray status/contents  Consumables status  Billing/Usage  Quick Links  |
| Print Queue Viewing                   | Job print queue management—view and delete   |
| Job Submission                        | Print-ready files (PS (with optional PostScript option), PCL, PDF, XPS, JPEG)  |
| Device Administration                 | Allows simple, remote installation setting of configuration options and management of the device   |
| Browsers                              | Microsoft® Internet Explorer® 11<br>Microsoft Edge™ 38<br>Mozilla™ Firefox® 48<br>Apple® Safari® 9.1<br>Google Chrome™ 52  |
| Remote Services                       |  |
| Xerox® Meter Assistant® Service       | Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.   |
| Xerox® Supplies Assistant®<br>Service | Automatically orders supplies for Xerox® output devices based on actual usage, eliminating the need to manually manage supplies inventory.   |
| MaintenanceAssistant                  | Offers a fast (and free) way to resolve potential issues and receive assistance and automate the troubleshooting/repair process. Diagnostic data is sent to Xerox, allowing for problems to be solved faster with increased uptime.  |

| Supplies and Accessories                                      | Quantity   | Part Number                                      |
|---|--|--|
| Supplies  |  |  |
| High Capacity Print Cartridges                                | Cyan: 9,800 standard pages <sup>6</sup><br>Magenta: 9,800 standard pages <sup>6</sup><br>Yellow: 9,800 standard pages <sup>6</sup><br>Black: 16,100 standard pages <sup>6</sup>    | 106R03752<br>106R03751<br>106R03750<br>106R03749 |
| Extra High Capacity Print<br>Cartridges                       | Cyan: 16,500 standard pages <sup>6</sup><br>Magenta: 16,500 standard pages <sup>6</sup><br>Yellow: 16,500 standard pages <sup>6</sup><br>Black: 23,600 standard pages <sup>6</sup> | 106R03748<br>106R03747<br>106R03746<br>106R03745 |
| Metered Print Cartridges                                      | Cyan: 15,000 standard pages <sup>7</sup><br>Magenta: 15,000 standard pages <sup>7</sup><br>Yellow: 15,000 standard pages <sup>7</sup><br>Black: 22,000 standard pages <sup>7</sup> | 106R03736<br>106R03735<br>106R03734<br>106R03733 |
| Drum Cartridge  | Black: 109,000 <sup>8</sup><br>Cyan, Magenta, Yellow : 87,000 standard pages <sup>8</sup>  | 113R00780  |
| Waste Toner Bottle  | 30,000   | 115R00128  |
| LX Booklet Maker Cartridge<br>(8 cartridges per container)    | 16,000 staples<br>(2,000 each cartridge)   | 008R12897  |
| Staple Refills for Finishers<br>(3 refills per container)     | 15,000 staples<br>(5,000 each refill)  | 008R12941  |
| Staple Cartridge for Finishers<br>(1 cartridge per container) | 5,000 staples<br>(5,000 each cartridge)  | 008R12964  |
| Accessories / Options   |  | ,  |
| Single Tray Module  |  | 097S04910  |
| Single Tray with Stand Module                                 |  | 097S04907  |
| Three Tray Stand Module                                       |  | 097504908  |
| High-Capacity Tandem Tray Star                                | nd Module  | 097S04909  |
| Envelope Tray (Replaces Tray 1)                               |  | 497K17720  |
| Centre Output Tray (Dual Catch                                | Tray)  | 497K17800  |
| HDD (320 GB hard drive)                                       |  | 497K17740  |
| 1 Line Fax Kit (PSTN Fax)                                     |  | 497K17770  |
| 1 Line Fax Kit (PSTN Fax) (Brazil and Argentina)              |  | 497K17790  |
| 3 Line Fax Kit (PSTN Fax)                                     |  | 497K17780  |
| Wireless Network Adapter Kit                                  |  | 497K16750  |
| Internal Card Reader / RFID Kit                               |  | 497K18140  |
| PostScript Kit  |  | 497K18340  |
| Fax Over IP Kit   |  | 497K18330  |

<sup>1</sup> Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.
2 Expected regular monthly throughput.
3 Requires analogue phone line.
4 Paper capacities are based on 20 lb. / 75 gsm stock; capacities will vary with different weight stocks.
5 Power states defined per ENERGY STAR® Programme requirements for Imaging Equipment.
6 Average standard pages. Declared Yield in accordance with ISO/IEC 19798. Yield will vary based on image, area coverage and print mode.
7 Assumptions: Toner cartridge yield is based on 5 % area coverage on 8.5 x 11 in. / A4 LEF. Toner yield can vary due to many factors, including but not limited to, image area coverage, image content, media size, run mode, application types, monthly print volumes and image quality set-points.
8 Approximate pages. Declared yield will vary depending on job run length, media size/orientation and machine speed. For more information visit: http://www.office.xerox.com/latest/SUPGL-01.pdf

| Xerox® VersaLink® C7020/C7025/C7030 Colour Multifunction Printer  |
|---|
|   |
|   |
|   |
|   |
|   |
|   |
|   |
|   |
|   |
|   |
|   |
|   |
|   |
|   |
|   |
|   |
|   |
|   |
|   |
|   |
| Return spent imaging supplies through the Xerox Green World Alliance collection/reuse/recycling programme. For more information, visit www.xerox.com/about-xerox/recycling.   |
| For more information, visit us at www.xerox.com/office  |
| Configurations vary by geography.   |
|   |
| © 2017 Xerox Corporation. All rights reserved. Xerox®, Xerox and Design®, CentreWare®, ConnectKey® Global Print Driver®, Mobile Express Driver®, SuppliesAssistant® and VersaLink® are trademarks of Xerox Corporation in the United States and/or other countries. The information in this brochure is subject to change without notice. Undated 10/17 |

