

Xerox® VersaLink® C7020/C7025/C7030 Colour Multifunction Printer

Xerox[®] VersaLink[®] C7000 Series Colour Multifunction Printers are built on Xerox[®] ConnectKey[®] Technology. For more information, go to **www.connectkey.co.uk**.



SYSTEM SPECIFICATIONS	VERSALINK® C7020	VERSALINK® C7025	VERSALINK® C7030
One-sided Speed ¹			
A4/210 x 297 mm	Up to 20 ppm (pages per minute) long-edge feed (LEF)	Up to 25 ppm LEF	Up to 30 ppm LEF
216 x 356 mm	Up to 16 ppm	Up to 19 ppm	Up to 23 ppm
A3/297 x 420 mm	Up to 11 ppm	Up to 14 ppm	Up to 17 ppm
Two-sided Speed ¹			
A4/210 x 297 mm	Up to 16 ppm LEF	Up to 19 ppm LEF	Up to 23 ppm LEF
216 x 356 mm	Up to 9 ppm	Up to 10 ppm	Up to 12 ppm
A3/297 x 420 mm	Up to 8 ppm	Up to 9 ppm	Up to 11 ppm
Monthly Duty Cycle ²	Up to 87,000 pages/month ²	Up to 107,000 pages/month ²	Up to 129,000 pages/month ²
Recommended Average Monthly Print Volume ³	Up to 5,500 pages	Up to 6,250 pages	Up to 7,000 pages
Hard Drive	320 GB HDD (Optional on Desktop\Base Unit)		
Processor	1.05 GHz Dual-Core		
Memory	4 GB		

Detailed Specifications Page 1 of 14

Connectivity	Ethernet 10/100/1000 Base-T, High-speed USB 3.0, Wi-Fi 802.11n/g/b/a and Wi-Fi Direct with optional Wi-Fi Kit (concurrent wired and wireless connections supported), NFC Tap-to-Pair			
Controller Features	Unified Address Book, Configuration Cloning, Scan Preview, Xerox Extensible Interface Platform®, Xerox App Gallery, Xerox® Standard Accounting, Network Accounting Enabled, Role Based Permissions, Convenience Authentication Enabled, Online Support			
User Interface Languages	English, French, Italian, German, Spanish, Brazilian Portuguese, Russian, Dutch, Swedish, Danish, Finnish, Norwegian, Greek, Turkish, Polish, Czech, Hungarian, Romanian, Catalan, Ukrainian, Croatian			
DEVICE SPECIFICATIONS	VERSALINK® C7020	VERSALINK® C	7025	VERSALINK® C7030
ELECTRICAL REQUIREMENTS				
North America	Voltage: 110-127 V -10% Frequency: 50/60 Hz +/-3			
Europe and Other Geographies		Voltage: 220-240 V +/- 10 % Frequency: 50 Hz +/- 3 % , 8A		
POWER CONSUMPTION				
Printing ⁴	For 110 V: 20 ppm = 0.9 k	Wh; 25 ppm = 1.1 kWh; 30 p	pm = 1.5 kWh	
Standby Mode ⁴	80 Watts or less	80 Watts or less		94 Watts or less
Sleep Mode ⁴	0.72 Watts or less			
OPERATING ENVIRONMENT				
Required Temperature Range (Storage)	0 to 35 °C			
Required Temperature Range (Operating)	10 to 32 °C			
Required Relative Humidity	10% to 85%			
Sound Power Levels	Printing: 6.70 B(A) or less			
	• 20 ppm = 6.45 B(A); 25	ppm = 6.50 B(A); 30 ppm =	6.70 B(A)	
	Standby: 4.10 B(A) or less			
		20 ppm 1.10 b(1), 23 ppm 1.10 b(1), 30 ppm 1.10 b(1)		
	Full System (including Finisher and HCF) Printing: 20 ppm = 7.07 B(A); 25 ppm = 7.22 B(A); 30 ppm = 7.37 B(A)			
		(A); 25 ppm = 7.22 B(A); 30 p (A); 25 ppm = 4.10 B(A); 30 p	•	
Sound Pressure Levels	Printing: 52.0 dB(A)			
	· ·	25 ppm = 50.0 dB(A); 30 ppm	n = 52.0 dB(A)	
	Standby: 26.0 dB(A) • 20 ppm = 26.0 dB(A); 25 ppm = 26.0 dB(A); 30 ppm = 26.0 dB(A)			
		Full System (including Finisher and HCF)		
	Printing: 20 ppm = 55.5 dB(A); 25 ppm = 57.0 dB(A); 30 ppm = 58.5 dB(A) Standby: 20 ppm = 26.0 dB(A); 25 ppm = 26.0 dB(A); 30 ppm = 26.0 dB(A)			
Boot Time (from Off to UI Ready)	As fast as 98 seconds	(), s pp. see (), s		
Warm-up Time (from Sleep to UI Ready)	As fast as 12 seconds			
DIMENSIONS AND WEIGHT (UNPACKAGED)	WIDTH	DEPTH	HEIGHT	WEIGHT
Base Unit	590 mm	670.8 mm	767.9 mm	67.0 kg
Base Unit with Single Tray with Stand Module	615.7 mm	670.8 mm	1118.6 mm	92.0 kg
Base Unit with High Capacity Tandem Tray Module	615.7 mm	670.8 mm	1118.6 mm	92.4 kg
Base Unit with Three Tray Module	615.7 mm	670.8 mm	1118.6 mm	94.5 kg

Detailed Specifications Page 2 of 14

Base Unit with Three Tray Module and Office Finisher LX (with Booklet Maker)	1194.0 mm	681.8 r	nm	1118.6 mm		132.4 kg
Base Unit with Three Tray Module and Office Finisher (with Booklet Maker)	1148.6 mm	8.6 mm 678.6 mm		1118.6 mm		124.2 kg
CERTIFICATIONS						
To view the latest list of certification	ons go to www.xerox.c	om/OfficeCert	ifications			
PRINT	VERSALINK® C702		VERSALINK® C	7025	VEDSAL	.INK [®] C7030
First-Print-Out Time	As fast as 9.4 secon		As fast as 9.4 se			as 7.3 seconds colour
riist-riint-Out Tiine					_	
	As fast as 7.2 secon		As fast as 7.1 se	conds black	As fast o	as 5.6 seconds black
Print Resolution	Up to 1200 x 2400	dpi				
Page Description Languages	PCL® 5e, 6 PDF XPS TIFF JPEG HP-GL Adobe® PostScript® 3™ (Optional)					
Maximum Print Area	4 mm from Lead ed	ge of paper, 2 n	nm from Side and	Trail edges of pap	er	
	Application Defaults Banner Pages Enable/Disable Bi-directional Real-time Status Booklet Layout Colour Correction Colour Adjustments (lightness, contrast, saturation, colour balance) Draft Mode Finishing (requires finishing) Fit to New Paper Size Job Identification (Print ID or Banner, Print ID in margins on first page only or all pages) Job Monitoring (Client or Local User Interface)			ages)		
	LAN Fax (requires For N-up Page Layout (it Paper Selection by A Personal Print Print Around Enabled Print from USB Sample Set Saved Job Scaling Secure Print Skip Blank Pages Special Pages (exce Store and Recall Dri Stored Jobs Deletion Two-sided Printing (it Watermark (predefit Serve) Farth Smart	up to 16 pages p Attribute r/Disable ption page prog ver Settings n as default) ned and custom	gramming: covers,	inserts, exceptions	pages)	
Print from USB	Xerox® Earth Smart Driver Settings Allows walk-up printing from Type A USB port Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TIFF, XPS, PDF/A					

Detailed Specifications Page 3 of 14

$Xerox^{\circledR}\ VersaLink^{\circledR}\ C7020/C7025/C7030\ Colour\ Multifunction\ Printer$

Operating Systems	Windows® 7, 8, 8.1, 10			
. 5 ,	Windows Server 2008 SP2, Server 2008 R2 SP1, Server 2012, Server 2012 R2, Server 2016			
	Mac OS® version 10.12, 10.13			
	Citrix®			
	Redhat® Enterprise Linux®			
	Fedora Core			
	IBM® AIX®			
	HP-UX®			
	Oracle® Solaris			
	SUSE®			
	SAP®			
		ted versions for the above operating s evice at www.support.xerox.com/en		
Fonts	PostScript fonts: 136			
	PCL fonts: 83	· ·		
Xerox® Mobile Express Driver®	Makes it easy for mobile users to find, use and manage Xerox® and non-Xerox® devices in every new location. Plug into a new network and Mobile Express Driver® automatically discovers available printers and provides status and capability information. Save a list of "favourite" printers for each location, store application print settings for use on any printer in any network and greatly reduce mobile support calls to IT.			
Xerox® Global Print Driver®	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox® devices from a single driver. It provides a consistent, easy-to-use interface for end users, reducing the number of support calls and simplifying print services management.			
Xerox® Pull Print Driver	Makes it easy for IT managers to qualify, deploy and manage all print devices using a single driver in a Pull Print environment. Uses a single queue and single driver. The Xerox® Pull Print Driver extends convenience across a broad range of printing assets. IT administrators no longer need to manage and configure multiple drivers. Used in conjunction with Equitrac Office®, Ysoft® SafeQ®, Pharos® and others.			
COPY	VERSALINK [®] C7020	VERSALINK® C7025	VERSALINK® C7030	
Document Scanner	110-sheet Duplex Automatic Docun	nent Feeder (DADF)	'	
Document Scanner Size	Platen: Up to 332.0 x 437 mm DADF: Up to 297 x 431.8 mm			
Simplex Copy Speed	Up to 20 cpm (copies per minute) 216 x 279 mm	Up to 25 cpm (copies per minute) 216 x 279 mm	Up to 30 cpm (copies per minute) 216 x 279 mm	
	Up to 20 cpm A4 (210 x 297 mm)	Up to 25 cpm A4 (210 x 297 mm)	Up to 30 cpm A4 (210 x 297 mm)	
Duplex Copy Speed	Up to 17 cpm (copies per minute)	Up to 18 cpm (copies per minute)	Up to 18 cpm (copies per minute) 216 x 279 mm	
	216 x 279 mm	216 x 279 mm	210 X 27 3 111111	
	216 x 2/9 mm Up to 17 cpm A4 (210 x 297 mm)	Up to 18 cpm A4 (210 x 297 mm)	Up to 18 cpm A4 (210 x 297 mm)	
First-Copy-Out Time				
First-Copy-Out Time	Up to 17 cpm A4 (210 x 297 mm)	Up to 18 cpm A4 (210 x 297 mm)	Up to 18 cpm A4 (210 x 297 mm)	
First-Copy-Out Time Sides (input: output)	Up to 17 cpm A4 (210 x 297 mm) As fast as 9.0 seconds colour	Up to 18 cpm A4 (210 x 297 mm) As fast as 9.0 seconds colour	Up to 18 cpm A4 (210 x 297 mm) As fast as 7.2 seconds colour	
	Up to 17 cpm A4 (210 x 297 mm) As fast as 9.0 seconds colour As fast as 6.9 seconds black	Up to 18 cpm A4 (210 x 297 mm) As fast as 9.0 seconds colour	Up to 18 cpm A4 (210 x 297 mm) As fast as 7.2 seconds colour	
Sides (input: output)	Up to 17 cpm A4 (210 x 297 mm) As fast as 9.0 seconds colour As fast as 6.9 seconds black 1:1, 1:2, 2:2 and 2:1	Up to 18 cpm A4 (210 x 297 mm) As fast as 9.0 seconds colour	Up to 18 cpm A4 (210 x 297 mm) As fast as 7.2 seconds colour	
Sides (input: output) Quantity	Up to 17 cpm A4 (210 x 297 mm) As fast as 9.0 seconds colour As fast as 6.9 seconds black 1:1, 1:2, 2:2 and 2:1 1 to 999	Up to 18 cpm A4 (210 x 297 mm) As fast as 9.0 seconds colour As fast as 6.9 seconds black	Up to 18 cpm A4 (210 x 297 mm) As fast as 7.2 seconds colour	

Detailed Specifications Page 4 of 14

Copy Features	Annotation (Page Numbers, Comments, Date Stamp, Bates Stamping)*
	Auto-colour Sensing
	Automatic Background Suppression
	Book Copying with Centre Erase
	Booklet Copying*
	Collation
	Colour Balance
	Colour Effects
	Darkness Control
	Edge Erase
	Front Cover
	ID Card Copy
	Image Enhancement
	Image Shift
	Lighten/Darken
	N-up
	Original Orientation
	Original Size
	Original Type
	Page Layout
	Reduce/Enlarge 25% to 400%
	Sample Copy
	Saturation
	Sharpness
	*Requires HDD/Productivity Kit
SCAN	
SCAN Capability	Black-and-white and colour scanning
	Black-and-white and colour scanning Scan while the system is printing copy or network print jobs, or while it is transferring scan to network or fax jobs
Capability Concurrency	Scan while the system is printing copy or network print jobs, or while it is transferring scan to network or fax jobs
Capability	Scan while the system is printing copy or network print jobs, or while it is transferring scan to network or fax jobs Black-and-white: Scan up to 55 ipm — A4 (210 x 297 mm)
Capability Concurrency Simplex Input Speed	Scan while the system is printing copy or network print jobs, or while it is transferring scan to network or fax jobs Black-and-white: Scan up to 55 ipm – A4 (210 x 297 mm) Colour: Scan up to 55 ipm – A4 (210 x 297 mm)
Capability Concurrency	Scan while the system is printing copy or network print jobs, or while it is transferring scan to network or fax jobs Black-and-white: Scan up to 55 ipm – A4 (210 x 297 mm) Colour: Scan up to 55 ipm – A4 (210 x 297 mm) Black-and-white: Scan up to 26 ipm – A4 (210 x 297 mm)
Capability Concurrency Simplex Input Speed Duplex Input Speed	Scan while the system is printing copy or network print jobs, or while it is transferring scan to network or fax jobs Black-and-white: Scan up to 55 ipm – A4 (210 x 297 mm) Colour: Scan up to 55 ipm – A4 (210 x 297 mm) Black-and-white: Scan up to 26 ipm – A4 (210 x 297 mm) Colour: Scan up to 26 ipm – A4 (210 x 297 mm)
Capability Concurrency Simplex Input Speed Duplex Input Speed Resolution	Scan while the system is printing copy or network print jobs, or while it is transferring scan to network or fax jobs Black-and-white: Scan up to 55 ipm – A4 (210 x 297 mm) Colour: Scan up to 55 ipm – A4 (210 x 297 mm) Black-and-white: Scan up to 26 ipm – A4 (210 x 297 mm) Colour: Scan up to 26 ipm – A4 (210 x 297 mm) Optical – 600 x 600 dpi
Capability Concurrency Simplex Input Speed Duplex Input Speed Resolution Bit Depth	Scan while the system is printing copy or network print jobs, or while it is transferring scan to network or fax jobs Black-and-white: Scan up to 55 ipm – A4 (210 x 297 mm) Colour: Scan up to 55 ipm – A4 (210 x 297 mm) Black-and-white: Scan up to 26 ipm – A4 (210 x 297 mm) Colour: Scan up to 26 ipm – A4 (210 x 297 mm) Optical – 600 x 600 dpi 24-bit colour/8-bit greyscale
Capability Concurrency Simplex Input Speed Duplex Input Speed Resolution	Scan while the system is printing copy or network print jobs, or while it is transferring scan to network or fax jobs Black-and-white: Scan up to 55 ipm – A4 (210 x 297 mm) Colour: Scan up to 55 ipm – A4 (210 x 297 mm) Black-and-white: Scan up to 26 ipm – A4 (210 x 297 mm) Colour: Scan up to 26 ipm – A4 (210 x 297 mm) Optical – 600 x 600 dpi 24-bit colour/8-bit greyscale Platen: Up to 332 x 437 mm
Capability Concurrency Simplex Input Speed Duplex Input Speed Resolution Bit Depth	Scan while the system is printing copy or network print jobs, or while it is transferring scan to network or fax jobs Black-and-white: Scan up to 55 ipm – A4 (210 x 297 mm) Colour: Scan up to 55 ipm – A4 (210 x 297 mm) Black-and-white: Scan up to 26 ipm – A4 (210 x 297 mm) Colour: Scan up to 26 ipm – A4 (210 x 297 mm) Optical – 600 x 600 dpi 24-bit colour/8-bit greyscale
Capability Concurrency Simplex Input Speed Duplex Input Speed Resolution Bit Depth	Scan while the system is printing copy or network print jobs, or while it is transferring scan to network or fax jobs Black-and-white: Scan up to 55 ipm – A4 (210 x 297 mm) Colour: Scan up to 55 ipm – A4 (210 x 297 mm) Black-and-white: Scan up to 26 ipm – A4 (210 x 297 mm) Colour: Scan up to 26 ipm – A4 (210 x 297 mm) Optical – 600 x 600 dpi 24-bit colour/8-bit greyscale Platen: Up to 332 x 437 mm
Capability Concurrency Simplex Input Speed Duplex Input Speed Resolution Bit Depth Maximum Scan Area	Scan while the system is printing copy or network print jobs, or while it is transferring scan to network or fax jobs Black-and-white: Scan up to 55 ipm – A4 (210 x 297 mm) Colour: Scan up to 55 ipm – A4 (210 x 297 mm) Black-and-white: Scan up to 26 ipm – A4 (210 x 297 mm) Colour: Scan up to 26 ipm – A4 (210 x 297 mm) Optical – 600 x 600 dpi 24-bit colour/8-bit greyscale Platen: Up to 332 x 437 mm Document Feeder: 297 x 431.8 mm
Capability Concurrency Simplex Input Speed Duplex Input Speed Resolution Bit Depth Maximum Scan Area	Scan while the system is printing copy or network print jobs, or while it is transferring scan to network or fax jobs Black-and-white: Scan up to 55 ipm – A4 (210 x 297 mm) Colour: Scan up to 55 ipm – A4 (210 x 297 mm) Black-and-white: Scan up to 26 ipm – A4 (210 x 297 mm) Colour: Scan up to 26 ipm – A4 (210 x 297 mm) Optical – 600 x 600 dpi 24-bit colour/8-bit greyscale Platen: Up to 332 x 437 mm Document Feeder: 297 x 431.8 mm FTP
Capability Concurrency Simplex Input Speed Duplex Input Speed Resolution Bit Depth Maximum Scan Area	Scan while the system is printing copy or network print jobs, or while it is transferring scan to network or fax jobs Black-and-white: Scan up to 55 ipm – A4 (210 x 297 mm) Colour: Scan up to 55 ipm – A4 (210 x 297 mm) Black-and-white: Scan up to 26 ipm – A4 (210 x 297 mm) Colour: Scan up to 26 ipm – A4 (210 x 297 mm) Optical – 600 x 600 dpi 24-bit colour/8-bit greyscale Platen: Up to 332 x 437 mm Document Feeder: 297 x 431.8 mm FTP SMTP
Capability Concurrency Simplex Input Speed Duplex Input Speed Resolution Bit Depth Maximum Scan Area Network Filing Protocols	Scan while the system is printing copy or network print jobs, or while it is transferring scan to network or fax jobs Black-and-white: Scan up to 55 ipm – A4 (210 x 297 mm) Colour: Scan up to 55 ipm – A4 (210 x 297 mm) Black-and-white: Scan up to 26 ipm – A4 (210 x 297 mm) Colour: Scan up to 26 ipm – A4 (210 x 297 mm) Optical – 600 x 600 dpi 24-bit colour/8-bit greyscale Platen: Up to 332 x 437 mm Document Feeder: 297 x 431.8 mm FTP SMTP SMB
Capability Concurrency Simplex Input Speed Duplex Input Speed Resolution Bit Depth Maximum Scan Area Network Filing Protocols	Scan while the system is printing copy or network print jobs, or while it is transferring scan to network or fax jobs Black-and-white: Scan up to 55 ipm – A4 (210 x 297 mm) Colour: Scan up to 55 ipm – A4 (210 x 297 mm) Black-and-white: Scan up to 26 ipm – A4 (210 x 297 mm) Colour: Scan up to 26 ipm – A4 (210 x 297 mm) Optical – 600 x 600 dpi 24-bit colour/8-bit greyscale Platen: Up to 332 x 437 mm Document Feeder: 297 x 431.8 mm FTP SMTP SMB JPG
Capability Concurrency Simplex Input Speed Duplex Input Speed Resolution Bit Depth Maximum Scan Area Network Filing Protocols	Scan while the system is printing copy or network print jobs, or while it is transferring scan to network or fax jobs Black-and-white: Scan up to 55 ipm – A4 (210 x 297 mm) Colour: Scan up to 55 ipm – A4 (210 x 297 mm) Black-and-white: Scan up to 26 ipm – A4 (210 x 297 mm) Colour: Scan up to 26 ipm – A4 (210 x 297 mm) Optical – 600 x 600 dpi 24-bit colour/8-bit greyscale Platen: Up to 332 x 437 mm Document Feeder: 297 x 431.8 mm FTP SMTP SMTP SMB JPG TIFF (single and multi-page)
Capability Concurrency Simplex Input Speed Duplex Input Speed Resolution Bit Depth Maximum Scan Area Network Filing Protocols	Scan while the system is printing copy or network print jobs, or while it is transferring scan to network or fax jobs Black-and-white: Scan up to 55 ipm – A4 (210 x 297 mm) Colour: Scan up to 55 ipm – A4 (210 x 297 mm) Black-and-white: Scan up to 26 ipm – A4 (210 x 297 mm) Colour: Scan up to 26 ipm – A4 (210 x 297 mm) Optical – 600 x 600 dpi 24-bit colour/8-bit greyscale Platen: Up to 332 x 437 mm Document Feeder: 297 x 431.8 mm FTP SMTP SMB JPG TIFF (single and multi-page) XPS (single and multi-page)
Capability Concurrency Simplex Input Speed Duplex Input Speed Resolution Bit Depth Maximum Scan Area Network Filing Protocols	Scan while the system is printing copy or network print jobs, or while it is transferring scan to network or fax jobs Black-and-white: Scan up to 55 ipm – A4 (210 x 297 mm) Colour: Scan up to 55 ipm – A4 (210 x 297 mm) Black-and-white: Scan up to 26 ipm – A4 (210 x 297 mm) Colour: Scan up to 26 ipm – A4 (210 x 297 mm) Optical – 600 x 600 dpi 24-bit colour/8-bit greyscale Platen: Up to 332 x 437 mm Document Feeder: 297 x 431.8 mm FTP SMTP SMB JPG TIFF (single and multi-page) XPS (single and multi-page) PDF (single and multi-page)
Capability Concurrency Simplex Input Speed Duplex Input Speed Resolution Bit Depth Maximum Scan Area Network Filing Protocols	Scan while the system is printing copy or network print jobs, or while it is transferring scan to network or fax jobs Black-and-white: Scan up to 55 ipm – A4 (210 x 297 mm) Colour: Scan up to 55 ipm – A4 (210 x 297 mm) Black-and-white: Scan up to 26 ipm – A4 (210 x 297 mm) Colour: Scan up to 26 ipm – A4 (210 x 297 mm) Optical – 600 x 600 dpi 24-bit colour/8-bit greyscale Platen: Up to 332 x 437 mm Document Feeder: 297 x 431.8 mm FTP SMTP SMB JPG TIFF (single and multi-page) XPS (single and multi-page) PDF (single and multi-page) Searchable PDF via Optical Character Recognition (OCR)
Capability Concurrency Simplex Input Speed Duplex Input Speed Resolution Bit Depth Maximum Scan Area Network Filing Protocols File Formats	Scan while the system is printing copy or network print jobs, or while it is transferring scan to network or fax jobs Black-and-white: Scan up to 55 ipm – A4 (210 x 297 mm) Colour: Scan up to 55 ipm – A4 (210 x 297 mm) Black-and-white: Scan up to 26 ipm – A4 (210 x 297 mm) Colour: Scan up to 26 ipm – A4 (210 x 297 mm) Optical – 600 x 600 dpi 24-bit colour/8-bit greyscale Platen: Up to 332 x 437 mm Document Feeder: 297 x 431.8 mm FTP SMTP SMB JPG TIFF (single and multi-page) XPS (single and multi-page) PDF (single and multi-page) Searchable PDF via Optical Character Recognition (OCR) Password-protected PDF Linearised PDF (set via embedded web server) and PDF/A
Capability Concurrency Simplex Input Speed Duplex Input Speed Resolution Bit Depth Maximum Scan Area Network Filing Protocols	Scan while the system is printing copy or network print jobs, or while it is transferring scan to network or fax jobs Black-and-white: Scan up to 55 ipm – A4 (210 x 297 mm) Colour: Scan up to 55 ipm – A4 (210 x 297 mm) Black-and-white: Scan up to 26 ipm – A4 (210 x 297 mm) Colour: Scan up to 26 ipm – A4 (210 x 297 mm) Optical – 600 x 600 dpi 24-bit colour/8-bit greyscale Platen: Up to 332 x 437 mm Document Feeder: 297 x 431.8 mm FTP SMTP SMB JPG TIFF (single and multi-page) XPS (single and multi-page) XPS (single and multi-page) Searchable PDF via Optical Character Recognition (OCR) Password-protected PDF

Detailed Specifications Page 5 of 14

Supported Scan Destinations	Scan to Home
	Scan to USB
	Scan to Email
	Scan to Network (Browse FTP or Browse SMB)
NETWORK SCANNING – SOFTWAR	
Xerox® ConnectKey® Apps (Found at the Xerox App Gallery)	Increase user productivity by simplifying and shortening everyday tasks. Unlike traditional software, ConnectKey® Apps do not require a dedicated server, PC or IT resource. Instead, simply download these lightweight, serverless ConnectKey® Apps to the ConnectKey® Technology-enabled multifunction printer.
PSTN ONE-LINE OR THREE-LINE F	FAX (OPTIONAL)
FAX ⁵	
Fax Speed	33.6 Kbps
Resolution	Standard 200 x 100 dpi, Fine 200 x 200 dpi, Super Fine 300 x 300, 400 x 400, 600 x 600 dpi
Compression	MH, MR, MMR, JBIG
Fax Features	Walk-up Fax, includes LAN Fax, Direct Fax, Fax Forward to Email, Fax dialing via Unified Address Book (up to 2,000 contacts)
FAX OVER IP (OPTIONAL)	
Compliance	T.38 compliant IP/SIP
Resolution	Standard 200 x 100 dpi, Fine 200 x 200 dpi, Super Fine 300 x 300, 400 x 400, 600 x 600 dpi
Compression	MH, MR, MMR, JBIG
Fax Features	Walk-up Fax, includes LAN Fax, Direct Fax, Fax Forward to Email, Fax dialing via Unified Address Book (up to 2,000 contacts)
MOBILE SOLUTIONS AND MOBIL	E DEVICE APPS
Apple® AirPrint®	Print email, photos and important office documents directly from an Apple iPhone® or iPad® with no drivers to install and no cables to connect. With AirPrint, an iPhone or iPad automatically locates and connects to the AirPrint-enabled device over the office Wi-Fi network.
Mopria® Print Services	ConnectKey® Technology-enabled print devices are Mopria® certified. Mopria® certification ensures you can print wirelessly from your Mopria®-supported (Android) smart phone, tablet and other mobile devices instantly and easily.
@PrintByXerox App	@PrintByXerox App is a free service that allows secure printing from any email-enabled device (computer, phone, tablet, iOS, Android™, Google® Chromebook™ and more) to a Xerox® printer or multifuction printer using a single email address with no IT intervention. No training is needed. End users simply send attachments to the email address, and release them at the multifunction printer panel.
Xerox® Print Service Plug-in for Android™ (Free at Google Play™ Store)	The Xerox® Print Service Plug-in for Android KitKat (4.4 or greater) devices streamlines mobile printing without third-party apps or additional print drivers. You can easily print photos, web pages and documents when your mobile device is connected to multifunction printers using a wireless network. A robust print option set includes two-sided printing, stapling and secure code release. A free download is available from the Google Play™ store.
Xerox® Workplace Mobile App (download from the Xerox App Gallery)	The Xerox® Workplace Mobile App gives you the personal contactless connection you need with your multifunction printer (MFP), allowing you to save time on daily tasks and get work done safely. You can scan, print, copy or release jobs using your mobile smartphone as a remote control, without having to touch your MFP user panel. It takes the guesswork out of quickly and securely connecting your iOS and Android devices to your Xerox® Multifuction Printer. Download the app for free. Use it with Xerox® Workplace Solutions to access advanced features.
Xerox® Workplace Suiteand Xerox® Workplace Cloud	Xerox® Workplace Suite is a modular set of workflows designed to save customers time and money by providing effective control over their print fleet, while enabling worker productivity and mobility through a set of robust workflows. Xerox enables ultimate customer flexibility by offering these capabilities in both an onpremises server version (Workplace Suite) and with a cloud based-version (Workplace Cloud) of this solution.

Detailed Specifications Page 6 of 14

SECURITY	
Security Features	Access Controls
Security reactures	AES 256-bit encryption
	Audit log
	Certificate path validation
	Certificate Revocation List (CRL)/Status Protocol (OCSP)
	Detection of external program falsification (XCP plug-in)
	Cisco® Identity Services Engine (ISE) Integration Domain
	Filtering
	FIPS 140-2
	Firmware Verification
	Immediate Disk Overwrite*
	IP Address Filtering
	IPsec
	Network Authentication Port
	Filtering
	Pre-installed Self-Signed Certificates
	Role Based Permissions
	Secure Email
	Secure Fax
	Secure Print
	Security Certificate Management
	Smart Card Enablement (CAC/PIV/.NET)
	SNMPv3
	Status Protocol (OCSP)
	TLS/SSL
	*Requires HDD/Productivity Kit
ACCOUNTING	
XEROX® STANDARD ACCOUNTIN	IG/NETWORK ACCOUNTING (STANDARD)
Tracking	Copy, Print, Fax, Scan and Email usage
Accounting	Xerox® Standard Accounting Feature
,	Up to 1,000 User Accounts without HDD
	Up to 9,999 User Accounts with HDD
	Up to 500 General Accounts
	Network Accounting (Job-Based Accounting)
	Up to 1,000 User IDs; Up to 1,000 Account IDs without HDD
	Up to 60,000 User IDs; Up to 60,000 Account IDs with HDD
	Up to 14,000 Accounting Records (transactions)
Features	Administrator can manage the feature via the Embedded Web Server.
ACCOUNTING OPTIONS – NETWOR	RK ACCOUNTING (ALLOWS CENTRAL SERVER TO MANAGE ALL ACCOUNTING)
	Enhanced network accounting with up-to-the-minute data on how the system is being used
	 Comprehensive management and enterprise-scale tracking and reporting of device usage of copy, print, scan and fax
	Numerous solutions are available through Xerox Alliance Partners. For details visit www.xerox.co.uk
	Security enhancements include simultaneous support for HTTP/HTTPS protocols
	Device requests account authentication from third-party server, enabling larger databases of users and
	accounts
	Accept Authentication Login at control panel and pass to third-party Networking Account

Detailed Specifications Page 7 of 14

PAPER HANDLING	
DOCUMENT FEEDER	
Capacity ⁶	Duplex Automatic Document Feeder (DADF): 110 sheets
Sizes One-sided: Two-Sided	Custom sizes: 125 x 85 mm to 297 x 431.8 mm 125 x 110 mm to 297 x 431.8 mm
Weights One-sided: Two-Sided	38 to 128 gsm 50 to 128 gsm
BYPASS TRAY	
Capacity ⁶	100 sheets
Sizes	Custom sizes: 88.9 x 98.4 mm to 297 x 431.8 mm
Weights One-sided: Two-Sided	60 to 216 gsm 60 to 169 gsm
	Plain Paper Cardstock Custom Envelopes Hole Punched Labels Heavyweight Labels Letterhead Lightweight Card Stock Lightweight Glossy Cardstock Lightweight Glossy Cardstock Reload Pre-Printed Recycled
TRAY 1	
Capacity ⁶	520 sheets
Sizes	Custom sizes: 139.7 x 182.0 mm to 297.0 x 431.8 mm
Weights One-sided: Two-Sided	60 to 256 gsm 60 to 169 gsm
Types	Bond Plain Paper Cardstock Custom Hole-Punched Labels Heavyweight Labels Extra Heavyweight Labels Letterhead Lightweight Card Stock Lightweight Glossy Cardstock Lightweight Glossy Cardstock Reload Heavyweight Cardstock Pre-Printed Recycled

Detailed Specifications Page 8 of 14

SINGLE TRAY MODULE (OPTIONAL – BASE MODEL ONLY)
Capacity ⁶	520 sheets
Sizes	Custom sizes: 139.7 x 182.0 mm to 297.0 x 431.8 mm
Weights One-sided: Two-Sided	60 to 256 gsm 60 to 169 gsm
Types	Bond Plain Paper Cardstock Custom Hole-Punched Labels Heavyweight Labels Extra Heavyweight Labels Letterhead Lightweight Card Stock Lightweight Glossy Cardstock
SINGLE TRAY MODULE W	Lightweight Glossy Cardstock Reload Heavyweight Cardstock Pre-Printed Recycled VITH STAND (OPTIONAL)
Capacity ⁶	520 sheets
	Custom sizes: 139.7 x 182.0 mm to 297.0 x 431.8 mm
Sizes	Custom sizes: 139.7 x 182.0 min to 297.0 x 431.8 min
Weights One-sided: Two-Sided	60 to 256 gsm 60 to 169 gsm
Types	Bond Plain Paper Cardstock Custom Envelopes Hole Punched Labels Heavyweight Labels Letterhead Lightweight Card Stock Lightweight Glossy Cardstock Reload Pre-Printed Recycled
THREE TRAY MODULE (O	PTIONAL)
Capacity ⁶	Tray 2: 520 sheets Tray 3: 520 sheets Tray 4: 520 sheets
Sizes	Custom sizes: 139.7 x 182.0 mm to 297.0 x 431.8 mm
Weights One-sided: Two-Sided	60 to 256 gsm 60 to 169 gsm

Detailed Specifications Page 9 of 14

Types	Bond
	Plain Paper
	Cardstock
	Custom
	Hole Punched
	Labels
	Heavyweight Labels Extra
	Heavyweight Labels
	Letterhead
	Lightweight Card Stock
	Lightweight Glossy Cardstock
	Lightweight Glossy Cardstock Reload
	Heavyweight Cardstock
	Pre-Printed
	Recycled
HIGH CAPACITY TANDEM TRAY M	
Capacity ⁶	Tray 2: 520 sheets
cupacity	Tray 3: 870 sheets
	Tray 4: 1,130 sheets
Cina	
Sizes	Tray 2: Custom sizes: 139.7 x 182.0 mm to 297.0 x 431.8 mm
	Tray 3: Standard Sizes: A4 or B5
	Tray 4: Standard Sizes: A4 or B5
Weights	(0), 250
One-sided: Two-Sided	60 to 256 gsm 60 to 169 gsm
	Bond
Types	
	Plain Paper Cardstock
	Custom
	Hole Punched
	Labels
	Heavyweight Labels Extra
	Heavyweight Labels
	Letterhead
	Lightweight Card Stock
	Lightweight Glossy Cardstock
	Lightweight Glossy Cardstock Reload
	Heavyweight Cardstock
	Pre-Printed
	Recycled
ENVELOPE TRAY – REPLACES TRAY	
Capacity ⁶	Up to 60 envelopes
Sizes	No. 10 commercial, Monarch, DL, C5
	Custom sizes: 98 x 148 mm to 162 x 241 mm
Weights	75 to 90 gsm
HIGH CAPACITY FEEDER (OPTIONA	AL)
Capacity ⁶	2,000 sheets
Sizes	Standard Sizes: A4 or B5
51205	

Detailed Specifications Page 10 of 14

Weights	50. 246		
One-sided: Two-Sided	60 to 216 gsm 60 to 169 gsm		
TOTAL CAPACITY	00 to 105 gs.ii		
	620 sheets		
Base Unit Capacity ⁶			
Single Tray Module Capacity ⁶	1,140 sheets		
Single Tray Module with Stand Capacity ⁶	1,140 sheets		
Three Tray Module Capacity ⁶	2,180 sheets		
High-Capacity Tandem Tray Capacity ⁶	3,140 sheets		
FINISHING			
OUTPUT TRAYS (OPTIONAL ON BA	SE MODEL)		
Dual Catch Trays ⁶	250 sheets each; Lower tray offsets		
INTEGRATED OFFICE FINISHER TY	PE A AND INTEGRATED OFFICE FINISHER (OPTIONAL)		
Stacking Tray	500 sheets of 80 gsm – A4 or 250 sheets of 80 gsm – A3		
Sizes	89 x 98 mm to 297 x 432 mm		
Weights	Integrated Office Finisher Type A: 60 to 220 gsm Integrated Office Finisher: 60 to 256 gsm		
Stapling	Dual Auto Stapling (Single for Type A): 50 sheets maximum: Letter/A4/B5-size sheets (less than 90 gsm or (2) 220 gsm covers) 30 sheets maximum: Legal/Tabloid/A3/B4-size sheets (less than 90 gsm or (2) 220 gsm covers)		
OFFICE FINISHERS (OPTIONAL)			
Capacity ⁶	Stacking Tray: 2,000 sheets unstapled or 1,000 sheets single stapled or 750 sheets dual stapled (A4) (dual stapling only with optional booklet maker)		
Sizes:			
Office Finisher LX Office Finisher	210 x 182 mm to 297 x 432 mm 148.0 x 297.0 mm to 148.0 to 432.0 mm		
Weights	Office Finisher LX: 60 to 220 gsm Office Finisher: 60 to 256 gsm		
Multiposition Stapling	50 sheets of 24 lb bond/90 gsm		
Hole Punch (Optional)	Office Finisher LX up to 200 gsm/Office Finisher up to 220 gsm		
North America: Europe:	2-3 Hole Punch 2-4 Hole Punch		
	BOOKLET MAKER FOR OFFICE FINISHERS (SCORE/CREASE, SADDLE-STITCH STAPLE) (OPTIONAL)		
Capacity ⁶	40 booklets (2-15 sheets per booklet – 80 gsm or less)		
Sizes	Letter – A4 SEF Legal – B4 SEF Ledger – A3 SEF		
Saddle-stitch Stapling	2-15 sheets/8-60 page booklet		
	Office Finisher LX: 60 to 90 gsm		
	Office Finisher: 64 to 220 gsm		
Score/Crease	1-15 sheets/unstapled/64 -105 gsm		
CONVENIENCE STAPLER AND WOR	RK SURFACE (OPTIONAL)		
Capacity ⁶	50-sheet stapling		
	5,000 staples		
	Requires a separate outlet		

Detailed Specifications Page 11 of 14

DEVICE MANAGEMENT	
Network Protocols	TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD LDAP Bonjour®/AirPrint™ FTP Most protocols not in use can be disabled
Administrative Protocols	DHCP, SNMP, WINS, HTTP, HTTPS, TLS, SNTP, MDNS
XEROX® CENTREWARE® WEB SO	OFTWARE
	 A web-based server application for network administrators that permits web-browser-based device management from any workstation, whether running Windows, UNIX or any other operating system Works with any SNMP-managed printer from any manufacturer Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management
EMBEDDED WEB SERVER – INT	EGRATED DEVICE WEB PAGE
Device Status	 Tray Status/Contents Consumables Status Billing/Usage Quick Links Online Support
Print Queue Viewing	Job print queue management – view and delete
Job Submission	Print-ready files (PS (with optional PostScript option), PCL, PDF, XPS, JPEG)
Device Administration	Allows simple, remote installation setting of configuration options and management of the device
Browsers	Microsoft® Internet Explorer® Microsoft Edge™ Mozilla™ Firefox® Apple® Safari® Google Chrome™
REMOTE SERVICES	·
Xerox® Automatic Meter Readings (AMR)	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.
Automatic Supplies Replenishment (ASR)	Automatically orders supplies for Xerox® output devices based on actual usage, eliminating the need to manually manage supplies inventory.

Detailed Specifications Page 12 of 14

Xerox® VersaLink® C7020/C7025/C7030 Colour Multifunction Printer

SUPPLIES AND ACCESSORIES	QUANTITY	PART NUMBER
SUPPLIES	1	
High Capacity Print Cartridges ⁷	Cyan: 9,800 standard pages	106R03744
	Magenta: 9,800 standard pages	106R03743
	Yellow: 9,800 standard pages	106R03742
	Black: 16,100 standard pages	106R03741
Extra High Capacity Print Cartridges ⁷	Cyan: 16,500 standard pages	106R03740
	Magenta: 16,500 standard pages	106R03739
	Yellow: 16,500 standard pages	106R03738
	Black: 23,600 standard pages	106R03737
Metered Print Cartridges ⁸	Cyan: 15,000 standard pages	106R03736
	Magenta: 15,000 standard pages	106R03735
	Yellow: 15,000 standard pages	106R03734
	Black: 22,000 standard pages	106R03733
Drum Cartridge ⁹	Black: 109,000	113R00780
	Cyan, Magenta, Yellow: 87,000 standard pages	
Waste Toner Bottle	30,000	115R00128
Office Finishers Booklet Maker Cartridge (8 cartridges per container)	16,000 staples (2,000 each cartridge)	008R12897
Staple Refills for Finishers (3 refills per container)	15,000 staples (5,000 each refill)	008R12941
Staple Cartridge for Finishers (1 cartridge per container)	5,000 staples (5,000 each cartridge)	008R12964

Detailed Specifications Page 13 of 14

Xerox® VersaLink® C7020/C7025/C7030 Colour Multifunction Printer

ACCESSORIES/OPTIONS	PART NUMBER
Single Tray Module (does not include Stand – for Desktop Model only)	097S04910
Single Tray with Stand Module	097S04907
Three Tray Module	097504908
High Capacity Tandem Tray Module	097504909
Envelope Tray (Replaces Tray 1)	497K17720
Center Output Tray (Dual Catch Tray) (Optional on Desktop Model)	497K17800
HDD (320 GB hard drive) (Optional on Desktop Model)	497K17740
Integrated Office Finisher (Type A)	097S04911
Integrated Office Finisher	097504847
Office Finisher LX	097504848
Office Finisher	097S05019
Booklet Maker for Office Finisher LX	497K03852
Booklet Maker for Office Finisher	497K20590
2/3 Hole Punch for Office Finisher LX (available in Western Hemisphere)	497K03860
2/3 Hole Punch for Office Finisher (available in Western Hemisphere)	497K20600
2/4 Hole Punch for Office Finisher LX (available in Eastern Hemisphere)	497K03870
2/4 Hole Punch for Office Finisher (available in Eastern Hemisphere)	497K20610
1 Line Fax Kit (PSTN Fax)	497K17750
3 Line Fax Kit (PSTN Fax)	497K17760
Wireless Network Adapter Kit	497K16750
Internal Card Reader/RFID Kit	497K18120
PostScript Kit	497K18340
Fax Over IP Kit	497K18330

¹ Declared print speed in accordance with ISO/IEC 24734.

Return spent imaging supplies through the Xerox® Green World Alliance® collection/reuse/recycling programme. For more information, visit www.xerox.co.uk/recycling.

For more information, visit us at www.xerox.co.uk/office.

Configurations vary by geography.



² Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

³ Expected regular monthly throughput.

⁴ Power states defined per ENERGY STAR® Programme requirements for Imaging Equipment.

⁵ Requires analogue phone line.

 $^{^{6}}$ Paper capacities are based on 75 gsm stock; capacities will vary with different weight stocks.

⁷ Average standard pages. Declared Yield in accordance with ISO/IEC 19798. Yield will vary based on image, area coverage and print mode.

⁸ Assumptions: Toner cartridge yield is based on 5 % area coverage on A4 LEF. Toner yield can vary due to many factors, including but not limited to, image area coverage, image content, media size, run mode, application types, monthly print volumes and image quality set-points.

⁹ Approximate pages. Declared yield will vary depending on job run length, media size/orientation and machine speed. For more information visit: https://www.office.xerox.com/latest/SUPGL-01.pdf.