

XEROX®

print | copy | scan

Essential capabilities in one desktop device

Printer. Copier. Scanner.

The Xerox WorkCentre PE114e gives you the convenience of high-quality printing, copying and scanning all in one compact, hard-working machine. Scaled for the single-user, the WorkCentre PE114e is the perfect solution to streamline the work you do every day.



For more information please contact your nearest reseller or the local Xerox office.



WorkCentre® PE114e

SPECIFICATIONS

WorkCentre® PE114e

Performance	
Print / Copy speed	15 ppm (Letter), 14 ppm (A4)
First-Copy-Out time	Less than 13 seconds
Memory	8 MB
Print / Copy resolution	600 x 600 dpi
Scan resolution	Up to 600 dpi CIS
Recommended volume	500 to 1 500 images/month
Maximum duty cycle	Up to 10K pages/month
Paper Handling	
Paper Input	250 sheet tray, single sheet by-pass
Paper Output	150 sheets (face down), 1 sheet face up

CHARACTERISTICS

Print

Technology: Laser Monochrome
 Speed: 15 ppm (Letter), 14 (A4)
 Resolution: 600 x 600 dpi
 Language: GDI
 Print drivers: Windows 95 / 98 / NT 4.0 / 2000 / Me / XP
 Connectivity: USB 1.1 / IEEE 1284 Parallel (USB cable included)

Copy

Speed: 15 copies per min. (Letter)
 14 copies per min. (A4)
 Resolution: 600 x 600 dpi
 First-Copy-Out time: less than 13 seconds
 Reduce / Enlarge: 94%, 100%, 50%, 150%, 200%, custom
 Productivity Features:
 Multiple Copies: Up to 99 copies of original
 Pre Set Reduction Enlargement
 Clone, Poster and 2 sides to 1 page

Scan

Compatibility: TWAIN standard (driver included)
 Technology: flat-bed CID
 Bundled software: User Manual, Print Driver, Scan Driver, Remote Control Panel, Bundled OCR Software: ScanSoft®, Omni Page SE®.
 Connectivity: USB 1.1 / IEEE 1284 Parallel

Resolution Settings

Optical resolution 600 x 600 dpi (optical, monochrome and color)
 Enhanced resolution up to 4800 dpi interpolated
 Pre-scan: 75 dpi

Depth

Color: 24 bit
 Mono: 1 bit (text) / 8 bits (grayscale)
 Bundled software: User Manual, SmarThru 4, Print Driver, Scan Driver, RCP

Media handling

Input paper capacity

Main tray: 250 sheets (75 gr/m² 20 lb Bond)
 Minimum size: 76 x 127 mm / 3 x 5 in
 Maximum size: 216 x 356 mm / 8.5 x 14 in
 Weights: 60 to 90 gr/m² / 16 to 24 lb Bond
Bypass tray: single sheet
 Minimum size: 76 x 127 mm / 3 x 5 in
 Maximum size: 216 x 356 mm / 8.5 x 14 in
 Weights: 60 to 160 gr/m² / 16 to 43 lb
 Output capacity: 150 sheets (face down)
 Media types: plain paper, envelopes, labels, transparencies, cardstock

Physical characteristics

Dimensions (W x D x H):
 422 x 400 x 239 mm / 16.6 x 15.8 x 9.4 in
 Weight: 9.5 kg / 20.6 lb

Electrical

Power requirements

220 to 240 VAC, 50 / 60 Hz;
 100 to 127 VAC, 50 / 60 Hz
 Maximum power consumption: 320 watts
 Power saver mode: 19 watts
 Warm-up time: 42 seconds
 Energy saver: ENERGY STAR® compliant

Operating environment

Temperature

Maximum range:
 50° to 89° F / 10° to 32° C
 Recommended range:
 60.8° to 86° F / 16° to 30° C

Humidity

Maximum range: 20 to 80%
 Recommended range: 30 to 70%

Supplies

Approximate Yields

Toner/Photoreceptor
 Starter kit: 1 000 images;
 Replacement kit: 3 500 images
 @ 5% coverage on a Letter/A4-sized page.
 Part Number: 113R00607

Streamlined, printing, copying and scanning high-quality

Powerful technology, all in one device

- Enjoy fast, crisp black-and-white laser output printing and copying.
- Make multiple high-resolution copies, quickly and easily.
- Capture high-quality color paper documents and convert to digital.
- Repurpose text from scanned hard copy documents (OCR) automatically.

Less space More possibilities

- Smallest footprint in its class.
- Extremely easy to install and operate.
- Multiple features for enhanced office capabilities.
- Thoughtfully designed user-friendly interface.
- Print and copy on a wide variety of papers and special media.

Dependability you can count on

- Durable design is built to last.
- Single customer-replaceable cartridge maintains high quality and minimizes maintenance.
- Service and support directly from Xerox and its authorized representatives.

