

## Xerox® WorkCentre™ 3655 Multifunction Printer

The WorkCentre 3655 Multifunction Printer is built on Xerox® ConnectKey® Technology. For more information, go to www.connectkey.com.





System Specifications	WorkCentre 3655/S WorkCentre 3655/X		
Speed	Up to 45 ppm A4 / 210 x 297 mm		
Monthly Duty Cycle <sup>1</sup>	Up to 150,000 pages		
Recommended Average Monthly Print Volume²	Up to 15,000 pages		
Hard Drive / Processor / Memory	Minimum 250 GB / 1 GHz Dual-core / 2 GB		
Connectivity	10/100/1000Base-T Ethernet, High-Speed USB 2.0 Di	rect Print, Optional Wi-Fi (with Wireless Connectivity Kit)	
Controller Features	Unified Address Book, Remote Control Panel, Online Support (accessed from the user interface and print driver), Configuration Cloning		
Copy and Print			
Copy and Print Resolution	<b>Copy:</b> Up to 600 x 600 dpi; <b>Print:</b> Up to 1200 x 1200 dpi		
First-print-out Time	As fast as 8 seconds		
First-copy-out Time	As fast as 12 seconds		
Page Description Languages	Adobe® PostScript® 3™, PDF, PCL® 5c / PCL 6, XML Paper Specification (XPS®)		
Print Features	Print from USB, Earth Smart Driver Settings, Store and Recall Driver Settings, Bidirectional Status, Smart Duplex, Automatic Two-sided, Booklet Printing, Proof Print, N-up, Print Around		
Mobile Printing	Apple® AirPrint, Xerox® PrintBack, Xerox® Mobile Print Solution (Optional), Xerox® Mobile Print Cloud (Optional), Mopria™ certified		
Scan			
Standard	Destinations: Scan to Mailbox, Scan to USB, Scan to Email, Scan to Network; File Formats: PDF, PDF/A, XPS, JPEG, TIFF; Convenience Features: Scan to Home, Single Touch Scan, Searchable PDF, Single/Multi-page PDF/XPS/TIFF, Encrypted / Password Protected PDF, Linearised PDF / PDF/A		
Optional	Software Packages: ConnectKey® for SharePoint®, ConnectKey® for DocuShare®, ConnectKey® Share to Cloud, Xerox® Scan to PC Desktop® SE and Professional, other solutions available through various Xerox Alliance Partners		
Fax			
Standard Features	Internet Fax, Server Fax	Embedded Fax³, LAN Fax, Internet Fax, Server Fax	
Security			
Standard Features	McAfee® Embedded, McAfee ePolicy (ePO) Compatible, HDD Overwrite, 256-bit Encryption (FIPS 140-2 compliant), Common Criteria Certification (ISO 15408) <sup>4</sup> , Secure Print, Secure Fax, Secure Scan, Secure Email, Cisco® TrustSec Identity Services Engine (ISE) Integration, Network Authentication SSL, SNMPv3, Audit Log, Access Controls, User Permissions		
Optional Features	McAfee Integrity Control, Xerox Secure Access Unified ID System®, Smart Card Enablement Kit (CAC/PIV/.NET)		
Accounting			
Standard Features	Xerox® Standard Accounting (Copy, Print, Scan, Fax, Email), Network Accounting Enablement		
Optional Features	Equitrac Express®, Equitrac Office®, Equitrac Professional®, YSoft® SafeQ®, other solutions available through various Xerox Alliance Partners		

Control Panel Languages	_		The state of the s	Brazilian Portuguese, Swedish, Norwegian,	
	Danish, Finnish, Turkish, Greek, Russian, Czech, Polish, Hungarian				
Accessories					
Optional Accessories	550-sheet Feeder				
	Smart Card Enablement Kit	Stand Smart Card Enablement Kit			
	Xerox Secure Access Unified ID System® Wireless Connectivity Kit				
	McAfee® Integrity Control En	ablement Kit			
lectrical Requirements					
	Voltage: 220-240 VAC +/- 10 Frequency: 50/60 Hz +/- 3%,				
Power Consumption					
Running (Average)	525 watts				
itandby Mode	82 watts				
ow Power Mode	22 watts	22 watts			
Auto off / Sleep mode	0.6 watts				
Varm up (from Off)	As fast as <224 seconds (3 m	As fast as <224 seconds (3 minutes, 44 seconds) (Dependent on number of services registered)			
ow Power Recovery	<5 seconds				
Operating Environment					
Required Temperature Range	5° to 32° C				
Required Relative Humidity	15% to 85%				
Sound Power Levels	Operating 7.27 B(A), Standby: 4.8 B(A)				
Sound Pressure Levels	Operating: 55.9 dB(A), Standby: 31.9 dB(A)				
Dimensions and Weight (Unpackaged)	Width	Depth	Height	Weight	
WorkCentre 3655/S	560 mm	541 mm	577 mm	25.4 kg	
WorkCentre 3655/X	560 mm	541 mm	577 mm	26.3 kg	
550-sheet Feeder	495 mm	469 mm	96.3 mm	4.2 kg	
Stand	737 mm	699 mm	332 mm	12.9 kg	
Dimensions and Weight Packaged)	Width	Depth	Height	Weight	
WorkCentre 3655/S	653 mm	674 mm	723 mm	31.2 kg	
VorkCentre 3655/X	653 mm	674 mm	723 mm	32.1 kg	
550-sheet Feeder	575 mm	601 mm	241 mm	5.8 kg	
Stand	560 mm	530 mm	270 mm	16.6 kg	
Certifications					
	FCC Part 15, Class A FCC Part 68 CE Mark applicable to Directive	es 2006/95/EC, 2004/108/EC and 19			
	UL 60950-1/CSA 60950-1-07,		133131EC		
	EAC RoHS Directive 2011/65/EU				
	WEEE Directive 2012/19/EU				
	Citrix Cerner				
	Common Criteria (IEEE 2600.2	standard (undergoing evaluation))			
	Blue Angel ECOLOGO® (undergoing evalue	ation)			
	ENERGY STAR® qualified	2001)			
	To view the latest list of certif	ications, go to www.xerox.com/O	ficeCertifications.		

Paper Handling	
Duplex Automatic Document Feed	ler (DADF)
Capacity <sup>5</sup>	60 sheets
Speed	Up to 51 images per minute (ipm) black and white (simplex) Up to 24 ipm black and white (duplex) Up to 28 ipm colour (simplex) Up to 13 ipm colour (duplex)
Paper Sizes Sensed	139.7 x 139.7 mm to 216 x 356 mm
Weights	Simplex: 50 gsm to 125 gsm Duplex: 60 gsm to 125 gsm
Bypass Tray	
Capacity⁵	150 sheets
Sizes	Custom sizes: 76.2 x 127 mm to 216 x 356 mm
Weights	60 to 216 gsm
Types	Plain Punched Letterhead Lightweight Card stock Card stock Recycled Bond Labels Pre-printed Envelopes Custom
Tray 1	
Capacity <sup>5</sup>	550 sheets
Sizes	Custom Sizes from 139.7 x 210 mm to 216 x 356 mm
Weights	60 to 216 gsm
Types	Plain Punched Letterhead Lightweight Card stock Card stock Recycled Bond Labels Pre-printed Custom
Up to 3 Additional Trays	
Capacity <sup>5</sup>	550 sheets each
Sizes	Custom Sizes from 139.7 x 210 mm to 216 x 356 mm
Weights	60 to 216 gsm
Types	Plain Punched Letterhead Lightweight Card stock Card stock Recycled Bond Labels Pre-printed Custom
Total Capacity	
Device Standard Capacity <sup>5</sup>	700 sheets
Device Total Capacity <sup>5</sup>	2,350 sheets

Paper Output		
Capacity	Up to 250 sheets, automatic two-sided	
Offline Convenience Stapler (S	tandard on WorkCentre 3655/X, not available on WorkCentre 3655/S)	
Capacity <sup>5</sup>	20-sheet stapling, single position	
Сору		
Speed (cpm)	Up to 45 ppm A4 / 210 x 297 mm	
First-copy-out Time	As fast as 12 seconds	
Sides (input:output)	1-1, 1-2, 2-2, 2-1	
Quantity	1 to 9,999	
Resolution (max.)	Up to 600 x 600 dpi	
Reduction / Enlargement	Variable zoom from 25% to 400% in 1% increments	
Concurrency	Programme-ahead to allow job to be initiated while initial job is processed (Copy, Print, Fax and Scan)	
	Authentication for Services Auto Paper Select Auto Reduction & Enlargement to fit selected paper size Auto Tray Switching Automatic 2-sided / Duplex Booklet Creation Build Job: (Enables page-level programming and also lets you proof each section or delete last section as the job is built) Collation Covers (Front only, front and back, back only, printed inside and out: Blank or Printed) Dividers (blank) Edge Erase Features Help (Intuitive text and graphic descriptions) ID Card Copy Image Quality Adjustments Image Shift (with Auto Centre option) Invert Image (negative or mirror image) Large Job Interrupt Multi-up (up to 15 columns by 15 rows) Sample Set Save Job Settings Stapling	
Xerox® Copier Assistant®	Xerox® Copier Assistant® Software provides a PC-based alternative to the user interface touch screen. Used in conjunction with a customer-supp PC attached via the USB port, this software supports text-to-speech, screen magnification and easy PC keyboard access to basic and advanced of features. Section 508 compliant. For more information or to download Xerox® Copier Assistant® for free, visit www.xerox.com	
Print	Supplied to the property of the definition of the definition of the property o	
First-print-out Time	As fast as 8 seconds	
Print Resolution	Up to 1200 x 1200 dpi	
Print Features	Application Defaults Banner Sheet Enable / Disable Bidirectional Status Booklet Printing Cover Selection Delay Print (specific time) User Permissions Image Options (Toner Saver, Standard and High Resolution) Job Identification (Print ID or Banner, Print ID in margins on first page only or all pages) LAN Fax (requires optional Fax Kit) Layout / Watermark (N-up (up to 16 pages per sheet), Multi-up, Booklet layout / finishing, Fit to new paper size) Overlays Paper Selection by Attribute Print Around Proof Print Sample Set Saved Job Secure Print with Timed Deletion Special Pages (exception page programming: covers, inserts, exception pages) Store and Recall Driver Settings	
Print from USB	Sustainability Features (Xerox® Earth Smart Settings, Duplex, N-up, Turn-off Banner and Print ID, Smart Sample Set, Hold All Jobs)  Allows walk-up printing from Type A USB port Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TXT, TIFF, PS, XPS, PCL	

Operating Systems	Microsoft® Windows® XP SP3 (32- and 64-bit) Windows Server 2003 (32- and 64-bit) Windows Server 2008 and R2 (32- and 64-bit) Windows Server 2012 and R2 Windows Vista SP2 (32- and 64-bit) Windows 7 (32- and 64-bit) Windows 8 (32- and 64-bit) Windows 8 (32- and 64-bit) Windows 8.1 (32- and 64-bit) Mac OS 10.7, 10.8, 10.9 Linux® Redhat® Fedora® Core 19 x86 Ubuntu® 13.10 x64 openSUSE® 13.1 x64	
Network Protocols	TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6,WSD  NetWare: Bindery and NDS IPX/SPX, NDPS®/NEPS (with Server Gateway)  AppleTalk®: EtherTalk®  Microsoft Windows Networking over IP  Apple® Bonjour®  IPv6  Secure FTP  Most protocols not in use can be disabled	
Administrative Protocols	DHCP, BOOTP, SNMP, WINS, SLP® v2, HTTP, HTTPS, DHCP Autonet, SSL, NTP, DNS, SSDP	
Fonts	PCL: 93 scalable fonts, line printer and bitmap font (including Cyrillic font support) PostScript 3: 173 Type 1 fonts, 2 Multiple Master fonts	
Xerox <sup>®</sup> Mobile Express Driver <sup>®</sup>	Makes it easy for mobile users to find, use and manage Xerox® and non-Xerox devices in every new location. Plug into a new network, and Mobile Express Driver automatically discovers available printers and provides status and capability information. Save a list of "favourite" printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT.	
Xerox® Globαl Print Driver®	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox devices from a single driver. It provide consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.	
Xerox® Pull Print Driver	Makes it easy for IT managers to qualify, deploy and manage all print devices using a single driver in a Pull Print environment. Uses a single queue and single driver. The Xerox® Pull Print Driver extends convenience across a broad range of printing assets. IT administrators no longer need to manage and configure multiple drivers. Used in conjunction with Xerox Secure Access Unified ID System®, Equitrac Office®, Ysoft® SafeQ®, Pharos and others.	
Print Solutions		
Xerox® Mobile Print Cloud (Optional)	Xerox® Mobile Print Cloud addresses the needs of businesses with a mobile workforce and puts you ahead of the evolving mobile print need, but without burdening staff, budget or infrastructure. Getting started takes only a few minutes via the cloud. Print from any mobile device to nearly any brand of printer. Accurate printing with true Microsoft® Office® rendering and more. Print what you need, when, where and how you need it.	
Xerox® Mobile Print Solution (Optional)	Xerox® Mobile Print Solution is an ideal choice for sites that have additional requirements for control and security with an onsite server. Xerox® Mobile Print Solution allows users to print from most mobile devices to nearly any brand of printer or multifunction printer without drivers or added complexit Simply enter a release code (PIN) at the device and get accurate printing with true Microsoft Office rendering and more to use with your server for private, onsite deployment.	
Unified Address Book for Fax, In	ternet Fax, Email and Scan to	
Features	Services supported: Fax, Internet Fax, Email, Scan to Maximum contacts: 5,000 Contacts: Supports 1 or more destinations Favourites for quick access of fax numbers, emails, etc.	
Additional Scan Information		
Concurrency	Scan while the system is printing, copying, or while it is transferring scan to network or fax jobs (priority is for return of scanned originals and printing concurrent jobs)	
Input Speed	Up to 51 images per minute (ipm) black and white (simplex) Up to 24 ipm black and white (duplex) Up to 28 ipm colour (simplex) Up to 13 ipm colour (duplex)	
Resolution	72 x 72 dpi to 600 x 600 dpi Bit Depth: 1-bit (black and white), 8-bit (greyscale), 24-bit (colour)	
Maximum Scan Area	Up to 216 x 356 mm	
Scan Template Management	Support 250 scan templates Create Xerox® CentreWare® IS scan templates and share via device cloning to other multifunction printers Confirmation sheet options	
Network Protocols	sFTP, FTP, SMB, NetWare, HTTP, HTTPS	
File Compression	Colour TIFF (TIFF 6.0 or TTN2 with JPEG, LZW) Black and white TIFF (G3MH, G4 MMR compression - single or multiple pages) Searchable PDF and PDF/A (MRC, JPEG, G3 MH, G4 MMR, JBIG 2 Huffman, JBIG Arithmetic Compression, Deflate (for Black and white and within MRC)) Linearised PDF, PDF/A	

eatures only available in Network Scan to File Templates:  1 to 6 user programmable metadata fields per network scan to file templates and unlimited fields within the template – Metadata field consists of field name, default value and other configurations Customised fields viewed on user interface for variable data input  can Build Job ompression Quality / File Size Control riginal Type (Photo and Text, Photo, Text, Map, Newspaper / Magazine) uto Background and Shadow Suppression WAIN Support / WIA Support ound Originals dage Erase eduction / Enlargement ngle Touch Scan buttons (up to 10)  Email signatures (6 lines each of 128 character max), email message body (user configurable), email CentreWare IS confirmation sheet options Scan to Email S/MIME Encryption Email signing (requires Smart Card option) Auto send to self ddress list via LDAP (Windows Active Directory, Exchange, Notes, Domino) ownloaded address list (comma-separated file format)
Customised fields viewed on user interface for variable data input  can Build Job compression Quality / File Size Control riginal Type (Photo and Text, Photo, Text, Map, Newspaper / Magazine) uto Background and Shadow Suppression WAIN Support / WTA Support ound Originals dage Erase eduction / Enlargement ngle Touch Scan buttons (up to 10)  Email signatures (6 lines each of 128 character max), email message body (user configurable), email CentreWare IS confirmation sheet options Scan to Email S/MIME Encryption Email signing (requires Smart Card option) Auto send to self  ddress list via LDAP (Windows Active Directory, Exchange, Notes, Domino) ownloaded address list (comma-separated file format)  can to USB can to Network Folder (uses Unified Address Book entries)
ompression Quality / File Size Control riginal Type (Photo and Text, Photo, Text, Map, Newspaper / Magazine) uto Background and Shadow Suppression WAIN Support / WIA Support ound Originals olde Erase eduction / Enlargement ingle Touch Scan buttons (up to 10)  Email signatures (6 lines each of 128 character max), email message body (user configurable), email CentreWare IS confirmation sheet options Scan to Email S/MIME Encryption Email signing (requires Smart Card option) Auto send to self ddress list via LDAP (Windows Active Directory, Exchange, Notes, Domino) ownloaded address list (comma-separated file format)  can to USB can to Network Folder (uses Unified Address Book entries)
riginal Type (Photo and Text, Photo, Text, Map, Newspaper / Magazine) uto Background and Shadow Suppression WAIN Support / WIA Support ound Originals dge Erase eduction / Enlargement ingle Touch Scan buttons (up to 10)  Email signatures (6 lines each of 128 character max), email message body (user configurable), email CentreWare IS confirmation sheet options Scan to Email S/MIME Encryption Email signing (requires Smart Card option) Auto send to self  ddress list via LDAP (Windows Active Directory, Exchange, Notes, Domino) ownloaded address list (comma-separated file format)  can to USB can to Network Folder (uses Unified Address Book entries)
uto Background and Shadow Suppression WAIN Support / WIA Support ound Originals dge Erase eduction / Enlargement ingle Touch Scan buttons (up to 10)  Email signatures (6 lines each of 128 character max), email message body (user configurable), email CentreWare IS confirmation sheet options Scan to Email S/MIME Encryption Email signing (requires Smart Card option) Auto send to self  ddress list via LDAP (Windows Active Directory, Exchange, Notes, Domino) ownloaded address list (comma-separated file format)  can to USB can to Network Folder (uses Unified Address Book entries)
WAIN Support / WIA Support ound Originals of the state of
dge Erase eduction / Enlargement ngle Touch Scan buttons (up to 10)  Email signatures (6 lines each of 128 character max), email message body (user configurable), email CentreWare IS confirmation sheet options Scan to Email S/MIME Encryption Email signing (requires Smart Card option) Auto send to self ddress list via LDAP (Windows Active Directory, Exchange, Notes, Domino) ownloaded address list (comma-separated file format)  can to USB can to Network Folder (uses Unified Address Book entries)
Email signatures (6 lines each of 128 character max), email message body (user configurable), email CentreWare IS confirmation sheet options Scan to Email S/MIME Encryption Email signing (requires Smart Card option) Auto send to self ddress list via LDAP (Windows Active Directory, Exchange, Notes, Domino) ownloaded address list (comma-separated file format)  can to USB can to Network Folder (uses Unified Address Book entries)
Email signatures (6 lines each of 128 character max), email message body (user configurable), email CentreWare IS confirmation sheet options Scan to Email S/MIME Encryption Email signing (requires Smart Card option) Auto send to self ddress list via LDAP (Windows Active Directory, Exchange, Notes, Domino) ownloaded address list (comma-separated file format)  can to USB can to Network Folder (uses Unified Address Book entries)
Scan to Email S/MIME Encryption Email signing (requires Smart Card option) Auto send to self  ddress list via LDAP (Windows Active Directory, Exchange, Notes, Domino) ownloaded address list (comma-separated file format)  can to USB can to Network Folder (uses Unified Address Book entries)
Scan to Email S/MIME Encryption Email signing (requires Smart Card option) Auto send to self  ddress list via LDAP (Windows Active Directory, Exchange, Notes, Domino) ownloaded address list (comma-separated file format)  can to USB can to Network Folder (uses Unified Address Book entries)
Email signing (requires Smart Card option) Auto send to self  ddress list via LDAP (Windows Active Directory, Exchange, Notes, Domino) ownloaded address list (comma-separated file format)  can to USB can to Network Folder (uses Unified Address Book entries)
Auto send to self  ddress list via LDAP (Windows Active Directory, Exchange, Notes, Domino) ownloaded address list (comma-separated file format)  can to USB can to Network Folder (uses Unified Address Book entries)
ddress list via LDAP (Windows Active Directory, Exchange, Notes, Domino) ownloaded address list (comma-separated file format)  can to USB can to Network Folder (uses Unified Address Book entries)
can to USB can to Network Folder (uses Unified Address Book entries)
can to Network Folder (uses Unified Address Book entries)
can to Network Folder (uses Unified Address Book entries)
ns
desktop offering that provides advanced document imaging, archiving, editing and organisation tools: PaperPort Professional image viewing and file management software
- Complete PDF functionality
– Secure PDF workflow of all scanning applications
OmniPage Pro Office (for desktop/client installation) – Professional OCR software for digital archiving and document conversion
Image Retriever – provides fully automated retrieval of scanned images direct from a scan enabled Xerox® WorkCentre to individual desktops. Also includes email inbox polling capability
erox® ConnectKey® for SharePoint® simplifies and streamlines the way you scan, capture and store your paper-based documents. Using your
erox® multifunction printer, you can route documents directly into the precise document repository folder, just like you would from your PC. At the
nultifunction printer, you can browse to the folder, name the document, and add any key indexing information before you scan. With the flexibility
o capture and route to SharePoint as well as Windows folders, ConnectKey is the right solution for any office that needs to archive and share paper- ased documents.
erox® ConnectKey® Share to Cloud provides organisations with powerful, easy and secure document scanning capabilities that connect your Xerox®
nultifunction printer to popular cloud services and email, such as Google Docs™, SalesForce.com, Office 365 and Dropbox™ and gives employees
nytime, anywhere access to their most important documents using mobile devices.
erox® ConnectKey® for DocuShare®, a one-step scan-to-workflow solution, simplifies the process of incorporating hard copy content into enterprise ocument flows. Users can easily scan documents directly into a DocuShare collection or Windows folder via a multifunction printer.
ocument 1043. Osers can easily scan accuments ancety into a bocashare conceasin of Windows Totale, Walt Matthureton printer.
Expanded Authentication
- Network authentication to access device and/or device services via- Kerberos (UNIX / Windows Server 2003 / Windows Server 2008), SMB
(Windows Server 2003 / Windows Server 2008), NDS, LDAP
– Xerox Secure Access Unified ID System®
– Local Authentication (internal database) – Smart Card authentication -144k CAC / PIV Card Support (2048 bit certificate key) / .NET
Secure Data
– Digitally signed PDF (when using Smart Card authentication)
- Encrypted Scan to Email  Forward (Password Protested DDE (Email and Natural) Scan Tompletos only)
– Encrypted / Password Protected PDF (Email and Network Scan Templates only) – Secure Print (up to 10 digit PIN or Network Authentication)
- Immediate Image Overwrite
– On Demand Image Overwrite (Scheduled, Manual), includes sanitation of unused area of disk
– FIPS 140-2 256 bit Hard Disk Encryption
Expanded Authorisation  — SA access based on network credentials
– 3A access based of fletwork decentions  – Authorisation per user per service
– User Permissions required to access Print and Print Features are reflected in the print driver
Secure Network Access
IP Filter, IPsec, IPv6, SSL v3.0, SNMPv3, HTTPS, 802.1X, Cisco® TrustSec Identity Services Engine integration, Device Security  — McAfee® Embedded Security, Port disablement including USB ports, Audit Log, Hide Print Job Names, McAfee Integrity Control (optional)
– McAree® Embedded Security, Port disablement including OSB ports, Audit Log, Filae Print Job Names, McAree Integrity Control (optional)  Common Criteria Certification ISO 15408 (undergoing evaluation)
erox Secure Access Unified ID System® integrates your Xerox® multifunction printers with your existing employee/student ID PIN or badge
roviding a flexible and convenient authentication system. Allow your staff, employees or students to send documents to a centralised print server.
hen, at any multifunction printer on the network, they'll simply log in with a swipe of their magnetic or proximity ID card or their PIN to securely rint their job. For more information, go to www.office.xerox.com/software-solutions

Fax			
Embedded Fax³, LAN Fax, Internet	Fax, Server Fax (Embedded Fax and LAN Fax available on WorkCentre 3655/X only)		
Fax Speed	Up to 33.6 Kbps (analogue)		
Memory	Uses device memory		
Resolution	Up to 600 x 600 dpi (Super Fine) resolution Up to 200 x 200 dpi (Fine) resolution Up to 200 x 100 dpi (Standard) resolution		
Compression	MH, MR, MMR, JBIG		
Fax Features	Duplex Scanning Reports Auto Redial Auto Reduction Cover Page Delayed Send Fax Forward to Email Memory Receive Polling Secure Fax Speed Dials (up to 200 individual, 100 group)		
Device Management			
Management Support	SNMP Version 1. SNMP Version 2c and SNMP Version 3 trap over TCP/IP and IP MIB access (IETF-MIBII RFC 1213), Host Resources MIB RFC 2790, Printer MIB RFC 1759 v.2		
Xerox® CentreWare® Web	A Web-based server application for network administrators that permits Web browser-based device management from any workstation, whether running Windows, UNIX or any other operating system:  • Works with any SNMP-managed printer from any manufacturer.  • Provides help with device discovery and installation, health checks and troubleshooting, and device upgrades, as well as basic accounting and ass management.  • Requires Windows XP, Vista or Windows 7 and Internet Explorer 6.0 and higher.  • CentreWare Integration available for Tivoli® NetView®, Unicentre TNG®, Microsoft Management Console (MMC), HP® OpenView®		
Novell NDPS/NEPS	Server gateway application: centralised management tool.		
Xerox® Device Manager	Xerox® Device Manager collects and manages the data that drives fact-based decisions for your enterprise device management environment. It is a single tool to install print queues and configure, manage, monitor and report on both networked and locally connected devices – regardless of vendor – across your enterprise. Xerox® Device Manager provides:  • Device monitoring and troubleshooting  • Extensive reporting and discovery of new devices  • Usage collection, chargeback and billing capabilities		
Xerox® Device Types for SAP Environment	Xerox, together with SAP through our Gold-level membership in the SAP Printer Vendor Programme, provides seamless connectivity between SAP systems and your Xerox® printers and multifunction printers. And as an SAP customer you benefit from having SAP-certified Xerox® device types available right from SAP's online delivery model. SAP-certified device types for Xerox® printers and multifunction printers are available to download www.office.xerox.com/software-solutions		
Xerox® Device Types for SAP R/3 Intelligent Barcode Utility (optional)	Provides built-in process intelligence that allows the printing of barcodes on any appropriately configured PostScript printer in specific versions of SAP environment and within Latin-1 (ISO8859-1) SAP system code pages only. Used in conjunction with Xerox® PostScript Device Types for SAP environment and Xerox® Font Centre Barcode Fonts. Information available at www.office.xerox.com/software-solutions		
Xerox <sup>®</sup> Barcode Pro PS (optional)	Enables intelligent PostScript printing on Xerox® multifunction printers by storing Xerox® software, as well as, the barcode fonts on the printer hard disk. Enables the printing of barcodes from any application (SAP client or mainframe) that supports PostScript printing. Information available at www.office.xerox.com/software-solutions		
CentreWare Internet Services – Int	tegrated Web Pages Provided by the Device		
Device Status	Web server embedded in Network Controller:  Tray status/contents Consumables status Alerts Remote Control Panel		
Job Submission	Print ready files: PS, PCL, TIFF, PDF, JPG, XPS, TXT, PRN Output feature selection (2-sided, collate, orientation, staple, hole punch, folding, output destination) Delivery options (Immediate, sample set, delay and secure, Save job or reprint)		
Device Administration	Allows simple, remote installation setting of configuration options and management of the device		
Browsers	Internet Explorer 7.x, 8.x, 9.x Safari 5.x Mozilla Firefox 4.x, 5.x, 6.x, 7.x, 8.x, 9.x, 10.x, 11.x Opera 11.x Chrome 12		
Support	Install print / scan drivers and online support available via web page		
Languages Supported	International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish Russian, Simplified Chinese, Korean, Japanese		

## Xerox® WorkCentre™ 3655

Remote Print Services				
Automated Meter Reads (AMR)	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.			
Automatic Supplies Replenishment (ASR)	Automatically orders supplies for Xerox® output devices based on actual usage, eliminating the need to manually manage supplies inventory.			
Accounting				
Xerox® Standard Accounting (Star	ndard)			
Tracking	Copy, Print, Fax, Scan and Email usage			
Accounting	Up to 2,497 User accounts (User ID) Up to 500 General accounts (Client) Up to 498 Group accounts (Department)			
Features	<ul> <li>Administrator can manage the feature via the Web User Interface or device control panel in tools</li> <li>Administrator has the ability to import or export user accounts, Group Accounts, General Accounts and User limits via an industry standard CSV f</li> </ul>			
Accounting Options – Network Ac	counting – Third Party Enablement			
	<ul> <li>Comprehensive management and enterprise scale tracking and reporting of device usage of copy, print, scan and server fax</li> <li>Other solutions are available through Xerox Alliance Partners. For details visit www.xerox.com</li> <li>Security enhancements with the addition of HTTPS protocol support</li> <li>Device requests account authentication from third party server enabling larger databases of users and accounts</li> <li>Accept Authentication Login at control panel and pass to third party Networking Account</li> <li>Interface with third party accounting terminal for accounting user interface</li> </ul>			
What Comes in the Box				
	WorkCentre 3655 Multifunction Printer  Toner Cartridge (6,100 page capacity <sup>6</sup> )  Drum Cartridge (85,000 pages <sup>7</sup> )  Quick Installation Guide, Product Information Guide, Driver CD, Documentation  Power Cable	CD (User Manual, System Admin Guide	2)	
Supplies and Accessories	Description	Quantity	Part Number	
Supplies	Standard Capacity Toner Cartridge High Capacity Toner Cartridge Extra-high Capacity Toner Cartridge	6,100 pages <sup>6</sup> 14,400 pages <sup>6</sup> 25,900 pages <sup>6</sup>	106R02736 106R02738 106R02740	
	Drum Cartridge	85,000 pages <sup>7</sup>	113R00773	
	Staple Cartridge	3,000 staples	108R00823	
Accessories	550-sheet Feeder (Adjustable up to A4)	-	097S04625	
	Stand (Adds storage capacity for supplies, device stability, mobility and 332	-	497K14670	
	mm of height)			
	mm of height)  Wireless Connectivity Kit	-	497K11500	

<sup>&</sup>lt;sup>1</sup> Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

Smart Card Enablement Kit (CAC/PIV/.NET)

McAfee Integrity Kit

Return spent imaging supplies through the Xerox Green World Alliance collection/reuse/recycling programme. For more information, visit www.xerox.com/about-xerox/recycling.

For more information, visit us at www.xerox.com/office.



320S00665

498K17546

<sup>&</sup>lt;sup>2</sup> Expected regular monthly throughput.

 $<sup>^{\</sup>scriptscriptstyle 3}$  Requires analogue phone line.

<sup>&</sup>lt;sup>4</sup> Undergoing evaluation

<sup>&</sup>lt;sup>5</sup> Paper capacities are based on 75 gsm stock; capacities will vary with different weight stocks.

<sup>&</sup>lt;sup>6</sup> Average standard pages. Declared Yield in accordance with ISO/IEC19752. Yield will vary based on image, area coverage and print mode

<sup>&</sup>lt;sup>7</sup> Approximate pages. Declared Yield based on A4-75 gsm pages. Yield will vary based on media type, size, weight, orientation, and usage patterns.