

# XEROX®

WorkCentre® Pro C2128/C2636/C3545



Color

Detailed Specifications



*WorkCentre® Pro C2128 shown with One Tray and Cabinet and Office Finisher options.*



*WorkCentre® Pro C2636 shown with High-Capacity Feeder and Advanced Office Finisher options.*



*WorkCentre® Pro C3545 shown with Three Tray and Professional Finisher options.*

|  | <b>WorkCentre® Pro C2128</b><br>Color Advanced Multifunction System | <b>WorkCentre® Pro C2636</b><br>Color Advanced Multifunction System | <b>WorkCentre® Pro C3545</b><br>Color Advanced Multifunction System |
|--|---|---|---|
|--|---|---|---|

**OUTPUT SPEED—printing and copying**

|                        |   |   |   |
|------------------------|---|---|---|
| <b>Black-and-white</b> | 28 images per minute (ipm) letter (8.5 x 11" /216 x 279 mm/A4),<br>19 ipm legal (8.5 x 14" /216 x 356 mm),<br>17 ipm ledger (11 x 17"/ 279 x 432 mm/A3) | 36 ipm letter (8.5 x 11" /216 x 279 mm/A4)<br>22 ipm legal (8.5 x 14" /216 x 356 mm)<br>19 ipm ledger (11 x 17"/ 279 x 432 mm/A3) | 45 ipm letter (8.5 x 11" /216 x 279 mm/A4)<br>22 ipm legal (8.5 x 14" /216 x 356 mm)<br>22 ipm ledger (11 x 17"/ 279 x 432 mm/A3) |
| <b>Color</b>           | 21 ipm letter (8.5 x 11" /216 x 279 mm/A4)<br>15 ipm legal (8.5 x 14" /216 x 356 mm)<br>13 ipm ledger (11 x 17"/ 279 x 432 mm/A3)                       | 26 ipm letter (8.5 x 11" /216 x 279 mm/A4)<br>17 ipm legal (8.5 x 14" /216 x 356 mm)<br>15 ipm ledger (11 x 17"/ 279 x 432 mm/A3) | 35 ipm letter (8.5 x 11" /216 x 279 mm/A4)<br>17 ipm legal (8.5 x 14" /216 x 356 mm)<br>17 ipm ledger (11 x 17"/ 279 x 432 mm/A3) |

**WorkCentre® Pro C2128/C2636/C3545 Color Advanced Multifunction Systems**

**FIRST IMAGE OUT TIME—letter size, from platen to center tray**

|                        |             |
|------------------------|-------------|
| <b>Black-and-white</b> | 6.1 seconds |
| <b>Color</b>           | 8.5 seconds |

**NETWORK PRINTING—SMart™ Network Controller**

|   |  |
|---|--|
| <b>Processor</b>                                  | Intel® Celeron® 733 MHz  |
| <b>Memory</b>                                     | 128 MB RAM (256 MB max)  |
| <b>System Disk</b>                                | Minimum 30 GB  |
| <b>Printer Languages (auto sensing/switching)</b> | Postscript® 3 emulation<br>TIFF<br>PCL 5c emulation (PCL5e)<br>PDF 1.3 |



Color

## WorkCentre® Pro C2128/C2636/C3545 Color Advanced Multifunction Systems

### NETWORK PRINTING—resolution, printing via CentreWare® software

Postscript emulation: 600 x 600 dpi: 1200 x 1200 dpi  
 PCL emulation: 600 x 600 dpi

### NETWORK PRINTING—printing features

Print Calibration  
 Secure print  
 Delay print (specific time)  
 Sample set  
 Booklet creation  
 Cover selection  
 Paper selection by attribute  
 N-up  
 Saddle-stitch booklet making (requires Professional Finisher)  
 Hole Punch (requires Professional Finisher or Advanced Office Finisher)  
 V Folding (requires Professional Finisher)  
 Watermark  
 Fit to new paper size  
 Transparency interleave  
 Banner sheet enable/disable  
 Output tray selection  
 Image quality (Enhanced, Standard, TonerSaver)  
 Store and recall driver settings  
 Reduce/enlarge  
 Mirror image  
 Margins

### PRINT PROTOCOLS AND NETWORKS

|                          |   |
|--------------------------|---|
| <b>Physical</b>          | Ethernet 100BaseT/10BaseT, 10Base2, 10Base5 via adapter<br>USB printer port (optional)<br>Wireless Ethernet (IEEE 802.11b) via third-party adapters   |
| <b>Operating Systems</b> | Microsoft® Windows® 95, 98, Me® (Millennium), NT® 4.0, 2000, XP®, Windows Server 2003<br>Citrix<br>Novell® NetWare® 4.x, 5.x, 6<br>Mac OS® 8.x, 9.x, OS X<br>Solaris® 2.5.1, 2.6 and higher<br>HP-UX® 10.2, 11.x<br>IBM AIX® 4.2 and higher<br>Linux® Intel®<br>—Red Hat®<br>—Caldera®<br>—Mandrake™ (LPRNG printing infrastructure)<br>—Corel® (i386)<br>—TurboLinux® (i386)<br>—SuSE® (i386)<br>Linux Power PC®<br>—TurboLinux Server 6.0.2 |

Continued



Color

## WorkCentre® Pro C2128/C2636/C3545 Color Advanced Multifunction Systems

## PRINT PROTOCOLS AND NETWORKS (Continued)

**Network Protocols** TCP/IP: Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, NetBIOS, HTTP  
 Netware: Bindery and NDS IPX/SPX, NDPS®/NEPS (with Server Gateway)  
 AppleTalk®: EtherTalk®  
 Microsoft Windows Networking over IP and NetBEUI

**Administration Protocols** DHCP, BOOTP, SNMP, WINS, DDNS, SLP® v2, HTTP, RARP, DHCP Autonet

**Fonts** Postscript 3 emulation: 136 Type 1 fonts, 2 Multiple Master fonts  
 PCL: 80 scalable fonts, line printer bitmap font

| Print Drivers   | <i>Environment</i>   | <i>PCL 5c</i>  | <i>PostScript</i>         |
|---|--|--|---------------------------|
|   | Windows 95/98/Me   | Bidirectional (enhanced*)  | Bidirectional (enhanced*) |
| Windows NT 4.0  | Bidirectional with user-selectable interface (standard** and enhanced) | Bidirectional with user-selectable interface (standard** and enhanced) |                           |
| Windows 2000/XP<br>Windows Server 2003<br>(Microsoft certified) | Bidirectional with user-selectable interface (standard and enhanced)   | Bidirectional with user-selectable interface (standard and enhanced)   |                           |
| Macintosh® System 8.x, 9.x, OS X                                | N/A  | Enhanced PPD file  |                           |

| Print Submission Tools  | <i>Environment</i>  | <i>PostScript</i>   | <i>PCL</i>           |
|---|---|---|----------------------|
|   | Solaris, 2.4, 2.5.1, 2.6 and higher;<br>IBM AIX 4.2 and higher;<br>LPRNG printing infrastructure;<br>Linux Intel and Linux Power PC | Submission Tool with full feature set (includes administration, GUI/TTY print driver and software installation) | Submission Tool only |
| TIFF/PDF: Supported in Windows 95/98/Me/NT 4.0/2000/XP<br>Windows Server 2003 | Submission Tool for any TIFF or PDF file  |   |                      |

## DEVICE MANAGEMENT

**Management Support** SNMP Version 1 and SNMP Version 2c trap over TCP/IP and IP  
 MIB access (IETF-MIB II RFC 1213), Host Resources  
 MIB RFC 2790, Printer MIB RFC 1759 v. 2

**CentreWare Network Services** Device Discovery wizard (available at [www.xerox.com](http://www.xerox.com))  
 Device Administration wizard (available at [www.xerox.com](http://www.xerox.com))  
 Font Management Utility

**Xerox CentreWare Web**

- A Web-based server application for network administrators that permits Web browser-based device management from any workstation, whether running Windows or UNIX or any other operating system
- Works with any SNMP-managed printer from any manufacturer
- Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management

Continued

\*Enhanced: Xerox custom graphical user interface.  
 \*\* Standard: Driver based on Microsoft tree-structure user interface (includes Xerox features and functionality).



## WorkCentre® Pro C2128/C2636/C3545 Color Advanced Multifunction Systems

## DEVICE MANAGEMENT (Continued)

|   |  |
|---|--|
| <b>Novell NDPS/NEPS (gateway for WorkCentre Pro)</b>  | Server gateway application: Centralized management tool provides streamlined installations via printer agents, automated printer driver installation and downloads, printer and job configuration, configurable event notification   |
| <b>Xerox CentreWare® for Unicenter TNG®</b>   | <ul style="list-style-type: none"> <li>• Provides added identification to the general discovery performed by Unicenter TNG and the ability to see the device under a Unicenter TNG Business Process View</li> <li>• Provides full integration with event management and the choice to integrate with problem management and advanced Help Desk</li> </ul>  |
| <b>Xerox CentreWare® for Tivoli® NetView®</b>   | <ul style="list-style-type: none"> <li>• Provides for the identification of Xerox N-Series printers and WorkCentre Pro multifunction devices in the general discovery performed by Tivoli NetView</li> <li>• Provides the ability to see the discovered Xerox printers/devices in a Xerox Printers Set in addition to the Printers SmartSet</li> <li>• Provides full integration with the NetView and Event Browser and Tivoli Enterprise Console (TEC)</li> </ul>   |
| <b>Xerox CentreWare® MC for Microsoft Management Console (MMC)</b>  | CentreWare MC Snap-in supports printer discovery and management via a Microsoft Management Console (MMC) link to an embedded Web server. It is a general-purpose management display framework for hosting administrative tools   |
| <b>Xerox CentreWare® for HP® OpenView®</b>  | <ul style="list-style-type: none"> <li>• Provides for the identification of Xerox N-Series printers and WorkCentre Pro multifunction devices in the general discovery performed by HP OpenView</li> <li>• Provides the ability to see the current status of discovered Xerox printers/devices under a Xerox PrinterMap and IP Map via color-coded icons</li> <li>• Provides traps and message updates to the OpenView alarm browser and the ability to launch CentreWare Internet Services for device management directly from OpenView</li> </ul>     |
| <b>Xerox Device Types for SAP R/3 Environment</b>   | <p>Simplifies printing in SAP R/3 environments by providing users of SAP R/3 v4.6C, 4.x and 3.x ERP applications with enhanced WorkCentre Pro printing functionality (PostScript and PCL):</p> <ul style="list-style-type: none"> <li>—Simplex or duplex printing</li> <li>—Finishing—single or dual stapling</li> <li>—Tray pull location from any tray</li> <li>—Print security via PIN ID capability at the WorkCentre Pro</li> </ul>   |
| <b>Xerox SAP R/3 Intelligent Barcode Utility (Optional) Purchase via <a href="http://www.font.net">www.font.net</a></b> | <p>Provides built-in process intelligence that allows the printing of barcodes on any appropriately configured PostScript printer on the SAP R/3 4.x (or higher) network. Used in conjunction with Xerox Device Types for SAP R/3 Environment and Xerox Font Center Barcode Fonts. Utility automatically calculates checksum, placement of start/stop characters, and encoding of data string Web server embedded on SMart network controller</p> <ul style="list-style-type: none"> <li>—Tray status/contents</li> <li>—Consumables status</li> </ul> |
| <b>Xerox Barcode Pro PS (optional) Purchase via <a href="http://www.font.net">www.font.net</a></b>                      | Enables intelligent PostScript printing on Xerox multifunction printers by storing Xerox software as well as the barcode fonts on the printer hard disk. Enables the printing of barcodes from any application (client or mainframe) that supports PostScript printing. Automatically calculates the check digit, places start/stop and middle bar characters in the data string, compresses and encodes the data string, and rotates the barcode through 90 or 270 degrees.   |



Color

## WorkCentre® Pro C2128/C2636/C3545 Color Advanced Multifunction Systems

### CENTREWARE® INTERNET SERVICES—integrated device Web page

|                              |  |
|------------------------------|--|
| <b>Device Status</b>         | Web server embedded on SMart network controller<br>—Tray status/contents<br>—Consumables status  |
| <b>Print Queue Viewing</b>   | Complete job print queue management—hold, release, promote and delete  |
| <b>Job Submission</b>        | Print-ready files (PS, PCL, TIFF, PDF)<br>Output feature selection   |
| <b>Device Administration</b> | Allows simple, remote installation setting of configuration options and management of the device   |
| <b>Browsers</b>              | Windows XP, 2000/NT 4.0/Me/98/95: Netscape Navigator® 4.x and above, Microsoft Internet Explorer 4.x and above<br>Macintosh 9.x/OS X: Netscape Navigator 6.x<br>Linux: Netscape® 6.x |

### NETWORK SCANNING (optional)

|   |  |
|---|--|
| <b>Capability</b>                       | Color Scanning, Greyscale, Black and White   |
| <b>Concurrency</b>                      | Scan while the system is printing copy or network print jobs, or while it is transferring scan to network or fax jobs  |
| <b>Input Speed</b>                      | Scan at 32 ipm monochrome/22 ipm color (letter/8.5 x 11"/216 x 279 mm/A4 long edge feed )  |
| <b>Resolutions</b>                      | 600 x 600 dpi<br>400 x 400 dpi<br>300 x 300 dpi<br>200 x 200 dpi<br>Bit depth: 1 bit (monochrome), 8 bit (greyscale), 24 bit (color)   |
| <b>Maximum Scan Area</b>                | 11.7 x 17"/297 x 432 mm  |
| <b>Secure Access and Authentication</b> | Optional secure device login with network user name and password<br>Supports: Kerberos (Windows 2000/UNIX/Windows Server 2003), SMB (Windows NT 4.0/Windows 2000/Windows Server 2003),<br>Novell Netware 4.x/5.x/6.x<br>Optional PIN-based guest login |
| <b>Network Protocol</b>                 | Novell (NCP via IPX/SPX)<br>FTP via TCP/IP<br>Microsoft SMB via TCP/IP   |
| <b>File Formats</b>                     | TIFF 6.0 with JPEG, G4 MMR compression (single page or multiple pages)<br>PDF with G4 MMR, MRC, or JPEG compression<br>JPEG  |
| <b>Document Management Fields</b>       | One to six user-programmable metadata fields per scan job<br>Customized fields viewed on user interface<br>Variable data entered using virtual keyboard  |

Continued



Color

## WorkCentre® Pro C2128/C2636/C3545 Color Advanced Multifunction Systems

## NETWORK SCANNING (optional) (Continued)

|   |  |
|---|--|
| <b>Supported Scan Destinations</b><br>(Varies by scanning software options purchased) | <ul style="list-style-type: none"> <li>Scan to network server</li> <li>Scan to remote e-mail destinations via direct SMTP addresses or via various network scanning software options</li> <li>Scan to application (workflow, Electronic Document Management System/Repositories)</li> <li>Scan to Microsoft Exchange 2000 Web Folders</li> <li>Scan to Web URL</li> <li>Scan to remote printer</li> <li>Scan to PC Desktop™ (Standard and Deluxe editions)</li> <li>Scan to Windows XP client via WIA (Windows Image Acquisition)</li> </ul>   |
| <b>Scan-to-PC Desktop Standard</b>  | <ul style="list-style-type: none"> <li>— A desktop and server-based offering that provides document imaging, archiving, editing and organization tools</li> <li>— ScanSoft PaperPort SE 2.0 – image viewing and file management software</li> <li>— ScanSoft OmniPage SE 1.0 (for Distribution Server installation) and ScanSoft OmniPage SE 2.0 (for desktop/client installation) – OCR and file format conversion software</li> <li>— Image Retriever – provides fully automated retrieval of scanned images direct from a scan enabled Xerox WorkCentre Pro to individual desktops.</li> </ul>  |
| <b>Scan-to-PC Desktop Deluxe</b>  | <ul style="list-style-type: none"> <li>— A desktop and server based offering that provides document imaging, archiving, editing and organization tools</li> <li>— ScanSoft PaperPort Pro 9.0 Office – image viewing and file management software</li> <li>— ScanSoft OmniPage Pro 11.0 (for Distribution Server installation) and ScanSoft OmniPage Pro 12.0 Office (for desktop/client installation) – OCR and file format conversion software</li> <li>— Image Retriever – provides fully automated retrieval of scanned images direct from a scan enabled Xerox WorkCentre Pro to individual desktops. Also includes an E-Mail inbox polling capability.</li> </ul> |
| <b>E-MAIL— (included with Network Scanning Option)</b>                                |  |
| <b>Capability</b>   | <ul style="list-style-type: none"> <li>Color scanning, Greyscale, Black and White</li> <li>Direct document e-mail from device</li> <li>Manual or directory Exchange/Notes/LDAP address searching</li> </ul>  |
| <b>Resolutions</b>  | <ul style="list-style-type: none"> <li>600 x 600 dpi</li> <li>400 x 400 dpi</li> <li>300 x 300 dpi</li> <li>200 x 200 dpi</li> <li>Bit Depth: 1 bit (monochrome), 8 bit (greyscale), 24 bit (color)</li> </ul>   |
| <b>Maximum Scan Area</b>  | 11.7 x 17"/297 x 432 mm  |
| <b>Network Protocol</b>   | SMTP, MIME encoded   |
| <b>Authentication</b>   | <ul style="list-style-type: none"> <li>Device login with network user name and password</li> <li>Supports Kerberos (Windows NT 4.0/UNIX/Windows 2003 Server), SMB (Windows NT 4.0/Windows 2000/Windows 2003 Server), and Novell NetWare 4.x/5.x/6.x</li> <li>Optional PIN-based guest login</li> </ul>   |
| <b>Directory Access</b>   | <ul style="list-style-type: none"> <li>Corporate address list via LDAPv3</li> <li>Downloaded address list (comma-separated file format)</li> </ul>   |
| <b>File Formats</b>   | <ul style="list-style-type: none"> <li>TIFF 6.0 with JPEG, G4 MMR compression (single page or multiple pages)</li> <li>PDF, G4 MMR, MRC, JPEG</li> <li>JPEG</li> </ul>   |



Color

## WorkCentre® Pro C2128/C2636/C3545 Color Advanced Multifunction Systems

## INTERNET FAX (optional)

|                                 |  |
|---------------------------------|--|
| <b>Capability</b>               | <b>Ability to send documents in color</b><br>Direct document transmission to remote Internet Fax machines or e-mail clients (SMTP)<br>Reception and automatic printout of documents in color and black and white sent via e-mail from remote Internet Fax machines or e-mail clients |
| <b>Maximum Scan Area</b>        | 11.7 x 17"/297 x 432 mm  |
| <b>Authentication</b>           | Optional secure device login with network user name and password<br>Supports Kerberos (Windows 2000/UNIX/Windows 2003 Server), SMB (Windows NT 4.0/Windows 2000/Windows 2003), and Novell NetWare 4.x/5.x/6.x<br>Optional PIN-based guest login                                      |
| <b>Address Directory Access</b> | Corporate address list via LDAPv3<br>Downloaded address list (comma-separated file format)   |
| <b>File Formats</b>             | TIFF-FX Profiles S, F with G3 MH, G4 MMR, or JPEG compression<br>PDF with G3 MH, G4 MMR, or JPEG compression   |
| <b>Resolutions</b>              | 600 x 600 dpi<br>400 x 400 dpi<br>300 x 300 dpi<br>200 x 200 dpi<br>200 x 100 dpi<br>Bit Depth: 1 bit (monochrome), 8 bit (greyscale), 24 bit (color)  |
| <b>Network Protocols</b>        | SMTP<br>POP3 (RFC 1939)  |
| <b>Compliance</b>               | ITU-T T.37 compliant   |



Color

## WorkCentre® Pro C2128/C2636/C3545 Color Advanced Multifunction Systems

## NETWORK FAX SERVER INTEGRATION (optional)

|                             |   |
|-----------------------------|---|
| <b>Fax Send Features</b>    | <ul style="list-style-type: none"> <li>One- or two-sided scanning</li> <li>Phone number entry</li> <li>Add to send list (50 numbers maximum)</li> <li>Delay send (specific time)</li> <li>Resolution selection (fine, standard)</li> <li>Image quality selection (normal, photo and text, background suppression, seven levels of darker/lighter, seven levels of sharpness)</li> </ul> |
| <b>Fax Print Features</b>   | <ul style="list-style-type: none"> <li>One- or two-sided printing</li> <li>Quantity</li> <li>Staple on/off</li> <li>Collate on/off</li> <li>Finisher output tray selection (top tray or main tray)</li> <li>Secure print on/off</li> </ul>  |
| <b>Authentication</b>       | <ul style="list-style-type: none"> <li>Optional secure device login with network user name and password</li> <li>Supports Kerberos (Windows 2000/UNIX/Windows Server 2003), SMB (Windows NT 4.0/Windows 2000/ Windows Server 2003), and Novell NetWare 4.x/5.x/6.x</li> <li>Optional PIN-based guest login</li> </ul>   |
| <b>Fax Vendors</b>          | <ul style="list-style-type: none"> <li>Multiple vendors, certified by the Xerox Business Partners Program</li> <li>For details, visit <a href="http://www.xerox.com">www.xerox.com</a></li> </ul>   |
| <b>FAX (optional)</b>       |   |
|                             | ITU (CCITT) group 3 quality/resolution superfine/600x600, fine/200x200, standard/200x100 dpi  |
| <b>Speed/Modem(s)</b>       | V.34 modem(s): 33,600 bps. Less than four seconds per page transmission time. ISDN via third-party adapter.   |
| <b>Speed/Compression</b>    | MMR/MR/MH/G3/SuperG3  |
| <b>Fax Send Features</b>    | <ul style="list-style-type: none"> <li>Auto fax transmission reduction</li> <li>Page-by-page job status at the machine</li> <li>Fax from platen</li> <li>Delay start</li> <li>Automatic memory resend</li> <li>Automatic cover sheets</li> <li>Priority send</li> <li>Broadcast</li> </ul>  |
| <b>Fax Receive Features</b> | <ul style="list-style-type: none"> <li>One- or two-sided printing, stapled or unstapled</li> <li>Reduction at reception to fit available paper</li> <li>Junk Fax prevention</li> </ul>  |
| <b>Fax Reports</b>          | <ul style="list-style-type: none"> <li>Activity report</li> <li>Broadcasting</li> <li>Dial directory</li> <li>Transmission confirmation</li> <li>Pending fax</li> <li>Mailbox</li> </ul>  |

Continued



Color

## WorkCentre® Pro C2128/C2636/C3545 Color Advanced Multifunction Systems

## FAX (optional) (Continued)

|                              |   |
|------------------------------|---|
| <b>Fax Receive Mailboxes</b> | Up to 200 password-protected mailboxes  |
| <b>Auto Dialing</b>          | Auto redial, Batch send   |
| <b>Single Line option</b>    | Total of 200 speed dials (single-line option)<br>Up to 200 dial groups with up to 200 recipients per group (single line option) |
| <b>Dual Line option</b>      | 1,000 speed dials (dual line option)<br>Up to 400 dial groups with up to 400 recipients per group (dual line option)            |

## COPYING

|                              |   |
|------------------------------|---|
| <b>Document Scanner</b>      | Duplex Automatic Document Feeder with 50-sheet capacity   |
| <b>Sides (input:output)</b>  | 1:1, 1:2, 2:2 and 2:1   |
| <b>Quantity</b>              | 1 to 9,999  |
| <b>Resolution</b>            | 600 x 600 dpi   |
| <b>Concurrency</b>           | Concurrent scanning and printing  |
| <b>Digital Imaging</b>       | AutoIQ automatic digital image quality control<br>Auto rotation 90° or 270° when needed<br>Image shift<br>Edge erase<br>Auto centering<br>Original type selection (text, photo, text and photo, map, inkjet, highlighted)<br>Lighter/darker<br>Background suppression<br>Auto contrast<br>Sharpness<br>Color balance, color shift |
| <b>Copy Pre-collation</b>    | 256 MB RAM standard   |
| <b>Memory</b>                | 30 GB disk storage  |
| <b>Reduction/Enlargement</b> | Variable zoom from 25% to 400% in 1% increments<br>Anamorphic zoom<br>Six user-programmable percentages   |

Continued

\*Paper capacities are based on 20 lb/75 gsm stock; capacities will vary with different weight stocks.



Color

## WorkCentre® Pro C2128/C2636/C3545 Color Advanced Multifunction Systems

## COPYING (Continued)

## Special Features

Auto paper select  
 Auto reduction/enlargement to fit selected paper size  
 Auto registration  
 Auto tray switching  
 Automatic job recovery  
 Auto color  
 Full color  
 Single color  
 Copy calibration  
 Booklet creation  
 Multi-up—up to six columns by six rows maximum for letter/8.5 x 11"/216 x 279 mm/A4  
 Repeat image  
 Transparency dividers  
 Negative image  
 Mirror image  
 Covers insertion (front only, front and back, back only; blank or printed)  
 Build Job (enables special programming for different pages in one document—can be used for inserts, different paper sources, and mixing input from the document glass and the document feeder)  
 Store and recall job programming  
 Job interrupt  
 Bound document copying  
 Sample set  
 Mixed-size originals  
 Hole Punch (requires Professional Finisher or Advanced Office Finisher)  
 V-Folding (requires Professional Finisher)  
 Saddle-stitch booklets (requires Professional Finisher)  
 Stapling (single/dual/quad) quad requires Advanced Office Finisher or Professional Finisher

Foreign Device Interface/  
RS232 Port (optional)

Interface to third-party access control devices, coin machines and card readers  
 Supports a variety of vending stations available through the Xerox Custom Application Service

## Accessibility Option

Xerox Copier Assistant™ Software provides a PC-based alternative to the user interface touchscreen. Used in conjunction with a customer-supplied PC attached via the USB port, this software provides text-to-speech, screen magnification and easy PC keyboard access to basic and advanced copy features

## PAPER HANDLING—Duplex Automatic Document Feeder

## Capacity\*

50 sheets

## Speed

32 images per minute/8.5 x 11"/216 x 279 mm long edge feed (LEF)

## Paper Sizes Sensed

Statement/5.5 x 8.5"/140 x 216 mm/A5 long edge feed (LEF) or short edge feed (SEF)  
 Letter/8.5 x 11"/216 x 279 mm/A4 LEF or SEF  
 Legal/8.5 x 14"/216 x 356 mm SEF  
 Ledger/11 x 17"/279 x 432 mm/A3 SEF  
 8 x 10"/182 x 257 mm/B5 SEF

## Weights

13 to 32 lb bond/50 to 120 gsm

\*Paper capacities are based on 20 lb/75 gsm stock; capacities will vary with different weight stocks.



Color

## WorkCentre® Pro C2128/C2636/C3545 Color Advanced Multifunction Systems

## PAPER HANDLING—Bypass Tray

|                  |  |
|------------------|--|
| <b>Capacity*</b> | 100 sheets   |
| <b>Sizes</b>     | 4.13 x 5.83"/100 x 140 mm/A6 to 12 x 19"/320 x 483 mm                    |
| <b>Weights</b>   | 16 lb bond to 80 lb Cover/60 to 220 gsm                                  |
| <b>Types</b>     | Same as front-loading trays plus label stock<br>lightweight<br>envelopes |

## PAPER HANDLING—Front-Loading Paper Tray (Standard)

|                |   |
|----------------|---|
| <b>Tray 1</b>  | 520 sheets  |
| <b>Sizes</b>   | User adjustable from 5.5 x 8.5"/140 x 216 mm/A5 to 11 x 17"/279 x 432 mm/A3   |
| <b>Weights</b> | 17 to 80 lb Cover/64 to 220 gsm   |
| <b>Types</b>   | Plain paper<br>Letterhead<br>Bond<br>Preprinted forms<br>Cover<br>Hole-punched<br>Recycled paper<br>Transparencies<br>Heavyweight<br>Glossy |

## PAPER HANDLING—Input Tray Options—One Tray and Cabinet Option

|                |   |
|----------------|---|
| <b>Tray 2</b>  | 520 sheets  |
| <b>Sizes</b>   | User adjustable from 5.5 x 8.5"/140 x 216 mm/A5 to 11 x 17"/279 x 432 mm/A3   |
| <b>Weights</b> | 17 to 80 lb Cover/64 to 220 gsm   |
| <b>Types</b>   | Plain paper<br>Letterhead<br>Bond<br>Preprinted forms<br>Cover<br>Hole-punched<br>Recycled paper<br>Transparencies<br>Heavyweight<br>Glossy |

|                       |  |
|-----------------------|--|
| <b>Total Capacity</b> | 1,140 sheets (Includes Tray 1, Tray 2 and Bypass Tray) |
|-----------------------|--|

\*Paper capacities are based on 20 lb/75 gsm stock; capacities will vary with different weight stocks.



Color

## WorkCentre® Pro C2128/C2636/C3545 Color Advanced Multifunction Systems

## PAPER HANDLING—Input Tray Options—Three Tray Option (Tray One and Two plus Two-Tray Module)

|                        |   |
|------------------------|---|
| <b>Tray 2 – Tray 4</b> | 520 sheets  |
| <b>Sizes</b>           | User adjustable from 5.5 x 8.5"/140 x 216 mm/A5 to 11 x 17"/279 x 432 mm/A3   |
| <b>Weights</b>         | 17 to 80 lb Cover/64 to 220 gsm   |
| <b>Types</b>           | Plain paper<br>Letterhead<br>Bond<br>Preprinted forms<br>Cover<br>Hole-punched<br>Recycled paper<br>Transparencies<br>Heavyweight<br>Glossy |
| <b>Total Capacity*</b> | 2,180 sheets (Includes Tray 1, Tray 2, Trays 3-4 and Bypass Tray)   |

## PAPER HANDLING—Input Tray Options—High-Capacity Feeder Option

|                        |   |
|------------------------|---|
| <b>Tray 2</b>          | 520 sheets  |
| <b>Sizes</b>           | User adjustable from 5.5 x 8.5"/140 x 216 mm/A5 to 11 x 17"/279 x 432 mm/A3   |
| <b>Tray 3 – Tray 4</b> | 2,000 sheets  |
| <b>Sizes</b>           | 8.5 x 11", B5, A4   |
| <b>Weights</b>         | 17 to 80 lb Cover/64 to 220 gsm   |
| <b>Types</b>           | Plain paper<br>Letterhead<br>Bond<br>Preprinted forms<br>Cover<br>Hole-punched<br>Recycled paper<br>Transparencies<br>Heavyweight<br>Glossy |
| <b>Total Capacity*</b> | 3,140 sheets (Includes Tray 1, Tray 2, Bypass Tray and High Capacity Feeder)  |

## OUTPUT—Center Stacking Tray

|                      |   |
|----------------------|---|
| <b>Stacking Tray</b> | 400 sheets (200 sheets with finisher option)          |
| <b>Sizes</b>         | 4.13 x 5.83"/100 x 140 mm/A6 to 12 x 19"/320 x 483 mm |

## OUTPUT OPTIONS—Convenience Stapler Option

|                  |   |
|------------------|---|
| <b>Capacity*</b> | Up to 50 sheets (5,000 staples per cartridge) |
|------------------|---|

\*Paper capacities are based on 20 lb/75 gsm stock; capacities will vary with different weight stocks.



Color

WorkCentre® Pro C2128/C2636/C3545 Color Advanced Multifunction Systems

**OUTPUT OPTIONS—Office Finisher Option**

|                      |  |
|----------------------|--|
| <b>Stacking Tray</b> | 1,000 sheets   |
| <b>Sizes</b>         | 8 x 10"/B5 to 11 x 17"/A3  |
| <b>Weights</b>       | 17 to 28 lb bond/64 to 105 gsm   |
| <b>Stapling</b>      | Single and dual<br>Auto stapling (50 sheets maximum) – 20 lb/80 gsm<br>Letter, Legal, Tabloid, A3, A4, B4 and B5 sizes supported |

**OUTPUT OPTIONS—Advanced Office Finisher Option**

|                                 |   |
|---------------------------------|---|
| <b>Top Tray</b>                 | 500 sheets  |
| <b>Stacking – Stapling Tray</b> | 3,000 sheets  |
| <b>Sizes</b>                    | 8 x 10"/B5 to 11 x 17"/A3   |
| <b>Weights</b>                  | 17 to 80 lb Cover/60 to 220 gsm   |
| <b>Stapling</b>                 | Single, dual and quad<br>Auto stapling (50 sheets maximum) – 24 lb bond/90 gsm<br>Letter, Legal, Tabloid, A3, A4, B4 and B5 sizes supported |
| <b>Hole Punch</b>               | Three hole punch  |

**OUTPUT OPTIONS—Professional Finisher Option**

|                                 |   |
|---------------------------------|---|
| <b>Top Tray</b>                 | 500 sheets  |
| <b>Stacking – Stapling Tray</b> | 1,500 sheets  |
| <b>Sizes</b>                    | 8 x 10"/B5 to 11 x 17"/A3   |
| <b>Weights</b>                  | 17 to 110 lb index/60 to 220 gsm  |
| <b>Stapling</b>                 | Single, dual, and quad<br>Auto stapling (50 sheets maximum) – 24 lb/90 gsm<br>Letter, Legal, Tabloid, A3, A4, B4 and B5 sizes supported                             |
| <b>Booklets – Booklet Tray</b>  | Saddle-stitch up to 15 sheets (One 60 lb Cover/169 gsm plus fourteen 24 lb bond/90 gsm sheets)<br>V-fold up to 5 sheets<br>Letter, Legal, Tabloid, A3, A4 supported |
| <b>Hole Punch</b>               | Three hole punch  |

**ACCOUNTING**

|   |   |
|---|---|
| <b>Accounting with Third-Party Server Applications (optional)</b> | Up-to-the-minute data on how the system is being used; comprehensive usage tracking and reporting; print, scan, copy and fax  |
| <b>Internal Auditor</b>   | Tracks black and color copy and print usage, supports up to 2,000 user accounts or 300 general accounts<br>Note: Option to upload/download account and usage data via direct connection using Windows-based software.<br>Limits user to black-only copy and print |

WorkCentre® Pro C2128

WorkCentre® Pro C2636

WorkCentre® Pro C3545

**MONTHLY DUTY CYCLE**

|        |         |         |
|--------|---------|---------|
| 80,000 | 105,000 | 135,000 |
|--------|---------|---------|

\*Paper capacities are based on 20 lb/75 gsm stock; capacities will vary with different weight stocks. \*\*Features, configurations and options may vary by location.



Color

## WorkCentre® Pro C2128/C2636/C3545 Color Advanced Multifunction Systems

## BASIC CONFIGURATIONS\*\*

Network Multifunction System with network controller and stand

Notes: Platen cover, Duplex Automatic Document Feeder is available with all configurations

## ACCESSORIES

Office Finisher  
 Advanced Office Finisher  
 Professional Finisher  
 One-line fax option  
 Two-line fax option  
 Foreign Device Interface  
 Network Accounting Enablement  
 Network Scanning With E-Mail  
 Network Fax Server Integration  
 Internet Fax  
 Image Disk Overwrite Security  
 Scan to PC Desktop Client Software (Standard or Deluxe)  
 USB Port Printing  
 High Capacity Feeder  
 3 Tray option  
 1 Tray and Cabinet option

## ELECTRICAL REQUIREMENTS

110–127 V Nominal, 60 Hz, 15A or  
 220–240 V Nominal, 50 Hz, 10A

## POWER CONSUMPTION

|                    |                      |
|--------------------|----------------------|
| Running            | < 858 watts          |
| Standby            | < 277 watts          |
| Low-Power Mode     | < 157 watts          |
| Sleep Mode         | < 80 watts           |
| Warm-up            | 3 minutes (maximum)  |
| Low-Power Recovery | 30 seconds (maximum) |

## ENVIRONMENTAL CONSIDERATIONS

|                            |  |
|----------------------------|--|
| Required Temperature Range | 50° to 90° F (10° to 32° C)                                    |
| Required Relative Humidity | 10% to 85%   |
| Noise Emission             | 34.9 dB(A) standby<br>55.1 dB(A) running<br>66.7 dB(A) impulse |
| Heat Emission              | 2,927 BTU/Hr running<br>946 BTU/Hr standby                     |

\*\*Features, configurations and options may vary by location.



Color

WorkCentre® Pro C2128/C2636/C3545 Color Advanced Multifunction Systems

**DIMENSIONS AND WEIGHT**

|                  |                |              |                |                |
|------------------|----------------|--------------|----------------|----------------|
| Fully Configured | 53"/1,346 mm   | 25"/636 mm   | 43.9"/1,116 mm | 457 lbs/257 kg |
|                  | 71.5"/1,815 mm | 48"/1,210 mm | 78"/1,981 mm   |                |

**CERTIFICATIONS**

FCC Class A Compliant (U.S.), DOC Class A Compliant (Canada)  
 89/336/EEC (Europe)  
 UL Listed (UL 1950, Third Edition)  
 CB Certified (IEC 60950/EN 60950)  
 73/23/EEC (Europe)  
 Novell Tested and Approved  
 Windows Hardware Quality Labs

**SUPPLIES**

|                         | <i>Description</i>                    | <i>Order Number</i> |
|-------------------------|---------------------------------------|---------------------|
| <b>Toner Cartridges</b> | Black                                 | 6R1175              |
|                         | Cyan                                  | 6R1176              |
|                         | Magenta                               | 6R1177              |
|                         | Yellow                                | 6R1178              |
|                         | Drum Cartridges                       | 13R588              |
|                         | Waste Toner Container                 | 8R12903             |
|                         | Fuser Module (110 volt)               | 8R12933             |
| <b>Staple Refills</b>   | Office Finisher                       | 8R12915             |
|                         | Advanced Office/Professional Finisher | 8R12941             |
|                         | Professional Finisher (Booklet maker) | 8R12925             |
|                         | Convenience Stapler                   | 8R7644              |

**Total satisfaction guaranteed.**

The exclusive Xerox Total Satisfaction Guarantee, recognized as unique in the industry, covers every Xerox WorkCentre® Pro which has been continuously maintained by Xerox or its authorized representatives under a Xerox express warranty or Xerox Maintenance agreement. You decide when you're satisfied.



© 2005 Xerox Corporation. All rights reserved. XEROX®, WorkCentre® Pro, CentreWare® and Copier Assistant are trademarks of Xerox Corporation. In support of Xerox's environmental leadership goals, these models may contain some recycled components that are reconditioned. ENERGY STAR® is a U.S. registered mark. As an ENERGY STAR® Partner, Xerox Corporation has determined that these products (WorkCentre Pro 2128, WorkCentre Pro 2636 and WorkCentre Pro 3545) meet the ENERGY STAR® guidelines for energy efficiency. Postscript is a registered trademark of Adobe Systems Incorporated in the United States and/or other countries. Other marks are trademarks or registered trademarks of the companies with which they are associated. Terra Choice Environmental Services, Inc., of Canada has verified that this product conforms to all applicable Environmental Choice EcoLogo requirements for minimized impact to the environment. Product information and/or specifications are subject to change without notice. 10/04, 7/05, 10/05, 3/07 610P720230D W45SS-01UE