



**Color**

**Detailed Specifications**



*CopyCentre C2128 shown with One Tray and Cabinet and Office Finisher options.*



*CopyCentre C2636 shown with High-Capacity Feeder and Advanced Office Finisher options.*



*WorkCentre Pro C3545 shown with Three Tray and Professional Finisher options.*

**CopyCentre® C2128  
Color Digital Copier**

**CopyCentre® C2636  
Color Digital Copier**

**CopyCentre® C3545  
Color Digital Copier**

**OUTPUT SPEED—printing and copying**

<b>Black-and-white</b>	28 images per minute (ipm) letter (8.5 x 11" /216 x 279 mm/A4), 19 ipm legal (8.5 x 14" /216 x 356 mm), 17 ipm ledger (11 x 17"/ 279 x 432 mm/A3)	36 ipm letter (8.5 x 11" /216 x 279 mm/A4) 22 ipm legal (8.5 x 14" /216 x 356 mm) 19 ipm ledger (11 x 17"/ 279 x 432 mm/A3)	45 ipm letter (8.5 x 11" /216 x 279 mm/A4) 22 ipm legal (8.5 x 14" /216 x 356 mm) 22 ipm ledger (11 x 17"/ 279 x 432 mm/A3)
<b>Color</b>	21 ipm letter (8.5 x 11" /216 x 279 mm/A4) 15 ipm legal (8.5 x 14" /216 x 356 mm) 13 ipm ledger (11 x 17"/ 279 x 432 mm/A3)	26 ipm letter (8.5 x 11" /216 x 279 mm/A4) 17 ipm legal (8.5 x 14" /216 x 356 mm) 15 ipm ledger (11 x 17"/ 279 x 432 mm/A3)	35 ipm letter (8.5 x 11" /216 x 279 mm/A4) 17 ipm legal (8.5 x 14" /216 x 356 mm) 17 ipm ledger (11 x 17"/ 279 x 432 mm/A3)

**CopyCentre® C2128/C2636/C3545 Color Digital Copier**

**FIRST IMAGE OUT TIME—letter size, from platen to center tray**

<b>Black-and-white</b>	6.1 seconds
<b>Color</b>	8.5 seconds

**FAX (optional)**

ITU (CCITT) group 3 quality/resolution superfine/600x600, fine/200x200, standard/200x100 dpi

**Speed/Modem(s)** V.34 modem(s): 33,600 bps. Less than four seconds per page transmission time. ISDN via third-party adapter.

**Speed/Compression** MMR/MR/MH/G3/SuperG3

**Fax Send Features**

- Auto fax transmission reduction
- Page-by-page job status at the machine
- Fax from platen
- Delay start
- Automatic memory resend
- Automatic cover sheets
- Priority send
- Broadcast

*Continued*





## CopyCentre® C2128/C2636/C3545 Color Digital Copier

## FAX (optional) (Continued)

<b>Fax Receive Features</b>	One- or two-sided printing, stapled or unstapled Reduction at reception to fit available paper Junk Fax prevention
<b>Fax Reports</b>	Activity report Broadcasting Dial directory Transmission confirmation Pending fax Mailbox
<b>Fax Receive Mailboxes</b>	Up to 200 password-protected mailboxes
<b>Auto Dialing</b>	Auto redial, Batch send
<b>Single Line option</b>	Total of 200 speed dials (single-line option) Up to 200 dial groups with up to 200 recipients per group (single line option)
<b>Dual Line option</b>	1,000 speed dials (dual line option) Up to 400 dial groups with up to 400 recipients per group (dual line option)

## COPYING

<b>Document Scanner</b>	Duplex Automatic Document Feeder with 50-sheet capacity
<b>Sides (input:output)</b>	1:1, 1:2, 2:2 and 2:1
<b>Quantity</b>	1 to 9,999
<b>Resolution</b>	600 x 600 dpi
<b>Concurrency</b>	Concurrent scanning and printing
<b>Digital Imaging</b>	AutoIQ automatic digital image quality control Auto rotation 90° or 270° when needed Image shift Edge erase Edge-to-edge copying Auto centering Original type selection (normal, text, halftone, photo) Lighter/darker Background suppression Contrast Sharpness Screening
<b>Copy Pre-collation Memory</b>	256 MB RAM standard 18 GB disk storage
<b>Reduction/Enlargement</b>	Variable zoom from 25% to 400% in 1% increments Anamorphic zoom Six user-programmable percentages

Continued

\*Paper capacities are based on 20 lb/75 gsm stock; capacities will vary with different weight stocks.



## CopyCentre® C2128/C2636/C3545 Color Digital Copier

## COPYING (Continued)

## Special Features

Copy calibration  
 Auto paper select  
 Auto reduction/enlargement to fit selected paper size  
 Auto registration  
 Auto tray switching  
 Automatic job recovery  
 Auto color  
 Full color  
 Single color  
 Booklet creation  
 Multi-up—up to six columns by six rows maximum for letter/8.5 x 11"/216 x 279 mm/A4  
 Repeat image  
 Transparency dividers  
 Negative image  
 Mirror image  
 Covers insertion (front only, front and back, back only; blank or printed)  
 Build Job (enables special programming for different pages in one document—can be used for inserts, different paper sources, and mixing input from the document glass and the document feeder)  
 Store and recall job programming  
 Job interrupt  
 Bound document copying  
 Sample set  
 Mixed-size originals  
 Hole Punch (requires Professional Finisher or Advanced Office Finisher)  
 V-Folding (requires Professional Finisher)  
 Saddle-stitch booklets (requires Professional Finisher)  
 Stapling (single/dual/quad) quad requires Advanced Office Finisher or Professional Finisher

Foreign Device Interface/  
RS232 Port (optional)

Interface to third-party access control devices, coin machines and card readers  
 Supports a variety of vending stations available through the Xerox Custom Application Service

## Accessibility Option

Xerox Copier Assistant™ Software provides a PC-based alternative to the user interface touchscreen. Used in conjunction with a customer-supplied PC attached via the USB port, this software provides text-to-speech, screen magnification and easy PC keyboard access to basic and advanced copy features

## PAPER HANDLING—Duplex Automatic Document Feeder

## Capacity\*

50 sheets

## Speed

32 images per minute/8.5 x 11"/216 x 279 mm long edge feed (LEF)

## Paper Sizes Sensed

Statement/5.5 x 8.5"/140 x 216 mm/A5 long edge feed (LEF) or short edge feed (SEF)  
 Letter/8.5 x 11"/216 x 279 mm/A4 LEF or SEF  
 Legal/8.5 x 14"/216 x 356 mm SEF  
 Ledger/11 x 17"/279 x 432 mm/A3 SEF  
 8 x 10"/182 x 257 mm/B5 SEF

## Weights

13 to 32 lb bond/50 to 120 gsm

\*Paper capacities are based on 20 lb/75 gsm stock; capacities will vary with different weight stocks.



Color

## CopyCentre® C2128/C2636/C3545 Color Digital Copier

## PAPER HANDLING—Bypass Tray

<b>Capacity*</b>	100 sheets
<b>Sizes</b>	4.13 x 5.83"/100 x 140 mm/A6 to 12 x 19"/320 x 483 mm
<b>Weights</b>	16 lb bond to 80 lb Cover/60 to 220 gsm
<b>Types</b>	Same as front-loading trays plus label stock lightweight envelopes

## PAPER HANDLING—Front-Loading Paper Tray (Standard)

<b>Tray 1</b>	520 sheets
<b>Sizes</b>	User adjustable from 5.5 x 8.5"/140 x 216 mm/A5 to 11 x 17"/279 x 432 mm/A3
<b>Weights</b>	17 to 80 lb Cover/64 to 220 gsm
<b>Types</b>	Plain paper Letterhead Bond Preprinted forms Cover Hole-punched Recycled paper Transparencies Heavyweight Glossy

## PAPER HANDLING—Input Tray Options—One Tray and Cabinet Option

<b>Tray 2</b>	520 sheets
<b>Sizes</b>	User adjustable from 5.5 x 8.5"/140 x 216 mm/A5 to 11 x 17"/279 x 432 mm/A3
<b>Weights</b>	17 to 80 lb Cover/64 to 220 gsm
<b>Types</b>	Plain paper Letterhead Bond Preprinted forms Cover Hole-punched Recycled paper Transparencies Heavyweight Glossy

<b>Total Capacity</b>	1,140 sheets (Includes Tray 1, Tray 2 and Bypass Tray)
-----------------------	--------------------------------------------------------

\*Paper capacities are based on 20 lb/75 gsm stock; capacities will vary with different weight stocks.



Color

## CopyCentre® C2128/C2636/C3545 Color Digital Copier

## PAPER HANDLING—Input Tray Options—Three Tray Option (Tray One and Two plus Two-Tray Module)

<b>Tray 2 – Tray 4</b>	520 sheets
<b>Sizes</b>	User adjustable from 5.5 x 8.5"/140 x 216 mm/A5 to 11 x 17"/279 x 432 mm/A3
<b>Weights</b>	17 to 80 lb Cover/64 to 220 gsm
<b>Types</b>	Plain paper Letterhead Bond Preprinted forms Cover Hole-punched Recycled paper Transparencies Heavyweight Glossy
<b>Total Capacity*</b>	2,180 sheets (Includes Tray 1, Tray 2, Trays 3-4 and Bypass Tray)

## PAPER HANDLING—Input Tray Options—High-Capacity Feeder Option

<b>Tray 2</b>	520 sheets
<b>Sizes</b>	User adjustable from 5.5 x 8.5"/140 x 216 mm/A5 to 11 x 17"/279 x 432 mm/A3
<b>Tray 3 – Tray 4</b>	2,000 sheets
<b>Sizes</b>	8.5 x 11", B5, A4
<b>Weights</b>	17 to 80 lb Cover/64 to 220 gsm
<b>Types</b>	Plain paper Letterhead Bond Preprinted forms Cover Hole-punched Recycled paper Transparencies Heavyweight Glossy
<b>Total Capacity*</b>	3,140 sheets (Includes Tray 1, Tray 2, Bypass Tray and High Capacity Feeder)

## OUTPUT—Center Stacking Tray

<b>Stacking Tray</b>	400 sheets (200 sheets with finisher option)
<b>Sizes</b>	4.13 x 5.83"/100 x 140 mm/A6 to 12 x 19"/320 x 483 mm

## OUTPUT OPTIONS—Convenience Stapler Option

<b>Capacity*</b>	Up to 50 sheets (5,000 staples per cartridge)
------------------	-----------------------------------------------



Color

CopyCentre® C2128/C2636/C3545 Color Digital Copier

**OUTPUT OPTIONS—Office Finisher Option**

<b>Stacking Tray</b>	1,000 sheets
<b>Sizes</b>	8 x 10"/B5 to 11 x 17"/A3
<b>Weights</b>	17 to 28 lb bond/64 to 105 gsm
<b>Stapling</b>	Single and dual Auto stapling (50 sheets maximum) – 20 lb/80 gsm Letter, Legal, Tabloid, A3, A4, B4 and B5 sizes supported

**OUTPUT OPTIONS—Advanced Office Finisher Option**

<b>Top Tray</b>	500 sheets
<b>Stacking – Stapling Tray</b>	3,000 sheets
<b>Sizes</b>	8 x 10"/B5 to 11 x 17"/A3
<b>Weights</b>	17 to 80 lb Cover/60 to 220 gsm
<b>Stapling</b>	Single, dual and quad Auto stapling (50 sheets maximum) – 24 lb bond/90 gsm Letter, Legal, Tabloid, A3, A4, B4 and B5 sizes supported

<b>Hole Punch</b>	Three hole punch
-------------------	------------------

**OUTPUT OPTIONS—Professional Finisher Option**

<b>Top Tray</b>	500 sheets
<b>Stacking – Stapling Tray</b>	1,500 sheets
<b>Sizes</b>	8 x 10"/B5 to 11 x 17"/A3
<b>Weights</b>	17 to 110 lb index/60 to 220 gsm
<b>Stapling</b>	Single, dual, and quad Auto stapling (50 sheets maximum) – 24 lb/90 gsm Letter, Legal, Tabloid, A3, A4, B4 and B5 sizes supported

<b>Booklets – Booklet Tray</b>	Saddle-stitch up to 15 sheets (One 60 lb Cover/169 gsm plus fourteen 24 lb bond/90 gsm sheets) V-fold up to 5 sheets Letter, Legal, Tabloid, A3, A4 supported
--------------------------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------

<b>Hole Punch</b>	Three hole punch
-------------------	------------------

**ACCOUNTING**

<b>Internal Auditor</b>	Tracks black and color copy and print usage, supports up to 2,000 user accounts or 300 general accounts Note: Option to upload/download account and usage data via direct connection using Windows-based software. Limits user to black-only copy and print
-------------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

CopyCentre® Pro C2128

CopyCentre® C2636

CopyCentre® C3545

**MONTHLY DUTY CYCLE**

50,000

70,000

90,000



Color

## CopyCentre® C2128/C2636/C3545 Color Digital Copier

**BASIC CONFIGURATIONS\*\***

Color Digital Copier with stand

Notes: Platen cover, Duplex Automatic Document Feeder is available with all configurations

**ACCESSORIES**

WorkCentre Pro Upgrade to advanced multifunction system (Print, Scan, Email)  
 Office Finisher  
 Advanced Office Finisher  
 Professional Finisher  
 Convenience stapler  
 One-line fax option  
 Two-line fax option  
 Foreign Device Interface  
 Network Accounting Enablement (Upgrade to WorkCentre Pro)  
 Network Scanning With E-Mail (Upgrade to WorkCentre Pro)  
 Network Fax Server Integration (Upgrade to WorkCentre Pro)  
 Internet Fax (Upgrade to WorkCentre Pro)  
 Image Disk Overwrite Security  
 Scan to PC Desktop Client Software (Standard or Deluxe)  
 USB Port Printing (Upgrade to WorkCentre Pro)  
 High Capacity Feeder  
 3 Tray option  
 1 Tray and Cabinet option

**ELECTRICAL REQUIREMENTS**

110–127 V Nominal, 60 Hz, 15A or  
 220–240 V Nominal, 50 Hz, 10A

**POWER CONSUMPTION**

<b>Running</b>	< 838 watts
<b>Standby</b>	< 265 watts
<b>Low-Power Mode</b>	< 112 watts
<b>Sleep Mode</b>	< 80 watts
<b>Warm-up</b>	3 minutes (maximum)
<b>Low-Power Recovery</b>	30 seconds (maximum)

**ENVIRONMENTAL CONSIDERATIONS**

<b>Required Temperature Range</b>	50° to 90° F (10° to 32° C)
<b>Required Relative Humidity</b>	10% to 85%
<b>Noise Emission</b>	34.9 dB(A) standby 55.1 dB(A) running 66.7 dB(A) impulse
<b>Heat Emission</b>	2,837 BTU/Hr running 905 BTU/Hr standby

*Continued*



CopyCentre® C2128/C2636/C3545 Color Digital Copier

**DIMENSIONS AND WEIGHT**

<b>Fully Configured</b>	53"/1,346 mm	25"/636 mm	43.9"/1,116 mm	457 lbs/257 kg
	71.5"/1,815 mm	48"/1,210 mm	78"/1,981 mm	

**CERTIFICATIONS**

FCC Class A Compliant (U.S.), DOC Class A Compliant (Canada)  
 89/336/EEC (Europe)  
 UL Listed (UL 1950, Third Edition)  
 CB Certified (IEC 60950/EN 60950)  
 73/23/EEC (Europe)  
 Novell Tested and Approved  
 Windows Hardware Quality Labs

**SUPPLIES**

	<i>Description</i>	<i>Order Number</i>
<b>Toner Cartridges</b>	Black	6R1175
	Cyan	6R1176
	Magenta	6R1177
	Yellow	6R1178
	Drum Cartridges	13R588
	Waste Toner Container	8R12903
	Fuser Module (110 Volt)	8R12933
<b>Staple Refills</b>	Office Finisher	8R12915
	Advanced Office/Professional Finisher	8R12941
	Professional Finisher (Booklet Maker)	8R12925
	Convenience Stapler	8R7644

**Total satisfaction guaranteed.**

The exclusive Xerox Total Satisfaction Guarantee, recognized as unique in the industry, covers every Xerox WorkCentre® Pro which has been continuously maintained by Xerox or its authorized representatives under a Xerox express warranty or Xerox Maintenance agreement. You decide when you're satisfied.



© 2004 Xerox Corporation. All rights reserved. XEROX®, The Document Company™, the digital X®, WorkCentre® Pro, CentreWare® and Copier Assistant are trademarks of Xerox Corporation. In support of Xerox's environmental leadership goals, these models may contain some recycled components that are reconditioned. ENERGY STAR® is a U.S. registered mark. As an ENERGY STAR® Partner, Xerox Corporation has determined that these products meet the ENERGY STAR® guidelines for energy efficiency. Postscript is a registered trademark of Adobe Systems Incorporated in the United States and/or other countries. Other marks are trademarks or registered trademarks of the companies with which they are associated. Terra Choice Environmental Services, Inc., of Canada has verified that this product conforms to all applicable Environmental Choice EcoLogo requirements for minimized impact to the environment. Product information and/or specifications are subject to change without notice. 10/04 610P720240 W45SS-02UA