

# Xerox® WorkCentre® 4265 Multifunction Printer

The WorkCentre 4265 streamlines everyday office communications, providing the solutions you need to collaborate more effectively through simplified digital and paper-driven workflows – securely and cost effectively.



System Specifications	WorkCentre 4265/S	WorkCentre 4265/X	WorkCentre 4265/XF
<b>Single-sided Speed</b>	Up to 55 ppm 8.5 x 11 in. Up to 53 ppm A4 (210 x 297 mm) Up to 45 ppm 8.5 x 14 in.		
<b>Automatic Two-sided Speed</b>	Up to 50 ppm 8.5 x 11 in. Up to 48 ppm A4 (210 x 297 mm) Up to 40 ppm 8.5 x 14 in.		
<b>Monthly Duty Cycle<sup>1</sup></b>	Up to 250,000 pages / month		
<b>Recommended Average Monthly Print Volume<sup>2</sup></b>	Up to 25,000 pages / month		
<b>Hard Drive / Processor / Memory</b>	320 GB / 1 GHz / 2 GB		
<b>Connectivity</b>	10/100/1000Base-T Ethernet, High-Speed USB 2.0 Direct Print, Optional Wi-Fi (with Xerox® Wireless Networking Adapter)		
<b>User Interface</b>	7-inch Capacitive Color Touch Screen		
<b>Copy and Print</b>			
<b>Copy and Print Resolution</b>	<b>Copy:</b> Up to 600 x 600 dpi; <b>Print:</b> Up to 1200 x 1200 enhanced image quality		
<b>First-print-out Time</b>	As fast as 8 seconds		
<b>First-copy-out Time</b>	As fast as 5 seconds		
<b>Page Description Languages</b>	Adobe® PostScript® 3 compatibility, PCL® 5c/e / PCL 6 emulations, XML Paper Specification (XPS®)		
<b>Print Features</b>	Booklet Printing, Proof Print, Skip Blank Pages, N-up, Collation, Scaling, Reduce/Enlarge, Fit to Page, Covers, Custom-size Pages, Delay Print, Banner Sheet, Print from USB		
<b>Mobile Printing and Apps</b>	<b>Standard:</b> Apple® AirPrint™, Web Printing Service; <b>Free Download:</b> Xerox® Mobile Link App, Xerox® Print Service Plug-in for Android™; <b>Optional:</b> Xerox® Mobile Print, Xerox Mobile Print Cloud, Xerox® Wireless Print Solutions Adapter (includes Apple AirPrint, Google Cloud Print™ v2.0 and Mopria®. For more information, visit <a href="http://www.xerox.com/WPSA">www.xerox.com/WPSA</a> )		
<b>Scan</b>			
<b>Standard Features</b>	<b>Destinations:</b> Scan to USB, Scan to Email, Scan to Network (SMB, FTP, SFTP, HTTP, HTTPS); <b>File Formats:</b> PDF, XPS, JPEG, TIFF; <b>Convenience Features:</b> Scan to Home, Single Touch Scan, Single/Multi-Page PDF / XPS / TIFF, Linearised PDF, Xerox® Scan to PC Desktop SE (includes OCR, file conversion to Microsoft® Word®, Excel® and PowerPoint®. For more information, visit <a href="http://www.xerox.com/scan2pcSE">www.xerox.com/scan2pcSE</a> )		
<b>Optional Features</b>	Xerox® Scan to PC Desktop® Professional, numerous solutions available through various Xerox Alliance Partners		
<b>Fax</b>			
<b>Standard Features</b>	Optional	Embedded Fax <sup>3</sup> , LAN Fax, Server Fax <sup>4</sup>	
<b>Security</b>			
<b>Standard Features</b>	802.1X, Convenience Authentication, Kerberos Authentication (Unix / Linux / Windows ADS), LDAP Authentication (Secure LDAP), Local PIN Based Guest Login, Simple Authentication (one account with user name and Password), SMB Authentication (ADS), SMTP User Credentials via Kerberos, SMTP User Credentials via SMB (NTLM), Scan to Email with Authentication, Access Controls, User Permissions, Secure Print, Secure Fax Receive, SNMP v3, IPv6, SSL, SMTP over SSL, Smart Card Kit (CAC/PIV), USB port disablement, Audit Log, FIPS 140-2 Encryption, 256-bit Hard Disk Encryption, Image Overwrite, Software Verification Test, IP Filtering, HTTPS, SFTP, Common Criteria Certification (ISO 15408)		
<b>Optional Features</b>	Xerox® PrintSafe Software		
<b>Accounting</b>			
<b>Standard Features</b>	Xerox® Standard Accounting (Copy, Print, Scan, Fax, Email)		
<b>Optional Features</b>	Equitrac Express®, Equitrac Office®, YSoft® SafeQ®, Network Accounting Enablement, other network accounting solutions available through various Xerox Alliance Partners		

# Xerox® WorkCentre® 4265 Multifunction Printer

Device Specification				
<b>Control Panel Languages</b>	English, French, Italian, German, Spanish, Brazilian Portuguese, Russian, Dutch, Swedish, Danish, Finnish, Norwegian, Turkish, Polish, Czech, Hungarian, Greek			
Accessories				
<b>Optional Accessories</b>	520-sheet Paper Tray 4-Tray Stand (IOT plus 3 additional trays) 2-Tray Stand (IOT plus additional tray) 2100-sheet High Capacity Feeder Finisher Network Accounting Enablement Network Fax Server Enablement Fax Kit (Universal) Foreign Device Interface Common Access Card Enablement Kit Wireless Kit			
Electrical Requirements				
<b>North America</b>	Voltage: 110-127 VAC +6%, -10% Frequency: 50/60 Hz, 9 A			
<b>Europe</b>	Voltage: 220-247 VAC +6%, -10% Frequency: 50/60 Hz, 4.5 A			
Power Consumption				
<b>Printing</b>	Less than 900 watts			
<b>Standby Mode</b>	Less than 30 watts			
<b>Power Save Mode</b>	Less than 1.5 watts			
<b>Warm up (from Power Save)</b>	< 30 seconds			
<b>Warm up (from power on)</b>	< 60 seconds			
Operating Environment				
<b>Required Temperature Range</b>	50° to 90° F (10° to 32° C)			
<b>Required Relative Humidity</b>	Less than 85%			
<b>Sound Pressure Levels</b>	Operating: 59.0 dB(A), Standby – Fan On: 37.0 dB(A); Fan Off: 30 dB(A)			
Dimensions and Weights (Unpackaged)	Width	Depth	Height	Weight
<b>WorkCentre 4265/S</b>	24.5 in. / 621 mm	20.1 in. / 511 mm	24.6 in. / 624 mm	93.3 lb. / 42.32 kg
<b>WorkCentre 4265/X</b>	24.5 in. / 621 mm	20.1 in. / 511 mm	24.6 in. / 624 mm	93.6 lb. / 42.44 kg
<b>WorkCentre 4265/XF</b>	39 in. / 990 mm	25.5 in. / 647 mm	45 in. / 1,143 mm	203.6 lb. / 92.34 kg
Dimensions and Weights (Packaged)	Width	Depth	Height	Weight
<b>WorkCentre 4265/S</b>	33.1 in. / 840 mm	24.1 in. / 613 mm	29 in. / 736 mm	112.04 lb. / 50.82 kg
<b>WorkCentre 4265/X</b>	33.1 in. / 840 mm	24.1 in. / 613 mm	29 in. / 736 mm	112.04 lb. / 50.82 kg
<b>WorkCentre 4265/XF</b>	35 in. / 876 mm	26 in. / 660 mm	80 in. / 2032 mm	279 lb. / 127 kg
Certifications				
	FCC Part 15, Class A FCC Part 68 CE Mark applicable to Directives 2006/95/EC, 2004/108/EC, 2011/65/EU and 1999/5/EC UL 60950-1/CSA 60950-1-07, 2nd Edition EAC ENERGY STAR® qualified GS Mark Blue Angel certification per Ral UZ-171 for Germany NOM Ukraine EPEAT Canadian EcoLogo India BIS Registration Chile Energy and Safety registration To view the latest list of certifications, go to <a href="http://www.xerox.com/OfficeCertifications">www.xerox.com/OfficeCertifications</a> .			

# Xerox® WorkCentre® 4265 Multifunction Printer

Paper Handling	
<b>Duplex Automatic Document Feeder (DADF)</b>	
<b>Capacity<sup>5</sup></b>	100 sheets
<b>Speed (black and white)</b>	Up to 55 images per minute (ipm) (simplex) – black and white and colour Up to 70 ipm (duplex) – black and white and colour
<b>Sizes</b>	Custom sizes: 5.7 x 5.7 in. to 8.5 x 14 in. / 145 x 145 mm to 216 x 356 mm
<b>Weights</b>	12.5 lb. bond to 28 lb. bond / 50 to 105 gsm
<b>Bypass Tray</b>	
<b>Capacity<sup>5</sup></b>	100 sheet
<b>Sizes</b>	Custom sizes: 3.9 x 5.8 in. to 8.5 x 14 in. / 98 x 148 mm to 216 x 356 mm
<b>Weights</b>	16 lb. bond to 43 lb. bond / 60 to 163 gsm
<b>Media Types</b>	Plain Paper Bond Punched Pre-Printed Recycled Envelopes Transparencies Labels Card Stock Letterhead Lightweight Heavyweight Archive Custom Other
<b>Tray 1 (Standard on WorkCentre 4265/S, X, XF)</b>	
<b>Capacity<sup>5</sup></b>	520 sheets
<b>Sizes</b>	Custom sizes: 3.9 x 5.8 in. to 8.5 x 14 in. / 98 x 148 mm to 216 x 356 mm
<b>Weights</b>	16 lb. bond to 28 lb. bond / 60 to 105 gsm
<b>Media Types</b>	Plain Paper Bond Punched Pre-Printed Recycled Envelopes Transparencies Labels Card Stock Letterhead Lightweight Heavyweight Archive Custom Other
<b>Tray 2 (Standard on WorkCentre 4265/XF, Optional on WorkCentre 4265/S, X)</b>	
<b>Capacity<sup>5</sup></b>	520 sheets
<b>Sizes</b>	Custom sizes: 3.9 x 5.8 in. to 8.5 x 14 in. / 98 x 148 mm to 216 x 356 mm
<b>Weights</b>	16 lb. bond to 28 lb. bond / 60 to 105 gsm
<b>Media Types</b>	Plain Paper Bond Punched Pre-Printed Recycled Envelopes Transparencies Labels Card Stock Letterhead Lightweight Heavyweight Archive Custom Other

# Xerox® WorkCentre® 4265 Multifunction Printer

Trays 3 and 4 (Optional on WorkCentre 4265/S, X)	
Capacity <sup>5</sup>	520 sheets each
Sizes	Custom sizes: 3.9 x 5.8 in. to 8.5 x 14 in. / 98 x 148 mm to 216 x 356 mm
Weights	16 lb. bond to 28 lb. bond / 60 to 105 gsm
Media Types	Plain Paper Bond Punched Pre-Printed Recycled Envelopes Transparencies Labels Card Stock Letterhead Lightweight Heavyweight Archive Custom Other
High Capacity Feeder (Standard on WorkCentre 4265/XF, Optional on WorkCentre 4265/S, XF)	
Capacity <sup>5</sup>	2,100 sheets
Sizes	Standard selectable sizes: A5, Statement, JIS B5, ISO B5, Executive, Letter, A4, Folio, Oficio, Legal
Weights	16 lb. bond to 28 lb. bond / 60 to 105 gsm
Media Types	Plain Paper Bond Punched Pre-Printed Recycled Card Stock Letterhead Lightweight Heavyweight Post Card Archive Custom Other
Total Capacity	
Device Standard Capacity <sup>5</sup>	WorkCentre 4265/S and X: 620 sheets WorkCentre 4265/XF: 3,240 sheets
Device Total Capacity <sup>5</sup>	WorkCentre 4265/S and X: 3,240 sheets WorkCentre 4265/XF: 3,240 sheets
Paper Output	
Capacity <sup>5</sup>	Up to 500 sheets, automatic two-sided
Finisher	
Capacity <sup>5</sup>	Up to 500 sheets, 50-sheet single-position stapling
Copy	
Scanner	Single-Pass (dual-head) Duplex Automatic Document Feeder with 100-sheet capacity
First-copy-out Time	As fast as 5 seconds
Sides (input/output)	1-1, 1-2, 2-2, 2-1
Quantity	1 to 999
Resolution (max.)	600 x 600 dpi
Concurrency	Programme-ahead to allow job to be initiated while initial job is processed (Copy, Print, Fax and Scan)

# Xerox® WorkCentre® 4265 Multifunction Printer

<b>Copy Features</b>	<ul style="list-style-type: none"> <li>Collation</li> <li>Background Suppression</li> <li>Book Copying</li> <li>Book Copying with Centre Erase</li> <li>Booklet Creation</li> <li>Build Job</li> <li>Covers</li> <li>Edge Erase</li> <li>ID Card Copy</li> <li>Image Shift</li> <li>Job Interrupt</li> <li>Lighten/Darken</li> <li>Mixed-size Originals</li> <li>N-up</li> <li>Programme Ahead</li> <li>Reduce/Enlarge 25 to 400 % (from Platen and ADF)</li> <li>Save Job Settings</li> <li>Transparency Separators</li> </ul>
<b>Print</b>	
<b>First-print-out Time</b>	As fast as 8 seconds
<b>Print Resolution</b>	Up to 1200 x 1200 enhanced image quality
<b>Print Features</b>	<ul style="list-style-type: none"> <li>Application Defaults</li> <li>Banner Sheet</li> <li>Booklet Printing</li> <li>Collation</li> <li>Custom page size</li> <li>Delayed Print</li> <li>Fit to Page</li> <li>Job Monitoring</li> <li>N-Up</li> <li>Paper Selection by Attribute</li> <li>Print Around</li> <li>Print from USB Memory</li> <li>Print to / From Hard Drive</li> <li>Drive</li> <li>Proof Print</li> <li>Saved Job</li> <li>Scaling</li> <li>Secure Print</li> <li>Skip Blank Pages</li> <li>Store and Recall Driver Settings</li> <li>Watermark</li> </ul>
<b>Print from USB</b>	<ul style="list-style-type: none"> <li>Allows walk-up printing from Type A USB port</li> <li>Supports direct printing from computer via Type B USB port</li> <li>Supported file formats: PRN, TXT, PDF, TIFF, JPEG</li> </ul>
<b>Operating Systems</b>	<ul style="list-style-type: none"> <li>Windows® XP/2003 Server/2008 Server/2012 Server/Vista/7/8</li> <li>Mac OS® 10.5/10.6/10.7/10.8/10.9</li> <li>Citrix Presentation Server 4.5</li> <li>Citrix XenApp 5.0 &amp; up</li> <li>Oracle® Solaris 10, 11</li> <li>Redhat®</li> <li>Fedora® Core18</li> <li>HP-UX® 11iv3</li> <li>IBM® AIX® 5</li> <li>openSUSE® 12 x64</li> <li>Ubuntu® 12.10 x64</li> <li>Xerox® Global Print Driver®</li> <li>Xerox® Mobile Express Driver®</li> </ul>
<b>Network Protocols</b>	<ul style="list-style-type: none"> <li>TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6.WSD</li> <li>Apple® Bonjour®</li> <li>IPv4</li> <li>IPv6</li> <li>Secure FTP</li> <li>Most protocols not in use can be disabled</li> </ul>
<b>Administrative Protocols</b>	DHCP, BOOTP, SNMP, WINS, SLP® v2, HTTP, HTTPS, DHCP Autonet, SSL, NTP, DNS, SSDP
<b>Fonts</b>	<ul style="list-style-type: none"> <li>136 PostScript fonts</li> <li>111 PCL® fonts</li> </ul>
<b>Xerox® Mobile Express Driver®</b>	Makes it easy for mobile users to find, use and manage Xerox® and non-Xerox® devices in every new location. Plug into a new network, and Mobile Express Driver automatically discovers available printers and provides status and capability information. Save a list of "favourite" printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT.
<b>Xerox® Global Print Driver®</b>	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox® devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.

# Xerox® WorkCentre® 4265 Multifunction Printer

<b>Xerox® Pull Print Driver</b>	Makes it easy for IT managers to qualify, deploy and manage all print devices using a single driver in a Pull Print environment. Uses a single queue and single driver. The Xerox® Pull Print Driver extends convenience across a broad range of printing assets. IT administrators no longer need to manage and configure multiple drivers. Used in conjunction with Equitrac Office®, Ysoft® SafeQ®, Pharos® and others.
<b>Scan</b>	
<b>Capability</b>	Black and white and colour scanning
<b>Concurrency</b>	Scan while the system is printing copy or network print jobs, or while it is transferring scan to network or fax jobs
<b>Input Speed</b>	Up to 55 ipm simplex (black and white and colour) Up to 70 ipm duplex (black and white and colour)
<b>Resolution</b>	600 x 600 dpi 400 x 400 dpi 300 x 300 dpi 200 x 200 dpi 100 x 100 dpi 72 x 72 dpi
<b>Maximum Scan Area</b>	Up to 8.35 x 14 in. / 212 x 356 mm
<b>Network Protocol</b>	FTP SFTP SMB HTTP HTTPS WSD
<b>File Formats</b>	TIFF Multipage TIFF JPEG PDF Image only PDF Linearised PDF XPS
<b>Supported Scan Destinations</b>	Scan to Home Scan to PC via SMB Scan to Email Secure Scan to Email Scan to Folder Scan to SMB, FTP, SFTP, Client Scan to Network (WIA, TWAIN) Scan to HTTP, HTTPS WSD Scanning
<b>Scan to Email</b>	<ul style="list-style-type: none"> <li>• Direct document email from device</li> <li>• Manual or directory Exchange/Notes/LDAP address searching</li> <li>• Email From field auto-populated from LDAP when network authentication is used</li> </ul>
<b>Network Scanning</b>	Uses templates to send scanned images to predefined locations
<b>Scan to USB</b>	Scans can be loaded directly onto a user's portable USB storage device
<b>Scanning Solutions</b>	
<b>Xerox® Scan to PC Desktop® Personal Edition (1 Seat)</b>	A desktop and server-based offering that provides document imaging, archiving, editing and organisation tools <ul style="list-style-type: none"> <li>• Nuance PaperPort – image viewing and file management software</li> <li>• Nuance OmniPage (for desktop/client installation) – OCR and file format conversion software</li> <li>• Image Retriever – provides fully automated retrieval of scanned images direct from a scan-enabled Xerox® multifunction printer to individual desktops</li> </ul>
<b>Security</b>	
<b>Security Features</b>	256-bit AES HDD Encryption 802.1X Access Controls Audit Log Convenience Authentication FIPS 140-2 Encryption HTTPS (SSL) IP Filtering IPsec IPv6 Image Overwrite Kerberos Authentication LDAP Authentication SMB Authentication (ADS) SNMPv3 Scan to Email with Authentication Secure Fax (enabled when Fax Kit is added) Secure Print Smart Card Enablement (CAC/PIV) User Permissions

# Xerox® WorkCentre® 4265 Multifunction Printer

Fax	
<b>Embedded Fax<sup>3</sup>, LAN Fax, Server Fax<sup>4</sup> (Optional on WorkCentre 4265/S)</b>	
<b>Fax Speed</b>	33.6 Kbps
<b>Memory</b>	320 GB (50 MB dedicated fax memory)
<b>Resolution</b>	Up to 300 x 300 dpi (superfine) resolution
<b>Compression</b>	MH, MR, MMR and JBIG
<b>Fax Features</b>	Address Book Auto Answer Delay Auto Memory Resend Auto Redial Broadcast Sending Delayed Start Fax Forward to Email Fax Forward to Fax Fax Mailboxes Secure Fax
Device Management	
<b>Management Support</b>	SNMP Version 1. SNMP Version 2c and SNMP Version 3 trap over TCP/IP and IP MIB access (IETF-MIBII RFC 1213) Host Resources MIB RFC 2790, Printer MIB RFC 1759 v.2
<b>Xerox® CentreWare® Web</b>	A Web-based server application for network administrators that permits Web browser-based device management from any workstation, whether running Windows, UNIX or any other operating system: <ul style="list-style-type: none"> <li>• Works with any SNMP-managed printer from any manufacturer.</li> <li>• Provides help with device discovery and installation, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management.</li> <li>• Requires Windows XP, Vista or Windows 7 and Internet Explorer 6.0 and higher.</li> <li>• CentreWare Integration available for Tivoli® NetView®, Unicentre TNG®, Microsoft Management Console (MMC), HP® OpenView®</li> </ul>
<b>Xerox® Device Manager</b>	Xerox® Device Manager collects and manages the data that drives fact-based decisions for your enterprise device management environment. It is a single tool to install print queues and configure, manage, monitor and report on both networked and locally connected devices – regardless of vendor – across your enterprise. Xerox® Device Manager provides: <ul style="list-style-type: none"> <li>• Device monitoring and troubleshooting</li> <li>• Extensive reporting and discovery of new devices</li> <li>• Usage collection, chargeback and billing capabilities</li> </ul>
<b>Xerox® Device Types for SAP Environment</b>	Xerox, together with SAP through our Gold-level membership in the SAP Printer Vendor Programme, provides seamless connectivity between SAP systems and your Xerox® printers and multifunction printers. And as an SAP customer you benefit from having SAP-certified Xerox® device types available right from SAP's online delivery model. SAP-certified device types for Xerox® printers and multifunction printers are available to download. Information available at <a href="http://www.office.xerox.com/software-solutions">www.office.xerox.com/software-solutions</a> .
<b>Xerox® Device Types for SAP R/3 Intelligent Barcode Utility (optional)</b>	Provides built-in process intelligence that allows the printing of barcodes on any appropriately configured PostScript printer in specific versions of SAP environment and within Latin-1 (ISO8859-1) SAP system code pages only. Used in conjunction with Xerox® PostScript Device Types for SAP environment and Xerox® Font Centre Barcode Fonts. Information available at <a href="http://www.office.xerox.com/software-solutions">www.office.xerox.com/software-solutions</a> .
<b>Xerox® Barcode Pro PS (optional)</b>	Enables intelligent PostScript printing on Xerox® multifunction printers by storing Xerox® software, as well as, the barcode fonts on the printer hard disk. Enables the printing of barcodes from any application (SAP client or mainframe) that supports PostScript printing. Information available at <a href="http://www.office.xerox.com/software-solutions">www.office.xerox.com/software-solutions</a> .
CentreWare Internet Services – Integrated Web Pages Provided by the Device	
<b>Device Status</b>	Web server embedded in Network Controller: <ul style="list-style-type: none"> <li>• Tray status/contents</li> <li>• Consumables status</li> <li>• Alerts</li> <li>• Remote Control Panel</li> </ul>
<b>Job Submission</b>	Print ready files: PS, PCL, TIFF, PDF, JPG, XPS, TXT, PRN Output feature selection (2-sided, collate, orientation, staple, output destination) Delivery options (Immediate, sample set, delay and secure, Save job or reprint)
<b>Device Administration</b>	Allows simple, remote installation setting of configuration options and management of the device
<b>Browsers</b>	Internet Explorer 7.x, 8.x, 9.x Safari 5.x Mozilla Firefox 4.x, 5.x, 6.x, 7.x, 8.x, 9.x, 10.x, 11.x Opera 11.x Chrome 12
<b>Support</b>	Install print / scan drivers and online support available via web page
<b>Languages Supported</b>	English, French, Italian, German, Spanish, Brazilian Portuguese, Russian
Remote Services	
<b>Xerox® MeterAssistant®</b>	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.
<b>Xerox® SuppliesAssistant®</b>	Automatically orders supplies for Xerox® output devices based on actual usage, eliminating the need to manually manage supplies inventory.
<b>MaintenanceAssistant</b>	Offers a fast (and free) way to resolve potential issues and receive assistance and automate the troubleshooting/repair process. Diagnostic data is sent to Xerox, allowing for problems to be solved faster with increased uptime.

# Xerox® WorkCentre® 4265 Multifunction Printer

Accounting			
Xerox® Standard Accounting			
Tracking	Copy, Print, Fax, Scan and Email usage		
Accounting	Up to 500 User accounts Up to 250 General accounts Up to 250 Group accounts		
Features	<ul style="list-style-type: none"> <li>Administrator can manage the feature via the Web User Interface or device control panel in tools</li> <li>Administrator has the ability to import or export user accounts, Group Accounts, General Accounts and User limits via an industry standard CSV file</li> </ul>		
Accounting Options – Network Accounting – Third Party Enablement (Optional)			
	<ul style="list-style-type: none"> <li>Enhanced network accounting with up to the minute data on how the system is being used</li> <li>Comprehensive management and enterprise scale tracking and reporting of device usage of copy, print, scan and server fax</li> <li>Numerous solutions are available through Xerox Alliance Partners. For details visit <a href="http://www.xerox.com">www.xerox.com</a></li> <li>Security enhancements with the addition of HTTPS protocol support</li> <li>Device requests account authentication from third party server enabling larger databases of users and accounts</li> <li>Accept Authentication Login at control panel and pass to third party Networking Account</li> <li>Interface with third party accounting terminal for accounting user interface</li> </ul>		
What Comes in the Box			
	<ul style="list-style-type: none"> <li>WorkCentre 4265 Multifunction Printer</li> <li>Starter Toner Cartridge (10,000 print capacity<sup>6</sup>)</li> <li>Drum Cartridge (100,000 yield<sup>7</sup>)</li> <li>Installation Guide, Quick Use Guide, Documentation and Driver CD (Drivers, User Manual, System Admin Guide)</li> <li>Power Cable</li> <li>Fax Cord (WorkCentre 4265/X and XF)</li> </ul>		
Supplies and Accessories	Description	Quantity	Part Number
Supplies	Standard Toner Cartridge	Approx. 10,000 pages <sup>6</sup>	106R03105
	High Capacity Toner Cartridge	Approx. 25,000 pages <sup>6</sup>	106R02735
	Extra High Capacity Toner Cartridge	Approx. 50,000 pages <sup>6</sup>	106R03103
	Staple Cartridge	15,000 staples	008R12941
	Drum Cartridge	Approx. 100,000 pages <sup>7</sup>	113R00776
	Fuser Maintenance Kit (110v)	250,000 pages <sup>7</sup>	115R00086
	Fuser Maintenance Kit (220v)	250,000 pages <sup>7</sup>	115R00087
	Bias Transfer Roll Maintenance Kit	125,000 pages <sup>7</sup>	108R01266
	Feed Roll Maintenance Kit	250,000 pages <sup>7</sup>	108R01267
Accessories	520-sheet Paper Tray	–	097N01524
	4-Tray Stand (IOT plus 3 additional trays)	–	097S03678
	2-Tray Stand (IOT + 1 additional tray)	–	097S03677
	2100-sheet High Capacity Feeder	–	097N01684
	Finisher	–	097N02155
	Network Accounting Enablement	–	098S04928
	Network Fax Server Enablement	–	098S04931
	Fax Kit (Universal)	–	097N02154
	Foreign Device Interface (FDI)	–	097N01676
	Common Access Card Enablement Kit	–	497K09950
	Wireless Kit	–	097N02156

<sup>1</sup> Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

<sup>2</sup> Expected regular monthly throughput.

<sup>3</sup> Requires analogue phone line.

<sup>4</sup> Requires network fax server enablement.

<sup>5</sup> Paper capacities are based on 20 lb. / 75 gsm stock; capacities will vary with different weight stocks.

<sup>6</sup> Average standard pages. Declared Yield in accordance with ISO/IEC 19752. Yield will vary based on image, area coverage and print mode.

<sup>7</sup> Approximate pages. Declared Yield based on letter-/A4-size 20 lb. (75 gsm) pages. Yield will vary based on media type, size, weight, orientation, and usage patterns.

Return spent imaging supplies through the Xerox Green World Alliance collection/reuse/recycling programme. For more information, visit [www.xerox.com/about-xerox/recycling](http://www.xerox.com/about-xerox/recycling).

