

WorkCentre™

5735/5740/5745/5755/5765/5775/5790

Black and White Multifunction System



WorkCentre 5735/5740/5745/5755
shown with Duplex Automatic Document Handler with High Capacity Tandem Tray and Offset Catch Tray



WorkCentre 5735/5740/5745
shown with Duplex Automatic Document Handler with High Capacity Tandem Tray and Basic Office Finisher



WorkCentre 5735/5740/5745/5755/5765/5775
shown with Duplex Automatic Document Handler, High Capacity Tandem Tray and Office Finisher



WorkCentre 5740/5745/5755/5765/5775/5790 shown with Duplex Automatic Document Handler, High Capacity Tandem Tray, High Capacity Feeder and High Volume Finisher with Folder and Booklet Maker and Post Process Inserter

Output Speed		
	A4/210 x 297 mm	A3/297 x 420 mm
WorkCentre 5735:	Up to 35 ppm (pages per minute)	Up to 21 ppm
WorkCentre 5740:	Up to 40 ppm	Up to 31 ppm
WorkCentre 5745:	Up to 45 ppm	Up to 31 ppm
WorkCentre 5755:	Up to 55 ppm	Up to 31 ppm
WorkCentre 5765:	Up to 65 ppm	Up to 42 ppm
WorkCentre 5775:	Up to 75 ppm	Up to 42 ppm
WorkCentre 5790:	Up to 90 ppm	Up to 46 ppm

First-image-out Time (FCOT) – A4 size, from Platen to Offset Catch Tray	
	WorkCentre 5735: As fast as 4.7 seconds WorkCentre 5740/5745/5755: As fast as 3.4 seconds WorkCentre 5765/5775/5790: As fast as 2.7 seconds

Copy Specifications	
Copying	
Document Scanner	Platen (option available only on 5735) Duplex Automatic Document Handler (DADH) 75-sheet capacity (5735) Duplex Automatic Document Handler (DADH) 100-sheet capacity (5740/5745/5755/5765/5775/5790) Scans sizes up to A3/297 x 420 mm SEF
Sides (input:output)	1:1, 1:2, 2:2 and 2:1
Quantity	1 to 9,999
Resolution	600 x 600 x 8 bit dpi input / 4800 x 600 dpi interpolated output
Concurrency	Unlimited programme-ahead consistent with configuration (Copy, Print, Fax and Scan)

WorkCentre 5735/5740/5745/5755/5765/5775/5790

Copy Pre-Collation Memory (EPC)	384 MB (expandable to 1 GB with additional Memory Kit)	
Basic Copy Features/Options	Features Collation Automatic 2-Sided/Duplex Auto Reduction and Enlargement to fit selected paper size Auto Paper Select Auto Tray Switching	Options Hole Punching Stapling Booklet Creation (Optional with High Volume Finisher with Booklet Maker) Post Process Inserter (Optional with High Volume Finisher and High Volume Finisher with Booklet Maker) C/Z Folding (Optional with High Volume Finisher with Booklet Maker)
Imaging Copy Features	Image Quality <ul style="list-style-type: none"> • Original Type Selections: Normal, Text, Halftone, Photo • Output Quality Selections: Lighter/Darker, Background Suppression, Contrast, Sharpness or Screening Book Copying/Bound Copying Edge Erase (with Print to Edge option) Mixed Size Original Image Shift (with Auto Center option)	
Output Copy Features	ID Card Copy Booklet Creation Inserts and Tab copying Covers (Front only, Front and Back, Back only: Blank or Printed) Build Job (Enables page-level programming to include tab copying and also lets you proof each section or delete last section as the job is built) Annotation and Bates Stamping Multi-up (up to six columns by six rows) Invert Image (negative or mirror image) Sample Set and Job Storage (Store and Recall job programming) Transparencies (including dividers – blank or printed) Heavy weight paper (not rough stock)	
Other Copy/Device Features	Job Interrupt (Interrupt the current job) Help (Intuitive text and graphic descriptions) Onboard User Documentation Languages (Select up to 21 languages for User Interface – US English, International English, International French, Italian, German, International Spanish, Catalan, Dutch, Portuguese, Brazilian [Latin Portuguese], Swedish, Norwegian, Danish, Finnish, Turkish, Greek, Russian, Czech, Polish, Hungarian or Romanian)* * Language selection varies by location	
Reduction/Enlargement	Variable Zoom from 25 % - 400 % in 1 % increments Six User-Programmable percentages (25 %, 64 %, 78 %, 129 %, 154 % and 200 %)	
Foreign Device Interface (FDI) (Optional)	Interface to third-party access control devices, coin machines, card readers Supports a variety of vending stations available through Xerox Alliance Partner Programme	
USB Port	Xerox Copier Assistant® Customer device administration/software upgrade	
Accessibility Option	Xerox Copier Assistant (XCA) Software provides a PC-based alternative to the user interface touchscreen. Used in conjunction with a customer-supplied PC attached via the USB port, this software provides text-to-speech, screen magnification and easy PC keyboard access to basic and advanced copy features.	
Paper Handling – Duplex Automatic Document Handler (DADH) (Optional with 5735, standard on 5740/5745/5755/5765/5775/5790)		
Capacity ¹	5735: 75 sheets 5740/5745/5755/5765/5775/5790: 100 sheets	
Speed	Up to 60 ipm (images per minute), A4/210 x 297 mm long edge feed (LEF) (5735) Up to 80 ipm, A4/210 x 297 mm long edge feed (LEF) (5740/5745/5755/5765/5775/5790)	

¹ Paper capacities are based on 75 gsm stock; capacities will vary with different weight stocks.

WorkCentre 5735/5740/5745/5755/5765/5775/5790

Paper Sizes Sensed	A5/148 x 210 mm long edge feed (LEF) or short edge feed (SEF) A4/210 x 297 mm LEF or SEF A3/297 x 420 mm SEF
Weights	50 to 160 gsm
Paper Handling – Trays 1-2	
Capacity ¹	500 sheets each
Sizes	User Adjustable from A5/148 x 210 mm to A3/297 x 420 mm
Weights	60 to 200 gsm
Types	Letterhead Preprinted forms Plain Paper Drilled/Hole-punched Heavyweight Recycled Tab Stock Bond Custom Settings (up to 7)
Options	Envelope Tray Kit for Tray 2 (Capacity 50 envelopes): DL (110 x 220 mm), C5 (162 x 229 mm) & C6 (114 x 162 mm), custom
Paper Handling – Bypass Tray	
Capacity ¹	100 sheets
Sizes	User Adjustable from A6/105 x 148 mm to A3/297 x 420 mm
Weights	60 to 216 gsm
Types	Letterhead Preprinted forms Plain Paper Drilled/Hole-punched Heavyweight Recycled Label Stock Transparencies Tab Stock Bond Custom Settings (up to 7)
Paper Handling – High Capacity Tandem Tray (HCTT)	
Capacity ¹	Two trays: 1,600 and 2,000 sheets
Sizes	A4/210 x 297 mm LEF
Weights	60 to 200 gsm
Paper Handling – High Capacity Feeder (Optional with 5735/5740/5745/5755/5765/5775, highly recommended with 5790)	
Capacity ¹	4,000 sheets
Sizes	A4/210 x 297 mm LEF Optional A4 Short Edge Feed Kit – 210 x 297 mm SEF with 2,000 sheet capacity Optional A3 Short Edge Kit – A3/297 x 420 mm SEF with 2,000 sheet capacity
Weights	60 to 200 gsm

¹ Paper capacities are based on 75 gsm stock; capacities will vary with different weight stocks.

WorkCentre 5735/5740/5745/5755/5765/5775/5790

Paper Handling – Total Capacity	
Device Total Capacity ¹	8,700 sheets (with Bypass Tray, front loading paper trays, High Capacity Tandem Tray and High Capacity Feeder)
Output Option - Offset Catch Tray (Optional with 5735/5740/5745/5755)	
Capacity ¹	300 sheets
Sizes	A6/105 x 148 mm to A3/297 x 420 mm
Weights	60 to 216 gsm
Output Option - Basic Office Finisher (Optional with 5735/5740/5745)	
Capacity ¹	Top Tray – 250 sheets Stacking Tray – 1,000 sheets
Sizes	A6/105 x 148 mm to A3/297 x 420 mm
Weights	60 to 216 gsm
Stapling ¹	30 sheets Single position (top left hand corner)
Output Option – Office Finisher (Optional with 5735/5740/5745/5755/5765/5775)	
Capacity ¹	Top Tray – 250 sheets Stacking Tray – 2,000 sheets
Sizes	A6/105 x 148 mm to A3/297 x 420 mm
Weights	60 to 216 gsm
Stapling ¹	50 sheets Single (any corner) and dual
Hole Punch (Optional)	2-hole punch 4-hole punch 4-hole “Swedish” punch
Output Option – High Volume Finisher (Optional with 5740/5745/5755/5765/5775/5790)	
Capacity ¹	Top Tray – 250 sheets Stacking Tray – 3,000 sheets
Sizes	A6/105 x 148 mm to A3/297 x 420 mm
Weights	60 to 216 gsm
Stapling ¹	100 sheets Single (any corner), dual, front, rear, SEF and 4-stitch
Hole Punch (Optional)	2-hole punch 4-hole punch and 4-hole “Swedish” punch
Output Option – High Volume Finisher with Booklet Maker (Optional with 5740/5745/5755/5765/5775/5790)	
Capacity ¹	Top Tray – 250 sheets Stacking Tray – 3,000 sheets
Sizes	A6/105 x 148 mm to A3/297 x 420 mm
Weights	60 to 216 gsm

¹ Paper capacities are based on 75 gsm stock; capacities will vary with different weight stocks.

WorkCentre 5735/5740/5745/5755/5765/5775/5790

Stapling ¹	100 sheets Single (any corner), dual, front, rear, SEF and 4-stitch
Hole Punch (Optional)	2-hole punch 4-hole punch and 4-hole "Swedish" punch
Booklet Maker Capacity ¹	Tray stop up: 30 booklets (1-15 sheets per booklet) Tray stop down: Unlimited
Sizes	A4/210 x 297 mm A3/297 x 420 mm
Weights	60 to 216 gsm
Stapling ¹	Saddle-stitch (2-15 sheets / 8-60 page booklet)
Folding	V-folding (1-15 sheets / unstapled)

Output Option – Z-Fold / C-Fold Unit with HVF with Booklet Maker (Optional with 5740/5745/5755/5765/5775/5790)

Capacity ¹	50 sheets or unlimited capacity with tray stop in the down position
Sizes	A4/210 x 297 mm
Weights	60 to 216 gsm

Output Option – Post Process Inserter (Optional with HVF and HVF with Booklet Maker)

Capacity ¹	250 sheets
Sizes	A4/210 x 297 mm A3/297 x 420 mm
Weights	60 to 216 gsm

Output Option – Convenience Stapler Option

Capacity ¹	50 sheets
-----------------------	-----------

Print Specifications

Network Printing – Controller (Simultaneous rip, receive, programme-ahead, queue processing and transmit - standard with all configurations)

Processor	1.2 GHz Freescale dedicated
Memory (ESS)	640 MB (Expandable to 1024 MB or 1 GB with 1 GB Memory Kit)
System Disk	160 GB hard drive shared
Printer Language (PDL) auto switching	<ul style="list-style-type: none"> • PCL 6/PCL 5e • PostScript 3 emulation • TIFF (6.0 Old JPEG and New JPEG) • TIFF Fax Extended (TIFF-FX) • PDF • LCDS, SCS, XPS and IPDS through third party transforms

Network Printing – Resolution (printing via CentreWare software)

PostScript emulation: 600 x 600 dpi and 1200 x 1200 dpi (up to 256 shades of grey)
PCL: 600 x 600 dpi
Supports PCL and PS switching within job

¹ Paper capacities are based on 75 gsm stock; capacities will vary with different weight stocks.

Network Printing – Printing Features			
Advanced Features	Bidirectional Print Drivers Embedded web server for remote control/monitor/setup Job monitoring at the device and at desktop		
Paper Output	Special font, Banner Sheet, Rotate Image, Offset		
Network Printing – Print Driver Options			
Paper Output	Job Type <ul style="list-style-type: none"> • Secure, Sample, Delay • LAN Fax-with fax option • Save and Save & Print Paper Selection by attribute (including transparency separators) Duplex (2-sided) Finishing <ul style="list-style-type: none"> • Multiple stapling positions • Hole punch (if configured) • Booklet creation • Fit to new paper size • Saddle stitch with High Volume Finisher with Booklet Maker • Z-Fold / C-Fold Unit with High Volume Finisher with Booklet Maker Output tray selections Store and recall driver setting		
Special Pages	Exception Page programming (covers, inserts/tabs, exception pages)		
Image Options	Light/Dark Toner saver Resolution options (600 x 600 and 1200 x 1200 dpi) Reduction/Enlargement Margins (edge to edge printing) Invert Image (negative/mirror)		
Layout/Watermark	N-up (16)/Multi-up Booklet Layout/Finishing Fit to new paper size Image orientation Watermark options		
Printing Protocols and Networks			
Physical	Ethernet 10/100/1000 BaseT, IEEE802.5 (Token ring) [via third party adapter], Wireless Ethernet (IEEE802.11a/b/g [via third party adapter]), USB print		
Operating Systems	<ul style="list-style-type: none"> • Microsoft Windows, XP, Vista, Windows 7, Windows Server 2003, Windows Server 2008 • Novell NetWare 5.x, 6.x • Mac OS 10.4, 10.5, 10.6 • Solaris 8, 9, 10 SPARC, Solaris 10x86 • HP UX 11iv2 • IBM AIX 5 v5.3 • Linux Fedora Core 1-9 • RedHat Enterprise Linux 4 • openSUSE 10/11 		
Network Protocols	<ul style="list-style-type: none"> • TCP/IPv4/IPv6, LPR/LPD, Raw IP (Port 9100), NetBIOS SMB, IPX/SPX and Net BEUI, IPP • AppleTalk/EtherTalk 		
Administration Protocols	DHCP, BOOTP, SNMP, WINS, Bonjour, DDNS, SLP v2, SSDP, HTTP/S, RARP, LDAP, SMTP, POP3		
Security Protocols/Features	<table border="0"> <tr> <td style="vertical-align: top;"> Protocols <ul style="list-style-type: none"> • HTTPS • IPsec • 802.1X • SNMPv3 </td> <td style="vertical-align: top;"> Features <ul style="list-style-type: none"> • IP filtering • Unlimited Secure Print • Audit log • Image Overwrite • Data Encryption </td> </tr> </table>	Protocols <ul style="list-style-type: none"> • HTTPS • IPsec • 802.1X • SNMPv3 	Features <ul style="list-style-type: none"> • IP filtering • Unlimited Secure Print • Audit log • Image Overwrite • Data Encryption
Protocols <ul style="list-style-type: none"> • HTTPS • IPsec • 802.1X • SNMPv3 	Features <ul style="list-style-type: none"> • IP filtering • Unlimited Secure Print • Audit log • Image Overwrite • Data Encryption 		

Fonts	PCL: 80 scalable fonts, line printer and bitmap format line printer fonts (true type fonts) PostScript 3: 136 PostScript standard fonts (true type fonts/send fonts as/substitution table) Font Management Utility for downloading additional fonts (available for Windows and Mac)		
Print Drivers	Environment Windows XP (32 and 64 Bit), Windows 7, Windows Server 2003/2003 64 Bit, Windows Vista/ Vista 64 Bit, Windows Server 2008, Microsoft Certified	PCL6/5e Xerox custom graphical user interface Bidirectional features • Job, Paper and Toner status • Job status notification • Just in time Bi-Di • Auto population of IP address • Delete jobs	PostScript 3 Xerox custom graphical user interface Bidirectional features • Job, Paper and Toner status • Job status notification • Just in time Bi-Di • Auto population of IP address • Delete jobs
	Mac OS 10.4 - Generic PPD	N/A	Generic PPD
	Mac OS 10.5, 10.6 - Xerox custom	N/A	Xerox custom graphical user interface Bidirectional features • Toner, Fuser and Xerographic module status
Xerox Mobile Express Driver® (X-MED)	Makes it easy for mobile users to find, use and manage Xerox and non-Xerox devices in every new location. Plug into a new network, and X-MED automatically discovers available printers and provides status and capability information. Save a list of "favourite" printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT. • Printers are automatically discovered • Printer list can be managed based on location • Gives Bidirectional feedback device status, supplies, queue management		
Xerox Global Print Driver® (X-GPD)	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox and non-Xerox devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management. • Printers are automatically discovered • Printer list can be managed based on location • Gives Bidirectional feedback device status, supplies, queue management		
Print Submission Tools	Environment Solaris 8, 9, 10 SPARC, Solaris 10x86; HP UX 11.0, 11iv2, IBM AIX 5 v5.3; Linux Fedora Core 1-9; RedHat Enterprise Linux 4; openSUSE 10/11	PCL N/A	PostScript 3 Submission Tool with full feature set (includes administration, GUI/TTY print driver and software installation)
	TIFF/PDF: Supported in Windows XP, Windows Server 2003, Windows Server 2008, Windows Vista	N/A	Submission Tool for any TIFF or PDF file (via web only)
Device Management			
Management Support	SNMP Version 1. SNMP Version 2c and SNMP Version 3 MIB access (IETF-MIBII RFC 1213), host resources MIB RFC 2790, Printer MIB RFC v.2		
Xerox CentreWare Internet Services	Allows simple remote installation setting of configuration options and management of the device		
Xerox CentreWare Web	A Web-based server application for network administrators that permits Web browser-based device management from any workstation, whether running Windows, UNIX or any other operating system. Works with any SNMP-managed printer from any manufacturer. Provides help with device discovery and installation, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management. Requires Windows XP (Professional or Advanced Server) Windows 2003 and Internet Explorer 6.0 and higher		
Novell NDPS/NEPS (gateway for WorkCentre)	Server gateway application: centralised management tool		

Xerox CentreWare for Unicenter TNG	Provides added identification to the general discovery performed by Unicenter TNG and the ability to see the WorkCentre under a Unicenter TNG Business Process View
Xerox CentreWare for Tivoli NetView	Provides for the identification of Xerox WorkCentre multifunction systems in the general discovery performed by Tivoli NetView
Xerox CentreWare for HP OpenView	Provides for the identification of Xerox WorkCentre multifunction systems in the general discovery performed by HP Openview Provides traps and message updates to the Open View alarm browser and the ability to launch CentreWare Internet Services for device management directly from OpenView
Xerox Barcode Pro PS <i>Information available at www.xeroxofficesap.solutions.com</i>	Enables intelligent PostScript printing on Xerox multifunction systems by storing Xerox software, as well as, the barcode fonts on the printer hard disk. Enables the printing of barcodes from any application (SAP R/3 client or mainframe) that supports PostScript printing. Automatically calculates the check digit, places start/stop and middle bar characters in the data string, compresses and encodes the data string, and rotates the barcode through 90 or 270 degrees.
Xerox Device Types for SAP R/3 Environment are available at www.xeroxofficesap.solutions.com	Simplifies printing in SAP R/3 environments by providing users of SAP R/3 3.x, 4.x, 4.5x, 4.6x, SAP Enterprise 4.7x, ERP applications with enhanced WorkCentre printing functionality (PostScript and PCL): <ul style="list-style-type: none"> • One- to Two-sided printing • Finishing provides single or dual stapling • Tray pull location from any tray • Number of copies – provide the ability to print multiple copies • Paper Type and colour – provide ability to select different paper types and paper colours, such as transparency, red, etc. • Print security via PIN ID capability at the WorkCentre • Network Accounting (JBA) – Provides capability to add Job Based Accounting User IDs to SAP print jobs • Printer banner sheet – Provide the ability to enable/disable printer banner sheets • Barcode printing – Xerox standard PostScript device types available at www.xeroxofficesapsolutions.com supports Intelligent Barcode Printing with Xerox Barcode Pro PS. This Barcode Pro PS can be purchased at www.font.net
Xerox SAP R/3 Intelligent Barcode Utility (optional) <i>Purchase via www.font.net</i>	Provides built-in process intelligence that allows the printing of barcodes on any appropriately configured PostScript printer on the SAP R/3 4.1x, 4.5x, 4.6x and within Latin-1 (ISO8859-1) SAP system code pages only. Used in conjunction with Xerox PostScript Device Types for SAP R/3 environment and Xerox Font Centre Barcode Fonts. Utility enables automated checksum calculation, placement of start/stop characters, encoding of data string and data compression.

CentreWare Internet Services – Integrated device Web page

Device Status	Web server embedded on Controller <ul style="list-style-type: none"> • Tray status/contents • Consumables status • Alerts
Job-Print Queue Viewing	Complete job print queue management
Job Submission	Print ready files PS, PCL (TIFF, PDF with Copier/Printer only) Output feature selection (2-sided, staple, fold, hole punch, paper select) Delivery options (Immediate, proof, delay and secure)
Device Administration	Allows simple, remote installation setting of configuration options and management of the device
Scan Template Management	250 templates can be created Create device specific CentreWare scan templates Select confirmation sheet options Share scan templates via device cloning
Browsers	Netscape 6.2, 7.x (Mozilla 1.x) Internet Explorer 5.5.x, 6.x, 7.x Safari 1.x Mozilla Firefox 1.x
Support	Online support available via web page

Scan Specifications	
Scanning (Colour scanning available with 5735A/5740A/5745A/5755A/5765A/5775A/5790A)	
Concurrency	Scan while the system is printing, copying, or while it is transferring scan to network or fax jobs
Input Speed	Scan at up to 60 ipm (Black and white) – A4/210 x 297 mm LEF at all resolutions (5735) Scan up to 80 ipm (Black and white) – A4/210 x 297 mm LEF at all resolutions (5740/5745/5755) Scan at up to 60 ipm (Black and white), 80 ipm (Colour) - A4/210 x 297 mm LEF at all resolutions (5735A) Scan up to 80 ipm (Black and white), 80 ipm (Colour) – A4/210 x 297 mm LEF at all resolutions (5740A/5745A/5755A/5765A/5775A/5790A)
Resolutions	DPI Options 600 x 600 dpi 400 x 400 dpi 300 x 300 dpi 200 x 200 dpi 100 x 100 dpi 72 x 72 dpi
	Scan Presets <ul style="list-style-type: none"> • Archival Record (Normal Quality - Smallest file size) – 100 x 100 • For Sharing and Printing (Normal Quality - Small file size) – 200 x 200 • For High Quality Printing (High Quality - Large file size) – 300 x 300 • For OCR (High Quality - Large file size) – 300 x 300 • Simple Scan (Normal Quality - Small file size) – 200 x 200
	Quality/File Size <ul style="list-style-type: none"> • Normal Quality (Small file size) • Higher Quality (Large file size) • Maximum Quality (Largest file size)
Maximum Scan Area	A3/297 x 420 mm
File Formats	TIFF 6.0 with G3 MH, G4 MMR or JPEG ² compression (single page or multiple pages) PDF (image only with G3 MH, G4 MMR, MRC, JPEG or JBIG2 compression), PDF/A, XPS, Searchable PDF, PDF/A Searchable XPS
Network Scanning	
Capability	<ul style="list-style-type: none"> • Enables device-specific network scan workflows (destination templates) to be easily created and edited via CentreWare Internet Services • Scan to Home displays one template and populates with the user's directory path after authentication • Scan to file • Scan to network server / directory • Scan to Mailbox • Scan to Folder on hard disk for device access of documents • Scan to Windows XP client via Windows Image Acquisition (WIA) or TWAIN driver downloadable from www.xerox.com • Colour scanning (optional)
Network Protocol	Novell (NCP via IPX/SPX) FTP Microsoft SMB via TCP/IP HTTP/HTTPS
Document Management Fields (Metadata)	Features only available in Network Scan to File Templates: <ul style="list-style-type: none"> • 1-6 user programmable metadata fields per network scan to file templates and unlimited fields within the template • Metadata Fields consists of field name, display at the LUI or not, default value and other configurations • Customised fields viewed on user interface • Variable data entered using virtual keyboard at device

² JPEG only available with Colour Scanning

Scan Template Management	Share scan templates among WorkCentre via device cloning Scan template management (250 templates) with CentreWare Internet Services Select confirmation sheet option
Scan Features	Build job for Scan to file and Scan to Email (enables special programming for different pages in one document – can be used for inserts, mixing input from the document glass and document feeder), Duplex scanning, Auto detect document size, Scan mixed size originals, scan to edge.
Scan to Email	
Capability	Scan to Email (manual address entry or directory (Exchange/Notes/LDAP) address searching (internal address book or Public address book – up to 128 recipients)
Network Protocol	SMTP MIME encoded
Scan Features	Email signatures (6 lines each of 128 character max), email message body (user configurable), email CWIS confirmation sheet options

Network Scanning Software Solutions

Scan to PC Desktop Work Group Edition SE (optional)	A desktop offering that provides document imaging, archiving, editing and organisation tools ScanSoft PaperPort SE – image viewing and file management software ScanSoft OmniPage SE – offer desktop/client installation – OCR and file format conversion software Image Retriever – provides fully automated retrieval of scanned images direct from WorkCentre to individual desktops
Scan to PC Desktop Work Group Edition Professional (optional)	A desktop offering that provides advanced document imaging, archiving, editing and organisation tools. ScanSoft PaperPort Professional image viewing and file management software <ul style="list-style-type: none"> • Complete PDF functionality • Secure PDF workflow of all scanning applications ScanSoft OmniPage Pro Office (for desktop/client installation) Professional OCR software for digital archiving and document conversion Image Retriever – provides fully automated retrieval of scanned images direct from a scan enabled Xerox WorkCentre to individual desktops. Also includes an email inbox polling capability.
SMARTsend ³ (optional)	Server base document routing software that supports multiple scan-enabled multifunctional systems Enables transformation, distribution and routing of scanned documents Workflow creation via Web browser-based task creation (destinations, devices, document attributes – 20 file types including PDF, workflow settings, workflow summary) <ul style="list-style-type: none"> • Scan to File Destinations: email, Microsoft NetWare folder, network folder, FTP, Microsoft Exchange 2000 web folders, web URL, remote printers • Scan to Document Repository Destinations: DocuShare, Domino, Domino.doc, Microsoft SharePoint, Hummingbird DNS, Open Text Livelink, Documentum, Interwoven Work Site Workflow initiation via device scanning user interface (template selection at device UI) Adding of Metadata information
SMARTsend ³ Professional (optional)	Everything in SMARTsend, plus: <ul style="list-style-type: none"> • Workflow initiation via Paperware (Scan coversheets) • Server-based Optical Character Recognition (OCR) • Searchable PDF • Scan to Internet fax file destination • TrueMatch patented search technology

Fax Specifications

Fax Options – Walkup Option (One or Two Lines Options)

Compatibility	ITU (CCITT) Group 3
Memory	256 MB (One Line and Two Line options)
Speed/Modem(s)	1 or 2 V.34 modems: 33kbps. Less than 4 seconds per page transmission time, ISDN via third party adapter
Compression/Speed	MH/MR/MMR/JBIG/G3/Super G3

³ Features, configurations and options vary by location.

WorkCentre 5735/5740/5745/5755/5765/5775/5790

Fax Send Features	<p>Quality/Resolution</p> <ul style="list-style-type: none"> • Original type: Normal, text, half tone, photo, lighter/darker, background suppression • Fax – off Platen, mixed sizes or Bound/Book <p>Auto Send (Up to 5)</p> <p>Audio line monitor</p> <p>Transmission options (Report/Header)</p> <p>Reduce/Split large documents</p> <p>Cover letter</p> <p>Delayed send</p> <p>Build Job (up to 1000 images)</p> <p>Polling</p>
Fax Receive Features	<p>One or two-sided printing</p> <p>Stapled or unstapled, hole punch</p> <p>Receive print mode – Manual (size, margin, stock, header)/Auto</p> <p>Auto answer delay</p> <p>Secure receive</p> <p>Junk fax prevention</p> <p>Fax Forward to Email and File</p>
Fax Reports	<p>Activity</p> <p>Dial directory</p> <p>Group directory</p> <p>Options</p> <p>Pending Jobs</p>
Fax Mailboxes	<p>Up to 100 password-protected</p> <p>Poll Remote mailboxes (up to 255) password-protected</p>
Auto Dialing Features	<p>Speed Dials</p> <ul style="list-style-type: none"> • 200 (One-line option) • 1,000 (Two-line option) <p>Group Dials</p> <ul style="list-style-type: none"> • Up to 100 groups with up to 200 recipients per group (One-line option) • Up to 200 groups with up to 400 recipients per group (Two-line option) <p>Auto redial</p> <ul style="list-style-type: none"> • Up to 14 attempts • Up to 25 min intervals • Batch Send (up to memory capacity)
Resolutions	<p>200 x 100 dpi (Standard)</p> <p>200 x 200 dpi (Fine)</p> <p>300 x 300 dpi</p> <p>200 x 400 dpi</p> <p>400 x 400 dpi</p> <p>400 x 600 dpi</p> <p>600 x 600 dpi (Super Fine)</p>
Fax Options – LAN Fax with Walkup Fax (Optional)	
	<p>Driver based LAN fax for Windows and Macintosh users (PCL and PS drivers)</p> <p>Recipient options (add recipient or add from phone book)</p> <p>User personal phone book – up to 1,000 entries</p> <p>Confirmation sheet</p> <p>Send speed (14.4/33.6kbps or 4800bps)</p> <p>Send time</p> <p>Dialing options (prefix or credit card)</p> <p>Cover sheet (add notes)</p> <p>Preferences – Phonebook (personal or shared LDAP)</p>
Fax Options – Internet Fax Enablement (Standard with 5735A/5740A/5745A/5755A/5765A/5775A/5790A)	
Capability	<p>Direct document transmission to remote Internet Fax machines or e-mail clients (SMTP)</p> <p>Reception and automatic printout of documents sent via e-mail from remote Internet Fax machines or e-mail clients</p>

WorkCentre 5735/5740/5745/5755/5765/5775/5790

Maximum Scan Area	A3/297 x 420 mm
Address Directory Access	Corporate address list via LDAPv3 Downloaded address list (comma-separated file format) Internal LDAP or Public address book
File Formats	TIFF-FX profiles S, F with G3 MH or JPEG compression PDF (image only) with G3 MH, G4 MMR or JPEG compression PDF and Multi TIFF
Resolutions	600 x 600 dpi 400 x 400 dpi 300 x 300 dpi 200 x 200 dpi 200 x 100 dpi 100 x 100 dpi 72 x 72 dpi
Network Protocols	SMTP POP3 (RFC 1939)
Compliance	ITU-T T.37 compliant
Features	Signature (SA configurable –16 lines each of 128 character max) Delivery Confirmation <ul style="list-style-type: none"> • Email receipt option • Confirmation reply option • Cover sheet option • Subject (248 characters) • User configurable message body

Fax Options – Network Fax Server Enablement (Standard with 5735A/5740A/5745A/5755A/5765A/5775A/5790A)

Capability	Provides walk-up faxing and hard copy output of received faxes when integrated with fax server applications (fax server and software must be purchased separately from supplier). Transmission speeds, number of lines, compatibility and compression are dependent on fax server configuration (via SMTP).
Maximum Scan Size	A3/297 x 420mm
Network Protocols	Novell (NCP via IPX/SPX) FTP Microsoft SMB via TCP/IP HTTP/HTTPS SMTP
Fax Send Features	One or two-sided scanning (up to A3/297 x 420 mm) Phone number entry Add to send list (50 numbers maximum) Delay send (specific time) Resolution selection (fine, standard) Image quality selection (normal, text, lighten/darken, photo, background suppression, seven levels of contrast, seven levels of sharpness)
Fax Print Features	One or two-sided printing Quantity Staple on/off Collate on/off Secure print on/off Finisher output tray selection (top tray or main tray)
Supported Network Fax Vendors	Multiple vendors, certified by the Xerox Alliance Partner Programme. For details visit www.xerox.com

Device Management Specifications

Accounting Features – Xerox Standard Accounting (Standard)

Tracking	Copy, Print, Fax and Scan usage
----------	---------------------------------

Accounting	Up to 2,500 User accounts (User Id) Up to 500 General accounts (Client) Up to 500 Group accounts (Department)
Features	Enable/disable via the web UI or the GUI in tools, admin can manage the feature remotely via the web UI, Data can be exported via a CSV file, user required to enter XSA ID into the print driver when submitting a print job, similar to secure print. Xerox Standard Accounting can be used in conjunction with an external device via the FDI (e.g. Coin Op or Card Reader).

Accounting Features – Network Accounting Enablement Kit (Optional)

Enhanced network accounting with up to the minute data on how the WorkCentre system is being used; comprehensive management and enterprise scale tracking and reporting of device usage of copy, print, scan and server fax. Various options available through Xerox Alliance Partner solutions. For details visit www.xerox.com
Security enhancements with the addition of HTTPS protocol support
WorkCentre requests account authentication from 3rd party server enabling larger databases of users and accounts

Security – Review the Supplemental Security Brochure for Details

Authentication	Secure device login with network user name and password Supports Kerberos (Windows UNIX/Windows Server 2003) SMB (Windows NT 4.0/Windows Server 2003) Novell over IP/IPX (Novell NetWare 4.x/5.x/6.x) LDAP Secure Access
Features	802.1X Compliant IPv6 Ready (Phase 2) Disk Image Overwrite – Immediate, On Demand, Scheduled HTTPS (SSL) SNMP V3 IPsec Network Authentication Device Access Password Protection IP Filtering Audit Log Full Disk Encryption Secure Print Fax Security
Common Criteria Certification	Common Criteria Certification provides independent, objective validation of the reliability, quality and trustworthiness of IT products. It is a standard that customers can rely on to help them make informed decisions about their IT purchases. WorkCentre 5700 series is full system Common Criteria (ISO 15408) Certified.

Secure Access Unified ID System (Optional)

Secure Access Unified ID System adds an advanced layer of security at the device by enabling users to log-in to a Xerox multifunction system with a swipe of their magnetic or proximity ID card. When combined with Follow You Print functionality, Secure Access allows private print jobs to be accessed from any Xerox printer or multifunction system on your network.

Xerox Extensible Interface Platform (EIP)

Xerox EIP acts as a gateway, enabling simplified, server-based applications that personalise the user experience through customised touch-screen displays. Personalised for each user. These applications will yield simpler user interactions and result in less time interacting with the multifunction system which drives increased worker productivity and systems that easily adapt to your business processes. For example, combined with the optional SMARTsend solution, you can set up a digital repository for users to browse and print frequently requested documents.

WorkCentre 5735/5740/5745/5755/5765/5775/5790

Machine Specifications

Monthly Duty Cycle

5735 – up to 125,000 pages
5740 – up to 150,000 pages
5745 – up to 175,000 pages
5755 – up to 200,000 pages
5765 – up to 250,000 pages
5775 – up to 300,000 pages
5790 – up to 400,000 pages

Basic Configurations³

WorkCentre with Platen, Trays 1-2 and Stand (5735V_PN)
WorkCentre with DADH, Trays 1-2 and Stand (5735V_SN / 5740V_SN / 5745V_SN / 5755V_SN)
WorkCentre with DADH, Trays 1-2, High Capacity Tandem Tray and Colour Scan
(5735V_A / 5740V_A / 5745V_A / 5755V_A / 5765V_A / 5775V_A / 5790V_A)

Accessory Options³

High Capacity Feeder
Optional A4 Short Edge Kit for High Capacity Feeder
Optional A3 Short Edge Kit for High Capacity Feeder
Offset Catch Tray (5735/5740/5745/5755)
Basic Office Finisher (5735/5740/5745)
Office Finisher (5735/5740/5745/5755/5765/5775)
High Volume Finisher (5740/5745/5755/5765/5775/5790)
High Volume Finisher with Booklet Maker (5740/5745/5755/5765/5775/5790)
High Volume Finisher with Booklet Maker and Z-Fold/C-Fold unit (5740/5745/5755/5765/5775/5790)
Post Process Inserter (Optional with High Volume Finishers)
Convenience Stapler
Hole Punch (with Office Finisher and High Volume Finisher – see Output Options for details)
Envelope Tray Kit (in place of Tray 2)
Foreign Interface Device (FDI)
Xerox Copier Assistant (XCA)
Walkup Fax with LAN Fax: One line and Two lines
Scan to PC Desktop SE and Professional
Secure Access
SMARTsend
Enablement for Network Accounting and Xerox Alliance Partner Solutions
Xerox Unicode International Printing
1 GB Memory Kit

Electrical Requirements

220-240 Volt Nominal, 50 Hz, 10A
Note: Convenience Stapler requires separate 220-240V, 10A circuit

³ Features, configurations and options vary by location.

WorkCentre 5735/5740/5745/5755/5765/5775/5790

Power Consumption							
	5735 ⁴	5740 ⁴	5745 ⁴	5755 ⁴	5765 ⁴	5775 ⁴	5790 ⁵
Running	≤ 1130 watts	≤ 1130 watts	≤ 1230 watts	≤ 1330 watts	≤ 1640 watts	≤ 1690 watts	≤ 1840 watts
Standby	≤ 300 watts	≤ 300 watts	≤ 300 watts	≤ 300 watts	≤ 320 watts	≤ 320 watts	≤ 340 watts
Low Power Mode	≤ 125 watts	≤ 125 watts	≤ 125 watts	≤ 125 watts	≤ 160 watts	≤ 160 watts	≤ 160 watts
Auto Off / Sleep mode	≤ 15 watts						
Warm up Ready to Copy	≤ 30 seconds						
Warm up Ready to Print	≤ 30 seconds						
Low Power Recovery	≤ 9 seconds						

Environmental Considerations	
Required Temperature Range	10° to 32° C
Required Relative Humidity	10 % to 85 %

Dimensions and Weights (5735/5740/5745/5755)				
	Width ⁶	Depth	Height	Weight ⁷
Configuration with Offset Catch Tray	1,290 mm	645 mm	1,147 mm	124 kg
Configuration with Basic Office Finisher (5735/5740/5745)	1,524 mm	645 mm	1,147 mm	147 kg
Configuration with Office Finisher	1,524 mm	645 mm	1,147 mm	152 kg
With High Volume Finisher (5740/5745/5755)	1,960 mm	645 mm	1,147 mm	195 kg
With High Volume Finisher with Booklet Maker (5740/5745/5755)	1,985 mm	645 mm	1,180 mm	222 kg
With High Volume Finisher with C/Z Folder and Post Process Inserter (5740/5745/5755)	2,310 mm	645 mm	1,180 mm	250 kg
High Capacity Feeder	389 mm	645 mm	575 mm	30 kg

Dimensions and Weights (5765/5775/5790)				
	Width ⁶	Depth	Height	Weight ⁷
Configuration with Office Finisher (5765/5775)	1,524 mm	704 mm	1,147 mm	156 kg
With High Volume Finisher	1,960 mm	704 mm	1,147 mm	200 kg
With High Volume Finisher with Booklet Maker	1,985 mm	704 mm	1,180 mm	227 kg
With High Volume Finisher with C/Z Folder and Post Process Inserter	2,310 mm	704 mm	1,180 mm	258 kg
High Capacity Feeder	389 mm	704 mm	575 mm	30 kg

⁴ With Office Finisher

⁵ With High Volume Finisher

⁶ Includes Shelf

⁷ Weights do not include Shelf (1.36 kg)

Noise Levels ⁸							
	5735	5740	5745	5755	5765	5775	5790
Standby dB (A) SPL	35	35	35	35	35	35	35
Run Continuous dB (A) SPL	54	55	56	56	57	57	58
Run Impulse dB (A) L SPL	57	58	59	61	62	62	63

Certifications	
	FCC Class A Compliant (US), DOC Class A Compliant (Canada) 2004/108/EC (Europe) UL Listed (UL 1950, Third Edition) CB Certified (IEC 60950/EN 60950) 2006/95/EC (Europe) 95/5/EEC (Europe) Energy Star Blue Angel Certified Full system Common Criteria (ISO 15408) Certified

Supplies				
	Description	Order Number	No. per Box	Expected Yield
	Toner Cartridge 5735 - 5755	006R1046	2	> 36,000 at 6 % area coverage per bottle > 50,000 at 6 % area coverage per bottle
	5765 - 5790	006R1146	2	
	Waste Toner Bottle (supplied with each toner cartridge box)	008R12896	1	100,000
	Staple Cartridge (for Basic Office Finisher)	108R00535	3	3,000 per cartridge (9,000 staples)
	Staple Cartridge (for Office Finisher)	108R00493	3	5,000 per cartridge (15,000 staples)
	Staple Cartridge (for HVF with Booklet Maker – saddle-stitch stapling)	008R12897	8 (4 x 2)	2,000 per cartridge (16,000 staples)
	Staple Cartridge (for Convenience Stapler) • Complete Cartridge • Refill Cartridge	008R12964 008R12941	1 3	5,000 per cartridge 5,000 per cartridge (15,000 staples)
	Staple Cartridge (for HVF and HVF with Booklet Maker)	008R12912	1	5,000 per cartridge

⁸ Noise levels shown are “Not to Exceed” levels. Actual noise levels will be lower.

WorkCentre 5735/5740/5745/5755/5765/5775/5790

Smart Kits				
	Description	Order Number	No. per Box	Expected Yield
	Fuser Module (includes ozone filter) 5735 - 5755:	109R00751	1	400,000
	5765 - 5790:	109R00772	1	400,000
	Xerographic Module – Metered 5735:	113R00608	1	200,000
	5740 - 5790:	113R00672	1	400,000 – 500,000
	Xerographic Module Smart Sold 5735:	113R00607	1	200,000
	5740 - 5790:	113R00673	1	400,000 – 500,000
	Document Handler Feeder Rolls 5735:	113R00717	1	150,000 feeds
	5740 - 5790:	113R00718	1	150,000 feeds

