

Xerox® WorkCentre™ 5845/5855 Multifunction Printer

WorkCentre 5800 series multifunction systems are enabled by the Xerox® ConnectKey® Controller. These simple-to-implement systems give you real, practical solutions that easily streamline how you communicate, process and share important information, simplify complex paper-driven tasks, and drive down costs while keeping your data secure.



System Specifications	WorkCentre 5845 WorkCentre 5855		
Speed 8.5 x 11 in. / A4 (LEF) 8.5 x 13 to 8.5 x 14 in. / A4 to B4 (SEF) 11 x 17 in. / A3 (A3 SEF) (Bypass Tray will reduce speed by 10 to 20%)	45 ppm 36 ppm 31 ppm	55 ppm 36 ppm 31 ppm	
Monthly Duty Cycle ¹	Up to 175,000 pages	Up to 200,000 pages	
Recommended Average Monthly Print Volume ²	Up to 20,000 pages		
Hard Drive / Processor / Memory	Minimum 160 GB / 1 GHz Dual-core / 2 GB system		
Connectivity	10/100/1000Base-T Ethernet, High-Speed USB 2.0 Direct Print, Optional Wi-Fi (v	with Xerox® USB Wireless Adapter)	
Controller Features	Unified Address Book, Remote Control Panel, Online Support (accessed from t	he user interface and print driver), Configuration Cloning	
Copy and Print			
Copy and Print Resolution	Copy: Up to 600 x 600 dpi; Print: Up to 4800 x 600, 256 shades of grey, 1200 x 1200 emulation		
First-print-out Time	As fast as 3.7 seconds		
First-copy-out Time	As fast as 3.7 seconds from the Platen / 7.6 seconds from the Automatic Document Feeder		
Page Description Languages	Adobe® PostScript® 3™, PDF, PCL® 5c / PCL 6, XML Paper Specification (XPS®) (Optional)		
Print Features	Print from USB, Earth Smart Driver Settings, Job Identification, Booklet Creation, Store and Recall Driver Settings, Bidirectional Status, Scaling, Job Monitoring		
Mobile Printing	Apple® AirPrint, Xerox® PrintBack, Xerox® Mobile Print Solution (Optional), Xerox® Mobile Print Cloud (Optional), Mopria™ certified		
Scan			
Standard Features	Scan to Network, Scan to Email, Scan to Folder, Scan to SMB or FTP, Text Searchable PDF, PDF/A, XPS, Linearised PDF, JPEG, TIFF, Scan to USB Memory Device, Single Touch Scanning, TWAIN Support		
Optional Features	ConnectKey® for SharePoint®, ConnectKey® for DocuShare®, ConnectKey® Share to Cloud, Xerox® Scan to PC Desktop® SE and Professional, numerous solutions available through various Xerox Alliance Partners		
Fax			
Standard Features	Internet Fax, Fax Build Job, Network Server Fax Enablement		
Optional Features	Fax Forward to Email or SMB, Walk-up Fax (one-line and two-line options, includes LAN Fax)		
Security			
Standard Features	McAfee® Embedded, McAfee ePolicy (ePO) Compatible, HDD Overwrite, 256-bit Encryption (FIPS 140-2 compliant), Common Criteria Certification (ISO 15408), Secure Print, Secure Fax, Secure Scan, Secure Email, Cisco® TrustSec Identity Services Engine (ISE) Integration, Network Authentication, SSL, SNMPv3, Audit Log, Access Controls, User Permissions		
Optional Features	McAfee Integrity Control, Xerox Secure Access Unified ID System®, Smart Card Enablement Kit (CAC/PIV/.NET)		
Accounting			
Standard Features	Xerox® Standard Accounting (Copy, Print, Scan, Fax, Email), Network Accounting Enablement		
Optional Features	Equitrac Express®, Equitrac Office®, Equitrac Professional®, YSoft® SafeQ®, other network accounting solutions available through various Xerox Alliance Partners		

Device Specifications					
Control Panel Languages		ı, International French, Italian, Germ Czech, Polish, Hungarian or Romania	· ·	n Portuguese, Swedish, Norwegian, Danish,	
Accessories					
Optional	_	red) ith 5845 only) er et Maker olume Finisher with Booklet Maker) Volume Finisher with Booklet Maker; fork Surface) System® otions, includes LAN Fax)			
Foreign Device Interface (FDI) (Optional)	Also known as Auxiliary Access C	Device, this is an interface to third pa	rty access control devices, such as coin n	nachines and card readers.	
Electrical Requirements					
North America	Voltage : 110-127 VAC +/- 10% Frequency: 50/60 Hz +/- 5%, 10	A			
Europe	Voltage : 220-240 VAC +/- 10% Frequency: 50/60 Hz +/- 5%, 12 A				
Power Consumption	WorkCentre 5845		WorkCentre 5855	e 5855	
Running (Average)	1,150 watts 1,250 watts				
Standby Mode	290 watts				
Low Power Mode	≤125 watts				
Auto off / Sleep mode	≤4 watts (Default time to sleep = 2 minutes)				
Warm up (from Off)	As fast as <230 seconds (3 minutes, 50 seconds) (Dependent on number of services registered)				
Low Power Recovery	<4 seconds				
Recovery from Sleep	<28 seconds				
Operating Environment					
Required Temperature Range	50° to 90° F (10° to 32° C)				
Required Relative Humidity	15% to 85%				
Sound Power Levels	Operating 7.1 B(A), Standby: 5.0	Operating 7.1 B(A), Standby: 5.0 B(A)			
Sound Pressure Levels	Operating: 56 dB(A), Standby: 3	5 dB(A)			
Dimensions and Weight	Width	Depth	Height	Weight	
Base Configuration with OCT	39.0 in. / 990 mm	25.6 in. / 650 mm	43.5 in. / 1,104 mm	271.8 lbs. / 123.3 kg	
With Basic Office Finisher (5845 only)	47.6 in. / 1,209 mm	25.6 in. / 650 mm	43.5 in. / 1,104 mm	319.7 lbs. / 145 kg	
With Office Finisher	47.6 in. / 1,209 mm	25.6 in. / 650 mm	43.5 in. / 1,104 mm	329.6 lbs. / 149.5 kg	
With Office Finisher with Booklet Maker	47.6 in. / 1,209 mm	25.6 in. / 650 mm	43.5 in. / 1,104 mm	364.9 lbs. / 165.5 kg	
With High Volume Finisher	64.8 in. / 1,645 mm	25.6 in. / 650 mm	45.1 in. / 1,145 mm	425.1 lbs. / 192.8 kg	
With High Volume Finisher with Booklet Maker, C Fold / Z Fold Unit and Post Process Inserter	78.5 in. / 1,995 mm	25.6 in. / 650 mm	46.5 in. / 1,180 mm	485.7 lbs. / 220.3 kg	
High Capacity Feeder	15.3 in. / 389 mm	20.1 in. / 510 mm	22.6 in. / 510 mm	66.1 lbs. / 30 kg	
Work Surface (Does not add to overall width if combined with High Capacity Feeder	11.2 in. / 285 mm	-	-	-	

Certifications		
	FCC Class A Compliant (US), ICES Class A Compliant (Canada) CSA Listed (UL 60950-1, Second Edition) CB Certified (IEC 60950-1, Second Edition) GS Mark ENERGY STAR® EPEAT GOST NOM Environmental Choice CE Mark Common Criteria (IEEE 2600.2 standard) Citrix® Certified WHQL IPv6 Ready MEDITECH SAP Cerner To view the latest list of certifications, go to www.xerox.com/OfficeCertifications.	
Paper Handling	to view the latest list of certain actions, go to www.seroxicomportrecertain actions.	
Single-pass Automatic Document	Feeder	
Capacity ³	200 sheets	
Speed (black and white and colour)	Up to 105 images per minute (ipm) (simplex) Up to 200 ipm (duplex)	
Paper Sizes Sensed	4.9 x 5.4 in. to 11.7 x 17 in. / 125 x 138 mm to 297 x 432 mm	
Weights	13 lb. bond to 43 lb. bond / 50 gsm to 160 gsm	
Bypass Tray		
Capacity ³	100 sheets	
Sizes	Custom sizes: 4.25 x 5.5 in. to 11 x 17 in. / A6 to A3	
Weights	16 lb. bond to 80 lb. cover / 60 to 216 gsm	
Types	Bond Carbonless Card Stock Envelopes Hole punched Index Labels Letterhead Plain Preprinted Recycled Transparencies Tabs	
Trays 1 and 2		
Capacity ³	500 sheets each	
Sizes	Custom Sizes from 5.5 x 8.5 in. LEF to 11 x 17 in. SEF / A5 to A3	
Weights	16 lb. bond to 53 lb. bond / 60 to 200 gsm	
Types	Bond Card Stock Glossy Hole punched Index Labels Letterhead Lightweight Card Stock Plain Preprinted Recycled Tabs	

High Capacity Tandem Tray			
Capacity ³	Tray 3: 1,600 sheets		
	Tray 4: 2,000 sheets		
Sizes	Standard Sizes: 8.5 x 11 in. LEF / A4		
Weights	16 lb. bond to 53 lb. bond / 60 to 216 gsm		
Types	Bond Card Stock Glossy Hole punched Index Letterhead Lightweight Card Stock Plain Preprinted Recycled		
High Capacity Feeder (HCF) (Optio			
Capacity ³	4,000 sheets Optional HCF Kits: 2,000 sheets with Letter/Legal HCF Kit or 2,000 sheets with Tabloid SEF HCF Kit (Optional)		
Sizes	8.5 x 11 in. / A4 LEF Optional HCF Kits: 8.5 x 11 in. / A4 or 11 x 17 in. / A3		
Weights	16 lb. bond to 58 lb. bond / 60 to 216 gsm		
Types	Bond Card Stock Hole punched Index Letterhead Plain Preprinted Recycled		
Envelope Tray (Optional–Replaces Tray 2)			
Capacity ³	Up to 50 envelopes		
Sizes	#10 Commercial (9.25 x 4.125 in.), #9 Commercial (8.875 x 3.875 in.), Monarch, DL, C5		
Weights	20 lb. bond to 24 lb. bond / 75 to 90 gsm		
Total Capacity			
Device Total Capacity ³	8,700 sheets		
Finishing			
Offset Catch Tray (OCT) (Standard			
Capacity	Up to 300 sheets of 20 lb. bond / 80 gsm		
Basic Office Finisher (Optional with	h 5845)		
Top Tray Capacity Stacking Tray Capacity	250 sheets of 20 lb. bond / 80 gsm 1,000 sheets of 20 lb. bond / 80 gsm		
Top Tray Sizes Stacking Tray Sizes	4.25 x 5.85 in. to 11 x 17 in. / A6 to A3 5.5 x 8.5 in. to 11 x 17 in. / A5 to A3		
Weights	16 lb. bond to 58 lb. bond / 60 to 216 gsm		
Stapling	Single Auto stapling:30 sheets maximum: Letter / A4 / B5-size sheets (less than 90 gsm or (2) 220 gsm covers) 30 sheets maximum: Legal / Tabloid / A3 / B4-size sheets (less than 90 gsm or (2) 220 gsm covers)		
Office Finisher (Optional)	Office Finisher (Optional)		
Top Tray Capacity Stacking Tray Capacity	250 sheets unstapled of 80 gsm 2,000 sheets unstapled of 80 gsm or 1,000 sheets single stapled or 750 sheets dual stapled (8.5 x 11 in. / A4)		
Top Tray Sizes Stacking Tray Sizes	4.25 x 5.85 in. to 11 x 17 in. / A6 to A3 5.5 x 8.5 in. to 11 x 17 in. / A5 to A3		
Weights	16 lb. bond to 58 lb. bond / 60 to 216 gsm		
Multiposition Stapling	50 sheets of 20 lb. bond / 80 gsm		
Hole Punch (Optional) North America: Europe:	2-3 Hole Punch 2-4 Hole Punch		

Office Einisher with Booklet Mak	or (Ontional)
Office Finisher with Booklet Mak	· · ·
Top Tray Capacity Stacking Tray Capacity	250 sheets unstapled of 80 gsm 2,000 sheets unstapled of 80 gsm or 1,000 sheets single stapled or 750 sheets dual stapled (8.5 x 11 in. / A4)
Top Tray Sizes Stacking Tray Sizes	4.25 x 5.85 in. to 11 x 17 in. / A6 to A3 5.5 x 8.5 in. to 11 x 17 in. / A5 to A3
Weights	16 lb. bond to 58 lb. bond / 60 to 216 gsm
Multiposition Stapling	50 sheets of 20 lb. bond / 80 gsm
Hole Punch (Optional)	
North America: Europe:	2-3 Hole Punch 2-4 Hole Punch
Booklet Making Capacity ³	40 booklets (2-15 sheets per booklet – 20 lb. / 80 gsm or less)
Booklet Making Sizes	Letter – 8.5 x 11 in. / A4 SEF Legal – 8.5 x 14 in. / B4 SEF Ledger – 11 x 17 in. / A3 SEF
Saddle-stitch Stapling	2-15 sheets / 8 – 60 page booklet 16 lb. bond to 24 lb. bond / 60 to 90 gsm
Score / Crease	1-15 sheets / unstapled
High Volume Finisher (HVF) (Opt	tional)
Capacity ³	Top Tray – 250 sheets Stacking Tray – 3,000 sheets
Sizes	4.25 x 5.5 in. / to 11 x 17 in. / A6 to A3 / 105 x 148 mm to 297 x 420 mm
Weights	16 lb. to 57 lb. bond / 80 lb cover / 60 to 216 gsm
Stapling ³	100 sheets Single (any corner), dual, front, rear, SEF and 4-stitch
Hole Punch (Optional) North America:	3-hole punch 2-hole Legal punch
Europe:	2-hole punch 4-hole punch and 4-hole "Swedish" punch
High Volume Finisher with Bookl	et Maker (Optional)
Capacity ³	Top Tray – 250 sheets Stacking Tray – 3,000 sheets
Sizes	4.25 x 5.5 in. to 11 x 17 in. / A6 to A3 / 105 x 148 mm to 297 x 420 mm
Weights	16 lb. to 57 lb. bond / 80 lb. cover / 60 to 216 gsm
Stapling ³	100 sheets Single (any corner), dual, front, rear, SEF and 4-stitch
Hole Punch (Optional)	
North America:	3-hole punch 2-hole Legal punch
Europe:	2-hole punch
	4-hole punch and 4-hole "Swedish" punch
Booklet Maker Capacity³	Tray stop up: 30 booklets (1-15 sheets per booklet) Tray stop down: Unlimited
Booklet Maker Sizes	Letter – 8.5 x 11 in. / A4 / 210 x 297 mm Legal – 8.5 x 14 in. / 216 x 356 mm Ledger – 11 x 17 in. / A3 / 297 x 420 mm
Booklet Maker Weights	16 lb. to 57 lb. bond / 80 lb. cover / 60 to 216 gsm
Saddle-stitch Stapling ³	Saddle-stitch (2-15 sheets / 8-60 page booklet)
Folding	V-folding (1-15 sheets / unstapled)
Z Fold / C Fold Unit (Optional wit	th HVF with Booklet Maker)
Capacity ³	50 sheets or unlimited capacity with tray stop in the down position
Sizes	Letter – 8.5 x 11 in. / A4 / 210 x 297 mm
Weights	16 lb. to 57 lb. bond / 80 lb. cover / 60 to 216 gsm
	·

Post Process Inserter (Optional	Post Process Inserter (Optional with HVF and HVF with Booklet Maker)		
Capacity ³	250 sheets		
Sizes	Letter – 8.5 x 11 in. / A4 / 210 x 297 mm Legal – 8.5 x 14 in. / 216 x 356 mm Ledger – 11 x 17 in. / A3 / 297 x 420 mm		
Weights	16 lb. to 57 lb. bond / 80 lb. cover / 60 to 216 gsm		
Convenience Stapler (Optional-	-Includes Work Surface)		
Capacity ³	50-sheet stapling 5,000 staples Requires a separate power outlet		
Сору			
First-copy-out Time	3.7 seconds from the Platen / 7.6 seconds from the Automatic Document Feeder		
Sides (input:output)	1-1, 1-2, 2-2, 2-1		
Quantity	1 to 9,999		
Resolution (max.)	Up to 600 x 600 dpi		
Reduction / Enlargement	Variable zoom from 25 % to 400 % in 1 % increments		
Concurrency	Programme-ahead to allow job to be initiated while initial job is processed (Copy, Print, Fax and Scan)		
Copy Features	Annotation and Bates™ stamping (with colour capability and font size adjustment) Authentication for Services Auto Paper Select Auto Reduction & Enlargement to fit selected paper size Auto Tray Switching Automatic 2-sided / Duplex Booklet Creation Build Job: (Enables page-level programming and also lets you proof each section or delete last section as the job is built) Collation Covers (Front only, front and back, back only, printed inside and out: Blank or Printed) Dividers (blank) Edge Erase Features Help (Intuitive text and graphic descriptions) ID Card Copy Image Quality Adjustments Image Shift (with Auto Centre option) Invert Image (negative or mirror image) Large Job Interrupt Multi-up (up to 15 columns by 15 rows) Sample Set Save Job Settings Stapling Transparencies		
Xerox® Copier Assistαnt®	Xerox® Copier Assistant® Software provides a PC-based alternative to the user interface touch screen. Used in conjunction with a customer-supplied PC attached via the USB port, this software supports text-to-speech, screen magnification and easy PC keyboard access to basic and advanced copy features. Section 508 compliant. For more information or to download Xerox® Copier Assistant for free, visit www.xerox.com		

Print	
First-print-out Time	As fast as 7 seconds
Print Resolution	Up to 4800 x 600, 256 shades of grey, 1200 x 1200 emulation
Print Features	Application Defaults Banner Sheet Enable / Disable Bidirectional Status Cover Selection Delay Print (specific time) User Permissions Image Options (Toner Saver, Resolution (Standard, Enhanced, High) Job Identification (Print ID or Banner, Print ID in margins on first page only or all pages) LAN Fax (requires optional Fax Kit) Layout / Watermark (N-up (up to 16 pages per sheet), Multi-up, Booklet layout / finishing, Fit to new paper size) Overlays Paper Selection by Attribute Sample Set Saved Job Secure Print with Timed Deletion Special Pages (exception page programming: covers, inserts, exception pages) Store and Recall Driver Settings Sustainability Features (Xerox® Earth Smart Settings, Duplex, N-up, Turn-off Banner and Print ID, Smart Sample Set, Hold All Jobs) TWAIN Support
Print from USB	Allows walk-up printing from Type A USB port on front panel Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TIFF, PS, XPS, PCL
Operating Systems	Microsoft® Windows® XP (32- and 64-bit) Windows Server 2003 (32- and 64-bit) Windows Server 2012 Windows Vista (32- and 64-bit) Windows 7 (32- and 64-bit) Windows 8 (32- and 64-bit) Windows 8 (32- and 64-bit) Windows 8 (32- and 64-bit) Windows 8.1 (32- and 64-bit) Windows 8.1 (32- and 64-bit) Mac OS 10.5, 10.6, 10.7, 10.8 PowerPC AIX 5 Solaris® 9, 10 Solaris SPARC 10 HP-UX® 11v2 IBM® AIX® 5 Redhat® Fedora® Core 15-17, 19 x86 Redhat Enterprise 4 and 5 openSUSE® 11 and 12 Ubuntu® 12, 10 x64 Itanium HP-UX 11i v3 Unix®
Network Protocols	TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6,WSD NetWare: Bindery and NDS IPX/SPX, NDPS®/NEPS (with Server Gateway) AppleTalk®: EtherTalk® Microsoft Windows Networking over IP Apple® Bonjour® IPv6 Secure FTP Most protocols not in use can be disabled
Administrative Protocols	DHCP, BOOTP, SNMP, WINS, SLP® v2, HTTP, HTTPS, DHCP Autonet, SSL, NTP, DNS, SSDP
Fonts	PCL: 93 scalable fonts, line printer and bitmap font (including Cyrillic font support) PostScript 3: 173 Type 1 fonts, 2 Multiple Master fonts
Xerox® Mobile Express Driver®	Makes it easy for mobile users to find, use and manage Xerox® and non-Xerox devices in every new location. Plug into a new network, and Mobile Express Driver automatically discovers available printers and provides status and capability information. Save a list of "favourite" printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT.
Xerox® Global Print Driver®	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.
Xerox® Pull Print Driver	Makes it easy for IT managers to qualify, deploy and manage all print devices using a single driver in a Pull Print environment. Uses a single queue and single driver. The Xerox® Pull Print Driver extends convenience across a broad range of printing assets. IT administrators no longer need to manage and configure multiple drivers. Used in conjunction with Xerox Secure Access Unified ID System®, Equitrac Office®, Ysoft® SafeQ®, Pharos® and others.

Print Solutions	
Xerox® Mobile Print Cloud (Optional)	Xerox® Mobile Print Cloud addresses the needs of businesses with a mobile workforce and puts you ahead of the evolving mobile print need, but without burdening staff, budget or infrastructure. Getting started takes only a few minutes via the cloud. Print from any mobile device to nearly any brand of printer. Accurate printing with true Microsoft® Office® rendering and more. Print what you need, when, where and how you need it.
Xerox® Mobile Print Solution (Optional)	Xerox® Mobile Print Solution is an ideal choice for sites that have additional requirements for control and security with an onsite server. Xerox® Mobile Print Solution allows users to print from most mobile devices to nearly any brand of printer or multifunction printer without drivers or added complexity. Simply enter a release code (PIN) at the device and get accurate printing with true Microsoft Office rendering and more to use with your server for private, onsite deployment.
Unified Address Book for Fax, Inte	ernet Fax, Email and Scan to
Features	Services supported: Fax, Internet Fax, Email, Scan to Maximum contacts: 5,000 Contacts: Supports 1 or more destinations Favourites for quick access of fax numbers, emails, etc.
Scan	
Concurrency	Scan while the system is printing, copying, or while it is transferring scan to network or fax jobs (priority is for return of scanned originals and printing concurrent jobs)
Input Speed	Scan at up to 200 ipm colour scanning and black and white – 8.5 x 11 in. / A4 LEF
Resolution	72 x 72 dpi to 600 x 600 dpi Bit Depth: 1-bit (black and white), 8-bit (greyscale), 24-bit (colour)
Maximum Scan Area	11 x 17 in. / A3
Scan Template Management	Support 250 scan templates Create Xerox® CentreWare® IS scan templates and share via device cloning to other multifunction printers Confirmation sheet options
Network Protocols	sFTP, FTP, SMB, NetWare, HTTP, HTTPS
File Formats	Colour TIFF (TIFF 6.0 or TTN2 with JPEG, LZW) Black and white TIFF (G3MH, G4 MMR compression—single or multiple pages) Searchable PDF and PDF/A (MRC, JPEG, G3 MH, G4 MMR, JBIG 2 Huffman, JBIG Arithmetic Compression, Deflate (for Black and white and within MRC)) JPEG XPS Encrypted / Password Protected PDF (Network Scan Templates only) Linearised PDF
Document Management Fields (Meta Data)	Features only available in Network Scan to File Templates: • 1 to 6 user programmable metadata fields per network scan to file templates and unlimited fields within the template – Metadata field consists of field name, default value and other configurations • Customised fields viewed on user interface for variable data input
Scan Features	Mixed Size Originals Scan Build Job Compression Quality / File Size Control Original Type (Photo and Text, Photo, Text, Map, Newspaper / Magazine) Auto Background and Shadow Suppression Size for Size (for mixed size originals) TWAIN Support Bound Originals Edge Erase Reduction / Enlargement Single Touch Scan buttons (up to 10)
Supported Scan Destinations (Standard)	Local Scan to USB Drive Scan to Mailbox Remote Scan to Email Scan to Email Scan to FTP and HTTPS Scan to Home Scan to Application
Supported Scan Destinations (Optional)	Xerox® Scan to PC Desktop® (Professional and SE) ScanFlowStore® Xerox® ConnectKey® for SharePoint® Xerox® ConnectKey® for DocuShare® Xerox® ConnectKey® Share to Cloud Various Xerox Alliance Partner Solutions

Authentication	Supports Kerberos (UNIX / Windows Server) SMB (Windows Server) NDS LDAP Xerox Secure Access Unified ID System® Locally on device (internal database) Convenience Authentication via Magstripe, Proximity and Smart Card (CAC/PIV/.NET) readers (optional)
Scan to Email (Standard)	
Scan Features	Email signatures (6 lines each of 128 character max), email message body (user configurable), email CentreWare IS confirmation sheet options Scan to Email S/MIME Encryption Email signing (requires Smart Card option) Auto send to self
Directory Access	Address list via LDAP (Windows Active Directory, Exchange, Notes, Domino) Downloaded address list (comma-separated file format)
Scan to (Standard)	
Features	Scan to USB Scan to Network Folder (uses Unified Address Book entries)
Network Scanning – Software Sol	utions
Xerox® Scan to PC Desktop® Professional (Optional)	A desktop offering that provides advanced document imaging, archiving, editing and organisation tools: • PaperPort Professional image viewing and file management software — Complete PDF functionality — Secure PDF workflow of all scanning applications • OmniPage Pro Office (for desktop/client installation) — Professional OCR software for digital archiving and document conversion • Image Retriever — provides fully automated retrieval of scanned images direct from a scan enabled Xerox® WorkCentre to individual desktops. Also includes email inbox polling capability
Xerox® ConnectKey® for SharePoint® (Optional)	Xerox® ConnectKey for SharePoint simplifies and streamlines the way you scan, capture and store your paper-based documents. Using your Xerox® multifunction printer, you can route documents directly into the precise document repository folder, just like you would from your PC. At the multifunction printer, you can browse to the folder, name the document, and add any key indexing information before you scan. With the flexibility to capture and route to SharePoint as well as Windows folders, ConnectKey is the right solution for any office that needs to archive and share paper-based documents.
Xerox® ConnectKey® Share to Cloud (Optional)	Xerox® ConnectKey Share to Cloud provides organisations with powerful, easy and secure document scanning capabilities that connect your Xerox® multifunction printer to popular cloud services and email, such as Google Docs™, SalesForce.com, Office 365 and Dropbox™ and gives employees anytime, anywhere access to their most important documents using mobile devices.
Xerox [®] ConnectKey [®] for DocuShare [®] (Optional)	Xerox® ConnectKey for DocuShare, a one-step scan-to-workflow solution, simplifies the process of incorporating hard copy content into enterprise document flows. Users can easily scan documents directly into a DocuShare collection or Windows folder via a multifunction printer.
Security	
Features	Expanded Authentication Network authentication to access device and/or device services via- Kerberos (UNIX / Windows Server 2003 / Windows Server 2008), SMB (Windows Server 2003 / Windows Server 2008), NDS, LDAP Xerox Secure Access Unified ID System® Local Authentication (internal database) Smart Card authentication -144k CAC / PIV Card Support (2048 bit certificate key) / .NET Secure Data Digitally signed PDF (when using Smart Card authentication) Encrypted Scan to Email Encrypted / Password Protected PDF (when using Network Scan Templates only) Secure Print (up to 10 digit PIN or Network Authentication) Immediate Image Overwrite On Demand Image Overwrite (Scheduled, Manual), includes sanitation of unused area of disk FIPS 140-2 256 bit Hard Disk Encryption Expanded Authorisation SA access based on network credentials Authorisation per user per service User Permissions required to access Print and Print Features (e.g. colour access, or time restrictions) reflects in the print driver Secure Network Access IP Filter, IPsec, IPv6, SSL v3.0, SNMPv3, HTTPS, 802.1X, Cisco® TrustSec integration, Device Security McAfee® Embedded Security, Port disablement including USB ports, Audit Log, Hide Print Job Names, McAfee Integrity Control (optional) Common Criteria Certification ISO 15408
Xerox Secure Access Unified ID System® (Optional)	Xerox Secure Access Unified ID System integrates your Xerox® multifunction systems with your existing employee/student ID PIN or badge providing a flexible and convenient authentication system. Allow your staff, employees or students to send documents to a centralised print server. Then, at any multifunction printer on the network, they'll simply log in with a swipe of their magnetic or proximity ID card or their PIN to securely print their job. For more information, go to www.office.xerox.com/software-solutions

Fax	
Network Server Fax Features	
Compatibility	ITU (CCITT) group 3 Various Xerox Alliance Partner Solutions
Maximum Scan Area	11 x 17 in. / A3
Fax Send Features	One- or Two-sided Scanning (up to 11 x 17 in. / A3) Add to Send List (50 numbers maximum) Build Job, Favourites, Delay Send (specific time) Original Type (photo, text or photo and text)
Fax Print Features	One- or Two-sided Printing, Staple, Secure Print
Transmission Resolution	Superfine: 400 x 200 dpi (Scan at 600 x 600 dpi) Fine: 200 x 200 dpi Standard: 200 x 100 dpi
Internet Fax Features	
Capability	Direct print-ready document transmission to remote Internet Fax machines or email clients (SMTP) Reception and automatic printout of documents sent via email from remote Internet Fax machines or email clients
Directory Access	Utilises the Unified Address Book
Send / Receive	Multi-page TIFF, Image only PDF
Resolution	72 x 72 dpi to 600 x 600 dpi Bit Depth: 1-bit (black and white)
Network Protocols	SMTP (send), POP3 (receive)
Compliance	ITU-T T.37 compliant
Walk-up Fax Features (Optional (Co	ustomer-installable) – 1 and 2 lines)
Compatibility	ITU (CCITT) Group 3
Speed / Modems	One or Two V.34 moderns: 33,600 bps. Less than 4 seconds per page transmission time ATA analog terminal adapter utilising T38 (optional)
Compression / Speed	MH/G3, MMR/SG3
Resolution	Walkup Send: Standard: 200 x 100 dpi Fine: 200 x 200 dpi Superfine: 600 x 600 dpi Receive: Accepts all sizes
Fax Send Features	LAN Fax (fax from print driver) Auto Fax Transmission Reduction Page-by-page Job Status at the Machine Delay Start, Build Job, Favourites Automatic Memory Resend Automatic Cover Sheets PSTN Fax Batch Send (up to memory capacity)
Fax Receive Features	One- or Two-sided Printing Stapled or Unstapled Receive Print Mode – Manual (size, margin, stock, header) / Auto Output Tray Selection Up to 200 Password Protected Mailboxes Secure Receive
	Receive Timestamp Auto Answer Delay
Fax Forward	· ·
Fax Forward Fax Reports	Auto Answer Delay Forward to Email or SMB Location
	Auto Answer Delay Forward to Email or SMB Location Fax Forward on Receive Only Activity, Dial Directory, Group Directory, Transmission Confirmation, Pending Fax, Options Report, On Demand Overwrite Report, Mailbox Report,
Fax Reports	Auto Answer Delay Forward to Email or SMB Location Fax Forward on Receive Only Activity, Dial Directory, Group Directory, Transmission Confirmation, Pending Fax, Options Report, On Demand Overwrite Report, Mailbox Report, Broadcast Report Utilises the Unified Address Book

Device Management	
Management Support	SNMP Version 1. SNMP Version 2c and SNMP Version 3 trap over TCP/IP and IP
Munugement Support	MIB access (IETF-MIBII RFC 1213), Host Resources MIB RFC 2790, Printer MIB RFC 1759 v.2
Xerox® CentreWare® Web	A Web-based server application for network administrators that permits Web browser-based device management from any workstation, whether running Windows, UNIX or any other operating system: • Works with any SNMP-managed printer from any manufacturer. • Provides help with device discovery and installation, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management. • Requires Windows XP, Vista or Windows 7 and Internet Explorer 6.0 and higher. • CentreWare Integration available for Tivoli® NetView®, Unicentre TNG®, Microsoft Management Console (MMC), HP® OpenView®
Novell NDPS/NEPS	Server gateway application: centralised management tool.
Xerox® Device Manager	Xerox® Device Manager collects and manages the data that drives fact-based decisions for your enterprise device management environment. It is a single tool to install print queues and configure, manage, monitor and report on both networked and locally connected devices – regardless of vendor – across your enterprise. Xerox® Device Manager provides: • Device monitoring and troubleshooting • Extensive reporting and discovery of new devices • Usage collection, chargeback and billing capabilities
Xerox® Device Types for SAP Environment	Xerox, together with SAP through our Gold-level membership in the SAP Printer Vendor Programme, provides seamless connectivity between SAP systems and your Xerox® printers and multifunction printers. And as an SAP customer you benefit from having SAP-certified Xerox® device types available right from SAP's online delivery model. SAP-certified device types for Xerox® printers and multifunction printers are available to download. www.office.xerox.com/software-solutions
Xerox® Device Types for SAP R/3 Intelligent Barcode Utility (optional)	Provides built-in process intelligence that allows the printing of barcodes on any appropriately configured PostScript printer in specific versions of SAPenvironment and within Latin-1 (ISO8859-1) SAP system code pages only. Used in conjunction with Xerox® PostScript Device Types for SAP environment and Xerox® Font Centre Barcode Fonts. Information available at www.office.xerox.com/software-solutions
Xerox® Barcode Pro PS (optional)	Enables intelligent PostScript printing on Xerox® multifunction systems by storing Xerox® software, as well as, the barcode fonts on the printer hard disk. Enables the printing of barcodes from any application (SAP client or mainframe) that supports PostScript printing. Information available at www.office.xerox.com/software-solutions
CentreWare Internet Services – Int	regrated Web Pages Provided by the Device
Device Status	Web server embedded in Network Controller: Tray status/contents Consumables status Alerts Remote Control Panel
Job Submission	Print ready files: PS, PCL, TIFF, PDF, JPG, XPS, TXT, RRN Output feature selection (2-sided, output colour, collate, orientation, staple, hole punch, folding, output destination) Delivery options (Immediate, sample set, delay and secure, Save job or reprint)
Device Administration	Allows simple, remote installation setting of configuration options and management of the device
Browsers	Internet Explorer 7.x, 8.x, 9.x Safari 5.x Mozilla Firefox 4.x, 5.x, 6.x, 7.x, 8.x, 9.x, 10.x, 11.x Opera 11.x Chrome 12
Support	Install print / scan drivers and online support available via web page
Languages Supported	International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish or Russian, Simplified Chinese, Korean, Japanese
Remote Print Services	
Automatic Meter Reading (AMR)	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.
Automatic Supplies Replacement (ASR)	Automatically orders supplies for Xerox® output devices based on actual usage, eliminating the need to manually manage supplies inventory (may not be available in all countries).
Accounting	
Xerox® Standard Accounting (Stand	dard)
Tracking	Copy, Print, Fax, Scan and Email usage
Accounting	Up to 2,497 User accounts (User ID) Up to 500 General accounts (Client) Up to 498 Group accounts (Department)
Features	 Administrator can manage the feature via the Web User Interface or device control panel in tools Administrator has the ability to import or export user accounts, Group Accounts, General Accounts and User limits via an industry standard CSV file

Xerox® WorkCentre™ 5845/5855

Accounting Options – Network Accounting – Third Party Enablement • Enhanced network accounting with up to the minute data on how the system is being used • Comprehensive management and enterprise scale tracking and reporting of device usage of copy, print, scan and server fax • Numerous solutions are available through Xerox Alliance Partners. For details visit www.xerox.com • Security enhancements with the addition of HTTPS protocol support • Device requests account authentication from third party server enabling larger databases of users and accounts • Accept Authentication Login at control panel and pass to third party Networking Account • Interface with third party accounting terminal for accounting user interface **Supplies** Quantity Part Number Toner Cartridge Includes 2 Toner Cartridges and Waste Toner Bottle 006R01551 76,000 pages⁴ (38,000 pages each)4 008R12896 **Waste Toner Bottle** Supplied with each Toner Cartridge Box 100,000 pages4 **Staple Cartridges** Basic Office Finisher – Complete Cartridge 3,000 per cartridge 108R00682 108R00535 - Refill Cartridge 3,000 per cartridge (9,000 staples) Office Finisher 5,000 per cartridge 108R00493 (15,000 staples) Office Finisher with Booklet Maker 108R00493 5,000 per cartridge (15,000 staples) Office Finisher with Booklet Maker – saddle-stitch stapling 2,000 per cartridge 108R01158 (8,000 staples) HVF and HVF with Booklet Maker 008R12912 - Complete Cartridge 5,000 per cartridge 008R12898 - Refill Cartridge 5,000 per cartridge (15,000 staples) 008R12897 HVF with Booklet Maker – saddle-stitch stapling 2.000 per cartridae (16,000 staples) Convenience Stapler 008R12964 Complete Cartridae 5,000 per cartridge – Refill Cartridge 5,000 per cartridge 008R12941 (15 000 staples) Xerox® SmartKit® Fuser Module Includes Ozone Filter 400.0004 109R00751 50 Hz 60 Hz 400,0004 109R00752 Xerographic Module - Sold 450,0004 113R00674

Document Handler

Feeder Rolls

Return spent imaging supplies through the Xerox Green World Alliance collection/reuse/recycling programme. For more information, visit www.xerox.com/about-xerox/recycling.

For more information, visit us at www.xerox.com/office.



113R00718

150,000 feeds

Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

² Expected regular monthly throughput.

³ Paper capacities are based on 20 lb. / 75 gsm stock; capacities will vary with different weight stocks.

[&]quot;Approximate pages. Declared Yield based on 5 page job size, 6% area coverage, using letter-/ A4-size media. Yield will vary based on media size, image area coverage, media orientation and usage patterns.