

# Xerox® WorkCentre™ 5845/5855 Multifunction System

WorkCentre 5800 series multifunction systems are powered by the Xerox® ConnectKey® Controller. These simple-to-implement systems give you real, practical solutions that easily streamline how you communicate, process and share important information, simplify complex paper-driven tasks and drive down costs while keeping your data secure.



	(3643 Offity)	• • • • • • • • • • • • • • • • • • • •	
System Specifications	WorkCentre 5845	WorkCentre 5855	
Speed A4 (LEF) A4 to B4 (SEF) A3 (A3 SEF) (Bypass Tray will reduce speed by 10 to 20%)	45 ppm 36 ppm 31 ppm	55 ppm 36 ppm 31 ppm	
Monthly Duty Cycle <sup>1</sup>	Up to 175,000 pages	Up to 200,000 pages	
Recommended Average Monthly Print Volume <sup>2</sup>	Up to 20,000 pages		
Hard Drive / Processor / Memory	160 GB / 1 GHz Dual-core / 2 GB system		
Connectivity	10/100/1000Base-T Ethernet, High-Speed USB 2.0 direct print, Optional Wi-Fi (with Wireless Connectivity Kit)		
Controller Features	Unified Address Book, Remote Control Panel, Online Support, Configuration Cloning		
Copy and Print			
First-print-out Time	As fast as 3.7 seconds		
First-copy-out Time	3.7 seconds from the Platen / 7.6 seconds from the Single-pass Automatic Document Feeder		
Copy and Print Resolution	<b>Copy:</b> Up to 600 x 600 dpi; <b>Print:</b> Up to 4800 x 600, 256 shades of grey, 1200 x 1200 emulation		
Page Description Languages	Adobe® PostScript® 3™, PDF, PCL® 5c / PCL 6, XML Paper Specification XPS (Optional)		
Print Features	Print from USB, Earth Smart Driver Settings, Job Identification, Booklet Creation, Store and Recall Driver Settings, Bidirectional Real-time Status, Scaling, Job Monitoring		
Mobile Printing	AirPrint, Xerox® Mobile Print® (Optional), Xerox® Mobile Print Cloud® (Optional)		
Scan			
Standard Features	Scan to Network, Scan to Email, Scan to Folder, Scan to SMB or FTP, Text Searchable PDF, PDF/A, XPS, Linearised PDF, JPEG, TIFF, Scan to USB Memory Device, Single-touch Scanning, TWAIN Support		
Optional Features	ConnectKey for SharePoint®, ConnectKey Share to Cloud, Xerox® Scan to PC Desktop® SE, Xerox® Scan to PC Desktop Professional, Numerous solutions available through various Xerox® Alliance Partners		
Fax			
Standard Features	Internet Fax, Fax Build Job, Network Server Fax Enablement (solutions available through various Xerox® Alliance Partners)		
Optional Features	Fax Forward to Email or SMB, Walk-up Fax (one-line and two-line options, includes LAN Fax),		

Security			
Standard Features	McAfee® Embedded, McAfee (ePO) Compatible, HDD Overwrite, 256-bit Encryption (FIPS 140-2 compliant), Common Criteria Certification (ISO 15408), Secure Print with Timed Deletion, Secure Fax, Secure Scan, Secure Email, Cisco® TrustSec Identity Services Engine (ISE) Integration, Network Authentication, SSL, SNMPv3, Audit Log, Access Controls, User Permissions		
Optional Features	McAfee Integrity Control, Smart Card Enablement Kit (CAC/PIV, .NET), Xerox Secure Access Unified ID System® with Follow-You Printing®		
Accounting			
Standard Features	Xerox® Standard Accounting (Copy, Print, Scar	n, Fax, Email)	
Optional Features	Equitrac Office®, Equitrac Professional®, YSoft® various Xerox® Alliance Partners	SafeQ®, other network accounting solutions available through	
Device Specifications			
Control Panel Languages		French, Italian, German, International Spanish, Dutch, Brazilian n, Turkish, Greek, Russian, Czech, Polish, Hungarian or Romanian, Catalan	
Accessories			
Optional	High Capacity Feeder (HCF) HCF Kit (A4 SEF) (HCF required) HCF Kit (A3 SEF) (HCF required) Envelope Tray (Replaces Tray 2) Basic Office Finisher (optional with 5845 only) Office Finisher Office Finisher with Booklet Maker Hole Punch for Office Finisher High Volume Finisher High Volume Finisher with Booklet Maker Z Fold / C Fold Unit (with High Volume Finishe Post Process Inserter (with High Volume Finish Convenience Stapler Work Surface Smart Card Enablement Kit Xerox Secure Access Unified ID System® (USB Walk up Fax (One- or Two-line options, include ScanFlowStore® Wireless Connectivity Kit McAfee® Integrity Control Enablement Kit XPS Print Option Kit	r with Booklet Maker) er with Booklet Maker) Card Reader) with Follow-You Printing®	
Foreign Device Interface (FDI) (Optional)	Also known as Auxiliary Access Device, this is a machines and card readers.	an interface to third party access control devices, such as coin	
Electrical Requirements	machines and cara reducis.		
	Voltage: 220-240 VAC +/- 10 % Frequency: 50/60 Hz +/- 5 %, 12 A		
Power Consumption	WorkCentre 5845	WorkCentre 5855	
Running (Average)	1,150 watts	1,250 watts	
Standby Mode	290 watts		
Low Power Mode	≤125 watts		
Sleep mode	<4 watts		
Ready to Scan and Print (from Power On)	<230 seconds (3 minutes, 50 seconds)		
Recovery from Low Power	<4 seconds		
Recovery from Sleep	<28 seconds		
Operating Environment			
Required Temperature Range	10° to 32° C		
Required Relative Humidity	15% to 85%		
Sound Power Levels	Operating 7.1 B(A), Standby: 5.0 B(A)		
Sound Pressure Levels	Operating: 56 dB(A), Standby: 35 dB(A)		

Dimensions and Weight	Width	Depth	Height	Weight
Base Configuration with OCT	990 mm	650 mm	1,104 mm	123.3 kg
With Basic Office Finisher (5845 only)	1,209 mm	650 mm	1,104 mm	145 kg
With Office Finisher	1,209 mm	650 mm	1,104 mm	149.5 kg
With Office Finisher with Booklet Maker	1,209 mm	650 mm	1,104 mm	165.5 kg
With High Volume Finisher	1,645 mm	650 mm	1,145 mm	192.8 kg
With High Volume Finisher with Booklet Maker, C Fold / Z Fold Unit and Post Process Inserter	1,995 mm	650 mm	1,180 mm	220.3 kg
High Capacity Feeder	389 mm	510 mm	510 mm	30 kg
Work Surface (Does not add to overall width if combined with High Capacity Feeder)	285 mm	-	-	-

#### Certifications

FCC Class A Compliant (US), ICES Class A Compliant (Canada)

CSA Listed (UL 60950-1, Second Edition) CB Certified (IEC 60950-1, Second Edition)

**ENERGY STAR®** 

GOST NOM

Environmental Choice

CE Marked

Common Criteria (ISO 15408) (pending)

EPEAT
GS Mark
Citrix® Certified
WHQL
MEDITECH

Cerner

To view the latest list of certifications, go to www.xerox.com/OfficeCertifications.

Paper Handling			
Single-pass Automatic Doc	Single-pass Automatic Document Feeder		
Capacity <sup>3</sup>	200 sheets		
Speed (black and white and colour)	Up to 105 images per minute (ipm) (simplex) Up to 200 ipm (duplex)		
Paper Sizes Sensed	125 x 138 mm to 297 x 432 mm		
Weights	50 gsm to 160 gsm		
Bypass Tray			
Capacity <sup>3</sup>	100 sheets		
Sizes	Custom sizes: A6 to A3		
Weights	60 to 216 gsm		
Types	Bond Carbonless Card Stock Envelopes Hole punched Index Labels Letterhead Plain Preprinted Recycled Transparencies Tabs		

Trays 1 and 2	
Capacity <sup>3</sup>	500 sheets each
Sizes	Custom Sizes from A5 LEF to A3 SEF
Weights	60 to 200 gsm
Types	Bond Card Stock Glossy Hole punched Index Labels Letterhead Lightweight Card Stock Plain Preprinted Recycled Tabs
High Capacity Tandem Tro	ду
Capacity <sup>3</sup>	Tray 3: 1,600 sheets Tray 4: 2,000 sheets
Sizes	Standard Sizes: A4 LEF
Weights	60 to 216 gsm
Types	Bond Card Stock Glossy Hole punched Index Letterhead Lightweight Card Stock Plain Preprinted Recycled
High Capacity Feeder (HC	F) (Optional)
Capacity <sup>3</sup>	4,000 sheets Optional HCF Kits: 2,000 sheets with A4 HCF Kit or 2,000 sheets with A3 SEF HCF Kit (Optional)
Sizes	A4 LEF Optional HCF Kits: A4/A3
Weights	60 to 216 gsm
Types	Bond Card Stock Hole punched Index Letterhead Plain Preprinted Recycled
Envelope Tray (Optional –	
Capacity <sup>3</sup>	Up to 50 envelopes
Sizes	DL, C5
Weights	75 to 90 gsm
Total Capacity	
Device Total Capacity <sup>3</sup>	8,700 sheets

Finishing	
	ntional)
Offset Catch Tray (OCT) (O	
Capacity  Basic Office Finisher (Option	Up to 300 sheets of 80 gsm
Top Tray Capacity	250 sheets of 80 qsm
Stacking Tray Capacity	1,000 sheets of 80 gsm
Top Tray Sizes Stacking Tray Sizes	A6 to A3 A5 to A3
Weights	60 to 216 gsm
Stapling	Single Auto stapling:30 sheets maximum: A4 / B5 sheets (less than 90 gsm or (2) 220 gsm covers) 30 sheets maximum: A3 / B4 sheets (less than 90 gsm or (2) 220 gsm covers)
Office Finisher (Optional)	
Top Tray Capacity Stacking Tray Capacity	250 sheets unstapled of 80 gsm 2,000 sheets unstapled of 80 gsm or 1,000 sheets single stapled or 750 sheets dual stapled (A4)
Top Tray Sizes Stacking Tray Sizes	A6 to A3 A5 to A3
Weights	60 to 216 gsm
Multiposition Stapling	50 sheets of 80 gsm
Hole Punch (Optional)	2-4 Hole Punch
Office Finisher with Bookle	t Maker (Optional)
Top Tray Capacity Stacking Tray Capacity	250 sheets unstapled of 80 gsm 2,000 sheets unstapled of 80 gsm or 1,000 sheets single stapled or 750 sheets dual stapled (A4)
Top Tray Sizes Stacking Tray Sizes	A6 to A3 A5 to A3
Weights	60 to 216 gsm
Multiposition Stapling	50 sheets of 80 gsm
Hole Punch (Optional)	2-4 Hole Punch
Booklet Making Capacity <sup>3</sup>	40 booklets (2-15 sheets per booklet – 80 gsm or less)
Booklet Making Sizes	A4 SEF B4 SEF A3 SEF
Saddle-stitch Stapling	2-15 sheets / 8-60 page booklet 60 to 90 gsm
Score / Crease	1-15 sheets / unstapled
High Volume Finisher (HVF	(Optional)
Capacity <sup>3</sup>	Top Tray – 250 sheets Stacking Tray – 3,000 sheets
Sizes	A6 to A3 / 105 x 148 mm to 297 x 420 mm
Weights	60 to 216 gsm
Stapling <sup>3</sup>	100 sheets Single (any corner), dual, front, rear, SEF and 4-stitch
Hole Punch (Optionαl)	2-hole punch 4-hole punch and 4-hole "Swedish" punch
High Volume Finisher with	Booklet Maker
Capacity <sup>3</sup>	Top Tray – 250 sheets Stacking Tray – 3,000 sheets
Sizes	A6 to A3 / 105 x 148 mm to 297 x 420 mm
Weights	60 to 216 gsm
Stapling <sup>3</sup>	100 sheets Single (any corner), dual, front, rear, SEF and 4-stitch
Hole Punch (Optional)	2-hole punch 4-hole punch and 4-hole "Swedish" punch

Booklet Maker Capacity³	Tray stop up: 30 booklets (1-15 sheets per booklet) Tray stop down: Unlimited
Booklet Maker Sizes	A4 / 210 x 297 mm 216 x 356 mm A3 / 297 x 420 mm
Booklet Maker Weights	60 to 216 gsm
Saddle-stitch Stapling <sup>3</sup>	Saddle-stitch (2-15 sheets / 8-60 page booklet)
Folding	V-folding (1-15 sheets / unstapled)
Z Fold / C Fold Unit with H	VF with Booklet Maker
Capacity <sup>3</sup>	50 sheets or unlimited capacity with tray stop in the down position
Sizes	A4 / 210 x 297 mm
Weights	60 to 216 gsm
-	onal with HVF and HVF with Booklet Maker)
Capacity <sup>3</sup>	250 sheets
Sizes	A4 / 210 x 297 mm 216 x 356 mm A3 / 297 x 420 mm
Weights	60 to 216 gsm
Convenience Stapler (Option	onal – recommend use with optional Work Surface)
Capacity <sup>3</sup>	50-sheet stapling 5,000 staples Requires a separate outlet
Сору	
First-copy-out Time	3.7 seconds from the Platen / 7.6 seconds from the Single-pass Automatic Document Feeder
Sides (input:output)	1-1, 1-2, 2-2, 2-1
Quantity	1 to 9,999
Resolution (max.)	Up to 600 x 600 dpi
Reduction / Enlargement	Variable zoom from 25% to 400% in 1% increments
Concurrency	Programme-ahead to allow job to be initiated while initial job is processed (Copy, Print, Fax and Scan)
Copy Features	Annotation and Bates™ stamping (with colour capability and font size adjustment) Authentication for Services Auto Paper Select Auto Reduction & Enlargement to fit selected paper size Auto Tray Switching Automatic 2-sided/Duplex Booklet Creation Build Job: (Enables page-level programming and also lets you proof each section or delete last section as the job is built) Collation Covers (Front only, front and back, back only, printed inside and out: Blank or Printed) Dividers (blank) Edge Erase Features Help (Intuitive text and graphic descriptions) ID Card Copy Image Quality Adjustments Image Shift (with Auto Centre option) Invert Image (negative or mirror image) Large Job Interrupt Multi-up (up to 15 columns by 15 rows) Sample Set Save Job Settings Stapling
Xerox® Copier Assistant®	Transparencies  Xerox® Copier Assistant® (XCA) Software provides a PC-based alternative to the user interface touch screen. Used in conjunction with a customer-supplied PC attached via the USB port, this software supports text-to-speech, screen magnification and easy PC keyboard access to basic and advanced copy features. Section 508 compliant. For more informationor to download Xerox® Copier Assistant for free, visit <a href="https://www.xerox.com">www.xerox.com</a>

Print First print out Time	As fast as 7 seconds
First-print-out Time	As fast as 7 seconds
Print Resolution	Up to 4800 x 600, 256 shades of grey, 1200 x 1200 emulation
Print Features	Application Defaults Banner Sheet Enable / Disable Bidirectional Real-time Status Cover Selection Delay Print (specific time) User Permissions Image Options (Toner Saver, Resolution (Standard, High, Enhanced)) Job Identification (Print ID or Banner, Print ID in margins on first page only or all pages) Layout / Watermark (N-up), (up to 16 pages per sheet), Multi-up, Booklet layout / finishing, Fit to new paper size Overlays Paper Selection by Attribute LAN Fax (requires optional Fax Kit) Sample Set Secure Print with Timed Deletion Special Pages (exception page programming: covers, inserts, exception pages) Store and Recall Driver Settings Saved Job Sustainability Features (Xerox® Earth Smart Settings, Duplex, N-up, Turn-off Banner and Print ID, Smart Sample Se Hold All Jobs) TWAIN Print Driver
Print from USB	Allows walk-up printing from Type A USB port on front panel Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TXT
Operating Systems	Microsoft® Windows® XP (32- and 64-bit) Windows Server 2003 (32- and 64-bit) Windows Server 2008 (32- and 64-bit) Windows Server 2012 Windows Vista (32- and 64-bit) Windows 7 (32- and 64-bit) Windows 8 (32- and 64-bit) Mindows 8 (32- and 64-bit) Mac OS® 10.5, 10.6, 10.7, 10.8 Solaris 9, 10 HP UX 11v2 IBM® AIX® 5 Redhat® Fedora Core 15-17 Redhat Enterprise 4 and 5 openSUSE® 11 and 12 Ubuntu® Unix®
Network Protocols	TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6,WSD NetWare: Bindery and NDS IPX/SPX, NDPS®/NEPS (with Server Gateway) AppleTalk®: EtherTalk® Microsoft Windows Networking over IP Bonjour® IPv6 Secure FTP Most protocols not in use can be disabled
Administrative Protocols	DHCP, BOOTP, SNMP, WINS, SLP® v2, HTTPS, HTTP, DHCP Autonet, SSL, NTP, DNS, SSDP
Fonts	PCL: 93 scalable fonts, line printer and bitmap font (including Cyrillic font support) PostScript 3: 173 Type 1 fonts, 2 Multiple Master fonts
Xerox® Mobile Express Driver® (X-MED)	Makes it easy for mobile users to find, use and manage Xerox® and non-Xerox devices in every new location. Plug into a new network, and X-MED automatically discovers available printers and provides status and capability information. Save a list of "favourite" printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT.
Xerox® Global Print Driver®	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.
Xerox® Pull Print Driver	Makes it easy for IT managers to qualify, deploy and manage all print devices using a single driver in a Pull Print environment. Uses a single queue and single driver. The Xerox® Pull Print Driver extends convenience across a broad range of printing assets. IT administrators no longer need to manage and configure multiple drivers. Used i conjunction with Xerox Secure Access Unified ID System®, Equitrac Office®, Ysoft® SafeQ®, Pharos® and others.

Print Solutions		
Xerox® Mobile Print Cloud (Optional)	Xerox® Mobile Print Cloud addresses the needs of businesses with a mobile workforce and puts you ahead of the evolving mobile print need, but without burdening staff, budget or infrastructure. Getting started takes only a few minutes via the cloud. Print from any mobile device to nearly any brand of printer. Accurate printing with true Microsoft® Office® rendering and more. Print what you need, when, where and how you need it.	
Xerox® Mobile Print Solution (Optional)	Xerox® Mobile Print Solution is an ideal choice for sites that have additional requirements for control and security with an onsite server. Xerox® Mobile Print Solution allows users to print from most mobile devices to nearly any brand of printer or multifunction system without drivers or added complexity. Simply enter a release code (PIN) at the device and get accurate printing with true Microsoft Office rendering and more to use with your server for private, onsite deployment.	
Scan		
Concurrency	Scan while the system is printing, copying, or while it is transferring scan to network or fax jobs (priority is for return of scanned originals and printing concurrent jobs)	
Input Speed	Scan at up to 200 ipm (duplex) colour scanning and black and white – A4 LEF	
Resolution	72 x 72 dpi to 600 x 600 dpi Bit Depth: 1-bit (black and white), 8-bit (greyscale), 24-bit (colour)	
Maximum Scan Area	A3	
Scan Template Management	Support 250 scan templates Create Xerox® CentreWare® IS scan templates and share via device cloning to other multifunction systems Confirmation sheet options	
Network Protocols	FTP, SMB, NetWare, HTTP, HTTPS, sFTP	
File Formats	Colour TIFF (TIFF 6.0 or TTN2 with JPEG, LZW) Black and white TIFF (G3MH, G4 MMR compression – single or multiple pages) Searchable PDF and PDF/A (MRC, JPEG, G3 MH, G4 MMR, JBIG 2 Huffman, JBIG Arithmetic Compression, Deflate (for Black and white and within MRC)) JPEG XPS Encrypted / Password Protected PDF (Network scan templates only) Linearised PDF	
Document Management Fields (Meta Data)	Features only available in Network Scan to File Templates:  • 1 to 6 user programmable metadata fields per network scan to file templates and unlimited fields within the template – Metadata field consists of field name, default value and other configurations  • Customised fields viewed on user interface for variable data input	
Scan Features	Mixed Size Originals Scan Build Job Compression Quality/File Size Control Original Type (Photo and Text, Photo, Text, Map, Newspaper / Magazine) Auto Background and Shadow Suppression Size for Size (for mixed size originals) TWAIN Driver Bound Originals Edge Erase Reduction/Enlargement	
Supported Scan Destinations (Standard)	Scan to USB Drive Scan to Email Scan to PC / Server Client (SMB or FTP) Scan to Mailbox Scan to Secure FTP and HTTPS Scan to Home	
Supported Scan Destinations (Optional)	Scan to Application Scan to Microsoft Exchange 2000 Web Folders Scan to PC Desktop (Professional and SE) ScanFlowStore ScanSoft PaperPort ScanSoft OmniPage Xerox® ConnectKey® for SharePoint Xerox® ConnectKey Share to Cloud Various Xerox® Alliance Partner Solutions	
Authentication	Supports Kerberos (UNIX / Windows Server) SMB (Windows Server) NDS LDAP Xerox Secure Access Unified ID System® Locally on device (internal database) Convenience Authentication via Magstripe, Proximity and Smart Cards (CAC / PIV and .NET) readers	

Scan to Email (Standard)		
Directory Access	Address list via LDAP (Windows Active Directory, Exchange, Notes, Domino) Downloaded address list (comma-separated file format)	
Scan Features	Email signatures (6 lines each of 128 character max), email message body (user configurable), email CWIS confirmation sheet options     Scan to Email S/MIME     Email signing (requires Smart Card option)     Auto send to self	
Network Scanning – Softw	are Solutions	
Xerox® Scan to PC Desktop® Professional (Optional)	A desktop offering that provides advanced document imaging, archiving, editing and organisation tools:  Nuance PaperPort Professional image viewing and file management software  Complete PDF functionality  Secure PDF workflow of all scanning applications  Nuance OmniPage Pro Office (for desktop/client installation) — Professional OCR software for digital archiving and document conversion  Image Retriever — provides fully automated retrieval of scanned images direct from a scan enabled Xerox®  WorkCentre to individual desktops. Also includes email inbox polling capability	
Xerox® ConnectKey® for SharePoint® (Optional)	Xerox® ConnectKey for SharePoint simplifies and streamlines the way you scan, capture and store your paper-based documents. Using your Xerox® multifunction system, you can route documents directly into the precise document repository folder, just like you would from your PC. At the multifunction system, you can browse to the folder, name the document, and add any key indexing information before you scan. With the flexibility to capture and route to SharePoint as well as Windows folders, ConnectKey is the right solution for any office that needs to archive and share paper-based documents.	
Xerox® ConnectKey Share to Cloud (Optional)	ConnectKey Share to Cloud, provides organisations with powerful, easy and secure document scanning capabilities that connect your Xerox® multifunction system to popular cloud services and email, such as Google Docs, SalesForce.com, Office 365 and Dropbox™ and gives employees anytime, anywhere access to their most important documents using mobile devices.	
Security		
Features	Expanded Authentication Network authentication to access device and/or device services via- Kerberos (UNIX / Windows Server 2003 / Windows Server 2008), SMB (Windows 2000 / Windows Server 2003 / Windows Server 2008), NDS, LDAP  Xerox Secure Access Unified ID System® Local Authentication (internal database) Smart Card authentication -144k CAC/PIV Card Support (2048 bit certificate key), .NET  Secure Data Digitally signed PDF (when using Smart Card authentication) Encrypted Scan to Email Encrypted / Password Protected PDF (when using Network Scan Templates only) Secure Print (up to 10 digit PIN or Network Authentication) Immediate Image Overwrite On Demand Image Overwrite On Demand Image Overwrite (Scheduled, Manual), includes sanitation of unused area of disk FIPS 140-2 256 bit Hard Disk Encryption Expanded Authorisation SA access based on network credentials Authorisation per user per service User Permissions required to access Print and Print Features (e.g. colour access, or time restrictions) reflects in the print driver Secure Network Access IP Filter, IPsec, IPv6, SSL, SNMPv3, HTTPs, 802.1X, Cisco® TrustSec ISE integration (optional), Device Security McAfee® Embedded Security, Port disablement including USB ports, Audit Log, Hide Print Job Names, McAfee Integrity Control (optional) Common Criteria Certification ISO 15408	
Xerox® Secure Access Unified ID System® (Optional)	Xerox® Secure Access Unified ID System integrates your Xerox® multifunction systems with your existing employee/student ID PIN or badge providing a flexible and convenient authentication system. Allow your staff, employees or students to send documents to a centralised print server. Then, at any multifunction system on the network, they'll simply log in with a swipe of their magnetic or proximity ID card or their PIN to securely print their job. For more information, go to <a href="https://www.office.xerox.com/software-solutions">http://www.office.xerox.com/software-solutions</a>	

Fax		
Network Server Fax Feature	es	
Compatibility	ITU (CCITT) group 3 Various Xerox® Alliance Partner Solutions	
Maximum Scan Area	A3	
Fax Send Features	One- or two-sided scanning (up to A3) Add to send list (50 numbers maximum) Build Job, Speed Dial, Delay send (specific time) Original type (photo, text or photo and text)	
Fax Print Features	One- or two-sided printing, staple, Secure Print	
Transmission Resolution	Superfine: 400 x 200 dpi (Scan at 600 x 600 dpi) Fine: 200 x 200 dpi Standard: 200 x 100 dpi	
Internet Fax Features		
Capability	Direct print-ready document transmission to remote Internet Fax machines or email clients (SMTP) Reception and automatic printout of documents sent via email from remote Internet Fax machines or email clients	
Address Directory Access	Send: Multi-page TIFF, PDF, PDF/A Receive: TIFF, MTIFF, PDF, PDF/A, PS, text, PCL, PRN, JPEG	
Resolution	72 x 72 dpi to 600 x 600 dpi Bit Depth: 1-bit (black and white)	
Network Protocols	SMTP (send), POP3 (receive)	
Compliance	ITU-T T.37 compliant	
Walk-up Fax Features (Opt	ional (Customer-installable) – 1 and 2 lines)	
Compatibility	ITU (CCITT) Group 3	
Speed / Modems	One or Two V.34 modems: 33,600 bps. Less than 4 seconds per page transmission time ATA analogue terminal adaptor utilising T38 (optional)	
Compression / Speed	MH/G3, MMR/SG3	
Resolution	Walkup Send: Standard: 200 x 100 dpi Fine: 200 x 200 dpi Superfine: 600 x 600 dpi Receive: Accepts all sizes	
Fax Send Features	LAN Fax (fax from print driver) Auto fax transmission reduction Page-by-page job status at the machine Delay start, Build Job, Favourites Automatic memory resend Automatic cover sheets PSTN Fax Device Address Book (up to 1,000 contacts)	
Fax Receive Features	One- or two-sided printing Stapled or unstapled Receive print mode – Manual (size, margin, stock, header) / Auto Output tray selection Junk Fax Prevention Up to 200 password protected mailboxes Secure receive Receive timestamp Auto Answer Delay	
Fax Forward	Forward to Email or SMB Location Fax forward on receive only	
Fax Reports	Activity, Dial directory, Group directory, Transmission confirmation, Pending fax, Options report, On demand overwrite report, Mailbox report, Broadcast report	
Auto Dialing	Speed Dials: 5,000 total (one- or two-line options) Group Dials: Up to 200 groups with up to 400 recipients per group (one- or two-line options) Auto Redial: Up to 14 attempts (per country requirements)  • 1 to 25 minute intervals  • Batch send (up to memory capacity)	

Management Support	SNMP Version 1. SNMP Version 2c and SNMP Version 3 trap over TCP/IP and IP	
anagemene sappore	MIB access (IETF-MIBII RFC 1213), Host Resources MIB RFC 2790, Printer MIB RFC 1759 v.2	
Xerox® CentreWare® Web	<ul> <li>A Web-based server application for network administrators that permits Web browser-based device management from any workstation, whether running Windows, UNIX or any other operating system:</li> <li>Works with any SNMP-managed printer from any manufacturer.</li> <li>Provides help with device discovery and installation, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management.</li> <li>Requires Windows XP, Vista or Windows 7 and Internet Explorer 6.0 and higher.</li> <li>CentreWare Integration available for Tivoli® NetView®, Unicentre TNG®, Microsoft Management Console (MMC), HP® OpenView®</li> </ul>	
Novell NDPS/NEPS	Server gateway application: centralised management tool.	
Xerox® Device Manager	Xerox® Device Manager collects and manages the data that drives fact-based decisions for your enterprise device management environment. It is a single tool to install print queues and configure, manage, monitor and report on both networked and locally connected devices – regardless of vendor – across your enterprise. Xerox® Device Manager provides:  • Device monitoring and troubleshooting  • Extensive reporting and discovery of new devices  • Usage collection, chargeback and billing capabilities	
Xerox® Device Types for SAP Environment	Xerox, together with SAP through our Gold-level membership in the SAP Printer Vendor Programme, provides seamless connectivity between SAP systems and your Xerox® printers and multifunction systems. And as an SAP customer you benefit from having SAP-certified Xerox® device types available right from SAP's online delivery model. SAP-certified device types for Xerox® printers and multifunction systems are available to download. http://www.office.xerox.com/software-solutions	
Xerox® SAP R/3 Intelligent Barcode Utility (optional)	Provides built-in process intelligence that allows the printing of barcodes on any appropriately configured PostScript printer in specific versions of SAPenvironment and within Latin-1 (ISO8859-1) SAP system code pages only. Used in conjunction with Xerox® PostScript Device Types for SAP environment and Xerox® Font Centre Barcode Fonts. Information available at <a href="http://www.office.xerox.com/software-solutions">http://www.office.xerox.com/software-solutions</a>	
Xerox® Barcode Pro PS (optional)	Enables intelligent PostScript printing on Xerox® multifunction systems by storing Xerox® software, as well as, the barcode fonts on the printer hard disk. Enables the printing of barcodes from any application (SAP client or mainframe) that supports PostScript printing. Information available at <a href="http://www.office.xerox.com/software-solutions">http://www.office.xerox.com/software-solutions</a>	
CentreWare Internet Service	es – Integrated Web Pages Provided by the Device	
Device Status	Web server embedded in Network Controller:  • Tray status/contents  • Consumables status  • Alerts	
Job Submission	Print ready files: PS, PCL, TIFF, PDF, JPG, XPS Output feature selection (2-sided, output colour, collate, orientation, staple, hole punch, folding, output destination) Delivery options (Immediate, sample set, delay and secure, Save job or reprint)	
Device Administration	Allows simple, remote installation setting of configuration options and management of the device	
Browsers	Internet Explorer 7.x, 8.x, 9.x Safari 5.x Mozilla Firefox 4.x, 5.x, 6.x, 7.x, 8.x, 9.x, 10.x, 11.x Opera 11.x Chrome 12	
Support	Install print / scan drivers and online support available via web page	
Languages Supported	International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish or Russian, Simplified Chinese, Korean, Japanese	

Remote Print Services					
Automatic Meter Reading (ASR)	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.				
Automatic Supplies Replenishment (ASR)	Automatically orders supplies for Xerox® output devices based on actual usage, eliminating the need to manually manage supplies inventory.				
Accounting					
Xerox® Standard Accounting (Standard)					
Tracking	Copy, Print, Fax, Scan and Email usage				
Accounting	Up to 2,497 User accounts (User ID) Up to 500 General accounts (Client) Up to 498 Group accounts (Department)				
Features	<ul> <li>Administrator can manage the feature via the Web User Interface or device control panel in tools</li> <li>Administrator has the ability to import or export user accounts, Group Accounts, General Accounts and User limits via an industry standard CSV file</li> </ul>				
Accounting Options – Netw	vork Accounting – Third Party Enablement				
	<ul> <li>Comprehensive management and enterprise scale tracking and reporting of device usage of copy, print, scan and server fax</li> <li>Numerous solutions are available through Xerox® Alliance Partners. For details visit www.xerox.com</li> <li>Security enhancements with the addition of HTTPS protocol support</li> <li>WorkCentre requests account authentication from third party server enabling larger databases of users and accounts</li> <li>Accept Authentication Login at control panel and pass to third party Networking Account</li> <li>Interface with third party accounting terminal for accounting user interface</li> </ul>				
Supplies	Description	Quantity	Part Number		
Toner Cartridge	Includes 2 Toner Cartridges and Waste Toner Bottle	76,000 pages <sup>4</sup> (38,000 pages each) <sup>4</sup>	006R01551		
Waste Toner Bottle	Supplied with each Toner Cartridge Box	100,000 pages <sup>4</sup>	008R12896		
Staple Cartridges	Basic Office Finisher  — Complete Cartridge  — Refill Cartridge	3,000 per cartridge 3,000 per cartridge (9,000 staples)	108R00682 108R00535		
	Office Finisher	5,000 per cartridge (15,000 staples)	108R00493		
	Office Finisher with Booklet Maker	5,000 per cartridge (15,000 staples)	108R00493		
	Office Finisher with Booklet Maker – saddle-stitch stapling	2,000 per cartridge (8,000 staples)	108R01158		
	HVF and HVF with Booklet Maker – Complete Cartridge – Refill Cartridge	5,000 per cartridge 5,000 per cartridge (15,000 staples)	008R12912 008R12898		

HVF with Booklet Maker – saddle-stitch stapling

Convenience Stapler

Complete CartridgeRefill Cartridge

2,000 per cartridge (16,000 staples)

5,000 per cartridge 5,000 per cartridge (15,000 staples) 008R12897

008R12964 008R12941

Smart Kits®				
Fuser Module	Includes Ozone Filter	400,0004	109R00751	
Xerographic Module – Metered (Print Cartridge)		450,0004	109R00672	
Xerographic Module – Sold (Print Cartridge)		450,0004	113R00673	
Document Handler Feeder Rolls		150,000 feeds	113R00718	

<sup>&</sup>lt;sup>1</sup> Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

Our products allow use of papers certified by the FSC, PEFC and SFI, and those made with post consumer recycled content and chlorine-free paper. For more information regarding our entire line of paper and specialty media, contact your Xerox® representative or visit us at www.xerox.com/supplies.

Return spent imaging supplies through the Xerox® Green World Alliance collection/reuse/recycling programme. For more information, visit www.xerox.com/about-xerox/recycling.

For more information, call or visit us at www.xerox.com/office



<sup>&</sup>lt;sup>2</sup> Expected regular monthly throughput

<sup>&</sup>lt;sup>3</sup> Paper capacities are based on 75 gsm stock; capacities will vary with different weight stocks.

<sup>&</sup>lt;sup>4</sup> Approximate pages. Declared Yield based on 5 page job size, 6% area coverage, using A4 media. Yield will vary based on media size, image area coverage, media orientation and usage patterns.