

Xerox® WorkCentre® 5945/5955 Multifunction Printer

The WorkCentre 5945/5955 Multifunction Printer is built on Xerox® ConnectKey® Technology. For more information, go to www.connectkey.com.







WorkCentre 5955 shown with Office Finisher with Booklet Maker

	WorkCentre 5945 shown with Office Finisher	WorkCentre 5955 shown with Office Finisher with Booklet Maker	
System Specifications	stem Specifications WorkCentre 5945 WorkCentre 5955		
Simplex Speed 8.5 x 11 in. / A4 (LEF) 8.5 x 13 to 8.5 x 14 in. / A4 to B4 (SEF) 11 x 17 in. / A3 (A3 SEF) (Bypass Tray will reduce speed by 10 to 20%)	45 ppm 36 ppm 31 ppm	55 ppm 36 ppm 31 ppm	
Auto Duplex Speed 8.5 x 11 in. / A4 (LEF) 11 x 17 in. / A3 (SEF)	Up to 45 ipm / 2-sided 22.5 sheets per minute Up to 31 ipm / 2-sided 15.5 sheets per minute	Up to 55 ipm / 2-sided 27.5 sheets per minute Up to 31 ipm / 2-sided 15.5 sheets per minute	
Monthly Duty Cycle ¹	Up to 175,000 pages	Up to 200,000 pages	
Recommended Average Monthly Print Volume ²	Up to 20,000 pages		
Hard Drive / Processor / Memory	Minimum 250 GB / 1 GHz Dual-core / 2 GB system		
Connectivity	10/100/1000Base-T Ethernet, High-Speed USB 2.0 direct print, Optional Wi-Fi (w	vith Xerox® USB Wireless Adapter)	
Controller Features	Unified Address Book, Remote Control Panel, Online Support (accessed from the u	ser interface and print driver), Configuration Cloning	
Copy and Print			
Copy and Print Resolution	Copy : Up to 600 x 600 dpi; Print : Up to 1200 x 1200 dpi, 256 shades of gray		
First-copy-out Time	As fast as 3.7 seconds from the Platen / 7.6 seconds from the Automatic Document Feeder		
Page Description Languages	Adobe® PostScript® 3™, PDF, PCL® 5c / PCL 6, XML Paper Specification (XPS®) (Optional)		
Print Features	Print from USB, Earth Smart Driver Settings, Job Identification, Booklet Creation, Store and Recall Driver Settings, Bi-directional Status, Scaling, Job Monitoring		
Mobile Printing	Apple® AirPrint™, Xerox® PrintBack, Xerox® Mobile Print (Optional), Xerox® Mobile Print Cloud® (Optional), Mopria™ certified, Xerox® Print Service (plug-in for Android™)		
Scan			
Standard	Destinations: Scan to Mailbox; Scan to USB, Scan to Email, Scan to Network; File Single Touch Scan, Searchable PDF, Single/Multi-Page PDF / XPS / TIFF, Encrypted		
Optional	Software Packages: ConnectKey® for SharePoint®, ConnectKey® for DocuShare®, ConnectKey® Share to Cloud, Xerox® Scan to PC Desktop® Professional, other solutions available through various Xerox Business Innovation Partners		
Fax			
Standard Features	Internet Fax, Fax Build Job, Network Server Fax Enablement		
Optional Features	Fax Forward to Email or SMB, Walk-up Fax (one-line and two-line options, includes	LAN Fax, Fax Forward to Email or SMB, Walk-up Fax)	
Security			
Standard Features	McAfee® Embedded, McAfee ePolicy (ePO) Compatible, HDD Overwrite, 256-bit Encryption (FIPS 140-2 compliant), Common Criteria Certification (ISO 15408) (undergoing evaluation), Secure Print, Secure Fax, Secure Scan, Secure Email, Cisco® TrustSec Identity Services Engine (ISE) Integration, Network Authentication, SSL, SNMPv3, Audit Log, Access Controls, User Permissions		
Optional Features	McAfee Integrity Control, Xerox Secure Access Unified ID System®, Smart Card Enablement Kit (CAC/PIV/.NET)		
Accounting			
Standard Features	Xerox® Standard Accounting (Copy, Print, Scan, Fax, Email), Network Accounting E	nablement	
Optional Features	quitrac Express®, Equitrac Office®, Equitrac Professional®, YSoft® SafeQ®, other network accounting solutions available through various Xerox® Business anovation Partners		

Device Specifications				
Control Panel Languages	US English, International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Turkish, Greek, Russian, Czech, Polish, Hungarian or Romanian, Catalan			
Accessories				
Optional	Envelope Tray Kit (replaces Tray 2) Office Finisher Office Finisher with Booklet Maker Hole Punch for Office Finisher Convenience Stapler (includes Work Surface) Smart Card Enablement Kit Xerox Secure Access Unified ID System® (with USB Card Reader) Walk up Fax (One- or Two-line options, includes LAN Fax) ScanFlowStore® Xerox® USB Wireless Adapter McAfee® Integrity Control Enablement Kit XPS Print Option Kit			
Foreign Device Interface (FDI) (Optional)	Also known as Auxiliary Access Device,	this is an interface to third party access co	ntrol devices, such as coin machines and	d card readers.
Electrical Requirements				
North America	Voltage : 110-127 VAC +/- 10 % Frequency: 50/60 Hz +/- 5 %, 15 A			
Europe	Voltage: 220-240 VAC +/- 10 % Frequency: 50/60 Hz +/- 5%, 10 A			
Power Consumption	WorkCentre 5945		WorkCentre 5955	
Running (Average) Base Unit with Offset Catch Tray: Base Unit with Office Finisher: Base Unit with Office Finisher with Booklet Maker:	1,150 watts 1,230 watts 1,230 watts		1,250 watts 1,330 watts	
Standby Mode Base Unit with Offset Catch Tray: Base Unit with Office Finisher: Base Unit with Office Finisher with Booklet Maker:	45 watts 55 watts 55 watts		45 watts 55 watts	
Sleep mode	3 watts			
Ready to Scan and Print (from Power On)	As fast as 230 seconds (3 minutes, 50 seconds)			
Recovery from Low Power	As fast as 4 seconds			
Recovery from Sleep	As fast as 28 seconds	As fast as 28 seconds		
Operating Environment				
Required Temperature Range	50° to 90° F (10° to 32° C)			
Required Relative Humidity	15% to 85%			
Sound Power Levels	Operating 7.1 B(A), Standby: 5.0 B(A)			
Sound Pressure Levels	Operating: 56 dB(A), Standby: 35 dB(A)			
Dimensions and Weight	Width	Depth	Height	Weight
Base Configuration with Internal Tray	33.5 in. / 850 mm	26.2 in. / 665 mm	45.3 in. / 1,150 mm	249 lbs. / 113 kg
With Office Finisher	57.9 in. / 1,470 mm	26.2 in. / 665 mm	45.3 in. / 1,150 mm	314.5 lbs. / 142.5 kg
With Office Finisher with Booklet Maker	60.2 in. / 1,530 mm	26.2 in. / 665 mm	45.3 in. / 1,150 mm	349.5 lbs. / 158.5 kg
Work Surface (does not add to overall width with Bypass Tray open	11.2 in. / 285 mm	-	-	-

Certifications	Certifications			
	FCC Class A Compliant (US), ICES Class A Compliant (Canada) CSA Listed (UL 60950-1, Second Edition) CB Certified (IEC 60950-1, Second Edition) ENERGY STAR® GOST NOM Blue Angel ECOLOGO® CE Marked Common Criteria (IEEE 2600.2 standard) (undergoing evaluation) EPEAT (United States) GS Mark Citrix® Certified WHQL MEDITECH Cerner To view the latest list of certifications, go to www.xerox.com/OfficeCertifications.			
Paper Handling				
Single-pass Automatic Document Fe	eder			
Capacity ³	200 sheets			
Speed (black-and-white and color)	Up to 105 images per minute (ipm) (simplex) Up to 200 ipm (duplex) black-and-white, up to 160 ipm (duplex) color			
Paper Sizes Sensed	4.9 x 5.4 in. to 11.7 x 17 in. / 125 x 138 mm to 297 x 432 mm			
Weights	13 lb. bond to 43 lb. bond / 50 gsm to 160 gsm			
Bypass Tray				
Capacity ³	100 sheets			
Sizes	Custom sizes: 4.25 x 5.5 in. to 11 x 17 in. / A6 to A3			
Weights	16 lb. bond to 80 lb. cover / 60 to 216 gsm			
Types	Bond Carbonless Card Stock Envelopes Hole punched Index Labels Letterhead Plain Preprinted Recycled			
Trays 1 and 2				
Capacity ³	500 sheets each			
Sizes	Custom Sizes from 5.5 x 8.5 in. LEF to 11 x 17 in. SEF / A5 to A3			
Weights	16 lb. bond to 53 lb. bond / 60 to 200 gsm			
Types	Bond Card Stock Glossy Hole punched Index Labels Letterhead Lightweight Card Stock Plain Preprinted Recycled Transparencies (Tray 2 only)			

High Capacity Tandem Tray			
Capacity ³	Tray 3: 1,600 sheets Tray 4: 2,000 sheets		
Sizes	Standard Sizes: 8.5 x 11 in. LEF / A4		
Weights	16 lb. bond to 53 lb. bond / 60 to 216 gsm		
Types	Bond Card Stock Glossy Hole punched Index Letterhead Lightweight Card Stock Plain Preprinted Recycled		
Envelope Kit (Replaces Tray 2)			
Capacity ³	Up to 50 envelopes		
Sizes	#10 Commercial (9.25 x 4.125 in.), DL, C5		
Weights	20 lb. bond to 24 lb. bond / 75 to 90 gsm		
Total Capacity			
Device Total Capacity ³	4,700 sheets		
Finishing			
Center Offsetting Tray			
Capacity	Up to 400 sheets of 20 lb. bond / 80 gsm		
Office Finisher (Optional)			
Top Tray Capacity Stacking Tray Capacity	250 sheets unstapled of 80 gsm 2,000 sheets unstapled of 80 gsm or 1,000 sheets single stapled or 750 sheets dual stapled (8.5 x 11 in. / A4)		
Top Tray Sizes Stacking Tray Sizes	4.25 x 5.85 in. to 11 x 17 in. / A6 to A3 5.5 x 8.5 in. to 11 x 17 in. / A5 to A3		
Weights	16 lb. bond to 58 lb. bond / 60 to 216 gsm		
Multiposition Stapling	50 sheets of 20 lb. bond / 80 gsm		
Hole Punch (Optional) North America: Europe:	2-3 Hole Punch 2-4 Hole Punch		
Office Finisher with Booklet Maker (Optional)			
Top Tray Capacity Stacking Tray Capacity	250 sheets unstapled of 80 gsm 2,000 sheets unstapled of 80 gsm or 1,000 sheets single stapled or 750 sheets dual stapled (8.5 x 11 in. / A4)		
Top Tray Sizes Stacking Tray Sizes	4.25 x 5.85 in. to 11 x 17 in. / A6 to A3 5.5 x 8.5 in. to 11 x 17 in. / A5 to A3		
Weights	16 lb. bond to 58 lb. bond / 60 to 216 gsm		
Multiposition Stapling	50 sheets of 20 lb. bond / 80 gsm		
Hole Punch (Optional) North America: Europe:	2-3 Hole Punch 2-4 Hole Punch		
Booklet Making Capacity ³	40 booklets (2-15 sheets per booklet – 20 lb. / 80 gsm or less)		
Booklet Making Sizes	Letter – 8.5 x 11 in. / A4 SEF Legal – 8.5 x 14 in. / B4 SEF Ledger – 11 x 17 in. / A3 SEF		
Saddle-stitch Stapling	2-15 sheets / 8 – 60 page booklet 16 lb. bond to 24 lb. bond / 60 to 90 gsm		
Folding	1-15 sheets / unstapled		
Convenience Stapler (Optional - Inc	ludes Work Surface)		
Capacity ³	50-sheet stapling 5,000 staples Requires a separate power outlet		

Сору	
First-copy-out Time	As fast as 3.7 seconds from the Platen / 7.6 seconds from the Automatic Document Feeder
Sides (input:output)	1-1,1-2,2-2,2-1
Quantity	1 to 9,999
Resolution (max.)	Scan: Up to 600 x 600 dpi; Print: Up to 1200 x 1200 dpi, 256 shades of gray
Reduction / Enlargement	Variable zoom from 25% to 400% in 1% increments
Concurrency	Program-ahead to allow job to be initiated while initial job is processed (Copy, Print, Fax and Scan)
Copy Features	Annotation and Bates™ stamping (with color capability and font size adjustment)
	Authoratication for Services Auto Paper Select Auto Reduction & Enlargement to fit selected paper size Auto Tray Switching Automatic 2-sided / Duplex Booklet Creation Build Job: (Enables page-level programming and also lets you proof each section or delete last section as the job is built) Collation Covers (Front only, front and back, back only, printed inside and out: Blank or Printed) Dividers (blank) Edge Erase Features Help (Intuitive text and graphic descriptions) ID Card Copy Image Quality Adjustments Image Shift (with Auto Center option) Invert Image (negative or mirror image) Large Job Interrupt Multi-up (up to 15 columns by 15 rows) Sample Set Save Job Settlings Stapling Transparencies
Xerox® Copier Assistant®	Xerox® Copier Assistant® (XCA) Software provides a PC-based alternative to the user interface touch screen. Used in conjunction with a customer-supplied PC attached via the USB port, this software supports text-to-speech, screen magnification and easy PC keyboard access to basic and advanced copy features. Section 508 compliant. For more information or to download Xerox® Copier Assistant for free, visit www.xerox.com
Print	
First-print-out Time	As fast as 7 seconds
Print Resolution	Up to 1200 x 1200 dpi, 256 shades of gray
Print Features	Application Defaults Banner Sheet Enable / Disable Bi-directional Status Cover Selection Delay Print (specific time) User Permissions Image Options (Toner Saver, Resolution (Standard, Enhanced, High) Job Identification (Print ID or Banner, Print ID in margins on first page only or all pages) LAN Fax (requires optional Fax Kit) Layout / Watermark (N-up (up to 16 pages per sheet), Multi-up, Booklet layout / finishing, Fit to new paper size) Overlays Paper Selection by Attribute Sample Set Saved Job Secure Print with Timed Deletion Special Pages (exception page programming: covers, inserts, exception pages) Store and Recall Driver Settings Sustainability Features (Xerox® Earth Smart Settings, Duplex, N-up, Turn-off Banner and Print ID, Smart Sample Set, Hold All Jobs)
Print from USB	Allows walk-up printing from Type A USB port on front panel Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TIFF, PS, XPS ⁴ , PCL
Operating Systems	Microsoft® Windows® XP SP3 (32- and 64-bit) Windows Server 2003 (32- and 64-bit) Windows Server 2008 and R2 (32- and 64-bit) Windows Server 2012 and R2 Windows Vista SP2 (32- and 64-bit) Windows 7 (32- and 64-bit) Windows 8 (32- and 64-bit) Windows 8 (132- and 64-bit) Windows 8.1 (32- and 64-bit) Mac OS 10.7, 10.8, 10.9 Linux® Redhat® Fedora® Core 19 x86 Ubuntu® 13.10 x64 openSUSE® 13.1 x64

Network Protocols	TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6,WSD NetWare: Bindery and NDS IPX/SPX, NDPS®/NEPS (with Server Gateway) AppleTalk®: EtherTalk® Microsoft Windows Networking over IP Apple® Bonjour® IPv6 Secure FTP Most protocols not in use can be disabled	
Administrative Protocols	DHCP, BOOTP, SNMP, WINS, SLP® v2, HTTP, HTTPS, DHCP Autonet, SSL, NTP, DNS, SSDP	
Fonts	PCL: 93 scalable fonts, line printer and bitmap font (including Cyrillic font support) PostScript 3: 173 Type 1 fonts, 2 Multiple Master fonts	
Xerox® Mobile Express Driver®	Makes it easy for mobile users to find, use and manage Xerox® and non-Xerox® devices in every new location. Plug into a new network, and Xerox® Mobile Express Driver automatically discovers available printers and provides status and capability information. Save a list of "favorite" printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT.	
Xerox® Global Print Driver®	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox® devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.	
Xerox® Pull Print Driver	Makes it easy for IT managers to qualify, deploy and manage all print devices using a single driver in a Pull Print environment. Uses a single queue and single driver. The Xerox® Pull Print Driver extends convenience across a broad range of printing assets. IT administrators no longer need to manage and configure multiple drivers. Used in conjunction with Xerox Secure Access Unified ID System®, Equitrac Office®, Ysoft® SafeQ®, Pharos® and others.	
Print Solutions		
Xerox® Mobile Print Cloud (Optional)	Xerox® Mobile Print Cloud addresses the needs of businesses with a mobile workforce and puts you ahead of the evolving mobile print need, but without burdening staff, budget or infrastructure. Getting started takes only a few minutes via the cloud. Print from any mobile device to nearly any brand of printer. Accurate printing with true Microsoft® Office® rendering and more. Print what you need, when, where and how you need it.	
Xerox® Mobile Print Solution (Optional)	Xerox® Mobile Print Solution is an ideal choice for sites that have additional requirements for control and security with an onsite server. Xerox® Mobile Print Solution allows users to print from most mobile devices to nearly any brand of printer or MFP without drivers or added complexity. Simply enter a release code (PIN) at the device and get accurate printing with true Microsoft Office rendering and more to use with your server for private, onsite deployment.	
Unified Address Book		
Features	Services supported: Fax, Internet Fax, Email, Scan to Maximum contacts: 5,000 Contacts: Supports 1 or more destinations Favorites for quick access of fax numbers, emails, etc.	
Scan		
Concurrency	Scan while the system is printing, copying, or while it is transferring scan to network or fax jobs (priority is for return of scanned originals and printing concurrent jobs)	
Input Speed	Scan at up to 160 ipm color scanning and 200 ipm black-and-white scanning — 8.5 x 11 in. / A4 LEF	
Resolution	72 x 72 dpi to 600 x 600 dpi Bit Depth: 1-bit (black-and-white), 8-bit (grayscale), 24-bit (color)	
Maximum Scan Area	11 x 17 in. / A3	
Scan Template Management	Support 250 scan templates Create Xerox® CentreWare® IS scan templates and share via device cloning to other MFPs Confirmation sheet options	
Network Protocols	sFTP, FTP, SMB, NetWare, HTTP, HTTPS	
File Compression	Color TIFF (.1FF 6.0 or TTN2 with JPEG, LZW) Black-and-white TIFF (G3MH, G4 MMR compression - single or multiple pages) Searchable PDF and PDF/A (MRC, JPEG, G3 MH, G4 MMR, JBIG 2 Huffman, JBIG Arithmetic Compression, Deflate (for Black-and-white and within MRC)) Linearized PDF / PDF/A	
Document Management Fields (Meta Data)	Features only available in Network Scan to File Templates: • 1 to 6 user programmable metadata fields per network scan to file templates and unlimited fields within the template – Metadata field consists of field name, default value and other configurations • Customized fields viewed on user interface for variable data input	
Scan Features	Mixed Size Originals Scan Build Job Compression Quality / File Size Control Original Type (Photo and Text, Photo, Text, Map, Newspaper / Magazine) Auto Background and Shadow Suppression Size for Size (for mixed size originals) TWAIN Support / WIA Support Bound Originals Edge Erase Reduction / Enlargement Single Touch Scan buttons (up to 10)	

Scan to Email (Standard)		
	- Empilicipatures (6 lines each of 120 character may) amail moscage hady/year f	
Scan Features	 Email signatures (6 lines each of 128 character max), email message body (user configurable), email CWIS confirmation sheet options Scan to Email S/MIME Encryption Email signing (requires Smart Card option) Auto send to self 	
Directory Access	Address list via LDAP (Windows Archive Directory, Exchange, Notes, Domino) Downloaded address list (comma-separated file format) Utilizes the Unified Address Book	
Scan to (Standard)		
Features	Scan to USB Scan to Network Folder (uses Unified Address Book entries)	
Network Scanning – Software Solution	ons	
Xerox® Scan to PC Desktop® Professional (Optional)	A desktop offering that provides advanced document imaging, archiving, editing and organization tools: • PaperPort Professional image viewing and file management software — Complete PDF functionality — Secure PDF workflow of all scanning applications • OmniPage Pro Office (for desktop/client installation) — Professional OCR software for digital archiving and document conversion • Image Retriever — provides fully automated retrieval of scanned images direct from a scan enabled Xerox® WorkCentre to individual desktops. Also includes email inbox polling capability	
Xerox® ConnectKey® for SharePoint® (Optional)	Xerox® ConnectKey for SharePoint simplifies and streamlines the way you scan, capture and store your paper-based documents. Using your Xerox® MFP, you can route documents directly into the precise document repository folder, just like you would from your PC. At the MFP, you can browse to the folder, name the document, and add any key indexing information before you scan. With the flexibility to capture and route to SharePoint as well as Windows folders, ConnectKey Technology is the right solution for any office that needs to archive and share paper-based documents.	
Xerox® ConnectKey Share to Cloud (Optional)	Xerox® ConnectKey Share to Cloud provides organizations with powerful, easy and secure document scanning capabilities that connect your Xerox® MFP to popular cloud services and email, such as Google Docs™, SalesForce.com, Office 365 and Dropbox™ and gives employees anytime, anywhere access to their most important documents using mobile devices.	
Xerox® ConnectKey® for DocuShare® (Optional)	Xerox® ConnectKey for DocuShare, a one-step scan-to-workflow solution, simplifies the process of incorporating hard copy content into enterprise document flows. Users can easily scan documents directly into a DocuShare collection or Windows folder via a multifunction printer (MFP).	
Security		
Features Xerox Secure Access Unified ID	Expanded Authentication Network authentication to access device and/or device services via- Kerberos (UNIX / Windows Server 2003 / Windows Server 2008), SMB (Windows 2000 / Windows Server 2008), Windows Server 2008), NDS, LDAP Xerox® Secure Access Local Authentication (internal database) Smart Card authentication :144k CAC / PIV Card Support (2048 bit certificate key) / .NET Secure Data Digitally signed PDF (when using Smart Card authentication) Encrypted Scan to Email Encrypted / Password Protected PDF (Email and Network Scan Templates only) Secure Pint (up to 10 digit PIN or Network Authentication) Immediate Image Overwrite On Demand Image Overwrite On Demand Image Overwrite (Scheduled, Manual), includes sanitation of unused area of disk FIPS 140-2 256 bit Hard Disk Encryption Expanded Authorization Sa access based on network credentials Authorization per user per service User Permissions required to access Print and Print Features (e.g. color access, or time restrictions) reflects in the print driver Secure Network Access IP Filter, IPSec, IPv6, SSL v3.0, SNMPv3, HTTPS, 802.1X, Cisco® TrustSec Identity Services Engine integration (optional), Device Security McAfee® Embedded Security, Port disablement including USB ports, Audit Log, Hide Print Job Names, , McAfee Integrity Control (optional) Common Criteria Certification ISO 15408 (undergoing evaluation) Xerox Secure Access Unified ID System integrates your Xerox® multifunction printers with your existing employee/student ID PIN or badge providing a flexible and	
System [®] (Optional)	convenient authentication system. Allow your staff, employees or students to send documents to a centralized print server. Then, at any multifunction printer on the network, they'll simply log in with a swipe of their magnetic or proximity ID card or their PIN to securely print their job. For more information, go to www.office.xerox.com/software-solutions	
Fax		
Network Server Fax Features		
Compatibility	ITY (CCITT) group 3 Various Xerox® Business Innovation Partner Solutions	
Maximum Scan Area	11 x 17 in. / A3	
Fax Send Features	One- or two-sided scanning (up to 11 x 17 in. / A3) Add to send list (50 numbers maximum) Build Job, Favorites, Delay send (specific time) Original type (photo, text or photo and text)	

Fax Print Features	One- or two-sided printing, staple, Secure Print	
Transmission Resolution	Superfine: 400 x 200 dpi (Scan at 600 x 600 dpi) Fine: 200 x 200 dpi Standard: 200 x 100 dpi	
Internet Fax Features		
Capability	Direct print-ready document transmission to remote Internet Fax machines or email clients (SMTP) Reception and automatic printout of documents sent via email from remote Internet Fax machines or email clients	
Address Directory Access	Send: Multi-page TIFF, PDF, PDF/A Receive: TIFF, MTIFF, PDF, PDF/A, PS, text, PCL, PRN, JPEG	
Resolution	72 x 72 dpi to 600 x 600 dpi Bit Depth: 1-bit (black-and-white)	
Network Protocols	SMTP (send), POP3 (receive)	
Compliance	ITU-T T.37 compliant	
Walk-up Fax Features (Optional (Cust	comer-installable) – 1 and 2 lines)	
Compatibility	ITU (CCITT) Group 3	
Speed / Modems	One or Two V.34 moderns: 33,600 bps. Less than 4 seconds per page transmission time ATA analogue terminal adapter utilizing T38 (optional)	
Compression / Speed	MH/G3, MMR/SG3	
Resolution	Walkup Send: Standard: 200 x 100 dpi Fine: 200 x 200 dpi Superfine: 600 x 600 dpi Receive: Accepts all sizes	
Fax Send Features	LAN Fax (fax from print driver) Auto fax transmission reduction Page-by-page job status at the machine Delay start, Build Job, Favorites Automatic memory resend Automatic cover sheets PSTN Fax Device Address Book (up to 1,000 contacts)	
Fax Receive Features	One- or two-sided printing Stapled or unstapled Receive print mode – Manual (size, margin, stock, header) / Auto Output tray selection Up to 200 password protected mailboxes Secure receive Receive timestamp Auto answer delay	
Fax Forward	Forward to Email or SMB Location	
F B 4.	Fax forward on receive only	
Fax Reports Auto Dialing	Activity, Dial directory, Group directory, Transmission confirmation, Pending fax, Options report, On demand overwrite report, Mailbox report, Broadcast report Speed Dials: 5,000 total (one- or two-line options) Group Dials: Up to 200 groups with up to 400 recipients per group (one- or two-line options) Auto Redial: Up to 14 attempts (per country requirements) • 1 to 25 minute intervals • Batch send (up to memory capacity)	
Device Management		
Management Support	SNMP Version 1. SNMP Version 2c and SNMP Version 3 trap over TCP/IP and IP MIB access (IETF-MIBII RFC 1213), Host Resources MIB RFC 2790, Printer MIB RFC 1759 v.2	
Xerox® CentreWare® Web	A Web-based server application for network administrators that permits Web browser-based device management from any workstation, whether running Windows, UNIX or any other operating system: • Works with any SNMP-managed printer from any manufacturer. • Provides help with device discovery and installation, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management. • Requires Windows XP, Vista or Windows 7 and Internet Explorer 6.0 and higher. • CentreWare Integration available for Tivoli® NetView®, Unicenter TNG®, Microsoft Management Console (MMC), HP® OpenView®	

Xerox® Device Manager	Xerox® Device Manager collects and manages the data that drives fact-based decisions for your enterprise device management environment. It is a single tool to install print queues and configure, manage, monitor and report on both networked and locally connected devices – regardless of vendor – across your enterprise. Xerox® Device Manager provides: Device monitoring and troubleshooting Extensive reporting and discovery of new devices Usage collection, chargeback and billing capabilities	
Xerox® Device Types for SAP Environment	Xerox, together with SAP through our Gold-level membership in the SAP Printer Vendor Program, provides seamless connectivity between SAP systems and your Xerox® printers and MFPs. And as an SAP customer you benefit from having SAP-certified Xerox® device types available right from SAP's online delivery model. SAP-certified device types for Xerox® printers and MFPs are available to download. www.office.xerox.com/software-solutions	
Xerox® SAP R/3 Intelligent Barcode Utility (optional)	Provides built-in process intelligence that allows the printing of barcodes on any appropriately configured PostScript printer in specific versions of SAP environment and within Latin-1 (ISO8859-1) SAP system code pages only. Used in conjunction with Xerox® PostScript Device Types for SAP environment and Xerox® Font Cente Barcode Fonts. Information available at www.office.xerox.com/software-solutions	
Xerox [®] Barcode Pro PS (optional)	Enables intelligent PostScript printing on Xerox® multifunction systems by storing Xerox software, as well as, the barcode fonts on the printer hard disk. Enables the printing of barcodes from any application (SAP client or mainframe) that supports PostScript printing. Information available at www.office.xerox.com/software-solutions	
CentreWare Internet Services – Inte	grated Web Pages Provided by the Device	
Device Status	Web server embedded in Network Controller: • Tray status/contents • Consumables status • Alerts Remote Control Panel	
Job Submission	Print ready files: PS, PCL, TIFF, PDF, JPG, XPS ^a , TXT, PRN Output feature selection (2-sided, output color, collate, orientation, staple, hole punch, folding, output destination) Delivery options (Immediate, sample set, delay and secure, Save job or reprint)	
Device Administration	Allows simple, remote installation setting of configuration options and management of the device	
Browsers	Internet Explorer 7.x, 8.x, 9.x Safari 5.x Mozilla Firefox 4.x, 5.x, 6.x, 7.x, 8.x, 9.x, 10.x, 11.x Opera 11.x Chrome 12	
Support	Install print / scan drivers and online support available via web page	
Languages Supported	International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish or Russian, Simplified Chinese, Korean, Japanese	
Remote Services		
Xerox® MeterAssistant®	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.	
Xerox® SuppliesAssistant®	Automatically orders supplies for Xerox output devices based on actual usage, eliminating the need to manually manage supplies inventory.	
Xerox [®] MaintenanceAssistant	Offers a fast (and free) way to resolve potential issues and receive assistance and automate the troubleshooting/repair process. Diagnostic data is sent to Xerox, allowing for problems to be solved faster with increased uptime.	
Accounting		
Xerox® Standard Accounting (Standa	ard)	
Tracking	Copy, Print, Fax, Scan and Email usage	
Accounting	Up to 2,497 User accounts (User ID) Up to 500 General accounts (Client) Up to 498 Group accounts (Department)	
Features	 Administrator can manage the feature via the Web User Interface or device control panel in tools Administrator has the ability to import or export user accounts, Group Accounts, General Accounts and User limits via an industry standard CSV file 	
Accounting Options – Network Acco	unting – Third Party Enablement	
	Enhanced network accounting with up to the minute data on how the system is being used Comprehensive management and enterprise scale tracking and reporting of device usage of copy, print, scan and server fax Numerous solutions are available through Xerox Business Innovation Partners. For details visit www.xerox.com Security enhancements with the addition of HTTPS protocol support WorkCentre requests account authentication from third party server enabling larger databases of users and accounts Accept Authentication Login at control panel and pass to third party Networking Account Interface with third party accounting terminal for accounting user interface.	

Supplies	Description	Quantity	Part Number	
Toner Cartridge	Includes 2 Toner Cartridges	88,000 pages ⁵ (44,000 pages each) ⁵	006R01604	
Toner Cartridge (sold)	Includes 2 Toner Cartridges	88,000 pages ⁵ (44,000 pages each) ⁵	006R01605	
	Office Finisher with Booklet Maker – saddle-stitch stapling	2,000 per cartridge (8,000 staples)	108R01158	
	Convenience Stapler – Complete Cartridge – Refill Cartridge	5,000 per cartridge 5,000 per cartridge (15,000 staples)	008R12964 008R12941	
Smart Kits®				
Fuser Module	North America: Europe:	350,000 ⁵ 350,000 ⁵	109R00847 109R00848	
Print Cartridge	Includes xerographic drums, developer module, including dual auger ring, toner despense, toner concentration sensor, development roll, trim bar and developer material	200,000 ⁵	013R00669	

¹ Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

Return spent imaging supplies through the Xerox® Green World Alliance collection/reuse/recycling program. For more information, visit www.xerox.com/about-xerox/recycling.

For more information, call **1-800-ASK-XEROX** or visit us at www.xerox.com/office.



² Expected regular monthly throughput

 $^{^{3}}$ Paper capacities are based on 20 lb. / 75 gsm stock; capacities will vary with different weight stocks.

⁴ XPS option is required to print XPS files.

⁵ Average standard pages. Declared Yield in accordance with ISO/IEC 19752. Yield will vary based on image, area cover and print mode.