


Xerox[®] WorkCentre[™] 5865/5875/5890 Multifunction Printer

The WorkCentre 5865/5875/5890 Multifunction Printer is built on Xerox[®] ConnectKey[®] Technology. For more information, go to **www.connectkey.com**.



Standard Features	McAfee® Embedded, McAfee (ePO) Compatible, HDD Overwrite, 256-bit Encryption (FIPS 140-2 compliant), Common Criteria Certification (ISO 15408), Secure Print with Timed Deletion, Secure Fax, Secure Scan, Secure Email, Cisco® TrustSec Identity Service Engine (ISE) Integration, Network Authentication, SSL, SNMPv3, Audit Log, Access Controls, User Permissions		
Optional Features	McAfee Integrity Control, Smart Card Enablement Kit (CAC/PIV/.NET), Xerox Secure Access Unified ID System®		
Accounting			
Standard Features	Xerox [®] Standard Accounting (Copy, Print,		
Optional Features	Equitrac Express®, Equitrac Office®, Equitra Xerox® Alliance Partners	ac Professional®, YSoft® SafeQ®,	other solutions available through variou
Device Specifications			
Control Panel Languages	US English, International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Turkish, Greek, Russian, Czech, Polish, Hungarian, Romanian, Catalan		
Accessories			
Optional	High Capacity Feeder (HCF) HCF Kit (A4 SEF) (HCF required) HCF Kit (A3 SEF) (HCF required) Envelope Tray (Replaces Tray 2) Offset Catch Tray Office Finisher (optional with 5865/5875 Office Finisher with Booklet Maker (option Hole Punch for Office Finisher (optional w High Volume Finisher High Volume Finisher with Booklet Maker Z Fold / C Fold Unit (with High Volume Fin Post Process Inserter (with High Volume Fin Convenience Stapler Work Surface Smart Card Enablement Kit	al with 5865/5875 only) th 5865/5875 only) isher with Booklet Maker)	
	Xerox Secure Access Unified ID System® Walk up Fax (One- or Two-line options, inc Wireless Connectivity Kit McAfee® Integrity Control Enablement Kit XPS Print Option Kit		
	Walk up Fax (One- or Two-line options, inc Wireless Connectivity Kit McAfee® Integrity Control Enablement Kit		access control devices, such as coin
(FDI) (Optional)	Walk up Fax (One- or Two-line options, inc Wireless Connectivity Kit McAfee® Integrity Control Enablement Kit XPS Print Option Kit Also known as Auxiliary Access Device, thi		access control devices, such as coin
(FDI) (Optional)	Walk up Fax (One- or Two-line options, inc Wireless Connectivity Kit McAfee® Integrity Control Enablement Kit XPS Print Option Kit Also known as Auxiliary Access Device, thi		iccess control devices, such αs coin
(FDI) (Optional) Electrical Requirements	Walk up Fax (One- or Two-line options, inc Wireless Connectivity Kit McAfee® Integrity Control Enablement Kit XPS Print Option Kit Also known as Auxiliary Access Device, thi machines and card readers. Voltage : 220-240 VAC +/- 10 %		access control devices, such as coin WorkCentre 5890
(FDI) (Optional) Electrical Requirements Power Consumption	 Walk up Fax (One- or Two-line options, inc Wireless Connectivity Kit McAfee® Integrity Control Enablement Kit XPS Print Option Kit Also known as Auxiliary Access Device, thi machines and card readers. Voltage : 220-240 VAC +/- 10% Frequency: 50/60 Hz +/- 5%, 16 A 	s is an interface to third party a	
(FDI) (Optional) Electrical Requirements Power Consumption Running (Average)	 Walk up Fax (One- or Two-line options, inc Wireless Connectivity Kit McAfee® Integrity Control Enablement Kit XPS Print Option Kit Also known as Auxiliary Access Device, thi machines and card readers. Voltage : 220-240 VAC +/- 10% Frequency: 50/60 Hz +/- 5%, 16 A WorkCentre 5865 	s is an interface to third party o WorkCentre 5875	WorkCentre 5890
(FDI) (Optional) Electrical Requirements Power Consumption Running (Average) Standby Mode	 Walk up Fax (One- or Two-line options, inc Wireless Connectivity Kit McAfee® Integrity Control Enablement Kit XPS Print Option Kit Also known as Auxiliary Access Device, thi machines and card readers. Voltage : 220-240 VAC +/- 10% Frequency: 50/60 Hz +/- 5%, 16 A WorkCentre 5865 1,550 watts 	s is an interface to third party o WorkCentre 5875	WorkCentre 5890
(FDI) (Optional) Electrical Requirements Power Consumption Running (Average) Standby Mode Low Power Mode	 Walk up Fax (One- or Two-line options, inc Wireless Connectivity Kit McAfee® Integrity Control Enablement Kit XPS Print Option Kit Also known as Auxiliary Access Device, thi machines and card readers. Voltage : 220-240 VAC +/- 10% Frequency: 50/60 Hz +/- 5%, 16 A WorkCentre 5865 1,550 watts 310 watts 	s is an interface to third party a WorkCentre 5875 1,600 watts	WorkCentre 5890
(FDI) (Optional) Electrical Requirements Power Consumption Running (Average) Standby Mode Low Power Mode Auto Off/ Sleep mode	Walk up Fax (One- or Two-line options, inclusted on the second strength of the sec	WorkCentre 5875 1,600 watts	WorkCentre 5890 1,650 watts
(FDI) (Optional) Electrical Requirements Power Consumption Running (Average) Standby Mode Low Power Mode Auto Off/ Sleep mode Warm up (from Off)	Walk up Fax (One- or Two-line options, inc. Wireless Connectivity Kit McAfee® Integrity Control Enablement Kit XPS Print Option Kit Also known as Auxiliary Access Device, thi machines and card readers. Voltage : 220-240 VAC +/- 10% Frequency: 50/60 Hz +/- 5%, 16 A WorkCentre 5865 1,550 watts 310 watts <160 watts	WorkCentre 5875 1,600 watts	WorkCentre 5890 1,650 watts
(FDI) (Optional) Electrical Requirements Power Consumption Running (Average) Standby Mode Low Power Mode Auto Off/ Sleep mode Warm up (from Off) Low Power Recovery	Walk up Fax (One- or Two-line options, inclusted wireless Connectivity Kit McAfee® Integrity Control Enablement Kit XPS Print Option Kit Also known as Auxiliary Access Device, thi machines and card readers. Voltage : 220-240 VAC +/- 10% Frequency: 50/60 Hz +/- 5%, 16 A WorkCentre 5865 1,550 watts 310 watts <160 watts	WorkCentre 5875 1,600 watts	WorkCentre 5890 1,650 watts
(FDI) (Optional) Electrical Requirements Power Consumption Running (Average) Standby Mode Low Power Mode Auto Off/ Sleep mode Warm up (from Off) Low Power Recovery Recovery from Sleep	Walk up Fax (One- or Two-line options, inclusted on the second stress of the second	WorkCentre 5875 1,600 watts	WorkCentre 5890 1,650 watts
(FDI) (Optional) Electrical Requirements Power Consumption Running (Average) Standby Mode Low Power Mode Auto Off/ Sleep mode Warm up (from Off) Low Power Recovery Recovery from Sleep Operating Environment Required Temperature	Walk up Fax (One- or Two-line options, inclusted wireless Connectivity Kit McAfee® Integrity Control Enablement Kit XPS Print Option Kit Also known as Auxiliary Access Device, thi machines and card readers. Voltage : 220-240 VAC +/- 10% Frequency: 50/60 Hz +/- 5%, 16 A WorkCentre 5865 1,550 watts 310 watts <160 watts	WorkCentre 5875 1,600 watts	WorkCentre 5890 1,650 watts
Foreign Device Interface (FDI) (Optional) Electrical Requirements Power Consumption Running (Average) Standby Mode Low Power Mode Auto Off/ Sleep mode Warm up (from Off) Low Power Recovery Recovery from Sleep Operating Environment Required Temperature Range Required Relative Humidity	Walk up Fax (One- or Two-line options, inclusion of Wireless Connectivity Kit McAfee® Integrity Control Enablement Kit XPS Print Option Kit Also known as Auxiliary Access Device, thi machines and card readers. Voltage : 220-240 VAC +/- 10% Frequency: 50/60 Hz +/- 5%, 16 A WorkCentre 5865 1,550 watts 310 watts <160 watts	WorkCentre 5875 1,600 watts	WorkCentre 5890 1,650 watts
(FDI) (Optional) Electrical Requirements Power Consumption Running (Average) Standby Mode Low Power Mode Auto Off/ Sleep mode Warm up (from Off) Low Power Recovery Recovery from Sleep Operating Environment Required Temperature Range Required Relative	Walk up Fax (One- or Two-line options, inclusted wireless Connectivity Kit McAfee® Integrity Control Enablement Kit XPS Print Option Kit Also known as Auxiliary Access Device, thi machines and card readers. Voltage : 220-240 VAC +/- 10% Frequency: 50/60 Hz +/- 5%, 16 A WorkCentre 5865 1,550 watts 310 watts <160 watts	WorkCentre 5875 1,600 watts	WorkCentre 5890 1,650 watts

Dimensions and Weight	Width	Depth	Height	Weight
Base Configuration with OCT	990 mm	650 mm	1,104 mm	123.3 kg
With Office Finisher 5865/5875 only)	1,209 mm	650 mm	1,104 mm	149.5 kg
With Office Finisher with Booklet Maker (5865/5875 only)	1,209 mm	650 mm	1,104 mm	165.5 kg
With High Volume Finisher	1,645 mm	650 mm	1,145 mm	192.8 kg
With High Volume Finisher with Booklet Maker, C Fold / Z Fold Unit and Post Process Inserter	1,995 mm	650 mm	1,180 mm	220.3 kg
High Capacity Feeder	389 mm	510 mm	510 mm	30 kg
Work Surface (Does not add to overall width if combined with High Capacity Feeder)	285 mm	-	-	-
Certifications				
	GOST NOM Blue Angel ECOLOGO® CE Mark Common Criteria (IEEE 2600.2 standard) Citrix® Certified WHQL IPv6 Ready MEDITECH SAP Cerner			
	To view the latest list of ce	rtifications, go to www	.xerox.com/OfficeCertificati	ions.
Paper Handling				
Single-pass Automatic Doc Capacity⁴	200 sheets			
Speed (Black and white and colour)	Up to 105 images per min Up to 200 ipm (duplex)	ute (ipm) (simplex)		
Paper Sizes Sensed	125 x 138 mm to 297 x 43	32 mm		
Weights	50 gsm to 160 gsm			
Bypass Tray				
Capacity⁴	100 sheets			
Sizes	Custom sizes: A6 to A3			
Weights	60 to 216 gsm			
Types	Bond Carbonless Card Stock Envelopes Hole punched Index Labels Letterhead Plain Preprinted Recycled Transparencies Tabs			

Trays 1 and 2		
Capacity ⁴	500 sheets each	
Sizes	Custom Sizes from A5 LEF to A3 SEF	
Weights	60 to 200 gsm	
Types	Bond Card Stock Glossy Hole punched Index Labels Letterhead Lightweight Card Stock Plain Preprinted Recycled Tabs	
High Capacity Tandem Tr	αγ	
Capacity⁴	Tray 3: 1,600 sheets Tray 4: 2,000 sheets	
Sizes	Standard Sizes: A4 LEF	
Weights	60 to 216 gsm	
Types	Bond Card Stock Glossy Hole punched Index Letterhead Lightweight Card Stock Plain Preprinted Recycled	
High Capacity Feeder (HC	F) (Optionαl)	
Capacity⁴	4,000 sheets Optional HCF Kits: 2,000 sheets with A4 HCF Kit or 2,000 sheets with A3 SEF HCF Kit (Optional)	
Sizes	A4 LEF Optional HCF Kits: A4 / A3	
Weights	60 to 216 gsm	
Types	Bond Card Stock Hole punched Index Letterhead Plain Preprinted Recycled	
Envelope Tray (Optional – Replaces Tray 2)		
Capacity ⁴	Up to 50 envelopes	
Sizes	DL, C5	
Weights	75 to 90 gsm	
Total Capacity		
Device Total Capacity ⁴	8,700 sheets	

Offset Catch Tray (UCT) (Up	tional on 5865/5875; not available with 5890)			
Capacity	Up to 300 sheets of 80 gsm			
Office Finisher (Optional wit	ith 5865/5875 only)			
Top Tray Capacity Stacking Tray Capacity	250 sheets unstapled of 80 gsm 2,000 sheets unstapled of 80 gsm or 1,000 sheets single stapled or 750 sheets dual stapled (A4)			
	A6 to A3 A5 to A3			
Weights	60 to 216 gsm			
Multiposition Stapling	50 sheets of 80 gsm			
Hole Punch (Optional)	2-4 Hole Punch			
Office Finisher with Booklet	Maker (Optional with 5865/5875 only)			
Top Tray Capacity Stacking Tray Capacity	250 sheets unstapled of 80 gsm 2,000 sheets unstapled of 80 gsm or 1,000 sheets single stapled or 750 sheets dual stapled (A4)			
	A6 to A3 A5 to A3			
Weights	60 to 216 gsm			
Multiposition Stapling	50 sheets of 80 gsm			
Hole Punch (Optional)	2-4 Hole Punch			
Booklet Making Capacity ³	40 booklets (2-15 sheets per booklet – 80 gsm or less)			
5	A4 SEF B4 SEF A3 SEF			
	2-15 sheets / 8-60 page booklet 60 to 90 gsm			
Folding	1-15 sheets / unstapled			
High Volume Finisher (HVF)	(Optional)			
	Top Tray – 250 sheets Stacking Tray – 3,000 sheets			
Sizes	A6 to A3 / 105 x 148 mm to 297 x 420 mm			
Weights	60 to 216 gsm			
Stapling⁴	100 sheets Single (any corner), dual, front, rear, SEF and 4-stitch			
	2-hole punch 4-hole punch and 4-hole "Swedish" punch			
High Volume Finisher with B	Booklet Maker (Optional)			
	Top Tray – 250 sheets Stacking Tray – 3,000 sheets			
Sizes	A6 to A3 / 105 x 148 mm to 297 x 420 mm			
_	60 to 216 gsm			
Stapling ⁴	100 sheets Single (any corner), dual, front, rear, SEF and 4-stitch			
	2-hole punch 4-hole punch and 4-hole "Swedish" punch			
Booklet Maker Capacity⁴	Tray stop up: 30 booklets (1-15 sheets per booklet) Tray stop down: Unlimited			
	A4 / 210 x 297 mm 216 x 356 mm A3 / 297 x 420 mm			
Booklet Maker Weights	60 to 216 gsm			
Saddle-stitch Stapling ⁴	Saddle-stitch (2-15 sheets / 8-60 page booklet)			
Folding	V-folding (1-15 sheets / unstapled)			

	nal with HVF with Booklet Maker)		
Capacity ⁴	50 sheets or unlimited capacity with tray stop in the down position		
Sizes	A4 / 210 x 297 mm		
Weights	60 to 216 gsm		
-	onal with HVF and HVF with Booklet Maker)		
Capacity⁴	250 sheets		
Sizes	A4 / 210 x 297 mm 216 x 356 mm A3 / 297 x 420 mm		
Weights	60 to 216 gsm		
Convenience Stapler (Optio	onal – recommend use with optional Work Surface)		
Capacity⁴	50-sheet stapling 5,000 staples Requires a separate outlet		
Сору			
First-copy-out Time	2.9 seconds from the Platen / 5.9 seconds from the Single-pass Automatic Document Feeder		
Sides (input:output)	1-1, 1-2, 2-2, 2-1		
Quantity	1 to 9,999		
Resolution (max.)	Up to 600 x 600 dpi		
Reduction / Enlargement	Variable zoom from 25 % to 400 % in 1 % increments		
Concurrency	Programme-ahead to allow job to be initiated while initial job is processed (Copy, Print, Fax and Scan)		
Copy Features	Annotation and Bates [™] stamping (with colour capability and font size adjustment) Authentication for Services Auto Paper Select Auto Reduction & Enlargement to fit selected paper size Auto Tray Switching Automatic 2-sided/Duplex Booklet Creation Build Job: (Enables page-level programming and also lets you proof each section or delete last section as the job is built) Collation Covers (Front only, front and back, back only, printed inside and out: Blank or Printed) Dividers (blank) Edge Erase Features Help (Intuitive text and graphic descriptions) ID Card Copy Image Quality Adjustments Image Shift (with Auto Centre option) Invert Image (negative or mirror image) Large Job Interrupt Multi-up (up to 15 columns by 15 rows) Sample Set Save Job Settings Stapling Transparencies		
Xerox® Copier Assistant®	Xerox [®] Copier Assistant [®] Software provides a PC-based alternative to the user interface touch screen. Used in conjunction with a customer-supplied PC attached via the USB port, this software supports text-to-speech, screen magnification and easy PC keyboard access to basic and advanced copy features. Section 508 compliant. For more information or to download Xerox [®] Copier Assistant for free, visit www.xerox.com		

Print		
First-print-out Time	As fast as 6.2 seconds	
Print Resolution	Up to 4800 x 1200, 256 shades of grey	
Print Features	Application Defaults Banner Sheet Enable / Disable Bidirectional Real-time Status Cover Selection Delay Print (specific time) User Permissions Image Options (Toner Saver, Standard, High Resolution) Job Identification (Print ID or Banner, Print ID in margins on first page only or all pages) Layout / Watermark (N-up) (up to 16 pages per sheet), Multi-up, Booklet layout / finishing, Fit to new paper size Overlays Paper Selection by Attribute LAN Fax (requires optional Fax Kit) Sample Set Secure Print with Timed Deletion Special Pages (exception page programming: covers, inserts, exception pages) Store and Recall Driver Settings Saved Job Sustainability Features (Xerox® Earth Smart Settings, Duplex, N-up, Turn-off Banner and Print ID, Smart Sample Set Hold All Jobs)	
Print from USB	Allows walk-up printing from Type A USB port on front panel Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TIFF, PS, XPS ³ , PCL	
Operating Systems	Microsoft® Windows® XP SP3 (32- and 64-bit) Windows Server 2003 R2 (32- and 64-bit) Windows Server 2008 and R2 (32- and 64-bit) Windows Server 2012 and R2 Windows Vista SP2 (32- and 64-bit) Windows 7 (32- and 64-bit) Windows 8 (32- and 64-bit) Windows 8.1 (32- and 64-bit) Mac OS 10.7, 10.8, 10.9 Linux Redhat Fedora Core 19 X86 Ubuntu 13.10 X64 openSUSE 13.1 X64	
Network Protocols	TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6,WSD NetWare: Bindery and NDS IPX/SPX, NDPS®/NEPS (with Server Gateway) AppleTalk®: EtherTalk® Microsoft Windows Networking over IP Bonjour® IPv6 Secure FTP Most protocols not in use can be disabled	
Administrative Protocols	DHCP, BOOTP, SNMP, WINS, SLP [®] v2, HTTP, HTTPS, DHCP Autonet, SSL, NTP, DNS, SSDP	
Fonts	PCL: 93 scalable fonts, line printer and bitmap font (including Cyrillic font support) PostScript 3: 173 Type 1 fonts, 2 Multiple Master fonts	
Xerox® Mobile Express Driver®	Makes it easy for mobile users to find, use and manage Xerox [®] and non-Xerox devices in every new location. Plug into a new network, and Mobile Express Driver automatically discovers available printers and provides status and capability information. Save a list of "favourite" printers for each location, store application print settings for use or any printer in any network, and greatly reduce mobile support calls to IT.	
Xerox® Global Print Driver®	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox [®] and non-Xerox devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.	
Xerox [®] Pull Print Driver	Makes it easy for IT managers to qualify, deploy and manage all print devices using a single driver in a Pull Print environment. Uses a single queue and single driver. The Xerox® Pull Print Driver extends convenience across a broad range of printing assets. IT administrators no longer need to manage and configure multiple drivers. Used ir conjunction with Xerox Secure Access Unified ID System®, Equitrac Office®, Ysoft® SafeQ®, Pharos® and others.	

Print Solutions			
Xerox® Mobile Print Cloud (Optional)	Xerox [®] Mobile Print Cloud addresses the needs of businesses with a mobile workforce and puts you ahead of the evolving mobile print need, but without burdening staff, budget or infrastructure. Getting started takes only a few minutes via the cloud. Print from any mobile device to nearly any brand of printer. Accurate printing with true Microsoft [®] Office [®] rendering and more. Print what you need, when, where and how you need it.		
Xerox® Mobile Print Solution (Optional)	Xerox [®] Mobile Print Solution is an ideal choice for sites that have additional requirements for control and security with an onsite server. Xerox [®] Mobile Print Solution allows users to print from most mobile devices to nearly any brand of printer or multifunction printer without drivers or added complexity. Simply enter a release code (PIN) at the device and get accurate printing with true Microsoft Office rendering and more to use with your server for private, onsite deployment.		
Unified Address Book for Fo	ax, Internet Fax, Email and Scan to		
Features	Services supported: Fax, Internet Fax, Email, Scan to Maximum contacts: 5,000 Contacts: Supports 1 or more destinations Favourites for quick access of fax numbers, emails, etc.		
Additional Scan Informatic	on		
Concurrency	Scan while the system is printing, copying, or while it is transferring scan to network or fax jobs (priority is for return of scanned originals and printing concurrent jobs)		
Input Speed	Scan at up to 200 ipm (duplex) colour scanning and black and white – A4 LEF		
Resolution	72 x 72 dpi to 600 x 600 dpi Bit Depth: 1-bit (black and white), 8-bit (greyscale), 24-bit (colour)		
Maximum Scan Area	A3		
Scan Template Management	Support 250 scan templates Create Xerox® CentreWare IS scan templates and share via device cloning to other multifunction printers Confirmation sheet options		
Network Protocols	sFTP, FTP, SMB, NetWare, HTTP, HTTPS		
File Compression	Colour TIFF (TIFF 6.0 or TTN2 with JPEG, LZW) Black and white TIFF (G3MH, G4 MMR compression–single or multiple pages) Searchable PDF and PDF/A (MRC, JPEG, G3 MH, G4 MMR, JBIG 2 Huffman, JBIG Arithmetic Compression, Deflate (for Black and white and within MRC)) Linearised PDF / PDF/A		
Document Management Fields (Meta Data)	 Features only available in Network Scan to File Templates: 1 to 6 user programmable metadata fields per network scan to file templates and unlimited fields within the template – Metadata field consists of field name, default value and other configurations Customised fields viewed on user interface for variable data input 		
Scan Features	Mixed Size Originals Scan Build Job Compression Quality/File Size Control Original Type (Photo and Text, Photo, Text, Map, Newspaper / Magazine) Auto Background and Shadow Suppression Size for Size (for mixed size originals) TWAIN Support/WIA Support Bound Originals Edge Erase Reduction/Enlargement Single Touch Scan buttons (up to 10)		
Scan to Email (Standard)			
Scan Features	 Email signatures (6 lines each of 128 character max), email message body (user configurable), email CentreWare IS confirmation sheet options Scan to Email S/MIME Encryption Email signing (requires Smart Card option) Auto send to self 		
Directory Access	Address list via LDAP (Windows Active Directory, Exchange, Notes, Domino) Downloaded address list (comma-separated file format)		
Scan to (Standard)			
Features	Scan to USB Scan to Network Folder (uses Unified Address Book entries)		

Network Scanning – Softwo	nre Solutions		
Xerox® Scan to PC Desktop® Professional (Optional)	 A desktop offering that provides advanced document imaging, archiving, editing and organisation tools: PaperPort Professional image viewing and file management software Complete PDF functionality Secure PDF workflow of all scanning applications OmniPage Pro Office (for desktop/client installation) – Professional OCR software for digital archiving and document conversion Image Retriever – provides fully automated retrieval of scanned images direct from a scan enabled Xerox[®] WorkCentre to individual desktops. Also includes email inbox polling capability 		
Xerox® ConnectKey® for SharePoint® (Optional)	Xerox [®] ConnectKey for SharePoint simplifies and streamlines the way you scan, capture and store your paper-based documents. Using your Xerox [®] multifunction printer, you can route documents directly into the precise document repository folder, just like you would from your PC. At the multifunction printer, you can browse to the folder, name the document, and add any key indexing information before you scan. With the flexibility to capture and route to SharePoint as well as Windows folders, ConnectKey is the right solution for any office that needs to archive and share paper-based documents.		
Xerox® ConnectKey® Share to Cloud (Optional)	ConnectKey Share to Cloud, provides organisations with powerful, easy and secure document scanning capabilities that connect your Xerox® multifunction printer to popular cloud services and email, such as Google Docs, SalesForce.com, Office 365 and Dropbox™ and gives employees anytime, anywhere access to their most important documents using mobile devices.		
Xerox® ConnectKey® for DocuShare® (Optional)	Xerox [®] ConnectKey for DocuShare, a one step scan-to-workflow solution, simplifies the process of incorporating hard copy content into enterprise document flows. Users can easily scan documents directly into a DocuShare collection or Windows folder via a multifunction printer.		
Security			
Features	 Expanded Authentication Network authentication to access device and/or device services via- Kerberos (UNIX / Windows Server 2003 / Windows Server 2008), SMB (Windows Server 2003 / Windows Server 2008), NDS, LDAP Xerox Secure Access Unified ID System[®] Local Authentication (internal database) Smart Card authentication -144k CAC/PIV Card Support (2048 bit certificate key)/ .NET Secure Data Digitally signed PDF (when using Smart Card authentication) Encrypted Scan to Email Encrypted / Password Protected PDF (Email and Network Scan Templates only) Secure Print (up to 10 digit PIN or Network Authentication) Immediate Image Overwrite On Demand Image Overwrite (Scheduled, Manual), includes sanitation of unused area of disk FIPS 140-2 256 bit Hard Disk Encryption Expanded Authorisation SA access based on network credentials Authorisation per user per service User Permissions required to access Print and Print Features (e.g. colour access, or time restrictions) reflects in the print driver Secure Network Access IP Filter, IPsec, IPv6, SSLv3.0, SNMPv3, HTTPs, 802.1X, Cisco[®] TrustSec Identity Services Engine (ISE) integration, Device Security McAfee[®] Embedded Security, Port disablement including USB ports, Audit Log, Hide Print Job Names, McAfee Integrity Control (optional) Common Criteria Certification ISO 15408 		
Xerox Secure Access Unified ID System® (Optional)	Xerox [®] Secure Access Unified ID System integrates your Xerox [®] multifunction printers with your existing employee/ student ID PIN or badge providing a flexible and convenient authentication system. Allow your staff, employees or students to send documents to a centralised print server. Then, at any multifunction printer on the network, they'll simply log in with a swipe of their magnetic or proximity ID card or their PIN to securely print their job. For more information, go to www.office.xerox.com/software-solutions		
Fax			
Network Server Fax Feature	25		
Compatibility	ITU (CCITT) group 3 Various Xerox® Alliance Partner Solutions		
Maximum Scan Area	A3		
Fax Send Features	One- or two-sided scanning (up to A3) Add to send list (50 numbers maximum) Build Job, Favourites, Delay send (specific time) Original type (photo, text or photo and text)		
Fax Print Features	One- or two-sided printing, staple, Secure Print		
Transmission Resolution	Superfine: 400 x 200 dpi (Scan at 600 x 600 dpi) Fine: 200 x 200 dpi Standard: 200 x 100 dpi		

Capability	Direct print-ready document transmission to remote Internet Fax machines or email clients (SMTP) Reception and automatic printout of documents sent via email from remote Internet Fax machines or email clients		
Directory Access	Utilises the Unified Address Book		
Send / Receive	Multi-page TIFF, Image only PDF		
Resolution	72 x 72 dpi to 600 x 600 dpi Bit Depth: 1-bit (black and white)		
Network Protocols	SMTP (send), POP3 (receive)		
Compliance	ITU-T T.37 compliant		
Walk-up Fax Features (Opti	ional (Customer-installable) – 1 and 2 lines)		
Compatibility	ITU (CCITT) Group 3		
Speed / Modems	One or Two V.34 modems: 33,600 bps. Less than 4 seconds per page transmission time ATA analogue terminal adaptor utilising T38 (optional)		
Compression / Speed	MH/G3, MMR/SG3		
Resolution	Walkup Send:Standard: 200 x 100 dpiFine: 200 x 200 dpiSuperfine: 600 x 600 dpiReceive:Accepts all sizes		
Fax Send Features	LAN Fax (fax from print driver) Auto Fax Transmission Reduction Page-by-page Job Status at the Machine Delay Start, Build Job, Favourites Automatic Memory Resend Automatic Cover Sheets PSTN Fax Batch Send (up to memory capacity)		
Fax Receive Features	One- or Two-sided Printing Stapled or Unstapled Receive Print Mode – Manual (size, margin, stock, header) / Auto Output Tray Selection Up to 200 Password Protected Mailboxes Secure Receive Receive Timestamp Auto Answer Delay		
Fax Forward	Forward to Email or SMB Location Fax forward on receive only		
Fax Reports	Activity, Dial Directory, Group Directory, Transmission Confirmation, Pending Fax, Options Report, On Demand Overwrite Report, Mailbox Report, Broadcast Report		
Directory Access	Utilises the Unified Address Book Group fax available		
Auto Redial	Up to 14 attempts (per country requirements) • 1 to 25 minute intervals)		
Auto Resend	Up to 5 attempts		
Device Management			
Management Support	SNMP Version 1. SNMP Version 2c and SNMP Version 3 trap over TCP/IP and IP MIB access (IETF-MIBII RFC 1213), Host Resources MIB RFC 2790, Printer MIB RFC 1759 v.2		
Xerox® CentreWare® Web	 A Web-based server application for network administrators that permits Web browser-based device management from any workstation, whether running Windows, UNIX or any other operating system: Works with any SNMP-managed printer from any manufacturer. Provides help with device discovery and installation, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management. 		
	 Requires Windows XP, Vista or Windows 7 and Internet Explorer 6.0 and higher. CentreWare Integration available for Tivoli[®] NetView[®], Unicentre TNG[®], Microsoft Management Console (MMC) HP[®] OpenView[®] 		

Xerox® Device Manager	 Xerox[®] Device Manager collects and manages the data that drives fact-based decisions for your enterprise device management environment. It is a single tool to install print queues and configure, manage, monitor and report on both networked and locally connected devices – regardless of vendor – across your enterprise. Xerox[®] Device Manager provides: Device monitoring and troubleshooting Extensive reporting and discovery of new devices Usage collection, chargeback and billing capabilities 		
Xerox [®] Device Types for SAP Environment	Xerox, together with SAP through our Gold-level membership in the SAP Printer Vendor Programme, provides seamless connectivity between SAP systems and your Xerox® printers and multifunction printers. And as an SAP customer you benefit from having SAP-certified Xerox® device types available right from SAP's online delivery model. SAP-certified device types for Xerox® printers and multifunction printers are available to download. www.office.xerox.com/software-solutions		
Xerox® Device Types for SAP R/3 Intelligent Barcode Utility (optional)	Provides built-in process intelligence that allows the printing of barcodes on any appropriately configured PostScript printer in specific versions of SAP environment and within Latin-1 (ISO8859-1) SAP system code pages only. Used in conjunction with Xerox [®] PostScript Device Types for SAP environment and Xerox [®] Font Centre Barcode Fonts. Information available at www.office.xerox.com/software-solutions		
Xerox® Barcode Pro PS (optional)	Enables intelligent PostScript printing on Xerox [®] multifunction printers by storing Xerox [®] software, as well as, the barcode fonts on the printer hard disk. Enables the printing of barcodes from any application (SAP client or mainframe) that supports PostScript printing. Information available at www.office.xerox.com/software-solutions		
CentreWare Internet Servi	ces – Integrated Web Pages Provided by the Device		
Device Status	Web server embedded in Network Controller: • Tray status/contents • Consumables status • Alerts Remote Control Panel		
Job Submission	Print ready files: PS, PCL, TIFF, PDF, JPG, XPS ³ , TXT, PRN Output feature selection (2-sided, output colour, collate, orientation, staple, hole punch, folding, output destination) Delivery options (Immediate, sample set, delay and secure, Save job or reprint)		
Device Administration	Allows simple, remote installation setting of configuration options and management of the device		
Browsers	Internet Explorer 7.x, 8.x, 9.x Safari 5.x Mozilla Firefox 4.x, 5.x, 6.x, 7.x, 8.x, 9.x, 10.x, 11.x Opera 11.x Chrome 12		
Support	Install print / scan drivers and online support available via web page		
Languages Supported	International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Russian, Simplified Chinese, Korean, Japanese		
Remote Print Services			
Automated Meter Reads (AMR)	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox [®] device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.		
Automatic Supplies Replenishment (ASR)	Automatically orders supplies for Xerox® output devices based on actual usage, eliminating the need to manually manage supplies inventory.		
Accounting			
Xerox [®] Standard Accountin	ng (Standard)		
Tracking	Copy, Print, Fax, Scan and Email usage		
Accounting	Up to 2,497 User accounts (User ID) Up to 500 General accounts (Client) Up to 498 Group accounts (Department)		
Features	 Administrator can manage the feature via the Web User Interface or device control panel in tools Administrator has the ability to import or export user accounts, Group Accounts, General Accounts and User limits via an industry standard CSV file 		
Accounting Options – Netv	work Accounting – Third Party Enablement		
	 Enhanced network accounting with up to the minute data on how the system is being used Comprehensive management and enterprise scale tracking and reporting of device usage of copy, print, scan and server fax Other solutions are available through Xerox® Alliance Partners. For details visit www.xerox.com Security enhancements with the addition of HTTPS protocol support Device requests account authentication from third party server enabling larger databases of users and accounts Accept Authentication Login at control panel and pass to third party Networking Account Interface with third party accounting terminal for accounting user interface 		

Supplies	Description	Quantity	Part Number
Toner Cartridge	Includes 2 Toner Cartridges and Waste Toner Bottle	110,000 pages ^s (55,000 pages each) ^s	006R01552
Waste Toner Bottle	Supplied with each Toner Cartridge Box	100,000 pages⁵	008R12896
Staple Cartridges	Office Finisher (5865/5875 only)	5,000 per cartridge (15,000 staples)	108R00493
	Office Finisher with Booklet Maker (5865/5875 only)	5,000 per cartridge (15,000 staples)	108R00493
	Office Finisher with Booklet Maker – saddle-stitch stapling (5865/5875 only)	2,000 per cartridge (8,000 staples)	108R01158
	HVF and HVF with Booklet Maker - Complete Cartridge - Refill Cartridge	5,000 per cartridge 5,000 per cartridge (15,000 staples)	008R12912 008R12898
	HVF with Booklet Maker – saddle-stitch stapling	2,000 per cartridge (16,000 staples)	008R12897
	Convenience Stapler - Complete Cartridge - Refill Cartridge	5,000 per cartridge 5,000 per cartridge (15,000 staples)	008R12964 008R12941
Xerox [®] Smart Kit [®]	·		
Fuser Module	Includes Ozone Filter	400,0005	109R00772
Xerographic Module – Metered (Print Cartridge)		450,000 ^₅	109R00672
Xerographic Module – Sold (Print Cartridge)		450,000⁵	113R00673
Document Handler Feeder Rolls		150,000 feeds	113R00718

¹ Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

² Expected regular monthly throughput.

³ XPS option is required to print XPS files.

⁴ Paper capacities are based on 75 gsm stock; capacities will vary with different weight stocks.

⁵ Approximate pages. Declared Yield based on 5 page job size, 6% area coverage, using A4 media. Yield will vary based on media size, image area coverage, media orientation and usage patterns.

Return spent imaging supplies through the Xerox[®] Green World Alliance collection/reuse/recycling programme. For more information, visit www.xerox.com/about-xerox/recycling.

For more information, call or visit us at www.xerox.com/office



©2014 Xerox Corporation. All rights reserved. Xerox®, Xerox and Design®, ConnectKey®, Copier Assistant®, DocuShare®, Global Print Driver®, Mobile Express Driver®, Scan to PC Desktop®, SmartKit®, WorkCentre[™] and Xerox Secure Access Unified ID System® are trademarks of Xerox Corporation in the United States and/or other countries. Mopria[™] is a trademark of the Mopria Alliance. As an ENERGY STAR® partner, Xerox Corporation has determined that this product meets the ENERGY STAR guidelines for energy efficiency. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. All other trademarks are the property of their respective manufacturers. The information in this brochure is subject to change without notice. Updated 12/14 WSVSS-01EA