Xerox[®] WorkCentre[®] 5865i/5875i/5890i Multifunction Printer

WorkCentre 5800i Series multifunction printers are built on Xerox[®] ConnectKey[®] Technology. For more information, go to **www.connectkey.com**.

			h Volume sher (HVF)	
	High Capacity Feeder	Booklet Maker for Office Finisher	HVF Booklet Maker for HVF	
System Specifications	WorkCentre 5865i	WorkCentre 5875i	WorkCentre 5890i	
Simplex Speed 8.5 x 11 in. / A4 (LEF) 8.5 x 13 to 8.5 x 14 in. / A4 to B4 (SEF) 11 x 17 in. / A3 (A3 SEF) (Bypass Tray will reduce speed by 10 to 20%)	65 ppm 49 ppm 42 ppm	75 ppm 49 ppm 42 ppm	90 ppm 54 ppm 47 ppm	
Auto Duplex Speed				
8.5 x 11 in. / A4 (LEF)	Up to 65 ppm (32.5 sheets)	Up to 75 ppm (37.5 sheets)	Up to 90 ppm (45 sheets)	
Monthly Duty Cycle ¹	Up to 250,000 pages	Up to 300,000 pages	Up to 400,000 pages	
Recommended Average Monthly Print Volume ²	25,000 to 110,000 pages	30,000 to 125,000 pages	50,000 to 150,000 pages	
Hard Drive / Processor / Memory	Minimum 250 GB HDD / 1 GHz Dual-core / 2 GB system			
Connectivity	10/100/1000Base-T Ethernet, High-Speed USB 2.0 direct print, Wi-Fi Direct wth Optional Xerox® USB Wireless Adapter			
Controller Features	Unified Address Book, Remote Control Panel, Online Support (accessed from the user interface and print driver), Configuration Cloning			
Copy and Print	1			
Copy and Print Resolution	Copy: Up to 600 x 600 dpi; Print: Up to 4800 x 1200, 256 shades of gray			
First-print-out Time	As fast as 2.9 seconds			
First-copy-out Time	As fast as 2.9 seconds from the Platen / 5.9 seconds from the Automatic Document Feeder			
Page Description Languages	Adobe® PostScript® 3™, Adobe® PDF version 1.7, PCL® 5c / PCL 6, XML Paper Specification (XPS®) (Optional)			
Print Features	Print from USB, Encrypted Secure Print, Xerox® Earth Smart Driver Settings, Job Identification, Booklet Creation, Store and Recall Driver Settings, Bi-directional Real-time Status, Scaling, Job Monitoring, Application Defaults, Two-sided Printing (as default), Hold All Jobs			
Mobile Printing and Apps	Standard: Apple® AirPrint [™] , Mopria® Certified, QR Code App, Xerox® App Gallery App, @PrintByXerox App; Free Download: Xerox® Print Service Plug-in for Android, Mopria® Print Service Plug-in for Android [™] , Xerox® Mobile Link App; Optional: Xerox® Mobile Print, Xerox® Mobile Print Cloud, Xerox® Easy Translator Service			
Scan				
Standard Features	Destinations: Scan to Mailbox, Scan to USB, Scan to Email, Scan to Network; File Formats: PDF, PDF/A, XPS, JPEG, TIFF; Convenience Features: Scan to Home, Single Touch Scan, Searchable PDF, Single/Multi-Page PDF / XPS / TIFF, Encrypted / Password Protected PDF, Linearized PDF / PDF/A			
Optional Features	ConnectKey® for DocuShare®, Xerox® Scan to PC De	esktop® SE and Professional, other solutions available	through various Xerox Business Innovation Partners	
Fax				
Standard Features	Internet Fax, Fax Build Job, Network Server Fax Ena	Iblement		
Optional Features	Fax Forward to Email or SMB, Walk-up Fax (one-line	e and two-line options, includes LAN Fax)		
Security				
Standard Features	Authentication, Common Criteria Certification (ISC	tible, HDD Overwrite, AES 256-bit Encryption (FIPS 1-) 15408) (undergoing evaluation), Encrypted Secure , Network Authentication, TLS, SNMPv3, Audit Log, Av	Print, Secure Fax, Secure Scan, Secure Email, Cisco®	
Ontional Features	Matter Tales at Control Constraints white			

McAfee Integrity Control, Smart Card Enablement Kit (CAC/PIV/.NET), Xerox® PrintSafe Software

Optional Features

Device Specifications					
Control Panel Languages	US English, International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Turkish, Greek, Russian, Czech, Polish, Hungarian, Romanian, Catalan, Arabic				
Accessories					
Optional	High Capacity Feeder (HCF) HCF Kit (Letter/Legal SEF) (HCF requi Envelope Tray (Replaces Tray 2) Office Finisher (optional with 58: Office Finisher (optional with 58: Office Finisher with Booklet Make Hole Punch for Office Finisher (op High Volume Finisher High Volume Finisher High Volume Finisher with Booklet Z Fold / C Fold Unit (with High Vo Post Process Inserter (with High Vo Convenience Stapler (includes W Smart Card Enablement Kit Walk up Fax (One- or Two-line op Wi-Fi Direct with Optional Xerox ⁴ McAfee [®] Integrity Control Enable XPS Print Option Kit	red) 65i/5875i only) er (optional with 58 ptional with 5865i/ et Maker olume Finisher with Volume Finisher with Volume Finisher with ork Surface) •tions, includes LAN • USB Wireless Ada	(5875i only) I Booklet Maker) th Booklet Maker) I Fax)		
Foreign Device Interface (FDI) (Optional)	Also known as Auxiliary Access D	evice, this is an int	erface to third par	ty access control devices, such a	s coin machines and card readers.
Electrical Requirements					
North America	Voltage: 110-127 VAC +/- 10 % Frequency: 50/60 Hz +/- 5 %, 20 A				
Europe	Voltage: 220-240 VAC +/- 10% Frequency: 50/60 Hz +/- 5%, 16 A				
Power Consumption	WorkCentre 5865i		WorkCentre 58	75i	WorkCentre 5890i
Running (Average)	1,550 watts		1,600 watts		1,650 watts
Standby Mode	310 watt	310 watt			
Low Power Mode	≤160 watts				
Auto off / Sleep mode	≤4 watts (Default time to sleep = 2 minutes)				
Warm up	Time from power off to when services are displayed: As fast as 170 seconds				
Low Power Recovery	<4 seconds				
Recovery from Sleep	<28 seconds				
Operating Environment					
Required Temperature Range	50° to 90° F (10° to 32° C)				
Required Relative Humidity	15% to 85%				
Sound Power Levels	Operating 7.2 B(A), Standby: 5.0	B(A)			Operating 7.3 B(A), Standby: 5.0 B(A)
Sound Pressure Levels	Operating: 57 dB(A), Standby: 35	Operating: 57 dB(A), Standby: 35 dB(A) Operating: 58 dB(A), Standby: 35 dB(A)			
Dimensions and Weight	Width	Depth		Height	Weight
Base Configuration with OCT	39.0 in. / 990 mm	25.6 in. / 650) mm	43.5 in. / 1,104 mm	271.8 lbs. / 123.3 kg
With Office Finisher (5865i/5875i only)	47.6 in. / 1,209 mm	25.6 in. / 650 mm 43.5 in. / 1,104 mm		43.5 in. / 1,104 mm	329.6 lbs. / 149.5 kg
With Office Finisher with Booklet Maker (5865i/5875i only)	47.6 in. / 1,209 mm	25.6 in. / 650 mm 43.5 in. / 1,104 mm		43.5 in. / 1,104 mm	364.9 lbs. / 165.5 kg
With High Volume Finisher	64.8 in. / 1,645 mm	25.6 in. / 650) mm	45.1 in. / 1,145 mm	425.1 lbs. / 192.8 kg
With High Volume Finisher with Booklet Maker, C Fold / Z Fold Unit and Post Process Inserter	78.5 in. / 1,995 mm	25.6 in. / 650) mm	46.5 in. / 1,180 mm	485.7 lbs. / 220.3 kg
High Capacity Feeder	15.3 in. / 389 mm	20.1 in. / 510) mm	22.6 in. / 510 mm	66.1 lbs. / 30 kg
Work Surface (Does not add to overall width if combined with High Capacity Feeder	11.2 in. / 285 mm	_		-	-

Certifications	
Certifications	
	FCC Class A Compliant (US), ICES Class A Compliant (Canada) CSA Listed (UL 60950-1, Second Edition)
	CB Certified (IEC 60950-1, Second Edition)
	GS Mark
	ENERGY STAR® EPEAT (United States)
	GOST
	NOM
	Apple [®] AirPrint [™] 1.4 Certification Mopria [®] Certified
	Wi-Fi Direct Certification
	Blue Angel
	ECOLOGO® CE Mark
	Common Criteria (IEEE 2600.2 standard) (undergoing evaluation)
	Citrix® Certified
	WHQL IPv6 Ready
	MEDITECH
	SAP
	Cerner To view the latest list of certifications, go to www.xerox.com/OfficeCertifications.
Paper Handling	
Single-pass Automatic Document	Feeder
Capacity ³	200 sheets
Speed (Black-and-white and	Up to 105 images per minute (ipm) (simplex)
color)	Up to 200 ipm (duplex)
Paper Sizes Sensed	4.9 x 5.4 in. to 11.7 x 17 in. / 125 x 138 mm to 297 x 432 mm
Weights	13 lb. bond to 43 lb. bond / 50 gsm to 160 gsm
Bypass Tray	
Capacity ³	100 sheets
Sizes	Custom sizes: 4.25 x 5.5 in. to 11 x 17 in. / A6 to A3
Weights	16 lb. bond to 80 lb. cover / 60 to 216 gsm
Туреѕ	Bond
	Carbonless Card Stock
	Envelopes
	Hole punched
	Index
	Labels Letterhead
	Plain
	Preprinted
	Recycled Transparencies
	Tabs
Trays 1 and 2	
Capacity ³	500 sheets each
Sizes	Custom Sizes from 5.5 x 8.5 in. LEF to 11 x 17 in. SEF / A5 to A3
Weights	16 lb. bond to 53 lb. bond / 60 to 200 gsm
Types	Bond Card Stock
	Glossy
	Hole punched
	Index Labels
	Labels Letterhead
	Lightweight Card Stock
	Plain
	Preprinted Recycled
	Tabs

High Capacity Tandem Tray	
Capacity ³	Tray 3: 1,600 sheets
capacity	Tray 4: 2,000 sheets
Sizes	Standard Sizes: 8.5 x 11 in. LEF / A4
Weights	16 lb. bond to 53 lb. bond / 60 to 216 gsm
Types	Bond Card Stock Glossy Hole punched Index Letterhead Lightweight Card Stock Plain Preprinted Recycled
High Capacity Feeder (HCF) (Optio	nal)
Capacity ³	4,000 sheets Optional HCF Kits: 2,000 sheets with Letter/Legal HCF Kit or 2,000 sheets with Tabloid SEF HCF Kit (Optional)
Sizes	8.5 x 11 in. / A4 LEF Optional HCF Kits: 8.5 x 11 in. / A4 or 11 x 17 in. / A3
Weights	16 lb. bond to 58 lb. bond / 60 to 216 gsm
Types	Bond Card Stock Hole punched Index Letterhead Plain Preprinted Recycled
Envelope Tray (Optional - Replaces	Tray 2)
Capacity ³	Up to 50 envelopes
Sizes	#10 Commercial (9.25 x 4.125 in.), #9 Commercial (8.875 x 3.875 in.), Monarch, DL, C5
Weights	20 lb. bond to 24 lb. bond / 75 to 90 gsm
Total Capacity	
Device Total Capacity ³	8,700 sheets
Finishing	
Offset Catch Tray (OCT) (Standard	on 5865i/5875i; not available with 5890i)
Capacity	Up to 300 sheets of 20 lb. bond / 80 gsm
Office Finisher (Optional with 5865	
Top Tray Capacity Stacking Tray Capacity	250 sheets unstapled of 80 gsm 2,000 sheets unstapled of 80 gsm or 1,000 sheets single stapled or 750 sheets dual stapled (8.5 x 11 in. / A4)
Top Tray Sizes Stacking Tray Sizes	4.25 x 5.85 in. to 11 x 17 in. / A6 to A3 5.5 x 8.5 in. to 11 x 17 in. / A5 to A3
Weights	16 lb. bond to 58 lb. bond / 60 to 216 gsm
Multiposition Stapling	50 sheets of 20 lb. bond / 80 gsm
Hole Punch (Optional) North America: Europe:	2-3 Hole Punch 2-4 Hole Punch
Office Finisher with Booklet Maker	(Optional with 5865i/5875i only)
Top Tray Capacity Stacking Tray Capacity	250 sheets unstapled of 80 gsm 2,000 sheets unstapled of 80 gsm or 1,000 sheets single stapled or 750 sheets dual stapled (8.5 x 11 in. / A4)
Top Tray Sizes Stacking Tray Sizes	4.25 x 5.85 in. to 11 x 17 in. / A6 to A3 5.5 x 8.5 in. to 11 x 17 in. / A5 to A3
Weights	16 lb. bond to 58 lb. bond / 60 to 216 gsm
Multiposition Stapling	50 sheets of 20 lb. bond / 80 gsm
Hole Punch (Optional) North America: Europe:	2-3 Hole Punch 2-4 Hole Punch
Booklet Making Capacity ³	40 booklets (2-15 sheets per booklet – 20 lb. / 80 gsm or less)

Booklet Making Sizes	Letter – 8.5 x 11 in. / A4 SEF Legal – 8.5 x 14 in. / B4 SEF Ledger – 11 x 17 in. / A3 SEF		
Saddle-stitch Stapling	2-15 sheets / 8-60 page booklet 16 lb. bond to 24 lb. bond / 60 to 90 gsm		
Folding (unstapled)	1-5 sheets / unstapled		
High Volume Finisher (HVF) (Opt	ional)		
Capacity ³	Top Tray – 250 sheets Stacking Tray – 3,000 sheets		
Sizes	4.25 x 5.5 in. / to 11 x 17 in. / A6 to A3 / 105 x 148 mm to 297 x 420 mm		
Weights	16 lb. to 57 lb. bond / 80 lb cover / 60 to 216 gsm		
Stapling ³	100 sheets Single (any corner), dual, front, rear, SEF and 4-stitch		
Hole Punch (Optional) North America:	3-hole punch 2-hole Legal punch		
Europe:	2-hole punch 4-hole punch and 4-hole "Swedish" punch		
High Volume Finisher with Bookl			
Capacity ³	Top Tray – 250 sheets		
cupacity	Stacking Tray – 3,000 sheets		
Sizes	4.25 x 5.5 in. to 11 x 17 in. / A6 to A3 / 105 x 148 mm to 297 x 420 mm		
Weights	16 lb. to 57 lb. bond / 80 lb. cover / 60 to 216 gsm		
Stapling ³	100 sheets Single (any corner), dual, front, rear, SEF and 4-stitch		
Hole Punch (Optional)			
North America:	3-hole punch 2-hole Legal punch		
Europe:	2-hole punch 4-hole punch and 4-hole "Swedish" punch		
Booklet Maker Capacity³	Tray stop up: 30 booklets (1-15 sheets per booklet) Tray stop down: Unlimited		
Booklet Maker Sizes	Letter – 8.5 x 11 in. / A4 / 210 x 297 mm Legal – 8.5 x 14 in. / 216 x 356 mm Ledger – 11 x 17 in. / A3 / 297 x 420 mm		
Booklet Maker Weights	16 lb. to 57 lb. bond / 80 lb. cover / 60 to 216 gsm		
Saddle-stitch Stapling ³	Saddle-stitch (2-15 sheets / 8-60 page booklet)		
Folding	V-folding (1-15 sheets / unstapled)		
Z Fold / C Fold Unit (Optional wit	h HVF with Booklet Maker)		
Capacity ³	50 sheets or unlimited capacity with tray stop in the down position		
Sizes	Letter – 8.5 x 11 in. / A4 / 210 x 297 mm		
Weights	16 lb. to 57 lb. bond / 80 lb. cover / 60 to 216 gsm		
Post Process Inserter (Optional w	Post Process Inserter (Optional with HVF and HVF with Booklet Maker)		
Capacity ³	250 sheets		
Sizes	Letter – 8.5 x 11 in. / A4 / 210 x 297 mm Legal – 8.5 x 14 in. / 216 x 356 mm Ledger – 11 x 17 in. / A3 / 297 x 420 mm		
Weights	16 lb. to 57 lb. bond / 80 lb. cover / 60 to 216 gsm		
Convenience Stapler (Optional - 1	Includes Work Surface (North America))		
Capacity ³	50-sheet stapling 5,000 staples Requires a separate power outlet		

Сору	
First-copy-out Time	2.9 seconds from the Platen / 5.9 seconds from the Single-pass Automatic Document Feeder
Sides (input:output)	1-1, 1-2, 2-2, 2-1
Quantity	1 to 9,999
Resolution (max.)	Up to 600 x 600 dpi
Reduction / Enlargement	Variable zoom from 25% to 400% in 1% increments
Concurrency	Program-ahead to allow job to be initiated while initial job is processed (Copy, Print, Fax and Scan)
Copy Feαtures	Annotation and Bates" stamping (with color capability and font size adjustment)Authentication for ServicesAuto Paper SelectAuto Reduction & Enlargement to fit selected paper sizeAuto Tray SwitchingAutomatic 2-sided / DuplexBooklet CreationBuild Job: (Enables page-level programming and also lets you proof each section or delete last section as the job is built)CollationCovers (Front only, front and back, back only, printed inside and out: Blank or Printed)Dividers (blank)Edge EraseFeatures Help (Intuitive text and graphic descriptions)ID Card CopyImage Shift (with Auto Center option)Invert Image (negative or mirror image)Large Job InterruptMulti-up (up to 15 columns by 15 rows)Sample SetSave Job SettingsStaplingTranservancing
Xerox® Copier Assistant®	Transparencies Xerox® Copier Assistant® Software provides a PC-based alternative to the user interface touchscreen. Used in conjunction with a customer-supplied PC attached via the USB port, this software supports text-to-speech, screen magnification and easy PC keyboard access to basic and advanced copy features. Section 508-compliant. For more information or to download Xerox® Copier Assistant for free, visit www.xerox.com.
Print	
First-print-out Time	As fast as 6.2 seconds
Print Resolution	Up to 4800 x 1200, 256 shades of gray
Print Features	Application Defaults Banner Sheet Enable / Disable Bi-directional Real-time Status Cover Selection Delay Print (specific time) User Permissions Image Options (Toner Saver, Resolution (Standard, Enhanced, High) Job Identification (Print ID or Banner, Print ID in margins on first page only or all pages) LAN Fax (requires optional Fax Kit) Layout / Watermark N-up (up to 16 pages per sheet) Booklet layout Finishing Fit to new paper size Hold All Jobs Paper Selection by Attribute Sample Set Saved Job Secure Print with Timed Deletion Special Pages (exception page programming: covers, inserts, exception pages) Store and Recall Driver Settings Sustainability Features (Xerox® Earth Smart Settings, Duplex, N-up, Turn-off Banner and Print ID, Smart Sample Set, Hold All Jobs) Two-sided Printing (as default)
Print from USB	Allows walk-up printing from Type A USB port on front panel Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TIFF, PS, XPS, PCL

Operating Systems	Microsoft® Windows® XP SP3 (32- and 64-bit) Windows Server 2003 SP2 R2 (32- and 64-bit) Windows Server 2012 and R2 (32- and 64-bit) Windows Server 2012 and R2 (64-bit) Windows Vista SP2 (32- and 64-bit) Windows 7 (32- and 64-bit) Windows 8 (32- and 64-bit) Windows 8 (32- and 64-bit) Windows 10 (32- and 64-bit) Mindows 10 (32- and 64-bit) Mindows 10 (32- and 64-bit) Linux® Redhat® Fedora® Core 20 x86 Ubuntu® 14.04 x64 openSUSE® 13.1 x64	
Network Protocols	TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6,WSD NetWare: Bindery and NDS IPX/SPX, NDPS®/NEPS (with Server Gateway) AppleTalk®: EtherTalk® Microsoft Windows Networking over IP Bonjour® / AirPrint™ IPv6 Secure FTP Most protocols not in use can be disabled	
Administrative Protocols	DHCP, SNMP, WINS, SLP® v2, HTTP, HTTPS, DHCP Autonet, TLS, NTP, MDNS, SSDP	
Fonts	PCL: 93 scalable fonts, line printer and bitmap font (including Cyrillic font support) PostScript 3: 173 Type 1 fonts, 2 Multiple Master fonts	
Xerox [®] Mobile Express Driver [®]	Makes it easy for mobile users to find, use and manage Xerox [®] and non-Xerox devices in every new location. Plug into a new network, and Mobile Express Driver automatically discovers available printers and provides status and capability information. Save a list of "favorite" printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT.	
Xerox® Global Print Driver®	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.	
Xerox [®] Pull Print Driver	Makes it easy for IT managers to qualify, deploy and manage all print devices using a single driver in a Pull Print environment. Uses a single queue and single driver. The Xerox® Pull Print Driver extends convenience across a broad range of printing assets. IT administrators no longer need to manage and configure multiple drivers. Used in conjunction with Equitrac Office®, Ysoft® SafeQ®, Pharos® and others.	
Print Solutions		
Xerox® Mobile Print Cloud (Optional)	Xerox [®] Mobile Print Cloud addresses the needs of businesses with a mobile workforce and puts you ahead of the evolving mobile print need, but without burdening staff, budget or infrastructure. Getting started takes only a few minutes via the cloud. Print from any mobile device to nearly any brand of printer. Accurate printing with true Microsoft [®] Office [®] rendering and more. Print what you need, when, where and how you need it.	
Xerox® Mobile Print Solution (Optional)	Xerox® Mobile Print Solution is an ideal choice for sites that have additional requirements for control and security with an onsite server. Xerox® Mobile Print Solution allows users to print from most mobile devices to nearly any brand of printer or MFP without drivers or added complexity. Simply enter a release code (PIN) at the device and get accurate printing with true Microsoft Office rendering and more to use with your server for private, onsite deployment.	
Xerox® Print Service Plug-in for Android™ (Free at Google Play™ Store)	The Xerox® Print Service Plug-in for Android KitKat (4.4 or greater) devices streamlines mobile printing without third-party apps or additional print drivers. You can easily print photos, Web pages and documents when your mobile device is connected to ConnectKey-enabled multifunction printers using a wireless network. A robust print option set includes two-sided printing, stapling and secure code release. A free download is available from the Google Play [™] store.	
Xerox [®] Mobile Link App (Free at Google Play Store and Apple [®] App Store)	The Xerox® Mobile Link App allows you to scan, email and fax from your phone or tablet by connecting with our multifunction printers and send data to and print data from cloud storage. It is easy to create Mobile Link One-Touch Workflows between a mobile device and a multifunction printer. Using a manual address or QR code identification for pairing, automatic device discovery makes it easy to find and pair a mobile device with a nearby Xerox® multifunction printer.	
Unified Address Book for Fax, Inter	net Fax, Email and Scan to	
Features	Services supported: Fax, Internet Fax, Email, Scan to Maximum contacts: 5,000 Contacts: Supports 1 or more destinations Favorites for quick access of all services supported	
Scan		
Concurrency	Scan while the system is printing, copying, or while it is transferring scan to network or fax jobs (priority is for return of scanned originals and printing concurrent jobs)	
Input Speed	Scan at up to 200 ipm color scanning and black-and-white – 8.5 x 11 in. / A4 LEF	
Resolution	72 x 72 dpi to 600 x 600 dpi Bit Depth: 1-bit (black-and-white), 8-bit (grayscale), 24-bit (color)	
Maximum Scan Area	11 x 17 in. / A3	
Scan Template Management	Support 250 scan templates Create Xerox® CentreWare® IS scan templates and share via device cloning to other MFPs Confirmation sheet options	
Network Protocols	sFTP, FTP, SMB, NetWare, HTTP, HTTPS	

File Compression	Color TIFF (TIFF 6.0 or TTN2 with JPEG, LZW) Black-and-white TIFF (G3MH, G4 MMR compression - single or multiple pages) Searchable PDF/OCR and PDF/A-1b (MRC, JPEG, G3 MH, G4 MMR, JBIG 2 Huffman, JBIG Arithmetic Compression, Deflate (for Black-and-white and within MRC)) Linearized PDF / PDF/A
Document Management Fields (Meta Data)	 Features only available in Network Scan to File Templates: 1 to 6 user programmable metadata fields per network scan to file templates and unlimited fields within the template – Metadata field consists of field name, default value and other configurations Customized fields viewed on user interface for variable data input
Scan Features	Mixed Size Originals Scan Build Job Compression Quality/File Size Control Original Type (Photo and Text, Photo, Text, Map, Newspaper / Magazine) Auto Background and Shadow Suppression Size for Size (for mixed size originals) TWAIN Support / WIA 2.0 Support Bound Originals Edge Erase Reduction/Enlargement Single Touch Scan buttons (up to 10)
Scan to Email (Standard)	
Scan Features	 Email signatures (6 lines each of 128 character max), email message body (user configurable), email CentreWare IS confirmation sheet options Scan to Email S/MIME Encryption Email signing (requires Smart Card option) Auto send to self
Directory Access	Address list via LDAP (Windows Active Directory, Exchange, Notes, Domino) Downloaded address list (comma-separated file format)
Scan to (Standard)	
Features	Scan to USB Scan to Network Folder (uses Unified Address Book entries)
Network Scanning – Software Solu	tions
Xerox® Scan to PC Desktop® Professional (Optional)	 A desktop offering that provides advanced document imaging, archiving, editing and organization tools: PaperPort Professional image viewing and file management software Complete PDF functionality Secure PDF workflow of all scanning applications OmniPage Pro Office (for desktop/client installation) – Professional OCR software for digital archiving and document conversion Image Retriever – provides fully automated retrieval of scanned images direct from a scan enabled Xerox® WorkCentre to individual desktops. Also includes email inbox polling capability
Xerox® ConnectKey® for DocuShare® (Optional)	Xerox® ConnectKey for DocuShare, a one-step scan-to-workflow solution, simplifies the process of incorporating hard copy content into enterprise document flows. Users can easily scan documents directly into a DocuShare collection or Windows folder via a multifunction printer (MFP).
Xerox® ConnectKey® Apps (Found at the Xerox® App Gallery)	Increase user productivity by simplifying and shortening everyday tasks. Unlike traditional software, ConnectKey Apps do not require a dedicated server, PC or IT resource. Instead, simply download these lightweight, serverless ConnectKey Apps to the ConnectKey-enabled multifunction printer.
Security	
Features	 Expanded Authentication Network authentication to access device and/or device services via- Kerberos (UNIX / Windows Server 2003 / Windows Server 2008), SMB (Windows Server 2003 / Windows Server 2008), NDS, LDAP authentication Local Authentication (internal database) Smart Card authentication -144k CAC / PIV Card Support (2048 bit certificate key) / .NET Secure Data Digitally signed PDF (when using Smart Card authentication) Encrypted Scan to Email Encrypted / Password Protected PDF (when using Email and Network Scan Templates only) Secure Print (up to 10 digit PIN or Network Authentication) Immediate Image Overwrite / Securely delete jobs using approved algorithms On Demand Image Overwrite (Scheduled, Manual), includes sanitation of unused area of disk FIPS 140-2 256 bit Hard Disk Encryption Expanded Authorization Secure Network credentials Authorization per user per service User Permissions required to access Print and Print Features (e.g. color access, or time restrictions) reflects in the print driver Secure Network Access IP Filter, IPsec, IPv6, TLS v1.0, v1.2, SNMPv3, HTTPs, 802.1X, Cisco® TrustSec integration, Device Security McAfee® Embedded Security, Port disablement including USB ports, Audit Log, Hide Print Job Names, McAfee Integrity Control (optional) Common Criteria Certification ISO 15408 (undergoing evaluation)
Xerox [®] PrintSafe Software	This authentication software integrates with trusted industry cards and readers and provides PIN access to nearly any printer in a customer's secured print environment. It works with both Xerox® devices and devices from other vendors. This software is open to work with a variety of industry standard secure readers and cards.

Fax	
Network Server Fax Features	
Compatibility	ITU (CCITT) group 3; Various Xerox Business Innovation Partner Solutions
Maximum Scan Area	11 x 17 in. / A3
Fax Send Features	One- or Two-sided Scanning (up to 11 x 17 in. / A3) Add to Send List (50 numbers maximum) Build Job, Favorites, Delay Send (specific time) Original Type (photo, text or photo and text)
Fax Print Features	One- or Two-sided Printing, Staple, Secure Print
Transmission Resolution	Superfine: 400 x 200 dpi (Scan at 600 x 600 dpi) Fine: 200 x 200 dpi Standard: 200 x 100 dpi
Internet Fax Features	
Capability	Direct print-ready document transmission to remote Internet Fax machines or email clients (SMTP) Reception and automatic printout of documents sent via email from remote Internet Fax machines or email clients
Directory Access	Utilizes the Unified Address Book
Send / Receive	Multi-page TIFF, Image only PDF
Resolution	72 x 72 dpi to 600 x 600 dpi; Bit Depth: 1-bit (black-and-white)
Network Protocols	SMTP (send), POP3 (receive)
Compliance	ITU-T T.37 compliant
Walk-up Fax Features (Optional (C	ustomer-installable) – 1 and 2 lines)
Compatibility	ITU (CCITT) Group 3
Speed / Modems	One or Two V.34 modems: 33,600 bps. Less than 4 seconds per page transmission time ATA analog terminal adapter utilizing T38 (optional)
Compression / Speed	MH/G3, MMR/SG3
Resolution	Walkup Send:Standard: 200 x 100 dpiFine: 200 x 200 dpiSuperfine: 600 x 600 dpiReceive:Accepts all sizes
Fax Send Features	LAN Fax (fax from print driver) Auto Fax Transmission Reduction Page-by-page Job Status at the Machine Delay Start, Build Job, Favorites Automatic Memory Resend Automatic Cover Sheets PSTN Fax Batch Send (up to memory capacity)
Fax Receive Features	One- or Two-sided Printing Stapled or Unstapled Receive Print Mode – Manual (size, margin, stock, header) / Auto Output Tray Selection Up to 200 Password Protected Mailboxes Secure Receive Receive Timestamp Auto Answer Delay
Fax Forward	Forward to Email or SMB Location Fax Forward on Receive Only
Fax Reports	Activity, Dial Directory, Group Directory, Transmission Confirmation, Pending Fax, Options Report, On Demand Overwrite Report, Mailbox Report, Broadcast Report
Directory Access	Utilizes the Unified Address Book Group fax available
Auto Redial	Up to 14 attempts (per country requirements) • 1 to 25 minute intervals
Auto Resend	Up to 5 attempts

Device Management	
Management Support	SNMP Version 1. SNMP Version 2c and SNMP Version 3 trap over TCP/IP and IP MIB access (IETF-MIBII RFC 1213), Host Resources MIB RFC 2790, Printer MIB RFC 1759 v.2
Xerox® CentreWare® Web	A Web-based server application for network administrators that permits Web browser-based device management from any workstation, whether running Windows, UNIX or any other operating system: Works with any SNMP-managed printer from any manufacturer. Provides help with device discovery and installation, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management. Requires Windows 8, Vista, Server 2009, Server 2012 or Windows 7 and Internet Explorer 8.x and higher. CentreWare Integration available for Tivoli® NetView®, Unicenter TNG®, Microsoft Management Console (MMC), HP® OpenView®
Novell NDPS/NEPS	Server gateway application: centralized management tool.
Xerox® Device Manager	Xerox® Device Manager collects and manages the data that drives fact-based decisions for your enterprise device management environment. It is a single tool to install print queues and configure, manage, monitor and report on both networked and locally connected devices – regardless of vendor – across your enterprise. Xerox® Device Manager provides: • Device monitoring and troubleshooting • Extensive reporting and discovery of new devices • Usage collection, chargeback and billing capabilities
Xerox [®] Device Types for SAP Environment	Xerox, together with SAP through our Gold-level membership in the SAP Printer Vendor Program, provides seamless connectivity between SAP systems and your Xerox® printers and MFPs. And as an SAP customer you benefit from having SAP-certified Xerox® device types available right from SAP's online delivery model. SAP-certified device types for Xerox® printers and MFPs are available to download. www.office.xerox.com/software-solutions
Xerox® Device Types for SAP R/3 Intelligent Barcode Utility (optional)	Provides built-in process intelligence that allows the printing of barcodes on any appropriately configured PostScript printer in specific versions of SAPenvironment and within Latin-1 (ISO8859-1) SAP system code pages only. Used in conjunction with Xerox® PostScript Device Types for SAP environment and Xerox® Font Center Barcode Fonts. Information available at www.office.xerox.com/software-solutions
Xerox [®] Barcode Pro PS (optional)	Enables intelligent PostScript printing on Xerox® multifunction systems by storing Xerox® software, as well as, the barcode fonts on the printer hard disk. Enables the printing of barcodes from any application (SAP client or mainframe) that supports PostScript printing. Information available at www.office.xerox.com/software-solutions
CentreWare Internet Services – Int	egrated Web Pages Provided by the Device
Device Status	Web server embedded in Network Controller: • Tray status/contents • Consumables status • Alerts Remote Control Panel
Job Submission	Print ready files: PS, PCL, TIFF, PDF, JPG, XPS ⁴ , TXT, PRN Output feature selection (2-sided, output color, collate, orientation, staple, hole punch, folding, output destination) Delivery options (Immediate, sample set, delay and secure, Save job or reprint)
Device Administration	Allows simple, remote installation setting of configuration options and management of the device
Browsers	Internet Explorer 7.x, 8.x, 9.x Safari 5.x Mozilla Firefox 4.x, 5.x, 6.x, 7.x, 8.x, 9.x, 10.x, 11.x Opera 11.x Chrome 12
Support	Install print / scan drivers and online support available via web page
Languages Supported	International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Russian, Simplified Chinese, Korean, Japanese, Arabic
Remote Services	
Xerox® MeterAssistant®	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.
Xerox® SuppliesAssistant®	Automatically orders supplies for Xerox [®] output devices based on actual usage, eliminating the need to manually manage supplies inventory.
MaintenanceAssistant	Offers a fast (and free) way to resolve potential issues and receive assistance and automate the troubleshooting/repair process. Diagnostic data is sent to Xerox, allowing for problems to be solved faster with increased uptime.
Accounting	
Xerox® Standard Accounting (Stand	dard)
Tracking	Copy, Print, Fax, Scan and Email usage
Accounting	Up to 2,497 User accounts (User ID) Up to 500 General accounts (Client) Up to 498 Group accounts (Department)
Features	 Administrator can manage the feature via the Web User Interface or device control panel in tools Administrator has the ability to import or export user accounts, Group Accounts, General Accounts and User limits via an industry standard CSV file

	 Enhanced network accounting with up to the minute data on how the system is being used Comprehensive management and enterprise scale tracking and reporting of device usage of copy, print, scan and server fax Numerous solutions are available through Xerox Alliance Partners. For details visit www.xerox.com Security enhancements with the addition of HTTPS protocol support Device requests account authentication from third party server enabling larger databases of users and accounts Accept Authentication Login at control panel and pass to third party Networking Account Interface with third party accounting terminal for accounting user interface 		
Supplies	Description	Quantity	Part Number
Toner Cartridge	Includes 2 Toner Cartridges and Waste Toner Bottle	110,000 pages ⁴ (55,000 pages each) ⁴	006R01552
Waste Toner Bottle	Supplied with each Toner Cartridge Box	100,000 pages4	008R12896
Staple Cartridges	Office Finisher (5865i/5875i only)	5,000 per cartridge (15,000 staples)	108R00493
	Office Finisher with Booklet Maker (5865i/5875i only)	5,000 per cartridge (15,000 staples)	108R00493
	Office Finisher with Booklet Maker – saddle-stitch stapling (5865i/5875i only)	2,000 per cartridge (8,000 staples)	108R01158
	HVF and HVF with Booklet Maker • Complete Cartridge • Refill Cartridge	5,000 per cartridge 5,000 per cartridge (15,000 staples)	008R12912 008R12898
	HVF with Booklet Maker – saddle-stitch stapling	2,000 per cartridge (16,000 staples)	008R12897
	Convenience Stapler • Complete Cartridge • Refill Cartridge	5,000 per cartridge 5,000 per cartridge (15,000 staples)	008R12964 008R12941
Xerox® SmartKit®			
Fuser Module	Includes Ozone Filter	400,0004	109R00773
Xerographic Module – Metered		450,0004	109R00672
Xerographic Module – Sold	North America: Europe:	450,000"	113R00674 113R00673
Document Handler Feeder Rolls		150.000 feeds	113R00718

¹ Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

² Expected regular monthly throughput.

³ Paper capacities are based on 20 lb. / 75 gsm stock; capacities will vary with different weight stocks.

⁴ Approximate pages. Declared Yield based on 5 page job size, 6% area coverage, using letter / A4 media. Yield will vary based on media size, image area coverage, media orientation and usage patterns.

Return spent imaging supplies through the Xerox Green World Alliance collection/reuse/recycling program. For more information, visit www.xerox.com/about-xerox/recycling.

For more information, visit us at www.xerox.com/office

©2016 Xerox Corporation. All rights reserved. Xerox®, Xerox and Design®, CentreWare®, ConnectKey®, Copier Assistant®, DocuShare®, Global Print Driver®, MeterAssistant®, Mobile Express Driver®, Scan to PC Desktop®, SmartKit®, SuppliesAssistant® and WorkCentre® are trademarks of Xerox Corporation in the United States and/or other countries. Mopria® is a trademark of the Mopria Alliance. As an ENERGY STAR® partner, Xerox Corporation has determined that this product meets the ENERGY STAR guidelines for energy efficiency. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. The information in this brochure is subject to change without notice. Updated 3/16 BR9614 W5ZSS-01UJ

