



Detailed Specifications



WorkCentre 7228
shown with the Three Tray option.



WorkCentre 7235
shown with High-Capacity Feeder and
Advanced Office Finisher options.



WorkCentre 7245
shown with High-Capacity Feeder and
Professional Finisher options.

	WorkCentre® 7228	WorkCentre® 7235	WorkCentre® 7245
OUTPUT SPEED – printing and copying			
Black and White	Up to 28 ipm (images per minute) A4/210 x 297 mm Up to 20 ipm 216 x 356 mm Up to 17 ipm A3/297 x 420 mm	Up to 35 ipm A4/210 x 297 mm Up to 21 ipm 216 x 356 mm Up to 17 ipm A3/297 x 420 mm	Up to 45 ipm A4/210 x 297 mm Up to 27 ipm 216 x 356 mm Up to 22 ipm A3/297 x 420 mm
Colour	Up to 26 ipm A4/210 x 297 mm Up to 13 ipm 216 x 356 mm Up to 15 ipm A3/297 x 420 mm	Up to 31 ipm A4/210 x 297 mm Up to 17 ipm 216 x 356 mm Up to 15 ipm A3/297 x 420 mm	Up to 35 ipm A4/210 x 297 mm Up to 21 ipm 216 x 356 mm Up to 17 ipm A3/297 x 420 mm

Print Specifications

SYSTEM	
Memory	768 MB
System Disk Minimum	40 GB
NETWORK PRINTING – Network Controller	
Processor	600 MHz
Memory	768 MB
System Disk	Minimum 40 GB
Printer Languages (auto sensing/switching)	Adobe Postscript® 3 TIFF PCL5 PDF 1.5 PCL 6 HP-GL, HP-GL2



Print Specifications

NETWORK PRINTING – resolution

Postscript 600 x 600 dpi: 1200 x 1200 dpi
 PCL emulation: 600 x 600 x 8: 1200 x 1200 dpi

NETWORK PRINTING – printing features

Print Calibration
 Secure print
 Delay print (specific time)
 Sample set
 Booklet creation
 Cover selection
 Paper selection by attribute
 N-up
 Poster mode
 Saddle-stitch booklet making (requires Professional Finisher)
 Hole Punch (requires Professional Finisher or Advanced Office Finisher)
 V Folding (requires Professional Finisher)
 Watermark
 Fit to new paper size (PCL)
 Transparency interleave
 Banner sheet enable/disable
 Output tray selection
 Image quality (High Speed, High Quality, High Resolution)
 Draft mode
 Annotation
 Store and recall driver settings
 Reduce/enlarge
 Mirror image
 Margins
 Email Print
 Bi-Directional
 CMYK Colour Balance

PRINT PROTOCOLS AND NETWORKS

Physical

- Ethernet 100BaseT/10BaseT
- USB printer port (optional)
- Wireless Ethernet (IEEE 802.11b) via third-party adapters
- Parallel Port (optional)

Continued



Print Specifications

PRINT PROTOCOLS AND NETWORKS (Continued)

Operating Systems	Microsoft® Windows® 95, 98, Me® (Millennium), NT® 4.0, 2000, XP®, Windows Server 2003 Citrix Mac OS® 7.x, 9.x, 10.x AIX 4.3.3 HP UX 11.0 Solaris 8, 9, 10 Linux® Red Hat 9® Linux Yellow Dog 9®
--------------------------	--

Network Protocols	TCP/IP: Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, NetBIOS, HTTP Netware: Bindery and NDS IPX/SPX, NDPS®/NEPS (with Server Gateway) AppleTalk®: EtherTalk® Microsoft Windows Networking over IP and NetBEUI
--------------------------	---

Administrative Protocols	DHCP, BOOTP, SNMP, WINS, DDNS, SLP® v2, HTTP, RARP, DHCP Autonet
---------------------------------	--

Fonts	Postscript 3: 136 Type 1 fonts, 2 Multiple Master fonts PCL: 84 scalable fonts, line printer bitmap font
--------------	---

Print Drivers	Environment	PCL 6	PostScript
	Windows 95/98/Me	Bidirectional (enhanced*)	Bidirectional (enhanced*)
	Windows NT 4.0	Bidirectional with user-selectable interface (standard** and enhanced)	Bidirectional with user-selectable interface (standard** and enhanced)
	Windows 2000/XP Windows Server 2003/2003 64 Bit Windows Vista/Vista 64 Bit (Microsoft certified)	Bidirectional with user-selectable interface (standard and enhanced)	Bidirectional with user-selectable interface (standard and enhanced)
	Macintosh® System 9.x, OS X	N/A	Enhanced PPD file

Print Submission Tools	<ul style="list-style-type: none"> • Command prompt LPR tool for print submission • TIFF/PDF/XPS: Supported in Windows 95/98/Me/NT 4.0/2000/XP Windows Server 2003 • Submission Tool with full feature set (includes administration, GUI/TTY print driver and software installation)
-------------------------------	---

*Enhanced: Xerox custom graphical user interface.

**Standard: Driver based on Microsoft tree structure user interface (includes Xerox features and functionality)



Print Specifications

DEVICE MANAGEMENT

Management Support	SNMP Version 1 and SNMP Version 2c trap over TCP/IP and IP MIB access (IETF-MIB II RFC 1213), Host Resources MIB RFC 2790, Printer MIB RFC 1759 v. 2
CentreWare Network Services	Device Discovery wizard (available at www.xerox.com) Device Administration wizard (available at www.xerox.com) Font Management Utility
Xerox CentreWare Web	<ul style="list-style-type: none"> • A Web-based server application for network administrators that permits Web browser-based device management from any workstation, whether running Windows or UNIX or any other operating system • Works with any SNMP-managed printer from any manufacturer • Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management
IP Filter	Allows administrator to control print access to device via IP address.
Xerox CentreWare® for Unicenter TNG®	<ul style="list-style-type: none"> • Provides added identification to the general discovery performed by Unicenter TNG and the ability to see the device under a Unicenter TNG Business Process View • Provides full integration with event management and the choice to integrate with problem management and advanced Help Desk
Xerox CentreWare® for Tivoli® Netware®	<ul style="list-style-type: none"> • Provides for the identification of Xerox N-Series printers and WorkCentre multifunction systems in the general discovery performed by Tivoli NetView • Provides the ability to see the discovered Xerox printers/devices in a Xerox Printers Set in addition to the Printers SmartSet • Provides full integration with the NetView and Event Browser and Tivoli Enterprise Console (TEC)
Xerox CentreWare® for Microsoft Management Console (MMC)	CentreWare MC Snap-in supports printer discovery and management via a Microsoft Management Console (MMC) link to an embedded Web server. It is a general-purpose management display framework for hosting administrative tools.
Xerox CentreWare® for HP® OpenView®	<ul style="list-style-type: none"> • Provides for the identification of Xerox N-Series printers and WorkCentre multifunction devices in the general discovery performed by HP OpenView • Provides the ability to see the current status of discovered Xerox printers/devices under a Xerox PrinterMap and IP Map via colour-coded icons • Provides traps and message updates to the OpenView alarm browser and the ability to launch CentreWare Internet Services for device management directly from OpenView

Continued



Print Specifications

DEVICE MANAGEMENT (Continued)

Xerox Device Types for SAP R/3 Environment	<p>Simplifies printing in SAP R/3 environments by providing users of SAP R/3 v4.6C, 4.x and 3.x ERP applications with enhanced WorkCentre printing functionality (PostScript and PCL):</p> <ul style="list-style-type: none"> – Simplex or duplex printing – Finishing– single or dual stapling – Tray pull location from any tray – Print security via PIN ID capability at the WorkCentre
Xerox SAP R/3 Intelligent Barcode Utility (Optional) <i>Purchase via www.font.net</i>	<p>Provides built-in process intelligence that allows the printing of barcodes on any appropriately configured PostScript printer on the SAP R/3 4.x (or higher) network. Used in conjunction with Xerox Device Types for SAP R/3 Environment and Xerox Font Centre Barcode Fonts. Utility automatically calculates checksum, placement of start/stop characters, and encoding of data string Web server embedded on SMart network controller</p> <ul style="list-style-type: none"> – Tray status/contents – Consumables status
Xerox Barcode Pro PS (optional) <i>Purchase via www.font.net</i>	<p>Enables intelligent PostScript printing on Xerox multifunction printers by storing Xerox software as well as the barcode fonts on the printer hard disk. Enables the printing of barcodes from any application (client or mainframe) that supports PostScript printing. Automatically calculates the check digit, places start/stop and middle bar characters in the data string, compresses and encodes the data string, and rotates the barcode through 90 or 270 degrees.</p>

CENTREWARE® INTERNET SERVICES – Integrated device Web Page

Device Status	<p>Web server embedded on SMart network controller</p> <ul style="list-style-type: none"> – Tray status/contents – Consumables status
Print Queue Viewing	Complete job print queue management – hold, release, promote and delete
Job Submission	<p>Print-ready files (PS, PCL, TIFF, PDF)</p> <p>Output feature selection</p>
Device Administration	Allows simple, remote installation setting of configuration options and management of the device
Browsers	<p>Windows XP, 2000/NT 4.0/Me/98/95: Netscape Navigator® 4.x and above, Microsoft Internet Explorer 4.x and above</p> <p>Macintosh 9.x/OS X: Netscape Navigator 6.x, Mac Safari, Firefox</p> <p>Linux: Netscape® 6.x</p>

Scan Specifications

SCANNING (Optional)

Capability	Colour Scanning, Greyscale, Black and White, Auto Colour
Concurrency	Scan while the system is printing copy or network print jobs, or while it is transferring scan to network or fax jobs

Continued



Scan Specifications

SCANNING (Optional) (Continued)

Resolution	600 x 600 dpi 400 x 400 dpi 300 x 300 dpi 200 x 200 dpi Bit depth: 1 bit (black and white), 8 bit (greyscale), 24 bit (colour)
Maximum Scan Area	297 x 432 mm
Secure Access and Authentication	Optional secure device login with network user name and password Supports: Kerberos (Windows 2000/UNIX/Windows Server 2003), SMB (Windows NT 4.0/Windows 2000/Windows Server 2003) LDAP
Network Protocol	FTP via TCP/IP Microsoft SMB via TCP/IP
File Formats	TIFF 6.0 or TTF2 with JPEG, G3MH, G4 MMR compression (single page or multiple pages) PDF with JPEG, G3 MH, MRC, G4 MMR, MRC, or JPEG compression JPEG High Compression PDF
Document Management Fields	One to six user-programmable metadata fields per scan job Customised fields viewed on user interface Variable data entered using virtual keyboard
Scan Feature Options	Mixed size originals Bound originals Edge erase Reduction enlargement Fit to size Scan Build Job Compression Quality/File Size Control Original type (photo and text, photo, text) Auto Background and Shadow Suppression
Supported Scan Destinations (Varies by scanning software options purchased.)	Scan to network server Scan to remote email destinations via direct SMTP addresses or via various network scanning software options Scan to application (workflow, Electronic Document Management System/Repositories) Scan to Microsoft Exchange 2000 Web Folders Scan to PC Desktop™ (Standard and Deluxe editions) Scan to Windows XP client SMB or FTP Scan to mailbox

Continued



Scan Specifications

SCANNING (Optional) (Continued)

Scan to -PC Desktop Standard	<ul style="list-style-type: none"> – A desktop and server-based offering that provides document imaging, archiving, editing and organisation tools – ScanSoft PaperPort – image viewing and file management software – ScanSoft OmniPage (for desktop/client installation) – OCR and file format conversion software – Image Retriever – provides fully automated retrieval of scanned images direct from a scan enabled Xerox WorkCentre to individual desktops.
-------------------------------------	---

Scan to PC Desktop Deluxe	<ul style="list-style-type: none"> – A desktop and server based offering that provides document imaging, archiving, editing and organisation tools – ScanSoft PaperPort Pro – image viewing and file management software – ScanSoft OmniPage Pro (for desktop/client installation) – OCR and file format conversion software – Image Retriever – provides fully automated retrieval of scanned images direct from a scan enabled Xerox WorkCentre to individual desktops. Also includes an Email inbox polling capability.
----------------------------------	--

EMAIL (Included with Scanning Option)

Capability	<p>Colour scanning, Auto Colour, Greyscale, Black and White</p> <p>Direct document email from device</p> <p>Manual or directory Exchange/Notes/LDAP address searching</p>
-------------------	---

Network Protocol	SMTP, MIME encoded
-------------------------	--------------------

Authentication	<p>Device login with network user name and password</p> <p>Supports: Kerberos (Windows NT 4.0/UNIX,/Windows 2003 Server), SMB (Windows NT 4.0/Windows 2000/Windows 2003 Server)</p> <p>LDAP</p>
-----------------------	---

Directory Access	<p>Corporate address list via LDAPv3</p> <p>Downloaded address list (comma-separated file format)</p>
-------------------------	---

SCAN TO MAILBOX (Included with the Scanning Option)

Capability	Colour, Auto Colour, Black and White
-------------------	--------------------------------------

Features	Images can be scanned, printed and faxed directly to the device hard drive and stored in a mailbox. Images that are stored in the mailbox can then be Emailed, sent via Fax, sent via IFax, routed to a PC, an FTP or SMB site.
-----------------	---

THUMBNAIL PREVIEW (Optional)

Images that are stored in the mailbox can be viewed from the device.



Fax Specifications

NETWORK FAX SERVER INTEGRATION (Optional)

Fax Send Features	<ul style="list-style-type: none"> One- or two-sided scanning Phone number entry Add to send list (50 numbers maximum) Delay send (specific time) Resolution selection (super fine/600 x 600, super fine/400 x 400, fine/200 x 200, standard/200 x 100 dpi) Original type (photo and text, photo, text)
--------------------------	---

Fax Print Features	<ul style="list-style-type: none"> One- or two-sided printing Quantity Staple on/off Collate on/off Finisher output tray selection (top tray or main tray) Secure print on/off
---------------------------	--

Fax Vendors	<p>Multiple vendors, certified by the Xerox Alliance Partner Programme For details, visit www.xerox.com</p>
--------------------	--

FAX (Optional) - Standard with One or Three line option

ITY (CCITT) group 3 quality/resolution superfine/600x600, super fine/400 x 400, fine/200x200, standard/200x100 dpi

Speed/Modem(s)	V.34 modem(s): 33,600 bps. Less than four seconds per page transmission time. ISDN via third-party adapter.
-----------------------	---

Speed/Compression	MH/G3, MMR/G4, JBig Super G3
--------------------------	------------------------------

Fax Send Features	<ul style="list-style-type: none"> Fax from print driver Auto fax transmission reduction Page-by-page job status at the machine Fax from platen Delay start Automatic memory resend Automatic cover sheets Priority send Broadcast Booklet Scan
--------------------------	---

Fax Receive Features	<ul style="list-style-type: none"> One- or two-sided printing Reduction at reception to fit available paper Junk Fax prevention
-----------------------------	--

Fax Forward to Email	When enabled with the scan and fax kit, faxes can be received into a mailbox. Images that are in the mailbox can be routed to an Email, an FTP or SMB location or a Fax.
-----------------------------	--



Fax Specifications

FAX (Optional) - Standard with One or Three line option (Continued)

Fax Reports	Activity report Dial directory Transmission confirmation Pending fax Mailbox
Fax Receive Mailboxes	Up to 200 password-protected mailboxes
Auto Dialing	Auto redial, Batch send
Single Line option	Total of 200 speed dials (single-line option) Up to 200 dial groups with up to 200 recipients per group (single line option)
Three Line option	1,000 speed dials (three line option) Up to 400 dial groups with up to 400 recipients per group (three line option)

INTERNET FAX (Optional) - Standard with One or Three line Fax option

Capability	Direct document transmission to remote Internet Fax machines or email clients (SMTP) Reception and automatic printout of documents in colour and black and white sent via email from remote Internet Fax machines or email clients
Maximum Scan Area	297 x 432 mm
Address Directory Access	Downloaded address list (comma-separated file format)
File Formats	TIFF-FX Profiles S, F with G3 MH, or G4 MMR
Resolutions	600 x 600 dpi 400 x 400 dpi 200 x 200 dpi 200 x 100 dpi Bit Depth: 1 bit (black and white), 8 bit (greyscale)
Network Protocols	SMTP POP3
Compliance	ITU-T T.37 compliant



Copy Specifications

FIRST-IMAGE-OUT TIME – A4 size, from platen to centre tray

Black and White	As fast as 5.7 Seconds	As fast as 5.7 Seconds	As fast as 4.8 Seconds
Colour	As fast as 7.5 Seconds	As fast as 7.5 Seconds	As fast as 7.2 Seconds

COPYING

Document Scanner	Duplex Automatic Document Feeder with 75-sheet capacity (based on 80 gsm paper)
Input Speed	Scan at 50 ipm black and white/45 ipm colour (216 x 279 mm/A4 long edge feed)
Sides (input:output)	1:1, 1:2, 2:2 and 2:1
Quantity	1 to 999
Resolution	600 x 600 dpi
Concurrency	Concurrent scanning and printing
Digital Imaging	<ul style="list-style-type: none"> Auto colour Auto rotation Image shift Edge erase Auto centering Original type selection (photo and text, photo, text, map) with subtypes Lighter/darker Background suppression Auto and manual contrast Sharpness Colour balance, colour shift and saturation
Reduction/Enlargement	<ul style="list-style-type: none"> Variable zoom from 25% to 400% in 1% increments Anamorphic zoom Six user-programmable percentages
Special Features	<ul style="list-style-type: none"> Auto paper select Auto reduction/enlargement to fit selected paper size Auto registration Auto tray switching Automatic job recovery Auto colour selection Poster mode

Continued



Copy Specifications

COPYING (Continued)

Special Features	<ul style="list-style-type: none"> Watermark Annotation Area Designation Full colour Single/Dual colour Copy calibration Booklet creation Multi-up – 2, 4 or 8 up Repeat image Transparency dividers Negative image Mirror image Covers insertion (front only, front and back, back only; blank or printed) Build Job (enables special programming for different pages in one document – can be used for inserts, different paper sources, and mixing input from the document glass and the document feeder) Store and recall job programming Job interrupt Bound document copying Sample set Mixed-size originals Hole Punch (requires Professional Finisher or Advanced Office Finisher) V-Folding (requires Professional Finisher) Saddle-stitch booklets (requires Professional Finisher) Stapling (single/dual/quad) quad requires Advanced Office Finisher or Professional Finisher
-------------------------	--

Foreign Device Interface/ RS232 Port (optional)	<ul style="list-style-type: none"> Interface to third-party access control devices, coin machines and card readers Supports a variety of vending stations available through the Xerox Custom Application Service
--	--

Device Specifications

PAPER HANDLING - Duplex Automatic Document Feeder

Capacity	75 sheets (based on 80 gsm paper)
Speed	42 images per minute (A4 long edge feed (LEF))
Paper Sizes Sensed	<ul style="list-style-type: none"> A5/148 x 210 mm long edge feed (LEF) or short edge feed (SEF) A4/210 x 297 mm LEF or SEF 216 x 356 mm SEF A3/297 x 420 mm SEF B5/182 x 257 mm SEF
Weights	38 to 128 gsm



Device Specifications

PAPER HANDLING - Bypass Tray

Capacity*	100 sheets
Sizes	A6/105 x 148 mm to SRA3/320 x 450 mm
Weights	60 to 220 gsm
Types	Same as front-loading trays plus label stock

PAPER HANDLING - Front-Loading Paper Tray (Standard)

Capacity*	520 sheets
Sizes	User adjustable from A5/148 x 210 mm to A3/297 x 420 mm
Weights	55 to 220 gsm
Types	Plain paper Bond Preprinted forms Recycled paper Transparencies Heavyweight

PAPER HANDLING - Input Tray Options - Three Tray Option (Tray One and Two plus Two Tray Module)

Tray 2 - Tray 4	520 sheets
Sizes	User adjustable from A5/148 x 210 mm to A3/297 x 420 mm
Weights	55 to 220 gsm
Types	Plain paper Bond Preprinted forms Recycled paper Transparencies Heavyweight
Total Capacity*	2,180 sheets (Includes Tray 1, Tray 2, Trays 3-4 and Bypass Tray)

Continued
*Paper capacities are based on 75 gsm stock; capacities will vary with different weight stocks.



Device Specifications

PAPER HANDLING - Input Tray Options - High-Capacity Feeder Option

Tray 2	520 sheets
Sizes	User adjustable from A5/148 x 210 mm to A3/297 x 420 mm
Tray 3 - Tray 4	2,000 sheets
Sizes	B5, A4
Weights	64 to 220 gsm
Types	Plain paper Bond Preprinted forms Recycled paper Transparencies Heavyweight
Total Capacity*	3,140 sheets (Includes Tray 1, Tray 2, Bypass Tray and High Capacity Feeder)

OUTPUT - Centre Stacking Tray

Stacking Tray	400 sheets (200 sheets with finisher option)
Sizes	A6/105 x 148 mm to 320 x 483 mm

OUTPUT - Office Finisher Option

Stacking Tray	1,000 sheets
Sizes	B5 to A3
Weights	64 to 105 gsm
Stapling	Single and dual Auto stapling (50 sheets maximum) – 80 gsm A3, A4, B4 and B5 sizes supported

Continued
*Paper capacities are based on 75 gsm stock; capacities will vary with different weight stocks.



Device Specifications

OUTPUT - Advanced Finisher Option

Top Tray	500 sheets
Stacking Stapling Tray	3,000 sheets
Sizes	B5 to A3
Weights	60 to 220 gsm
Stapling	Single and dual Auto stapling (50 sheets maximum) – 90 gsm A3, A4, B4 and B5 sizes supported
Hole Punch	2/4-hole punch

OUTPUT - Professional Finisher Option

Top Tray	500 sheets
Stacking Stapling Tray	1,500 sheets
Sizes	B5 to A3
Weights	60 to 220 gsm
Stapling	Single Auto stapling (50 sheets maximum) – 90 gsm A3, A4, B4 and B5 sizes supported
Booklets - Booklet Tray	Saddle-stitch up to 15 sheets (One 169 gsm plus 14 90 gsm sheets) V-fold up to 5 sheets A3, A4 supported
Hole Punch	2/4-hole punch

SECURITY

Capability	Secure Print, timed auto delete secure print, hard disk overwrite immediate or on demand, NDS Authentication over IP, LDAP/Kerberos/SMD, Secure Web Page via SSL
Optional Security Kit Capability	Secure Watermark, Password Protected PDF, Encrypted Disk, Audit Log and Encrypted Scan to Email.



Device Specifications

ACCOUNTING

Accounting with Third-Party Server Applications (optional) Up-to-the-minute data on how the system is being used; comprehensive usage tracking and reporting; print, scan, copy and fax

Internal Auditor Tracks black and colour copy and print usage, supports up to 1,000 user accounts
 Note: Option to upload/download account and usage data via direct connection using Windows-based software.
 Limits user to black-only copy and print

Accounting Control Job based accounting
 Third-party integration

ACCOUNTING OPTIONS - Xerox Standard Accounting

Tracking Copy, Print, Fax and Scan usage

Accounting Up to 2,500 User accounts (User ID)
 Up to 500 General accounts (Client)
 Up to 500 Group accounts (Department)

Features Enable/disable via the web UI or the GUI in tools, admin can manage the feature remotely via the web UI, Data can be exported via a CSV file, user required to enter XSA ID into the print driver when submitting a print job, similar to secure print.

WorkCentre® 7228

WorkCentre® 7235

WorkCentre® 7245

MONTHLY DUTY CYCLE

80,000

105,000

135,000

ACCESSORIES

- Office Finisher
- Advanced Office Finisher
- Professional Finisher
- Convenience Stapler
- One-line fax option
- Three-line fax option
- Foreign Device Interface
- Network Accounting Enablement
- Network Scanning With Email
- Scanner with Platen
- Scanner with Duplex Automatic Document Feeder
- Scanner Stand
- Thumbnail preview
- Internet Fax
- Image Disk Overwrite Security
- Scan to PC Desktop Client Software (Standard or Deluxe)
- USB Port Printing
- Parallel Port Printing
- High Capacity Feeder
- Three Tray Option
- Media Card Reader
- Mobility Plate

Continued



Device Specifications

ELECTRICAL REQUIREMENTS

220–240 V Nominal, 50/60 Hz, 10A

POWER CONSUMPTION

<i>Running</i>	< 1012 watts
<i>Standby</i>	< 277 watts
<i>Low-Power Mode</i>	< 157 watts
<i>Sleep Mode</i>	< 80 watts
<i>Warm Up</i>	45 seconds (maximum)
<i>Low-Power Recovery</i>	30 seconds (maximum)

POWER CONSUMPTION

<i>Required Temperature Range</i>	10° to 32° C
<i>Required Relative Humidity</i>	10% to 85%
<i>Noise Emission</i>	28 dB(A) standby 56 dB(A) running 61 dB(A) impulse
<i>Heat Emission</i>	4048 BTU/Hr running 946 BTU/Hr standby

DIMENSIONS AND WEIGHT

	<i>width</i>	<i>depth</i>	<i>height</i>	<i>weight</i>
<i>Fully Configured</i>	1,346 mm	635 mm	1,115 mm	257 kg
	1,816 mm	1,219 mm	1,981 mm	



Device Specifications

CERTIFICATIONS

89/336/EEC (Europe)
 73/23/EEC (Europe)
 FCC Class A Compliant (U.S.), DOC Class A Compliant (Canada)
 UL Listed (UL60950-1, First Edition)
 CB Certified (IEC 60950-1/EN 60950-1)
 Novell Tested and Approved
 Windows Hardware Quality Labs

SUPPLIES	Description	Order Number	
Toner Cartridges	Black	006R01280	
	Cyan	006R01281	
	Magenta	006R01282	
	Yellow	006R01283	
Staple Refills	For Office Finisher	008R12915	
	For Advanced Finisher	008R12941	Used on Advanced and Professional Finisher plus Convenience Stapler Three refills at 5,000 each
	For Professional Finisher	008R12925	Used on Professional Finisher (Booklet Function) Four refills at 5,000 each
Staple Cartridges	For Advanced and Professional Finishers	008R12964	Used on Advanced and Professional Finisher plus Convenience Stapler (One cartridge for repair)

SMART KITS

Smart Kit™ Drum Cartridge	013R00624
Smart Kit™ Waste Cartridge	008R12903
Smart Kit™ Fuser Module	008R13028

SMART eSOLUTIONS

Meter Assistant Via proxy

Supplies Assistant Via proxy