

Xerox® WorkCentre® 7775

Multifunction Printer



WorkCentre 7775 shown with Advanced Finisher and Convenience Stapler options



WorkCentre 7775 shown with Professional Finisher and Convenience Stapler options



WorkCentre 7775 shown with High Capacity Feeder and Light Production Finisher with CZ folding option

Xerox WorkCentre 7775	
Output Speed – Printing and Copying	
Color	Up to 50 ipm 8.5 x 11 in. (A4/210 x 297 mm)
Black and white	Up to 75 ipm 8.5 x 11 in. (A4/210 x 297 mm)
First-Copy-Out Time – Letter Size/A4, from Platen to Center Tray	
Color	As fast as 8.9 seconds
Black and white	As fast as 5.5 seconds
Copy Specifications	
Copying	
Document Scanner	Duplex Automatic Document Feeder (DADF) 250-sheet capacity ¹
Sides (input:output)	1-1, 1-2, 2-2, 2-1
Quantity	1 to 9,999
Resolution (max)	Scan at 600 x 600 dpi, output at 2400 x 2400 dpi
Concurrency	Unlimited program-ahead consistent with configuration (Copy, Print, Fax and Scan)
Copy Pre-collation Memory (EPC)	1 GB DRAM, 80 GB Disk minimum

¹ Paper capacities are based on 20 lb/75 gsm stock; capacities will vary with different weight stocks.

<p>Basic Copy Features & Options</p>	<p>Collation Automatic 2-sided/Duplex Auto Reduction & Enlargement to fit selected paper size Hole Punching Booklet Creation Stapling Large Job Interrupt Copy on Tabs support Auto Paper Select Authentication for Services (i.e. Color Copy) Auto Tray Switching</p>
<p>Imaging Copy Features</p>	<p>Image Quality:</p> <ul style="list-style-type: none"> • Original Type Selection: Photo & Text, Photo, Text, Newspaper/Magazine, Inkjet Original, Maps. • Image Options: Lighten/Darken, Sharpness, Saturation. • Image Enhancement: Auto Background Suppression, Auto and Manual Contrast. • Color Effects: Off, Single Color, Lively, Bright, Warm, Cool. • Color Balance: Normal, Basic Color, Advanced Color. <p>Color Shift:</p> <ul style="list-style-type: none"> • Superior Copy Image Quality <p>Book Copying/Bound Copying Edge Erase Single Color Repeat Image Mixed Size Original Image Shift (with Auto Center option) Image Shift Preset: Support for 3 Preset Options Annotation and Bates™ stamping (with color capability)</p>
<p>Output Copy Features</p>	<p>Transparencies (blank or printed) Dividers (blank) Booklet Creation Multi-up (up to 15 columns by 15 rows) Invert Image (negative or mirror image) Covers (Front only, front and back, back only, printed inside and out: Blank or Printed) Build Job: (Enables page-level programming to include tab copying and also lets you proof each section or delete last section as the job is built) Inserts and Tab copying Sample Set and Job Storage (Store and recall job programming) Heavyweight paper (not rough stock)</p>
<p>Features</p>	<p>Features Help (Intuitive text and graphic descriptions) Xerox Standard Accounting (Copy, Print, Scan, Fax) Languages: (Select up to 20 languages for user interface – International English, International French, Italian, German, International Spanish, Dutch, Portuguese, Brazilian (Brazilian Portuguese), Swedish, Norwegian, Danish, Finnish, Turkish, Greek, Russian, Czech, Polish, Hungarian or Romanian)</p>
<p>Security</p>	<p>IP Filtering for TCP/IP network communications Enable Secure Workflows Audit Log: Provide export capability of log, includes Username of log on attempts SNMPv3 Support Graphical User Interface (GUI) job queue Confidentiality: Require a PIN to delete a Secure print job Image Security Overwrite Auto On-demand Image Overwrite Encryption of user jobs stored on hard disk</p>

Reduction/Enlargement	Variable Zoom from 25% - 400% in 1% increments Size user-programmable percentages (100%, Auto%, 25%, 50%, 64%, 70%, 78%, 94%, 141%, 180%, 200%, 400%)
Foreign Device Interface (FDI) (Optional)	Interface to third party access control devices, coin machines, card readers Validates Metadata Accept Authentication Login at GUI and pass to 3rd party Networking Account Interface with 3rd party accounting terminal for accounting UI MIB Compliance – supports the Finishing MIB Support a variety of vending stations available through the Xerox Custom Application Service
USB Port²	PC Interface for upload/download of Xerox Copier Assistant For software upgrade
Accessibility Option	Xerox Copier Assistant (XCA) Software provides a PC-based alternative to the user interface touch screen. Used in conjunction with a customer-supplied PC attached via the USB port, this software supports text-to-speech, screen magnification and easy PC keyboard access to basic and advanced copy features.
Paper Handling – Duplex Automatic Document Feeder	
Capacity¹	250 sheets
Speed	80 images per minute mono, 50 ipm color
Paper Sizes Sensed	5.5 x 8.5 in. to 11 x 17 in. SEF or 5.5 x 8.5 in. to 8.5 x 11 in. LEF (A5/148 x 210 mm to A3/297 x 420 mm or A5/148 x 210 mm to A4/210 x 297 mm)
Weights	17 lb bond to 170 lb index (64 gsm to 300 gsm)
Paper Handling – Four Front Loading Paper Trays - Paper Trays 1, 2, 3 and 4	
Capacity¹	Trays 1 & 2: 500 sheets each tray Trays 3: 870 sheets Trays 4: 1,140 sheets
Sizes	Trays 1 & 2: 5.5 x 8.5 in. LEF to 11 x 17 in. SEF (A5/148 x 210 mm to A3/297 x 420 mm) Trays 3 & 4: 8.5 x 11 in. LEF (A4/210 x 297 mm)
Weights	17 lb bond to 110 lb index (64 to 220 gsm)
Types	Plain Bond Heavyweight Extra Heavyweight Glossy Heavyweight Glossy Labels Transparencies Custom
Paper Handling – Bypass Tray	
Capacity¹	250 sheets
Sizes	Custom sizes up to 13 x 19 in./SRA3
Weights	17 lb bond to 170 lb index (64 to 300 gsm)

¹ Paper capacities are based on 20 lb/75 gsm stock; capacities will vary with different weight stocks.

² USB Port cannot be used for direct print and thumb drives.

Types	Plain Bond Heavyweight Extra Heavyweight Glossy Heavyweight Glossy Labels Transparencies Custom Pre-cut Tabs	
Paper Handling – High Capacity Feeder (HCF)		
Capacity¹	2000 sheets	
Sizes	8.5 x 11 in. LEF (A4/210 x 297 mm)	
Weights	17 lb bond to 110 lb index (64 to 220 gsm)	
Paper Handling – Total Capacity		
Device Total Capacity	5,260 sheets	
Output Option – Offsetting Catch Tray (OCT) Option		
Capacity¹	500 sheets	
Output Option – Professional Finisher (with Booklet Maker)		
Capacity¹	Top Tray: 500 sheets Stacker Tray: 1,500 sheets 8.5 x 11 in. size (A4/210 x 297 mm)	
Sizes	4 x 6 in. SEF to 13 x 19 in. SEF (101.6 x 152.4 mm to 330.0 x 482.6 mm)	
Weights	17 lb bond to 170 lb index (64 to 300 gsm)	
Stapling¹	50 sheets of 24 lb bond (90 gsm)	
Hole Punch (Standard)	North America 2-3 Hole Punch	Europe 2-4 Hole Punch Swedish 4-Hole Punch (Optional)
Booklet Maker	Bi-folded booklets (5 sheets maximum) Saddle-stitched and Center folded booklets (15 sheet maximum)	
Output Option – Advanced Office Finisher		
Capacity¹	Top Tray: 500 sheets Stacker Tray: 3,000 sheets	
Sizes	5.5 x 8.5 in. (A5/148 x 210 mm) to 11 x 17 in. (A3/297 x 420 mm)	
Weights	17 lb bond to 170 lb index (64 to 300 gsm)	
Stapling¹	50 sheets Single, dual, front, SEF and 4-stitch	
Hole Punch (Standard)	North America 2-3 Hole Punch	Europe 2-4 Hole Punch Swedish 4-hole Punch (Optional)

¹ Paper capacities are based on 20 lb/75 gsm stock; capacities will vary with different weight stocks.

Output Option – Light Production Finisher			
Capacity ¹	Top Tray: 500 sheets Lower Tray: 2,000 sheets 20 lb bond 8.5 x 11 in. size (75 gsm, A4/210 x 297 mm)		
Sizes	4 x 6 in. SEF to 13 x 19 in. SEF (101.6 x 152.4 mm to 330.0 x 482.6 mm)		
Weights	17 lb bond to 170 lb index (64 to 300 gsm)		
Stapling ¹	Up to 100 sheets 20 lb bond (75 gsm)		
Hole Punch	<table border="0"> <tr> <td>North America 2-3 Hole Punch</td> <td>Europe 2-4 Hole Punch Swedish 4-Hole Punch (Optional)</td> </tr> </table>	North America 2-3 Hole Punch	Europe 2-4 Hole Punch Swedish 4-Hole Punch (Optional)
North America 2-3 Hole Punch	Europe 2-4 Hole Punch Swedish 4-Hole Punch (Optional)		
Booklet Maker Capacity ¹	Bi-folded booklets (5 sheets maximum) Saddle-stitched and Center folded booklets (15 sheet maximum)		
Tri-folding (Optional)	Single Sheet C- and Z-folding on 16 to 24 lb (60 to 90 gsm), Letter / Ledger / A4 / A3-sizes Folding Tray: Up to 40 sheets		
Post Process Interposer	200 sheet capacity		
Output Option – Convenience Stapler			
Capacity ¹	50-sheet stapling 5,000 staples Requires a separate outlet		
Print Specifications			
Network Printing – Smart Controller (Simultaneous rip, receive, program ahead, queue processing and transmit)			
Processor	1.33 GHz Freescale		
Memory (ESS)	2 GB		
System Disk	80 GB minimum		
Print Languages (PDL)	PCL 6 / PCL 5e emulation Adobe® PostScript® 3™ TIFF (6.0 Old JPEG and New JPEG) TIFF Fax Extended (TIFF - FX) PDF LCDS, SCS, XES and IPDS through 3rd-party transforms		
Network Printing – Resolution (printing via CentreWare® software)			
	PostScript: 600 x 600 dpi and 1200 x 1200 dpi (up to 256 shades of gray) PCL: 600 x 600 dpi Supports PCL and PS switching within job		
Network Printing – Printing Features			
	Bi-directional Print Drivers provide device and job status Embedded Web server for remote control/monitor/setup Job monitoring at the device and at desktop Special font Banner Sheet Rotate Image Offset Support PCL and PS switching Custom Macintosh Driver (Watermark, Booklet Creation, JBA, Secure, Sample, Delay Print) Support for Print on Tabs / Page Segmentation Linearized PDF Save and restore print job settings		

¹ Paper capacities are based on 20 lb/75 gsm stock; capacities will vary with different weight stocks.

Network Printing – Print Driver Options	
Paper Output	Job Type <ul style="list-style-type: none"> • Secure, Sample, Delay Paper Selection by attribute (including transparency separators) Duplex (2-sided) Finishing <ul style="list-style-type: none"> • Multiple stapling positions • Hole punch • Booklet creation • Fit to new paper size • Saddle stitch with Professional finisher Output tray selections Store and recall driver setting
Special Pages	Exception page programming (covers, inserts/tabs, exception pages)
Image Options	Light/Dark Toner saver Resolution options (600 x 600 and 1200 x 1200 dpi) Reduction/Enlargement Margins Invert Image (negative/mirror)
Layout/Watermark	N-up (16) / Multi-up Booklet Layout/Finishing Fit to new paper size Image orientation Watermark option
Print Protocols and Networks	
Physical	1000Base-T (Gigabit Ethernet) Ethernet 10/100Base-T, 10Base-T, 10Base-2 (IEEE802.5) (Token ring) – via adapter Wireless Ethernet (IEEE802.11a/b/g) – via 3rd party adapter IPv6 support for printing 802.1X support
Operating Systems	Microsoft Windows 2000, XP, Windows Server 2003, Windows Vista, Citrix, Novell NetWare 4.x, 5.x, 6 Mac OS 8.x, 9.x, OS X, 10.3 and higher Solaris 2.8, 2.9, 2.10 HPUX 11.0, 11iv2 AIX 5I v5.3 Linux RedHat Fedora 5 Linux RedHat Enterprise Linux 4
Network Protocols	TCP/IP, LPR/LPD, Raw IP (Port 9100), NetBIOS SMB, IPX/SPX, IPP, NDPS®/NEPS AppleTalk/EtherTalk, Bonjour
Administrative Protocols	DHCP, BOOTP, SNMP, WINS, DDNS, SLP v2, HTTP, RARP, DHCP Autonet
Security Protocols/ Features	Protocols: <ul style="list-style-type: none"> • HTTPS • IPsec Features: <ul style="list-style-type: none"> • IP filtering • Unlimited Secure Print • Audit log • Image Overwrite • Hide print job name and username in queue • Hard drive encryption • Auto On-demand Image Overwrite • Xerox Secure Access option

Fonts	PCL: 80 scalable fonts, line printer and bitmap format line printer fonts (TrueType fonts) PostScript 3: 136 PostScript standard fonts (TrueType fonts/send fonts as/substitution table) Font Management Utility for downloading additional fonts (available for Windows and Mac)		
Print Drivers	Environment	PCL XL/5C	PostScript 3
	Windows XP SP3, Windows Server 2003, Windows Vista, Windows Walk-up (PS), Microsoft Certified (32 bit and 64 bit)	Bi-directional enhanced (Xerox custom graphical user interface)	Bi-directional enhanced (Xerox custom graphical user interface)
	Macintosh System 8.x - 10.2	N/A	Generic PPD Bi-directional via AppleTalk (9.x)
	Macintosh System 10.3 and higher	N/A	Bi-directional enhanced (Xerox custom graphical user interface)
Xerox Mobile Express Driver™ (X-MED)	<p>Makes it easy for mobile users to find, use and manage Xerox and non-Xerox devices in every new location. Plug into a new network, and X-MED automatically discovers available printers and provides status and capability information. Save a list of “favorite” printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT.</p> <ul style="list-style-type: none"> • Printers are automatically discovered • Printer list can be managed based on location • Gives Bi-directional feedback device status, supplies, queue management 		
Xerox Global Print Driver® (X-GPD)	<p>A truly universal print driver that lets IT administrators install, upgrade and manage Xerox and non-Xerox devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.</p> <ul style="list-style-type: none"> • Printers are automatically discovered • Printer list can be managed based on location • Gives Bi-directional feedback device status, supplies, queue management 		
Print Submission Tools	Environment	PCL	PostScript 3
	Solaris 2.8, 2.9, 2.10 HPUX 11.0 AIX 5I v5.3 Linux RedHat Fedora 5 Linux RedHat Enterprise Linux 4	Submission Tool only	Submission Tool with full feature set (Includes administration, GUI/TTY print driver and software installation)
	TIFF/PDF: Supported in Windows 2000/XP, Windows Server 2003, Windows Vista	Submission Tool for any TIFF or PDF file	N/A
Device Management			
Software Installation and Upgrade	Network Controller Install Wizard Software Upgrade via Network		
Management Support	SNMP Version 1, SNMP Version 2c and SNMP Version 3 MIB access (IETF-MIBII RFC 1213), host resources MIB RFC 2790, Printer MIB RFC v.2		
E-Services	Automated Billing Meter Reads		
Xerox CentreWare® Internet Services	Allows simple remote installation setting of configuration options and management of the device.		

Xerox CentreWare® Web	A Web-based server application for network administrators that permits Web browser-based device management from any workstation, whether running Windows, UNIX or any other operating system: <ul style="list-style-type: none"> • Works with any SNMP-managed printer from any manufacturer. • Provides help with device discovery and installation, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management. • Requires Windows XP or 2000 (Professional or Advanced Server) Windows 2003 and Internet Explorer 6.0 and higher
Novell NDPS/NEPS	Server gateway application: centralized management tool
Xerox CentreWare® for Unicenter TNG®	Provides added identification to the general discovery performed by Unicenter TNG and the ability to see the WorkCentre under a Unicenter TNG Business Process View
Xerox CentreWare for Tivoli® NetView®	Provides for the identification of Xerox WorkCentre multifunction systems in the general discovery performed by Tivoli NetView
Xerox CentreWare for HP® OpenView®	Provides for the identification of Xerox WorkCentre multifunction systems in the general discovery performed by HP Openview Provides traps and message updates to the Open View alarm browser and the ability to launch CentreWare Internet Services for device management directly from OpenView
Xerox Barcode Pro PS (optional) Information available at www.xeroxofficesapsolutions.com	Enables intelligent PostScript printing on Xerox multifunction systems by storing Xerox software, as well as, the barcode fonts on the printer hard disk. Enables the printing of barcodes from any application (SAP R/3 client or mainframe) that supports PostScript printing. Automatically calculates the check digit, places start/stop and middle bar characters in the data string, compresses and encodes the data string, and rotates the barcode through 90 or 270 degrees.
Xerox Device Types for SAP R/3 Environment Information available at www.xeroxofficesapsolutions.com	Simplifies printing in SAP R/3 environments by providing users of SAP R/3 3.x, 4.x, 4.5x, 4.6x, SAP Enterprise 4.7x, ERP applications with enhanced WorkCentre printing functionality (PostScript and PCL): <ul style="list-style-type: none"> • One- to two-sided printing • Finishing provides single or dual stapling • Tray pull location from any tray • # of copies – provide the ability to print multiple copies • Paper Type and color – provide ability to select different paper types and paper colors, such as transparency, red, etc. • Print security via PIN ID capability • Job Based Accounting (JBA) – Provides capability to add JBA UserIDs to SAP print jobs • Printer banner sheet – Provide the ability to enable/disable printer banner sheets • Barcode printing – Xerox standard PostScript device types available at www.xeroxofficesapsolutions.com supports Intelligent Barcode Printing with Xerox Barcode Pro PS. This Barcode Pro PS can be purchased at www.font.net.
Xerox SAP R/3 Intelligent Barcode Utility (optional) Information available at www.xeroxofficesapsolutions.com	Provides built-in process intelligence that allows the printing of barcodes on any appropriately configured PostScript printer on the SAP R/3 4.1x, 4.5x, 4.6x and within Latin-1 (ISO8859-1) SAP system code pages only. Used in conjunction with Xerox PostScript Device Types for SAP R/3 environment and Xerox Font Center Barcode Fonts. Utility enables automated checksum calculation, placement of start/stop characters, encoding of data string and data compression.
CentreWare Internet Services – Integrated Web Pages Provided by the Device	
Device Status	Web server embedded in Smart Controller: <ul style="list-style-type: none"> • Tray status/contents • Consumables status • Alerts
Job Submission	Print ready files: PS, PCL, TIFF, PDF Output feature selection (2-sided, staple, fold, hole punch, paper select) Delivery options (Immediate, proof, delay and secure)
Device Administration	Allows simple, remote installation setting of configuration options and management of the device
Scan Template Management	Support 250 scan templates Create device specific CentreWare scan templates Select confirmation sheet options Share scan templates via device cloning

Browsers (minimum versions)	Netscape 7.x, 9.x Internet Explorer 6.x Safari 3.0 Mozilla Firefox 2.x Opera 9.x Chrome 1.0
Support	Online support available via web page
Scanning	
Concurrency	Scan while the system is printing, copying, or while it is transferring scan to network or fax jobs.
Input Speed	Scan at up to 50 ipm color scanning, up to 80 ipm black-and-white – 8.5 x 11 in. LEF (A4/210 x 297 mm) at all resolutions
Resolutions (DPI options)	600 x 600 dpi 400 x 400 dpi 300 x 300 dpi 200 x 200 dpi 100 x 100 dpi 72 x 72 dpi
Scan Presets	Archival Record (Normal Quality - Smallest file size) For Sharing and Printing (Normal Quality - Small file size) For High Quality Printing (High Quality - Large file size) For OCR (High Quality - Large file size) Simple Scan (Normal Quality - Small file size)
Quality/File Size	Normal Quality (Small file size) Higher Quality (Large file size) Maximum Quality (Largest file size)
Maximum Scan Area	11 x 17 in. (A3/297 x 420 mm)
Authentication	Secure device login with network user name and password Supports Kerberos (Windows 2000 / UNIX/Windows Server 2003) SMB (Windows NT 4.0 / Windows 2000 / Windows Server 2003) Novell over IP/IPX (Novell NetWare 4.x / 5.x / 6.x) PIN-based guest login
File Formats	TIFF 6.0 with G3 MH, G4 MMR, or JPEG compression (single page or multiple pages) PDF (image only and searchable PDFs with G3 MH, G4 MMR, MRC, JPEG or JBIG2 compression) JIFF with JPEG compression Microsoft XML Paper Spec (XPS)
File Compression	G3 (photo and halftone photo originals), G4 (text and mixed originals), MRC, JPEG, JBIG2
Scan Features	Mixed sized Original Support for Scan Export New scan to export compression formats: <ul style="list-style-type: none"> • MRC (multi-layer) • JBIG2 Simplify the scanning workflow User Interface (IQ, file size, Templates) Enhanced IQ Support for Barcode Readers and OCR Scan in Novell IP Build job for Scan to File Auto Detect Color or Black and White Image data Auto Contrast support for Scan Export – Enable better color and grayscale scanned Image Quality by correcting for different levels of black within a scanned image Scan to Searchable PDF, PDF/A and XPS Scan to Home Scan to Mailbox Store and reprint print jobs

Scan to Email – Optional	
Capability	Scan to email (manual address entry), directory (Exchange/Notes/LDAP) address searching, internal address book or Public address book (up to 128 recipients)
Network Protocol	SMTP MIME encoded
Scan Features	Email signatures (6 lines each of 128 character max), email message body (user configurable), email CWIS confirmation sheet options
Network Scanning	
Capability	Enables device-specific network scan workflows (destination templates) to be easily created and edited via CentreWare Internet Services: <ul style="list-style-type: none"> • Scan to file • Scan to network server / directory • Scan to Windows XP client via Windows Image Acquisition (WIA) or TWAIN driver • Scan to email • Scan to Microsoft Exchange public folders • Scan to PC Desktop
Network Protocol	Novell (NCP via IPX/SPX) FTP Microsoft SMB via TCP/IP HTTP/HTTPS
Document Management Fields (Metadata)	Features only available in Network Scan to File Templates: <ul style="list-style-type: none"> • 1-6 user programmable metadata fields per network scan to file templates and unlimited fields within the template – Metadata Field consists of field name, display at the LUI or not, default value and other configurations • Customized fields viewed on user interface • Variable data entered using virtual keyboard at device
Scan Template Management	Share scan templates among WorkCentre via device cloning Scan template management (250 templates) with CentreWare Internet Services Select confirmation sheet option
Scan Features	Build job (for scan to file only) (enables special programming for different pages in one document – can be used for inserts, mixing input from the document glass and document feeder), Duplex scanning, Auto detect document size, Scan mixed size originals, scan to edge
Network Scanning – Software Solutions	
Supported Scan Destinations - scan template creation (varies by scanning software options purchased)	Scan to application (workflow, Electronic Document Management System/Repositories) Scan to Microsoft Exchange 2000 Web folders Scan to web URL Scan to remote printer Scan to PC Desktop (SE and Professional editions) Scan to mailbox
Xerox Scan to PC Desktop Professional (optional)	A desktop offering that provides advanced document imaging, archiving, editing and organization tools: <ul style="list-style-type: none"> • Nuance PaperPort Professional image viewing and file management software: <ul style="list-style-type: none"> – Complete PDF functionality – Secure PDF workflow of all scanning applications • Nuance OmniPage Pro Office (for desktop/client installation) – Professional OCR software for digital archiving and document conversion • Image Retriever – provides fully automated retrieval of scanned images direct from a scan enabled Xerox WorkCentre to individual desktops. Also includes email inbox polling capability

Xerox SMARTsend® (optional)	<p>Server based document routing software that supports multiple scan-enabled multifunctional systems (up to 250 per server):</p> <ul style="list-style-type: none"> • Enables transformation, distribution and routing of scanned documents – with features like LDAP and auto discovery • Workflow creation via Web browser-based task creation (destinations, devices, document attributes – 20 file types including searchable PDF, workflow settings, workflow summary) • Scan to File Destinations: email, Novell Netware folder, network folder, SMB folder, FTP, Microsoft Exchange 2000 Web folders, Web URL, remote printers • Scan to Document Repository Destinations: DocuShare, Domino, Domino.doc, Microsoft SharePoint • Workflow initiation via device scanning user interface (template selection at device UI)
Xerox SMARTsend Professional (optional)	<p>Everything in Xerox SMARTsend, plus:</p> <ul style="list-style-type: none"> • Workflow initiation via Paperware (Scan cover sheets) • Server-based Optical Character Recognition (OCR) • Adding Metadata • Scan to Internet fax file destination
Fax Specifications	
Fax Options – Internet Fax	
Capability	<p>Direct document transmission to remote Internet Fax machines or email clients (SMTP) Reception and automatic printout of documents sent via email from remote Internet Fax machines or email clients</p>
Maximum Scan Area	11 x 17 in. (A3/ 297 x 420 mm)
Authentication	<p>Optional secure device login with network user name and password Supports: Kerberos (Windows 2000 / UNIX / Windows Server 2003) SMB (Windows NT 4.0 / Windows 2000 / Windows Server 2003) Novell over IP / IPX (Netware 4.x / 5.x / 6.x) Optional PIN-based guest login</p>
Address Directory Access	<p>Corporate address list via LDAPv3 Downloaded address list (comma-separated file format) Internal LDAP or Public address book</p>
File Formats	<p>TIFF-FX profiles S, F with G3 MH or JPEG compression PDF (image only) with G3 MH, G4 MMR or JPEG compression PDF and Multi TIFF</p>
Resolutions	<p>600 x 600 dpi 400 x 400 dpi 300 x 300 dpi 200 x 200 dpi 200 x 100 dpi 100 x 100 dpi 72 x 72 dpi</p>
Network Protocols	<p>SMTP POP3 (RFC 1939)</p>
Compliance	<p>ITU-T T.37 compliant 508 Compliant</p>
Features	<p>Signature (SA configurable –16 lines each of 128 character max) Delivery Confirmation:</p> <ul style="list-style-type: none"> • Email receipt option • Confirmation reply option • Cover sheet option • Subject (248 characters) • User configurable message body

Fax Features – Network Fax Server Enablement	
Capability	Provides walk-up faxing and hard copy output of received faxes when integrated with fax server applications (fax server and software must be purchased separately from supplier). Transmission speeds, number of lines, compatibility and compression are dependent on fax server configuration.
Maximum Scan Size	11 x 17 in. (A3/297 x 420 mm)
Authentication	Optional secure device login with network user name and password Supports Kerberos (Windows 2000 / UNIX / Windows Server 2003) SMB (Windows NT 4.0 / Windows 2000 / Windows Server 2003) Novell over IP / IPX (Netware 4.x / 5.x / 6.x) Optional PIN-based guest login
Network Protocols	Novell (NCP via IPX/SPX) or IP FTP Microsoft SMB via TCP/IP HTTP/HTTPS SMTP
Fax Send Features	One- or two-sided scanning (up to 11 x 17 in. – A3/297 x 420 mm) Phone number entry Add to send list (50 numbers maximum) Delay send (specific time) Resolution selection (fine, standard) Image quality selection (normal, text, lighten/darken, photo, background suppression, five levels of contrast, five levels of sharpness)
Fax Print Features	One- or two-sided printing Quantity Staple on/off Collate on/off Secure print on/off Finisher output tray selection (top tray or main tray)
Supported Network Fax Vendors	Multiple vendors, certified by the Xerox Alliance Partner Program. For details visit www.xerox.com .
Fax Options – Walk Up Option (one or two line options)	
Compatibility	ITU (CCITT) Group 3
Memory	32 MB (One line) 256 MB (Two line)
Speed/Modems	1 or 2 V.34 modems: 33,600 bps. Less than 4 seconds per page transmission time.
Compression/Speed	MH / MR / MMR / G3 / Super G3
Fax Send Features	Quality/Resolution <ul style="list-style-type: none"> • Original type: photo, photo/text, text only • Fax – off platen, mixed sizes or bound/book Auto Send (Up to 5) Audio line monitor Transmission options (Report/Header) Reduce / Split large documents Cover letter Delayed send Build Job (up to 1,000 images) Polling

Fax Receive Features	One- or two-sided printing Stapled or unstapled, hole punch Receive print mode – Manual (size, margin, stock, header) / Auto Auto answer delay Secure receive Junk fax prevention Fax Forward to Email
Fax Reports	Activity Dial directory Group directory Options Pending jobs
Fax Mailboxes	Up to 200 password-protected Poll Remote mailboxes (up to 255) password-protected
Auto Dialing Features	<p>Speed Dials:</p> <ul style="list-style-type: none"> • 200 (one-line option) • 1,000 (two-line option) <p>Group Dials:</p> <p>One-line Option:</p> <ul style="list-style-type: none"> • Up to 100 groups • Up to 200 recipients per group • Up to recipient entries: 200 <p>Two-line option:</p> <ul style="list-style-type: none"> • Up to 200 groups • Up to 400 recipients per group • Up to 1000 recipient entries <p>Auto Redial:</p> <ul style="list-style-type: none"> • Up to 14 attempts • 1 to 25 minute intervals • Batch send (up to memory capacity)
Resolutions	<p>Send:</p> <p>200 x 100 dpi (Standard) 200 x 200 dpi (Fine) 600 x 600 dpi (Superfine)</p> <p>Receive:</p> <p>200 x 100 dpi (Standard) 200 x 200 dpi (Fine) 300 x 300 dpi (Superfine) 400 x 400 dpi (Superfine) 600 x 600 dpi (Superfine)</p>
LAN Fax	Send fax directly from print drivers
Accounting Options – Xerox Standard Accounting	
Tracking	Copy, Print, Fax and Scan usage
Accounting	Up to 2,500 User accounts (User ID) Up to 500 General accounts (Client) Up to 500 Group accounts (Department)
Features	Enable/disable via the Web UI or the device GUI in tools, admin can manage the feature remotely via the Web UI, Data can be exported via a CSV file, supports entering XSA ID into the print driver when submitting a print job.

Accounting Options – Job Based Accounting – Third Party Enablement				
	Enhanced network accounting with up to the minute data on how the WorkCentre system is being used; comprehensive management and enterprise scale tracking and reporting of device usage of copy, print, scan and server fax. Various options are available through Xerox Alliance Partner solutions. For details visit www.xerox.com . Security enhancements with the addition of HTTPS protocol support. WorkCentre requests account authentication from 3rd-party server enabling larger databases of users and accounts.			
Machine Specifications				
Monthly Duty Cycle				
	Up to 300,000 pages/month			
Electrical Requirements				
North America	Voltage : 110 –127 VAC +/- 10% (99-140 VAC) Frequency: 50/60 Hz +/- 3% , 20 A (115 V) Power Consumption: 1.131 KVA maximum printing continuously			
Europe	Voltage : 220-240 VAC +/- 10% (198-264 VAC) Frequency: 50/60 Hz +/- 3% , 10 A (220/240 V) Power Consumption: 1.096 KVA maximum printing continuously			
Power Consumption (Base IOT)				
Running (Average)	< 1131 watts/hour			
Standby Mode	< 265 watts/hour			
Low Power Mode	< 218 watts/hour (Default time to Low Power = 15 minutes)			
Auto Off / Sleep mode	< 23.7 watts/hour (Default time to Sleep mode = 45 minutes)			
Warm-up Ready to Copy	< 28 seconds (Recovery from Sleep)			
Warm-up Ready to Print	< 130 seconds (Recovery from Sleep)			
Low Power Recovery	< 20 seconds			
Operating Environment				
Required Temperature Range	50° to 90° F (10° to 28° C)			
Required Relative Humidity	15% to 85%			
Sound Power Levels	Operating: 53 dB(A), Standby: 35 dB(A)			
Dimensions and Weight	Width	Depth	Height	Weight
Configuration with OCT	62 in. / 1,574 mm	31 in. / 787 mm	57 in. / 1,460 mm	611.0 lbs. / 277.7 kg
With Advanced Office Finisher	82.5 in. / 2,096 mm	31 in. / 787 mm	57 in. / 1,460 mm	773.7 lbs. / 351.7 kg
With Professional Finisher (with Booklet Maker)	82.5 in. / 2,096 mm	31 in. / 787 mm	57 in. / 1,460 mm	834.7 lbs. / 379.4 kg
With Light Production Finisher (without Folding option)	90 in. / 2,286 mm	31 in. / 787 mm	57 in. / 1,460 mm	876 lbs. / 398.2 kg
With Light Production Finisher (with Folding option)	98 in. / 2,489 mm	31 in. / 787 mm	57 in. / 1,460 mm	1,003 lbs. / 455.9 kg

Xerox® WorkCentre® 7775

Certifications		
	FCC Class A Compliant (US), DOC Class A Compliant (Canada) 89/336/EEC (Europe) UL Listed (UL 1950, Third Edition) CB Certified (IEC 60950/EN 60950) 73/23/EEC (Europe) 95/5/EEC (Europe) ENERGY STAR® GOST	
Device Specifications		
Xerox Extensible Interface Platform® (EIP)		
	Xerox EIP is a software platform inside the WorkCentre 7775 that enables personalized solutions you can access right from the device touch screen. These applications can leverage your existing databases and meet your specific business challenges.	
Supplies	Description	Order Number
Toner Cartridges	Black	006R01219
	Cyan	006R01222
	Magenta	006R01221
	Yellow	006R01220
Waste Toner Bottle	Supplied with each toner cartridge box	008R12990
Staple Cartridge	For Light Production Finisher	008R13029
Staple Cartridge	For Booklet maker saddle-stitch stapling	008R12925
Staple Cartridge	For Convenience Stapler/Advanced Office Finisher/Professional Finisher	008R12964 008R12941
	<ul style="list-style-type: none"> • Complete Cartridge • Refill Cartridge 	
Smart Kits®	Description	Order Number
Fuser Module	<ul style="list-style-type: none"> • North America • Europe 	008R12988 008R12989

