

WorkCentre[®] BookMark 40 & 55



WorkCentre BookMark 40
shown with Basic Office Finisher



WorkCentre BookMark 55
shown with Office Finisher

	WorkCentre BookMark 40	WorkCentre BookMark 55
Output Speed – Printing and copying	Up to 40 ipm (images per minute) 8.5 x 11 in. (A4/210 x 297 mm)	Up to 55 ipm (images per minute) 8.5 x 11 in. (A4/210 x 297 mm)
	Up to 25 ipm 8.5 x 14 in. (216 x 356 mm)	Up to 36 ipm 8.5 x 14 in. (216 x 356 mm)
	Up to 22 ipm 11 x 17 in. (A3/297 x 420 mm)	Up to 31 ipm 11 x 17 in. (A3/297 x 420 mm)
First-Image-Out Time (FCOT) – Letter-size, from Platen to Offset Catch Tray	As fast as 4.5 seconds	As fast as 4.5 seconds

Copy Specifications

Copying	
Platen	Scans sizes up to 11 x 17 in. (A3/297 x 420 mm) SEF
Sides (input:output)	1:1, 1:2, 2:2 and 2:1
Quantity	1 to 9,999
Resolution	600 x 600 x 8 bit dpi input / 4800 x 600 dpi interpolated output
Concurrency ¹	Unlimited program-ahead consistent with configuration (Copy, Print, Fax and Scan)
Copy Pre-Collation Memory (EPC)	128 MB std / 544 MB max (Copier); 512 MB std / 800 MB max (Copier / Printer)
Basic Copy	Features: Beveled edge for Book Copying, Collation, Automatic 2-Sided/Duplex, Auto Tray Switching
	Options: Hole Punching, Stapling, Paper Tray Lock Kit
Imaging Copy Features	Image Quality <ul style="list-style-type: none"> • Original Type Selections: Normal, Text, Halftone, Photo • Output Quality Selections: Lighter/Darker, Background Suppression, Contrast, Sharpness or Screening Book Copying/Bound Copying Edge Erase (with Print to Edge option) Image Shift (with Auto Center option)
Output Copy Features	Transparencies (including dividers – blank or printed) Invert Image (negative or mirror image) Covers (Front only, Front and Back, Back only: Blank or Printed) Annotation and Bates Stamping Build Job (Enables page-level programming to include tab copying and also lets you proof each section or delete last section as the job is built) Sample Set and Job Storage (Store and Recall job programming) Heavy weight paper (not rough stock)
Other Copy/Device Features	Job Interrupt (Interrupt the current job) Tray Lock Kit Help (Intuitive text and graphic descriptions) Internal Auditor (Copy) Languages (Select up to 20 languages for User Interface – US English, International English, International French, Italian, German, International Spanish, Dutch, Portuguese, Brazilian [Latin Portuguese], Swedish, Norwegian, Danish, Finnish, Turkish, Greek, Russian, Czech, Polish, Hungarian or Romanian)

¹ A minimum of 256 MB EPC memory required.

WorkCentre Bookmark 40 & 55

Reduction/Enlargement	Variable Zoom from 25% - 400% in 1% increments Six User-Programmable percentages (25%, 64%, 78%, 129%, 154% and 200%)
Foreign Device Interface (FDI) (Optional)	Interface to third-party access control devices, coin machines, card readers Supports a variety of vending stations available through the Xerox Custom Application Service
USB Port	PC interface for upload/download of internal auditron data and Xerox Copier Assistant Customer device administration/software upgrade
Accessibility Option	Xerox Copier Assistant (XCA) ² Software provides a PC-based alternative to the user interface touchscreen. Used in conjunction with a customer-supplied PC attached via the USB port, this software provides text-to-speech, screen magnification and easy PC keyboard access to basic and advanced copy features.
Paper Handling – Two Front Loading Paper Trays Capacity ³	550 sheets each
Sizes	User adjustable from 5.5 x 8.5 in. (A5/148 x 210 mm) to 11 x 17 in. (A3/297 x 420 mm)
Weights	16 lb to 53 lb bond/110 lb index (60 to 200 gsm)
Types	Letterhead Preprinted forms Plain Paper Drilled/Hole-punched Heavyweight Recycled Tab Stock Bond Envelopes Custom Settings (up to 7)
Options	Envelope Tray Kit (for occasional use with C10 envelopes)
Paper Handling – Bypass Tray Capacity ³	100 sheets
Sizes	User Adjustable from 4.13 x 5.83 in. (105 x 148 mm) to 11 x 17 in. (A3/297 x 420 mm)
Weights	16 lb to 57 lb bond/80 lb cover (60 to 216 gsm)
Types	Letterhead Preprinted forms Plain Paper Drilled/Hole-punched Heavyweight Recycled Label Stock Transparencies Tab Stock Bond Envelopes Custom Settings (up to 7)
Paper Handling – High Capacity Tandem Tray (HCTT) Capacity ³	Two trays: 1,600 and 2,000 sheets each
Sizes	8.5 x 11 in. (A4/210 x 297 mm) LEF
Weights	16 lb to 53 lb bond/110 lb index (60 to 200 gsm)
Paper Handling – Total Capacity Device Total Capacity ³	4,800 sheets (with Bypass tray, front loading paper trays and High Capacity Tandem Tray)
Output Option – Offset Catch Tray (OCT) Option Capacity ³	300 sheets
Sizes	4.25 x 5.5 in. (A6/105 x 148 mm) to 11 x 17 in. (A3/297 x 420 mm)
Weights	16 lb to 57 lb bond/80 lb cover (60 to 216 gsm)

² Not available in Canada.

³ Paper capacities are based on 20 lb. bond stock; capacities will vary with different weight stocks.

WorkCentre Bookmark 40 & 55

Output Option – Basic Office Finisher Option (available for BookMark 40 only) Capacity ³	Top Tray – 250 sheets Stacking Tray – 1,000 sheets
Sizes	4.25 x 5.5 in. (A6/105 x 148 mm) to 11 x 17 in. (A3/297 x 420 mm)
Weights	16 lb to 57 lb bond/80 lb cover (60 to 216 gsm)
Stapling ³	30 sheets Single position (top right hand corner)
Output Option – Office Finisher Option Capacity ³	Top Tray – 250 sheets Stacking Tray – 2,000 sheets
Sizes	4.25 x 5.5 in. (A6/105 x 148 mm) to 11 x 17 in. (A3/297 x 420 mm)
Weights	16 lb to 57 lb bond/80 lb cover (60 to 216 gsm)
Stapling ³	50 sheets Single (any corner) and dual
Hole Punch (Optional)	3-hole punch 2-hole Legal punch
Output Option – Convenience Stapler Option Capacity ³	50 sheets
Print Specifications	
Network Printing – SMart Controller (Simultaneous rip, receive, program ahead, queue processing, and transmit) Processor	1.4 GHz AMD Athlon dedicated
Memory (ESS)	Copier/Printer: 256 MB
System Disk	Copier/Printer: 80 GB Hard Drive shared
Printer Language (PDL) Auto Switching	Copier/Printer <ul style="list-style-type: none"> • PCL 6/PCL 5e • PostScript 3 emulation • TIFF (6.0 Old JPEG and New JPEG) • TIFF Fax Extended (TIFF - FX) • PDF • LCDS, SCS, XES and IPDS through third party transforms
Network Printing – Resolution (printing via CentreWare software)	PostScript emulation: 600 x 600 dpi and 1200 x 1200 dpi (up to 256 shades of grey) PCL: 600 x 600 dpi Supports PCL and PS switching within job
Network Printing – Printing Features	Bi-directional Print Drivers Embedded web server for remote control/monitor/setup Job monitoring at the device and at desktop
Advanced Features Included	Special font Banner Sheet Rotate Image Offset
Network Printing – Print Driver Options Paper Output	Job Type <ul style="list-style-type: none"> • Secure, Sample, Delay • LAN Fax-with fax option • Save and Save & Print Paper Selection by attribute (including transparency separators) Duplex (2-sided) Finishing <ul style="list-style-type: none"> • Multiple Stapling positions • Hole punch (if configured) • Booklet creation • Fit to new paper size Output tray selections Store and recall driver setting

³ Paper capacities are based on 20 lb. bond stock; capacities will vary with different weight stocks.

WorkCentre Bookmark 40 & 55

Special Pages	Exception Page programming (covers, inserts/tabs, exception pages)		
Image Options	Light/Dark Toner saver Resolution options (600 x 600 and 1200 x 1200 dpi) Reduction/Enlargement Margins (edge to edge printing) Invert Image (negative/mirror)		
Layout/Watermark	N-up (16)/Multi-up Booklet Layout/Finishing Fit to new paper size Image orientation Watermark options		
Print Protocols and Networks	Ethernet 10/100BaseT, 10BaseT, 10Base2(IEEE802.5) (Token ring) – via adapter, wireless Ethernet (IEEE802.11a/b/g) – via third party adapter		
Physical	USB 2.0 / (IEEE1284) Parallel Port Kit		
Operating Systems	Copier/Printer <ul style="list-style-type: none"> • Microsoft Windows 98, Me, NT 4.0, 2000, XP, Vista, Windows Server 2003, Citrix, Novell NetWare 4.x, 5.x, 6 • Mac OS 8.x, 9.x, OS X • Solaris 2.8, 2.9, 2.10 • HPUX 11.0 • IBM AIX 4.3.3 • Linux Fedora Core 1 (Intel) • Linux Yellow Dog 3.0 		
Network Protocols	Copier/Printer <ul style="list-style-type: none"> • TCP/IP, LPR/LPD, Raw IP (Port 9100), NetBIOS SMB, IPX/SPX and Net BEUI, IPP, NDPS, NEPS • AppleTalk/EtherTalk, Bonjour 		
Administration Protocols	DHCP, BOOTP, SNMP, WINS, DDNS, SLP v2, HTTP, RARP, DHCP Autonet		
Security	Protocols	<ul style="list-style-type: none"> • HTTPS • IPsec • 802.1x 	
	Features	<ul style="list-style-type: none"> • IP filtering • Unlimited Secure Print • Audit log • Image Overwrite • LDAP Secure Authentication / Secure LDAP • Data Encryption 	
Fonts	PCL: 80 scalable fonts, line printer and bitmap format line printer fonts (true type fonts) PostScript 3: 136 PostScript standard fonts (true type fonts/send fonts as/substitution table) Font Management Utility for downloading additional fonts (available for Windows and Mac)		
Print Drivers	Environment	PCL6/5e	PostScript 3
	Windows 98/Me, NT 4.0, 2000/XP, Windows Server 2003, Windows Walk-up (PS), Microsoft Certified	Xerox custom graphical user interface Bi-directional features <ul style="list-style-type: none"> • Job, Paper and Toner status • Job status notification • Just in time Bi-Di • Auto population of IP address • Delete jobs 	Xerox custom graphical user interface Bi-directional features <ul style="list-style-type: none"> • Job, Paper and Toner status • Job status notification • Just in time Bi-Di • Auto population of IP address • Delete jobs
	Macintosh System 8.x – 10.2	N/A	Generic PPD
	Macintosh System 10.3 and higher	N/A	Xerox custom graphical user interface Bi-directional features <ul style="list-style-type: none"> • Toner, Fuser and Xerographic module status
Print Submission Tools	Environment	PCL	PostScript 3
	Solaris 2.8, 2.9, 2.10; HPUX 11.0, IBM AIX 4.3.3; Linux Fedora Core 1 (Intel); Linux Yellow Dog 3.0	Submission Tool only	Submission Tool with full feature set (includes administration, GUI/TTY print driver and software installation)
	TIFF/PDF: Supported in Windows 98/Me/NT 4.0/2000/XP Windows Server 2003	Submission Tool for any TIFF or PDF file	N/A

WorkCentre Bookmark 40 & 55

Device Management Management Support	SNMP Version 1. SNMP Version 2c and SNMP Version 3 MIB access (IETF-MIBII RFC 1213), host resources MIB RFC 2790, Printer MIB RFC v.2
Xerox CentreWare Internet Services	Allows simple remote installation setting of configuration options and management of the device
Xerox CentreWare Web	A Web-based server application for network administrators that permits Web browser-based device management from any workstation, whether running Windows, UNIX or any other operating system. Works with any SNMP-managed printer from any manufacturer. Provides help with device discovery and installation, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management. Requires Windows XP or 2000 (Professional or Advanced Server) Windows 2003 and Internet Explorer 6.0 and higher
Novell NDPS/NEPS (gateway for WorkCentre)	Server gateway application: centralized management tool
Xerox CentreWare for Unicenter TNG	Provides added identification to the general discovery performed by Unicenter TNG and the ability to see the WorkCentre under a Unicenter TNG Business Process View
Xerox CentreWare for Tivoli NetView	Provides for the identification of Xerox N-Series printers and WorkCentre multifunction systems in the general discovery performed by Tivoli NetView
Xerox CentreWare for HP OpenView	Provides for the identification of Xerox N-Series printers and WorkCentre multifunction systems in the general discovery performed by HP Openview Provides traps and message updates to the Open View alarm browser and the ability to launch CentreWare Internet Services for device management directly from OpenView
Xerox Barcode Pro PS (optional) <i>Purchase via www.font.net</i>	Enables intelligent PostScript printing on Xerox multifunction systems by storing Xerox software, as well as, the barcode fonts on the printer hard disk. Enables the printing of barcodes from any application (SAP R/3 client or mainframe) that supports PostScript printing. Automatically calculates the check digit, places start/stop and middle bar characters in the data string, compresses and encodes the data string, and rotates the barcode through 90 or 270 degrees.
Xerox Device Types for SAP R/3 Environment <i>are available at www.xeroxoffice.com www.xeroxoffice.com</i>	Simplifies printing in SAP R/3 environments by providing users of SAP R/3 3.x, 4.x, 4.5x, 4.6x, SAP Enterprise 4.7x, ERP applications with enhanced WorkCentre printing functionality (PostScript and PCL): <ul style="list-style-type: none"> • One- to Two-sided printing • Finishing provides single or dual stapling • Tray pull location from any tray • # of copies – provide the ability to print multiple copies • Paper Type and color – provide ability to select different paper types and paper colors, such as transparency, red, etc. • Print security via PIN ID capability at the WorkCentre • Job Based Accounting (JBA) – Provides capability to add JBA UserIDs to SAP print jobs • Printer banner sheet – Provide the ability to enable/disable printer banner sheets • Barcode printing – Xerox standard PostScript device types available at www.xeroxoffice.com supports Intelligent Barcode Printing with Xerox Barcode Pro PS. This Barcode Pro PS can be purchased at www.font.net
Xerox SAP R/3 Intelligent Barcode Utility (optional) <i>Purchase via www.font.net</i>	Provides built-in process intelligence that allows the printing of barcodes on any appropriately configured PostScript printer on the SAP R/3 4.1x, 4.5x, 4.6x and within Latin-1 (ISO8859-1) SAP system code pages only. Used in conjunction with Xerox PostScript Device Types for SAP R/3 environment and Xerox Font Center Barcode Fonts. Utility enables automated checksum calculation, placement of start/stop characters, encoding of data string, and data compression.
Centraware Internet Services – <i>Integrated Device Web page</i> Device Status	Web server embedded on SMart Controller <ul style="list-style-type: none"> • Tray status/contents • Consumables status • Alerts
Job-Print Queue Viewing	Complete job print queue management
Job Submission	Print ready files PS, PCL Output feature selection (2-sided, staple, fold, hole punch, paper select) Delivery options (Immediate, proof, delay and secure)
Device Administration	Allows simple, remote installation setting of configuration options and management of the device
Scan Template Management	250 templates can be created Create device specific CentreWare scan templates Select confirmation sheet options Share scan templates via device cloning
Browsers	Netscape 6.2, 7.x (Mozilla 1.x) Internet Explorer 5.5.x, 6.x Safari 1.x Mozilla Firefox 1.x
Support	Online support available via web page

WorkCentre Bookmark 40 & 55

Scan Specifications	
Scanning	
Concurrency	Scan while the system is printing, copying, or while it is transferring scan to network or fax jobs
Input Speed	Scan at 55 ipm - 8.5 x 11 in. (A4/210 x 297 mm) LEF at all resolutions
Resolutions DPI Options	600 x 600 dpi 400 x 400 dpi 300 x 300 dpi 200 x 200 dpi 100 x 100 dpi 72 x 72 dpi
Scan Presets	<ul style="list-style-type: none"> • Archival Record (Normal Quality - Smallest file size) – 100 x 100 • For Sharing and Printing (Normal Quality - Small file size) – 200 x 200 • For High Quality Printing (High Quality - Large file size) – 300 x 300 • For OCR (High Quality - Large file size) – 300 x 300 • Simple Scan (Normal Quality - Small file size) – 200 x 200
Quality/File Size	<ul style="list-style-type: none"> • Normal Quality (Small file size) • Higher Quality (Large file size) • Maximum Quality (Largest file size)
Maximum Scan Area	11 x 17 in. (A3/297 x 420 mm)
File Formats	TIFF 6.0 with G3 MH, G4 MMR, MRC or JPEG compression (single page or multiple pages) PDF (image only with G3 MH, G4 MMR, JPEG or JBIG2 compression) Linearized PDF
Scan to Email (Standard with Network Scanning option) Capability	Scan to Email (manual address entry or directory (Exchange/Notes/LDAP) address searching (internal address book or Public address book – up to 128 recipients)
Network Protocol	SMTP MIME encoded
Scan Features	Email signatures (6 lines each of 128 character max), email message body (user configurable), email CWIS confirmation sheet options
Network Scanning (Optional with Copier/Printer) Capability	<ul style="list-style-type: none"> • Enables device-specific network scan workflows (destination templates) to be easily created and edited via CentreWare Internet Services • Scan to Home displays one template and populates with the user's directory path after authentication* • Scan to File • Scan to network server / directory • Scan to Mailbox⁴ • Scan to Windows XP client via Windows Image Acquisition (WIA) or TWAIN driver downloadable from www.xerox.com
Network Protocol	Novell (NCP via IPX/SPX) FTP Microsoft SMB via TCP/IP HTTP/HTTPS
Document Management Fields (Metadata)	Features only available in Network Scan to File Templates: 1-6 user programmable metadata fields per network scan to file templates and unlimited fields within the template - Metadata Fields consists of field name, display at the LUI or not, default value and other configurations Customized fields viewed on user interface Variable data entered using virtual keyboard at device
Scan Template Management	Share scan templates among WorkCentre via device cloning Scan template management (250 templates) with CentreWare Internet Services Select confirmation sheet option
Scan Features	Build job for scan to file only (enables special programming for different pages in one document – can be used for inserts, mixing input from the document glass), scan to edge.
Network Scanning Software Solutions	
Scan to PC	A desktop offering that provides document imaging, archiving, editing and organization tools
Desktop Workgroup Edition SE (optional)	ScanSoft PaperPort SE – image viewing and file management software ScanSoft OmniPage SE – offer desktop/client installation – OCR and file format conversion software Image Retriever – provides fully automated retrieval of scanned images direct from a Xerox WorkCentre to individual desktops

⁴ Features, configurations, and options vary by location.

WorkCentre Bookmark 40 & 55

Scan to PC Desktop Workgroup Edition Professional (optional)	<p>A desktop offering that provides advanced document imaging, archiving, editing and organization tools.</p> <p>ScanSoft PaperPort Professional 10 image viewing and file management software</p> <ul style="list-style-type: none"> • Complete PDF functionality • Secure PDF workflow of all scanning applications <p>ScanSoft OmniPage Pro Office (for desktop/client installation) Professional OCR software for digital archiving and document conversion</p> <p>Image Retriever – provides fully automated retrieval of scanned images direct from a scan enabled Xerox WorkCentre to individual desktops. Also includes an email inbox polling capability.</p> <ul style="list-style-type: none"> • PaperPort Scanning Platform (EIP application)
SMARTsend ⁴ (optional)	<p>Server base document routing software that supports multiple scan-enabled multifunctional systems</p> <p>Enables transformation, distribution and routing of scanned documents</p> <p>Workflow creation via Web browser-based task creation (destinations, devices, document attributes – 20 file types including PDF, workflow settings, workflow summary)</p> <ul style="list-style-type: none"> • Scan to File Destinations: email, Microsoft NetWare folder, network folder, FTP, Microsoft Exchange 2000 web folders, web URL, remote printers • Scan to Document Repository Destinations: DocuShare, Domino, Domino.doc, Microsoft SharePoint, Hummingbird DNS, Open Text Livelink, Documentum, Interwoven Work Site <p>Workflow initiation via device scanning user interface (template selection at device UI)</p> <p>Adding of Metadata information</p>
SMARTsend ⁴ Professional (optional)	<p>Everything in SMARTsend, plus:</p> <ul style="list-style-type: none"> • Workflow initiation via Paperware (Scan coversheets) • Server-based Optical Character Recognition (OCR) • Searchable PDF • Scan to Internet fax file destination • TrueMatch patented search technology

Fax Specifications

Fax Options – Walk-up Option (One Line)	
Compatibility	ITU (CCITT) Group 3
Memory	32MB (One Line)
Speed/Modem	1 V.34 modem: 33,600bps. Less than 4 seconds per page transmission time, ISDN via third party adapter
Compression/Speed	MH/MR/MMR/G3/Super G3
Fax Send Features	<p>Quality/Resolution</p> <ul style="list-style-type: none"> • Original type: Normal, text, half tone, photo, lighter/darker, background suppression • Fax – off Platen, mixed sizes or Bound/Book <p>Auto Send (Up to 5)</p> <p>Audio line monitor</p> <p>Transmission options (Report/Header)</p> <p>Reduce/Split large documents</p> <p>Cover letter</p> <p>Delayed send</p> <p>Build Job (up to 1000 images)</p> <p>Polling</p>
Fax Receive Features	<p>One or two-sided printing</p> <p>Stapled or unstapled, hole punch</p> <p>Receive print mode – Manual (size, margin, stock, header)/Auto</p> <p>Auto answer delay</p> <p>Secure receive</p> <p>Junk fax prevention</p>
Fax Reports	<p>Activity</p> <p>Dial directory</p> <p>Group directory</p> <p>Options</p> <p>Pending Jobs</p>

⁴ Features, configurations, and options vary by location.

WorkCentre Bookmark 40 & 55

Fax Mailboxes	Up to 100 password-protected Poll Remote mailboxes (up to 255) password-protected
Auto Dialing Features	Speed Dials <ul style="list-style-type: none"> • 200 (One-line option) Group Dials <ul style="list-style-type: none"> • Up to 100 groups with up to 200 recipients per group (One-line option) Auto redial <ul style="list-style-type: none"> • Up to 14 attempts • Up to 25 min intervals • Batch Send (up to memory capacity)
Resolutions	200 x 100 dpi (Standard) 200 x 200 dpi (Fine) 300 x 300 dpi 200 x 400 dpi 400 x 400 dpi 400 x 600 dpi 600 x 600 dpi (Superfine)
Fax Options – LAN Fax with Walkup Fax (Optional)	Driver based LAN fax for Windows and Macintosh users (PCL and PS drivers) Recipient options (add recipient or add from phone book) User personal phone book – up to 1,000 entries Confirmation sheet Send speed (14.4/33.6kbps or 4800bps) Send time Dialing options (prefix or credit card) Cover sheet (add notes) Preferences – Phonebook (personal or shared LDAP)
Fax Options – Internet Fax (Standard with Network Scanning option) Capability	Direct document transmission to remote Internet Fax machines or e-mail clients (SMTP) Reception and automatic printout of documents sent via e-mail from remote Internet Fax machines or e-mail clients
Maximum Scan Area	11 x 17 in. (A3/297 x 420 mm)
Address Directory Access	Corporate address list via LDAPv3 Downloaded address list (comma-separated file format) Internal LDAP or Public address book
File Formats	TIFF-FX profiles S, F with G3 MH or JPEG compression PDF (image only) with G3 MH, G4 MMR or JPEG compression PDF and Multi TIFF
Resolutions	600 x 600 dpi 400 x 400 dpi 300 x 300 dpi 200 x 200 dpi 200 x 100 dpi 100 x 100 dpi 72 x 72 dpi
Network Protocols	SMTP POP3 (RFC 1939)
Compliance	ITU-T T.37 complaint
Features	Signature (SA configurable –16 lines each of 128 character max) Delivery Confirmation <ul style="list-style-type: none"> • Email receipt option • Confirmation reply option • Cover sheet option • Subject (248 characters) • User configurable message body

WorkCentre Bookmark 40 & 55

Fax Options – Network Fax Server Enablement (Standard with Network Scanning option) Capability	Provides walk-up faxing and hard copy output of received faxes when integrated with fax server applications (fax server and software must be purchased separately from supplier). Transmission speeds, number of lines, compatibility and compression are dependent on fax server configuration (via SMTP).
Maximum Scan Size	11 x 17 in. (A3/297 x 420mm)
Network Protocols	Novell (NCP via IPX/SPX) FTP Microsoft SMB via TCP/IP HTTP/HTTPS SMTP
Fax Send Features	One- or two-sided scanning (up to 11 x 17 in. (A3/297 x 420 mm) Phone number entry Add to send list (50 numbers maximum) Delay send (specific time) Resolution selection (fine, standard) Image quality selection (normal, text, lighten/darken, photo, background suppression, seven levels of contrast, seven levels of sharpness)
Fax Print Features	One- or two-sided printing Quantity Staple on/off Collate on/off Secure print on/off Finisher output tray selection (top tray or main tray)
Supported Network Fax Vendors	Multiple vendors, certified by the Xerox Alliance Partner Program. For details visit www.xerox.com
Device Management Specifications	
Accounting Features – Internal Auditor Tracking	Copy usage
Accounting	Up to 2,150 User accounts Up to 5,925 General accounts Up to 256 Group accounts
Features	Auditor report printout, ability to upload/download account and usage data via direct connection using Microsoft Windows based software
Accounting Features – Xerox Standard Accounting (Standard with Copier/Printer/Scanner) Tracking	Copy, Print, Fax and Scan usage
Accounting	Up to 2,500 User accounts (User Id) Up to 500 General accounts (Client) Up to 500 Group accounts (Department)
Features	Enable/disable via the web UI or the GUI in tools, admin can manage the feature remotely via the web UI, Data can be exported via a CSV file, user required to enter XSA ID into the print driver when submitting a print job, similar to secure print.
Accounting Features – Network Accounting Enablement (Standard with Network Scanning option)	Enhanced network accounting with up to the minute data on how the WorkCentre system is being used; comprehensive management and enterprise scale tracking and reporting of device usage of copy, print, scan and server fax. Various options available through Xerox Alliance Partner solutions. For details visit www.xerox.com Security enhancements with the addition of HTTPS protocol support WorkCentre requests account authentication from 3rd party server enabling larger databases of users and accounts

WorkCentre Bookmark 40 & 55

Security – Review the Supplemental Security Brochure for Details Authentication	Secure device login with network user name and password Supports Kerberos (Windows 2000/UNIX/Windows Server 2003) SMB (Windows NT 4.0/Windows 2000/Windows Server 2003) Novell over IP/IPX (Novell NetWare 4.x/5.x/6.x) PIN-based guest login
Features	802.1x ⁴ HTTPS (SSL) SNMP V3 IPSec Network Authentication Device Access Password Protection IP Filtering Audit Log Disk Encryption – for Store Print and Scan to Mailbox features on Copier/Printer/Scanner Secure Print Fax Security Disk Image Overwrite – Immediate, On Demand, and Scheduled
Secure Access Unified ID System (optional)	Secure Access Unified ID System adds an advanced layer of security at the device by enabling users to log-in to a Xerox MFP system with a swipe of their magnetic or proximity ID card. When combined with Follow You Print functionality, Secure Access allows private print jobs to be accessed from any Xerox printer or MFP on your network.
Xerox Extensible Interface Platform™ (EIP)	Xerox EIP acts as a gateway, enabling simplified, server-based applications that personalize the user experience through customized touch-screen displays. Personalized for each user. These applications will yield simpler user interactions and result in less time interacting with the MFP which drives increased worker productivity and systems that easily adapt to your business processes. Combined with the optional SMARTsend solution, you can set up a digital repository for users to browse and print frequently requested documents.
Machine Specifications	
Monthly Duty Cycle	BookMark 40 – up to 100,000 pages BookMark 55 – up to 150,000 pages
Basic Configurations⁴	BookMark 40 Copier with Four Trays BookMark 40 Copier/Printer with Four Trays BookMark 55 Copier with Four Trays BookMark 55 Copier/Printer with Four Trays
Accessory Options⁵ BookMark Copier	Walkup Fax (One line) Offset Catch Tray (OCT) Basic Office Finisher (available with BookMark 40 only) Office Finisher (available with BookMark 55 only) Convenience Stapler Paper Tray Lock Kit Hole Punch (with Office Finisher – see Output Options for details) Envelope Kit 256 MB Pre Collation Memory (EPC) Foreign Interface Device (FDI) Xerox Copier Assistant (XCA) Upgrade Kits to Copier/Printer/Scanner Customized Application Service Kits ⁵ <ul style="list-style-type: none"> • Vending Station • Vending Station Download Kit • Y Harness • Vend Mounting • Angled Console • Accessory Shelf
BookMark Copier/Printer (in addition to above options)	Walkup Fax with LAN Fax (One line) USB 2.0 / (IEEE1284) Parallel Port Kit Scan to PC Desktop SE and Professional Secure Access Enablement for Fax/Scan/Accounting Xerox Alliance Partner solutions Network Scanning

⁴ Features, configurations, and options vary by location.

⁵ Not all items available in Canada. Check for local availability.

WorkCentre Bookmark 40 & 55

Electrical Requirements	110-140 Volt Nominal, 60 Hz, 15A Note: Convenience Stapler requires separate 110V 15A circuit			
Power Consumption	Copier		Copier/Printer/Scanner	
Running	≤ 1180 watts		≤ 1230 watts	
Standby	≤ 240 watts		≤ 290 watts	
Low Power Mode	≤ 100 watts		≤ 125 watts	
Auto Off / Sleep mode	≤ 5 watts		≤ 9 watts	
Warm up to Copy	≤ 28 seconds		≤ 28 seconds	
Ready to Print	NA		≤ 130 seconds	
Low Power Recovery	≤ 20 seconds		≤ 20 seconds	
Environmental Considerations				
Required Temperature Range	10° to 32° C			
Required Relative Humidity	10% to 85%			
Dimensions and Weights (BookMark Copier) Configuration With OCT	Width	Depth	Height	Weight
With Basic Office Finisher (BookMark 40 only)	44 in. / 1,118 mm	26 in. / 650 mm	41 in. / 1,041 mm	278 lbs / 126 kg
With Office Finisher (BookMark 55 only)	54 in. / 1,372 mm	26 in. / 650 mm	41 in. / 1,041 mm	328 lbs / 149 kg
With Office Finisher (BookMark 55 only)	54 in. / 1,372 mm	26 in. / 650 mm	41 in. / 1,041 mm	339 lbs / 154 kg
Dimensions and Weights (BookMark Copier/Printer) Configuration With OCT	Width	Depth	Height	Weight
With Basic Office Finisher (BookMark 40 only)	44 in. / 1,118 mm	28 in. / 711 mm	41 in. / 1,041 mm	293 lbs / 133 kg
With Office Finisher (BookMark 55 only)	54 in. / 1,372 mm	28 in. / 711 mm	41 in. / 1,041 mm	344 lbs / 156 kg
With Office Finisher (BookMark 55 only)	54 in. / 1,372 mm	28 in. / 711 mm	41 in. / 1,041 mm	355 lbs / 161 kg
Space Requirements (Fixed)	Width	Depth		Height
Configuration With OCT	122 in. / 3,099 mm	Copier: 104 in. / 2,650mm Copier/Printer: 107 in. / 2,710mm		78 in. / 1,981 mm
With Basic Office Finisher	133 in. / 3,378 mm	Copier: 104 in. / 2,650mm Copier/Printer: 107 in. / 2,710mm		78 in. / 1,981 mm
With Office Finisher	133 in. / 3,378 mm	Copier: 104 in. / 2,650mm Copier/Printer: 107 in. / 2,710mm		78 in. / 1,981 mm
Space Requirements (Moveable)	Width	Depth		Height
Configuration With OCT	77 in. / 1,955 mm	Copier: 65 in. / 1,650mm Copier/Printer: 67 in. / 1,710mm		78 in. / 1,981 mm
With Basic Office Finisher	87 in. / 2,214 mm	Copier: 65 in. / 1,650mm Copier/Printer: 67 in. / 1,710mm		78 in. / 1,981 mm
With Office Finisher	87 in. / 2,214 mm	Copier: 65 in. / 1,650mm Copier/Printer: 67 in. / 1,710mm		78 in. / 1,981 mm
Certifications	FCC Class A Compliant (US), DOC Class A Compliant (Canada) 89/336/EEC (Europe) UL Listed (UL 1950, Third Edition) CB Certified (IEC 60950/EN 60950) 73/23/EEC (Europe) 95/5/EEC (Europe)			

WorkCentre Bookmark 40 & 55

Supplies	Description	Order Number	No. per Box	Expected Yield
	Toner Cartridge	6R01046	2	30,000 at 6 % area coverage
	Waste Toner Bottle (supplied with each toner cartridge box)	6R01046	1	100,000
	Staple Cartridge (for Basic Office Finisher)	108R00682	1	3,000 per cartridge
	Staple Pack (for Basic Office Finisher)	108R00535	3	3,000 per cartridge (9,000 staples)
	Staple Cartridge (for Office Finisher)	108R00493	3	5,000 per cartridge (15,000 staples)
	Staple Cartridge (for Convenience Stapler) Complete Cartridge	8R12964	1	5,000 per cartridge
	Refill Cartridge	8R12941	3	5,000 per cartridge (15,000 staples)
Smart Kits	Description	Order Number	No. per Box	Expected Yield
	Fuser Module (includes ozone filter)	109R00752	1	400,000
	Xerographic Module - Metered	113R00672	1	400,000
	Xerographic Module - Sold	113R00674	1	400,000

