

### Detailed Specifications



WorkCentre Pro 55 shown with High-Capacity Feeder



WorkCentre Pro 55 shown with High-Capacity Feeder and optional Office Finisher.

### WorkCentre Pro 55 Advanced Multifunction System

#### OUTPUT SPEED—printing and copying

- 55 images per minute (ipm) letter  
(8.5 x 11 in. / 216 x 279 mm / A4)

---

- 36 ipm legal  
(8.5 x 14 in. / 216 x 356 mm)

---

- 31 ipm ledger  
(11 x 17 in. / 279 x 432 mm / A3)

#### FIRST-IMAGE-OUT TIME—letter size, from platen to offsetting catch tray

3.4 seconds

#### NETWORK PRINTING—Smart Network Controller

<b>Processor</b>	Intel® Celeron® 433 MHz
<b>Memory</b>	128 MB RAM
<b>System Disk</b>	Minimum 9.1 GB
<b>Printer Languages (auto switching)</b>	PCL® 6 (PCL 5e) emulation PostScript® 3 emulation TIFF PDF Walk Up™ Print Driver, TIFF, LCDS, SCS, XES and IPDS through third-party transforms

#### NETWORK PRINTING—resolution, printing via CentreWare® software

PostScript emulation: 600 x 600 dpi for 128 or 256 levels of gray: 1200 x 1200 dpi and 1800 x 1800 dpi for 256 levels of gray via patented emulation process  
PCL emulation: 600 x 600 dpi

## WorkCentre® Pro 55 Advanced Multifunction System

## NETWORK PRINTING—printing features\*

Edge-to-edge printing  
 Secure print  
 Delay print (specific time)  
 Sample set  
 Booklet creation  
 Cover selection  
 Paper selection by attribute  
 Multi-up  
 Stapling (single / dual) – optional  
 Output tray selection  
 Watermark  
 Fit to new paper size  
 Transparency interleave  
 Banner sheet enable / disable  
 Hole punching – optional  
 Image quality  
 Save and recall driver settings

## PRINT PROTOCOLS AND NETWORKS

<b>Physical</b>	Ethernet 100BaseT / 10BaseT, 10Base2, 10Base5 via adapter USB 1.1 port (optional) Wi-Fi Wireless ethernet (IEEE 802.11a/b/g) via third-party adapters
<b>Operating Systems</b>	Microsoft® Windows® 95, 98, Millennium® (Me), NT® 4.0, 2000, XP® Novell® NetWare® 4.x, 5.x, 6 Mac OS® 8.x, 9.x, OS X Solaris® 2.5.1, 2.6 and higher HP-UX® 10.2, 11.x IBM AIX® 4.2 and higher Linux® Intel® —Red Hat® —Caldera® —Mandrake™ (LPRNG printing infrastructure) —Corel® (i386) —TurboLinux® (i386) —SuSE® (i386) Linux Power PC® —TurboLinux Server 6.0.2
<b>Network Protocols</b>	TCP / IP: Internet Printing Protocol, LPR / LPD, Raw Socket Printing / Port 9100, NetBIOS, HTTP Netware: Bindery and NDS IPX / SPX, NDPS® / NEPS (with Server Gateway) AppleTalk®: EtherTalk® Microsoft Windows Networking over IP and NetBEUI

Continued

\*Not all features are available in every driver.

## WorkCentre® Pro 55 Advanced Multifunction System

PRINT PROTOCOLS AND NETWORKS *Continued*

<b>Administration Protocols</b>	DHCP, BOOTP, SNMP, WINS, DDNS, SLP® v2, HTTP, RARP, DHCP Autonet			
<b>Fonts</b>	PostScript 3: 136 PostScript standard fonts PCL: 80 scalable fonts, line printer and bitmap format line printer fonts Font Management Utility for downloading additional fonts			
<b>Print Drivers</b>	<b>Environment</b>	<b>PCL5e</b>	<b>PCL 6</b>	<b>PostScript</b>
	Windows 95 / 98 / Me	Bidirectional enhanced*	Bidirectional enhanced*	Bidirectional enhanced*
	Windows 2000 / XP (Microsoft certified)	Bidirectional with user-selectable interface (standard and enhanced)	Bidirectional with user-selectable interface (standard and enhanced)	Bidirectional with user-selectable interface (standard and enhanced)
	Windows NT 4.0	Bidirectional with user-selectable interface (standard** and enhanced)	Bidirectional enhanced	Bidirectional with user-selectable interface (standard** and enhanced)
	Macintosh® System 8.x, 9.x, OS X	N / A	N / A	Generic PPD
	Macintosh System 9.x	N / A	N / A	Bidirectional via AppleTalk
<b>Print Submission Tools</b>	<b>Environment</b>	<b>PCL</b>		<b>PostScript</b>
	Solaris 2.5.1, 2.6 and higher; IBM AIX 4.2 and higher; LPRNG printing infrastructure; Linux Intel and Linux Power PC	Submission Tool only		Submission Tool with full feature set (includes administration, GUI / TTY print driver and software installation)
	TIFF / PDF: Supported in Windows 95 / 98 / Me / NT 4.0 / 2000 / XP	Submission Tool for any TIFF or PDF file		

\*Enhanced: Xerox custom graphical user interface.

\*\* Standard: Driver based on Microsoft tree-structure user interface (includes Xerox features and functionality).

## WorkCentre® Pro 55 Advanced Multifunction System

## CENTREWARE® INTERNET SERVICES—integrated device Web page

<b>Device Status</b>	Web server embedded on SMart network controller —Tray status / contents —Consumables status
<b>Print Queue Viewing</b>	Complete job print queue management—hold, release, promote and delete
<b>Job Submission</b>	Print-ready files (PS, PCL, TIFF, PDF) Output feature selection
<b>Device Administration</b>	Allows simple, remote installation setting of configuration options and management of the device
<b>Browsers</b>	Netscape 6.2,7.x (Mozilla 1.x), Internet Explorer 5.5x,6.x, Safari 1.x, Mozilla Firefox 1.x

## NETWORK SCANNING – optional

<b>Concurrency</b>	Scan while the system is printing copy or network print jobs, or while it is transferring scan-to-network or fax jobs
<b>Input Speed</b>	Scan at rated speed (55 ipm) (letter / 8.5 x 11 in. / 216 x 279 mm / A4 long edge feed [LEF]) at all resolutions
<b>Resolutions</b>	600 x 600 dpi 300 x 300 dpi 200 x 200 dpi
<b>Maximum Scan Area</b>	11.7 x 17 in. / 297 x 432 mm
<b>Authentication</b>	Secure device login with network user name and password Supports Kerberos (Windows 2000 / UNIX), SMB (Windows NT 4.0 / Windows 2000), and Novell NetWare 4.x / 5.x / 6.x PIN-based guest login
<b>Network Protocol</b>	Novell (NCP via IPX / SPX) FTP via TCP / IP SMB via TCP / IP
<b>File Formats</b>	TIFF 6.0 with G3 MH, G4 MMR or JPEG compression (single page or multiple pages) PDF (image only) with G3 MH, G4 MMR or JPEG compression
<b>Document Management Fields</b>	One to six user-programmable metadata fields per scan job Customized fields viewed on WorkCentre Pro user interface Variable data entered using virtual keyboard at WorkCentre Pro
<b>Scan Destinations</b>	Scan to network server Scan to remote e-mail destinations via direct SMTP addresses Scan to e-mail Scan to application (workflow, Electronic Document Management System) Scan to Microsoft Exchange Public Folders Scan to PC Desktop™ (SE and Professional editions) Scan to Windows XP client via WIA (Windows Image Acquisition)

Continued

## WorkCentre® Pro 55 Advanced Multifunction System

NETWORK SCANNING *Continued*

<b>Network Scanning With E-Mail Includes</b>	<ul style="list-style-type: none"> <li>Scan to network directory</li> <li>Scan to e-mail distribution</li> <li>Scan to Xerox or third-party applications</li> <li>Scan to Windows XP client (requires WIA driver downloadable from xerox.com)</li> </ul>
<b>Scanning Software Options</b>	<ul style="list-style-type: none"> <li>Scan to PC Desktop SE               <ul style="list-style-type: none"> <li>— ScanSoft® PaperPort® SE—image viewing and file management software</li> <li>— ScanSoft OmniPage® SE—OCR and file format conversion software</li> </ul> </li> <li>Scan to PC Desktop Professional               <ul style="list-style-type: none"> <li>— ScanSoft PaperPort Professional—advanced image viewing and file management / sharing software</li> <li>— ScanSoft OmniPage Pro Office—advanced OCR and file format conversion software</li> </ul> </li> <li>Scan to FreeFlow SMARTsend</li> <li>Scan to FreeFlow SMARTsend Professional</li> </ul>
<b>E-MAIL (included with Network Scanning)</b>	
<b>Capability</b>	<ul style="list-style-type: none"> <li>Direct document e-mail from device</li> <li>Manual address entry or directory (Exchange / Notes / LDAP) address searching</li> </ul>
<b>Resolutions</b>	<ul style="list-style-type: none"> <li>600 x 600 dpi</li> <li>300 x 300 dpi</li> <li>200 x 200 dpi</li> </ul>
<b>Maximum Scan Area</b>	11.7 x 17 in. / 297 x 432 mm / A3
<b>Network Protocol</b>	SMTP, MIME encoded
<b>Authentication</b>	<ul style="list-style-type: none"> <li>Secure device login with network user name and password</li> <li>Supports Kerberos (Windows 2000 / UNIX), SMB (Windows NT 4.0 / Windows 2000), and Novell® NetWare 4.x / 5.x / 6.x PIN-based guest login</li> </ul>
<b>Directory Access</b>	<ul style="list-style-type: none"> <li>Corporate address list via LDAPv3 (Exchange / Notes)</li> <li>Downloaded address list (comma-separated file format)</li> </ul>
<b>File Formats</b>	<ul style="list-style-type: none"> <li>TIFF 6.0 with G3 MH, G4 MMR or JPEG compression (single page or multiple pages)</li> <li>PDF (image only) with G3 MH, G4 MMR or JPEG compression</li> </ul>

## WorkCentre® Pro 55 Advanced Multifunction System

## COPYING

<b>Document Scanner</b>	Duplex Automatic Document Feeder with 75-sheet capacity
<b>Sides (input:output)</b>	1:1, 1:2, 2:2 and 2:1
<b>Quantity</b>	1 to 9,999
<b>Resolution</b>	600 x 600 dpi x 8 bit
<b>Concurrency</b>	Full concurrency and unlimited program-ahead consistent with configuration
<b>Digital Imaging</b>	<ul style="list-style-type: none"> <li>AutoIQ automatic digital image quality control</li> <li>Auto rotation 180° or 270° when needed</li> <li>Image shift</li> <li>Edge erase</li> <li>Edge-to-edge copying</li> <li>Auto centering</li> <li>Original type selection (normal, text, halftone, photo)</li> <li>Lighter / darker</li> <li>Background suppression</li> <li>Contrast</li> <li>Sharpness</li> <li>Screening</li> </ul>
<b>Copy Pre-collation Memory</b>	256 MB (expandable to 512 MB)
<b>Reduction / Enlargement</b>	<ul style="list-style-type: none"> <li>Variable zoom from 25% to 400% in 1% increments</li> <li>Anamorphic zoom</li> <li>Six user-programmable percentages</li> </ul>
<b>Special Features</b>	<ul style="list-style-type: none"> <li>Auto paper select</li> <li>Auto reduction / enlargement to fit selected paper size</li> <li>Auto registration</li> <li>Auto tray switching</li> <li>Automatic job recovery</li> <li>Booklet creation</li> <li>N-up—six to one maximum for 8.5 x 11 in. / 216 x 279 mm / A4</li> <li>Transparency dividers (blank or printed)</li> <li>Negative image</li> <li>Mirror image</li> <li>Covers insertion (front only, front and back, back only; blank or printed)</li> <li>Build Job</li> <li>Page programming of tabs or paper inserts</li> <li>Store and recall job programming</li> <li>Job interrupt</li> <li>Bound document copying (produce multiple sets from stored job segments)</li> <li>Sample set</li> <li>Mixed-size originals</li> <li>Context-sensitive help screens</li> <li>Stapling (single / dual) with optional finisher</li> </ul>

Continued

## WorkCentre® Pro 55 Advanced Multifunction System

**COPYING** *Continued*

<b>Foreign Device Interface (optional)</b>	Interface to third-party access control devices, coin machines, card readers Supports a variety of vending stations available through the Xerox Custom Application Service
<b>USB Port (copier function only)</b>	PC interface for upload / download of internal auditor data and customer device administration / software upgrade
<b>Accessibility Option</b>	Xerox Copier Assistant™ Software provides a PC-based alternative to the user interface touchscreen. Used in conjunction with a customer-supplied PC attached via the USB port, this software provides text-to-speech, screen magnification and easy PC keyboard access to basic and advanced copy features.

**INTERNET FAX (optional)**

<b>Capability</b>	Direct document transmission to remote Internet Fax machines or e-mail clients (SMTP) Reception and automatic printout of documents sent via e-mail from remote Internet Fax machines or e-mail clients
<b>Maximum Scan Area</b>	11.7 x 17 in. / 297 x 432 mm / A3
<b>Authentication</b>	Secure device login with network user name and password Supports Kerberos (Windows 2000 / UNIX), SMB (Windows NT 4.0 / Windows 2000), and Novell Netware 4.x / 5.x / 6.x PIN-based guest login
<b>Address Directory Access</b>	Corporate address list via LDAPv3 Downloaded address list (comma-separated file format)
<b>File Formats</b>	TIFF-FX profiles S, F with G3 MH or JPEG compression PDF (image only) with G3 MH, G4 MMR or JPEG compression
<b>Resolutions</b>	600 x 600 dpi 300 x 300 dpi 200 x 200 dpi
<b>Network Protocols</b>	SMTP POP3 (RFC 1939)
<b>Compliance</b>	ITU-T T.37 compliant

**NETWORK FAX SERVER INTEGRATION (optional)**

	Provides walk-up faxing and hard-copy output of received faxes when integrated with third-party fax-server applications (fax server and software must be purchased separately from supplier). Transmission speeds, number of lines, compatibility and compression are dependent on fax server configuration.
<b>Fax Send Features</b>	One- or two-sided scanning (up to ledger / 11 x 17 in. / 279 x 432 mm / A3) Phone number entry Add to send list (50 numbers maximum) Delay send (specific time) Resolution selection (fine, standard) Image quality selection (normal, text, halftone photo, photo, background suppression, seven levels of contrast, seven levels of sharpness)

*Continued*

## WorkCentre® Pro 55 Advanced Multifunction System

NETWORK FAX SERVER INTEGRATION (optional) *Continued*

<b>Fax Print Features</b>	One- or two-sided printing Quantity Staple on / off Collate on / off Secure print on / off Finisher output tray selection (top tray or main tray)
<b>Authentication</b>	Secure device login with network user name and password Supports Kerberos (Windows 2000 / UNIX), SMB (Windows NT 4.0 / Windows 2000), and Novell NetWare 4.x / 5.x / 6.x PIN-based guest login
<b>Fax Vendors</b>	Multiple vendors, certified by the Xerox Business Partners Program. For details, visit <a href="http://www.xerox.com">www.xerox.com</a> .

## DEVICE MANAGEMENT

<b>Management Support</b>	SNMP Version 1 and SNMP Version 2c and SNMP Version 3 MIB access (IETF-MIB II RFC 1213), host resources MIB RFC 2790, Printer MIB RFC v. 2
<b>Xerox CentreWare Internet Services</b>	Allows simple remote installation setting of configuration options and management of the device
<b>Xerox CentreWare Web</b>	A Web-based server application for network administrators that permits Web browser-based device management from any workstation, whether running Windows, UNIX or any other operating system. Works with any SNMP-managed printer from any manufacturer. Provides help with device discovery and installation, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management. Requires Windows XP or 2000 (Professional or Advanced Server) or Windows 2003 and Internet Explorer 6.0 and higher
<b>Novell NDPS / NEPS (gateway for WorkCentre Pro)</b>	Server gateway application: centralized management tool.
<b>Xerox CentreWare® for Unicenter TNG®</b>	Provides added identification to the general discovery performed by Unicenter TNG and the ability to see the WorkCentre Pro under a Unicenter TNG Business Process View.
<b>Xerox CentreWare® for Tivoli® NetView®</b>	Provides for the identification of Xerox N-Series printers and WorkCentre Pro multifunction devices in the general discovery performed by Tivoli NetView.
<b>Xerox CentreWare® for HP® OpenView®</b>	Provides for the identification of Xerox N-Series printers and WorkCentre Pro multifunction devices in the general discovery performed by OpenView. Provides traps and message updates to the OpenView alarm browser and the ability to launch CentreWare Internet Services for device management directly from OpenView.
<b>Xerox Barcode Pro PS (optional)</b> <i>Purchase via <a href="http://www.font.net">www.font.net</a></i>	Enables intelligent PostScript printing on Xerox multifunction systems by storing Xerox software, as well as, the barcode font on the printer hard disk. Enables the printing of barcodes from any application (SAP R/3 client or mainframe) that supports PostScript printing. Automatically calculates the check digit, places a start/stop and middle par characters in the data string, compresses and encodes the data string and rotates the barcode though 90 or 270 degrees



## WorkCentre® Pro 55 Advanced Multifunction System

DEVICE MANAGEMENT *Continued***Xerox Device Types for SAP R / 3 Environment are available at**[www.xeroxofficesapsolutions.com](http://www.xeroxofficesapsolutions.com)

Simplifies printing in SAP R / 3 environments by providing users of SAP R / 3 v4.6C, 4.x and 3.x ERP applications with enhanced WorkCentre Pro printing functionality. (PostScript and PCL):

- Simplex or duplex printing
- Finishing—single or dual stapling
- Tray pull location from any tray
- Print security via PIN ID capability at the WorkCentre Pro
- Number of copies – Provides the ability to print multiple copies
- Paper type and color – Provides the ability to select different paper types and paper colors, such as transparency, red, etc.
- Job Based Accounting (JBA) – Provides capability to add JBA User IDs to SAP print Jobs
- Printer Banner Sheet – Provide the ability to enable /disable banner sheets
- Barcode Printing – Xerox standard PostScript device types available at [www.xeroxofficesapsolutions.com](http://www.xeroxofficesapsolutions.com) supports Intelligent Barcode Printing with Xerox Barcode Pro PS. This Barcode Pro PS can be purchased at [www.font.net](http://www.font.net)

**Xerox SAP R / 3 Intelligent Barcode Utility (Optional)**Purchase via [www.font.net](http://www.font.net)

Provides built-in process intelligence that allows the printing of barcodes on any appropriately configured PostScript printer on the SAP R / 3 4.x (or higher) and within Latin-1 (ISO8859-1). SAP system code pages only. Used in conjunction with Xerox Device Types for SAP R / 3 Environment and Xerox Font Center Barcode Fonts. Utility automatically calculates checksum, placement of start / stop characters, encoding of data string and data compression.

## PAPER HANDLING—Duplex Automatic Document Feeder

<b>Capacity*</b>	75 sheets
<b>Speed</b>	55 ipm (WCP55)—8.5 x 11 in. / 216 x 279 mm long edge feed (LEF)
<b>Paper Sizes Sensed</b>	Statement / 5.5 x 8.5 in. / 140 x 216 mm / A5 LEF or short edge feed (SEF) Letter / 8.5 x 11 in. / 216 x 279 mm / A4 LEF or SEF Legal / 8.5 x 14 in. / 216 x 356 mm SEF Ledger / 11 x 17 in. / 279 x 432 mm / A3 SEF
<b>Weights</b>	13 lb to 32 lb bond / 50 to 120 gsm

## PAPER HANDLING—Front-Loading Paper Trays

<b>Number</b>	Two
<b>Capacity*</b>	550 sheets each
<b>Sizes</b>	User adjustable from 5.5 x 8.5 in. / 140 x 216 mm / A5 to 11 x 17 in. / 279 x 432 mm / A3
<b>Weights</b>	16 lb bond to 110 lb index / 60 to 200 gsm
<b>Types</b>	Letterhead Bond Preprinted forms Plain Tab stock Envelopes (optional, Tray 2 only) Hole-punched Heavyweight Recycled paper

\*Paper capacities are based on 20 lb bond / 75 gsm stock; capacities will vary with different weight stocks.

## WorkCentre® Pro 55 Advanced Multifunction System

## PAPER HANDLING—Bypass Tray

<b>Capacity*</b>	100 sheets
<b>Sizes</b>	4.13 x 5.83 in. / 105 x 148 mm to 11.7 x 17 in. / 297 x 432 mm
<b>Weights</b>	16 lb bond to 80 lb cover / 60 to 216 gsm
<b>Types</b>	Letterhead Bond Preprinted forms Plain Tab stock Envelopes Hole-punched Heavyweight Recycled paper Label stock Transparencies

## PAPER HANDLING—High-Capacity Feeder

<b>Capacity*</b>	Two trays: 1,600 and 2,000 sheets
<b>Paper Size</b>	Letter / 8.5 x 11 in. / 216 x 279 mm / A4 LEF
<b>Weights</b>	16 lb bond to 110 lb index / 60 to 200 gsm
<b>Total Capacity*</b>	4,800 sheets (with Bypass Tray, Front-Loading Paper Trays and High-Capacity Feeder Two Tray Module)

## OUTPUT OPTION—Offsetting Catch Tray Option

<b>Capacity*</b>	300 sheets (Letter / 8.5 x 11 in. / 216 x 279 mm / A4)
<b>Sizes</b>	4.25 x 5.5 in. / A6 to 11 x 17 in. / A3

## OUTPUT OPTION—Office Finisher Option

<b>Top Tray</b>	Capacity:* 250 sheets
<b>Stacking Tray</b>	Capacity:* 2,000 sheets
<b>Sizes</b>	4.25 x 5.5 in. / A6 to 11 x 17 in. / A3
<b>Weights</b>	16 lb bond to 80 lb cover / 60 to 216 gsm
<b>Stapling</b>	Single (any corner) and dual Auto stapling (50 sheets maximum) Offline stapling (40 sheets maximum) Statement, letter, legal, A5, A4, A3, tabloid sizes supported
<b>Hole Punching (optional)</b>	Two and three hole

Continued

\*Paper capacities are based on 20 lb / 75 gsm stock; capacities will vary with different weight stocks.

## WorkCentre® Pro 55 Advanced Multifunction System

## FAX (optional)

<b>Compatibility</b>	ITU (CCITT) Group 3 quality / resolution of 600 x 600, 300 x 300, 200 x 200, 200 x 100 dpi
<b>Speed / Modem(s)</b>	V.34 modem(s): 33,600 bps. Less than four seconds per page transmission time. ISDN via third-party adapter.
<b>Speed / Compression</b>	MMR, MR, MH
<b>Fax Send Features</b>	Auto fax transmission reduction Page-by-page job status at the machine Fax from platen Delay start Automatic memory resend Automatic cover sheets Priority send Broadcast
<b>Fax Receive Features</b>	One- or two-sided printing, stapled or unstapled Reduction at reception to fit available paper Junk fax prevention
<b>Fax Reports</b>	Activity report Broadcasting Dial directory Transmission confirmation Pending fax Mailbox
<b>Fax Receive Mailboxes</b>	Up to 200 password-protected mailboxes
<b>Auto Dialing</b>	Total of 200 speed dials Up to 200 dial groups with up to 200 recipients per group Auto redial Batch send

## ACCOUNTING

<b>Accounting With Third-Party Server Applications (Optional)</b>	Up-to-the-minute data on how the WorkCentre Pro system is being used; comprehensive usage tracking and reporting; print, scan, copy and fax Multiple accounting vendors, certified by the Xerox Business Partner program. For details, visit <a href="http://www.xerox.com">www.xerox.com</a> .
<b>Internal Auditron</b>	Tracks copy usage Supports up to 2,150 user accounts, 5,925 general accounts and 256 group accounts Auditron report printout available Ability to upload / download account and usage data via direct connection using Microsoft® Windows-based software

## MONTHLY DUTY CYCLE

Up to 200,000

## BASIC CONFIGURATION\*

Network Multifunction System with network controller, High-Capacity Feeder and Duplex Automatic Document Feeder

## WorkCentre® Pro 55 Advanced Multifunction System

## ACCESSORIES

One-line fax option  
 Xerox Copy Assistant  
 Office Finisher  
 Two-hole legal punch option (N. America)  
 Three-hole punch option (N. America)  
 Foreign Device Interface  
 Offsetting Catch Tray  
 Network Accounting Enablement  
 Network Scanning With E-Mail  
 Network Fax Server Integration  
 Internet Fax  
 Image Overwrite Security  
 Scan to PC Desktop Client Software  
 Copy Pre Collation RAM Upgrade (256 MB)  
 Envelope Insert Kit (Tray 2)  
 Convenience Stapler (50 sheets)  
 SMARTsend  
 SMARTsend Professional

## ELECTRICAL REQUIREMENTS

110–140 V Nominal, 60 Hz, 15A

## POWER CONSUMPTION

<i>Running</i>	< 1247 watts
<i>Standby</i>	< 284 watts
<i>Low Power Mode</i>	< 223 watts
<i>Sleep Mode</i>	< 75 watts
<i>Warm-up</i>	105 seconds (maximum)
<i>Low-Power Recovery</i>	30 seconds (maximum)

## ENVIRONMENTAL CONSIDERATIONS

<i>Required Temperature Range</i>	50° to 90° F (10° to 32° C)
<i>Required Relative Humidity</i>	10% to 85%

\*Features, configurations and options may vary by location.

WorkCentre® Pro 55 Advanced Multifunction System

DIMENSIONS AND WEIGHT

	<i>Width</i>	<i>Depth</i>	<i>Height</i>	<i>Weight</i>
<i>Fully Configured With Office Finisher</i>	58.7 in. / 1,490 mm	28.3 in. / 720 mm	43.9 in. / 1,115 mm	399 lbs / 181 kg

SPACE REQUIREMENTS

	<i>Width</i>	<i>Depth</i>	<i>Height</i>
<i>Fully Configured With Office Finisher—Movable Surface</i>	88.3 in. / 2,245 mm	67 in. / 1,700 mm	78 in. / 1,981 mm

CERTIFICATIONS

FCC Class A Compliant (U.S.), DOC Class A Compliant (Canada)  
 89 / 336 / EEC (Europe)  
 UL Listed (UL 1950, Third Edition)  
 CB Certified (IEC 60950 / EN 60950)  
 73 / 23 / EEC (Europe)  
 Novell Tested and Approved  
 Windows Hardware Quality Labs  
 99 / 5 / EEC (Europe)

SUPPLIES

<i>Description</i>	<i>Order Number</i>	<i>No. per Box</i>	<i>Expected Yield</i>
Toner Cartridge	6R1046	2	30,000
Staple Cartridge	108R493	3	5,000 per cartridge
Convenience Stapler Cartridge			
Complete Cartridge	8R12964	1	5,000 per cartridge
Refill Cartridge	8R12941	3	5,000 per cartridge (15,000 staples)

Total satisfaction guaranteed.

The exclusive Xerox Total Satisfaction Guarantee, recognized as unique in the industry, covers every Xerox WorkCentre® Pro which has been continuously maintained by Xerox or its authorized representatives under a Xerox express warranty or Xerox Maintenance agreement. You decide when you're satisfied.



© 2006 XEROX CORPORATION. All rights reserved. XEROX®, CentreWare®, WorkCentre® Pro and Copier Assistant are trademarks of XEROX CORPORATION. Other marks are trademarks or registered trademarks of the companies with which they are associated. The in.Editor's Choice in. logo is the exclusive service mark of Better Buys for Business. In support of Xerox's environmental leadership goals, these models may contain some recycled components that are reconditioned. ENERGY STAR® is a U.S. registered mark. As an ENERGY STAR Partner, Xerox Corporation has determined that these products meet the ENERGY STAR guidelines for energy efficiency. Terra Choice Environmental Services, Inc., of Canada has verified that these products conform to all applicable Environmental Choice EcoLogo requirements for minimized impact to the environment. Product appearance, build status and / or specifications are subject to change without notice. 5/06 X555S-02UB 610P726320A