

Xerox® Integrated Copy/Print Server

for the Xerox® D95A/D110/D125 Copier/Printer

With the state-of-the-art Xerox® Integrated Copy/Print Server, the Xerox® D95A/110/125 Copier/Printer delivers a portfolio of the industry's most innovative features and capabilities. You'll get a simple workflow with an easy-to-use touch screen, FreeFlow® integration, excellent features and a small footprint.



- Ease of use. Straightforward graphic user interface is rich in easily accessible features with large 10.4 inch full color touch screen.
- **Superior scanning.** Create text-searchable files at the device for easy retrieval—compression technology reduces network load for fast transmission.
- Remotely manage your device. Xerox® CentreWare® Software IS Embedded Web Server automates installation, troubleshooting feature set-up and upgrading.
- Multiple Sets of Copies with Separators. Make multiple collated or uncollated sets separated by slip sheets for efficient distribution.
- **Security.** A large set of security features is packed into one compact device, including Secure Print, data encryption/overwrite capabilities and optional removable hard drives.
- Copy and Save/Print and Delete Modes. Select "copy and save" on the touch screen and, as you copy, document images and settings are saved to a mailbox/folder on the internal server.
- Thumbnail Preview. See a thumbnail view of your copy/scan job right at the touch screen.
- **Bates Stamping.** Built-in Bates Stamping feature generates copies with customized alpha-numeric descriptors on each page.
- Extensible Interface Platform®. This is a software platform that allows productivity-enhancing solutions to be easily accessed right at the copier/printer's touch screen interface. Learn more about our many solutions offerings by visiting www.xerox.com/software-solutions.
- Exception page programming. Easy programming of your jobs right at your PC or MAC® print driver, for example, color covers and inserts, tabs and Z-folds.

Xerox® D95A/D110/D125 Copier/Printer

Standard Integrated Copy/Print Server Specifications

Hardware Specifications

- 250 GB Hard Disk Drive, 2 GB RAM
- 10.4 inch color, touch screen flat-panel display
- Ethernet interface (10 MBTX/sec, 100 MBTX/sec and 1000MBTX/sec)

Client Environments Supported

- Windows XP SP1 and above (32 and 64 bit), Server 2003/2008 (32 and 64 bit), Vista (32 and 64 bit), Windows 7 (32 and 64 bit)
- Mac OS 10.4 and above
- Citrix
- Custom driver for Unix: AIX 5 v5.3, HP-UX® 11.0/11i v2
- Oracle Solaris® 8/9/10
- Linux® Fedora Core 1/5
- Red Hat® ES4, SUSE 10/11
- Citrix and WHQL certification*
 *Dependent on configuration, software version

File Format Support

- Adobe[®] PostScript[®] 3[™]
- PDF
- PCL® 5e and 6
- TIFF
- HP-GL. HP-GL2

Network Environments / Protocols

- TCP/IP, SNMP, SMB, Novell[®] IPX, AppleTalk[®], IPP
- Copy and Save to mailbox/folders
- Preview documents from mailbox before printing
- Mailbox backup and restore
- IPv6 compliant

Print Features

- Automatic two-sided
- Secure print
- Delay print
- Sample set
- Booklet creation
- Cover selection
- Paper selection by attribute
- N-up
- Watermarks
- Banner sheets
- Fit to new paper size
- Output tray selection
- Print from and Scan to USB

Accounting

- Auditron
- Xerox[®] Standard Accounting (copy, print, fax, scan)
- Enabling color access control
- Optional Network Accounting Enablement Kit
- Job Based Accounting

PDLs and Data Formats

- PDF, XPS[®], PCL 6 emulation, HP-GL2 (direct submission), TIFF, JPEG
- Adobe® PostScript® 3™

Scan and Copy

- Robust Set of Scan/Copy Functions –
 Plus Scan to Email, Scan to Folder, to PC, to Mailbox (private and public)
- Options include FTP, SMB, Desk, Text searchable PDF, PDF/A, XPS, Thumbnail Preview, Copy and store files for easy retrieval and reprint
- Scan to and Print from USB

Other Options

- Media Card Reader
- Common Access Card Enablement Kit
- Xerox Extensible Interface Platform® Enabled
- Foreign Device Interface
- Mobile / Smartphone Printing

Data Security

- Standard Secure Print
- Authentication with LDAP/Kerberos/ SMB/CAC
- Password Protected PDF
- FIPS 140-2 encryption
- S/MIME Encrypted Email
- IPsec
- 802.1X
- SNMP v3.0
- Email over SSL
- Image Overwrite (3x or 1x, Immediate, Scheduled, On Demand)
- Hard Disk Data Encryption
- Audit Log
- Optional CAC
- IPv6 Ready
- 256 Bit Encryption
- Common Criteria Certified

Electrical Requirements

- Print Engine:
 - 208 to 240 VAC, 60/50 Hz,
 15/13 amp service
- KVA Rating: Max Power Consumption:2.8 to 3.1 KVA
- Optional Feeding/Finishing:
- Each module requires 100 to 240 VAC, 60/50
 Hz power

Dimensions

Print Engine:

- Width: 28 in. / 711 mm
- Depth: 31 in. / 787 mm
- Height: 57.5 in. / 1,460.5 mm
- Weight: 606 lbs. / 275 kg

Agency Approvals

ENERGY STAR®, CSA.

Europe: CE, NEMKO, RoHS, WEEE compliance

For more information on the Xerox[®] Integrated Copy/Print Server for Xerox[®] D95A/D110/D125 Copier/Printer, contact your Xerox representative, call 1-800-ASK-XEROX or visit us at www.xerox.com.

