

C Druckerspezifikationen (nur Englisch)

Physical Specifications

Printer

- Width: 640 mm (25.2 in.)
- Depth: 525 mm (20.7)
- Height: 498 mm (19.6 in.)
- Weight: 41 kg (90 lbs.)

Optional Duplex Unit

- Width: 64 mm (2.52 in.)
- Depth: 458 mm (18 in.)
- Height: 211 mm (8.3 in.)
- Weight: 1.8 kg (4 lbs.)

Optional 1000-Sheet Feeder

- Width: 540 mm (21.3 in.)
- Depth: 520 mm (20.5 in.)
- Height: 280 mm (11 in.)
- Weight: 23 kg (50.7 lbs.)

Optional 2000-Sheet Feeder

- Width: 385.5 mm (15.2 in.)
- Depth: 600 mm (23.6 in.)
- Height: 363 mm (14.3 in.)
- Weight: 28 kg (62 lbs.)

Optional 3500-Sheet Finisher

- Width: 740 mm (29 in.)
- Depth: 650 mm (25.6 in.)
- Height: 1050 mm (41.3 in.)
- Weight: 49 kg (108 lbs.)

Environmental Specifications

Temperature

- Storage: 5–32 degrees C / 41–90 degrees F
- Operating: 5–32 degrees C / 41–90 degrees F

Relative Humidity

- Storage: 15%–85%
- Operating: 15%–85%

Electrical Specifications

Available in five (5) configurations: Phaser 5500B, 5500N, 5500DN, 5500DT, 5500DX

- 110–127 VAC, 50/60 Hz
- 220–240 VAC, 50/60 Hz
- ENERGY STAR qualified printer

Performance Specifications

Resolution

- 600 x 600 dpi
- True 1200 x 1200 dpi

Print Speed

- Up to 50 pages per minute (ppm)

Controller Specifications

- 500 MHz processor

Memory

- 128 MB PC133 DRAM standard on Phaser 5500B, 5500N, 5500DN, and 5500DT configurations
- 256 MB PC133 DRAM standard on Phaser 5500DX configuration
- Upgradable to a maximum of 512 MB

Page Description Languages (PDL)

- PCL
- Adobe PostScript 3

Fonts

- PostScript
- PCL

Interfaces

- IEEE 1284 parallel
- Ethernet 10BaseT and 100BaseTx (only for N, DN, DT, and DX configurations)
- USB