

C Especificações da impressora (apenas em inglês)

Physical Specifications

Printer

- Width: 439 mm (17.30 in.)
- Depth: 638 mm (25.14 in.)
- Height: 445 mm (17.53 in.)
- Weight: 37 kg (80 lbs.)

Optional High-Capacity Feeder

- Width: 439 mm (17.30 in.)
- Depth: 563 mm (22.18 in.)
- Height: 336 mm (13.24 in.)

Optional 500-Sheet Feeder

- Width: 439 mm (17.30 in.)
- Depth: 563 mm (22.18 in.)
- Height: 172 mm (6.78 in.)

Environmental Specifications

Temperature

- Storage: -20° to 60° C / -4° to 140° F
- Operating: 10° to 32° C / 50° to 90° F
- Optimum print quality environmental conditions: 17° to 26° C / 62° to 80° F

Relative Humidity

- Storage: 10% to 95%
- Operating: 10% to 85%
- Optimum print quality environmental conditions: 35% to 70%

Electrical Specifications

Available in two (2) models:

- 110-127 VAC, 50/60 Hz
- 220-240 VAC, 50/60 Hz

ENERGY STAR qualified printer

Performance Specifications

Resolution

- 600 x 600 dpi
- 2400 x 600 dpi

Print Speed

- Letter: 26 pages per minute (ppm)
- A4: 24 ppm

Controller Specifications

500 MHz processor

Memory

- 128 Mbytes PC133 DRAM standard on the Phaser® 6250B Color Laser Printer
- 256 Mbytes PC133 DRAM standard on the Phaser® 6250N Color Laser Printer
- 256 Mbytes PC133 DRAM standard on the Phaser® 6250DP Color Laser Printer
- 512 Mbytes PC133 DRAM standard on the Phaser® 6250DT Color Laser Printer
- 512 Mbytes PC133 DRAM standard on the Phaser® 6250DX Color Laser Printer
- Upgradable to a maximum of 512 Mbytes

Page Description Languages (PDL)

- PCL5c
- Adobe PostScript 3

Resident Fonts

- 136 PostScript Type 1

Interfaces

- IEEE 1284 parallel
- Ethernet 10BaseT and 100BaseTx
- USB