

# Xerox® Phaser® 3320 and WorkCentre™ 3315/3325

## Black and white Printer and Multifunction Printer



	Phaser 3320	WorkCentre 3315	WorkCentre 3325
<b>Output Speed</b>			
<b>One-sided printing</b>	Up to 35 ppm A4 (210 x 297 mm)	Up to 31 ppm A4 (210 x 297 mm)	Up to 35 ppm A4 (210 x 297 mm)
<b>Two-sided printing</b>	Up to 17 ppm A4 (210 x 297 mm)	Up to 15 ppm A4 (210 x 297 mm)	Up to 17 ppm A4 (210 x 297 mm)
<b>Paper Handling - Input</b>			
<b>Document Feeder</b>			
<b>Capacity<sup>1</sup></b>	NA	Automatic Document Feeder (ADF): 50 sheets	Duplex Automatic Document Feeder (DADF): 50 sheets
<b>Sizes</b>		Custom Sizes: 142 x 148 mm to 216 x 356 mm	
<b>Weights</b>		60 to 105 gsm	50 to 105 gsm
<b>Bypass Tray</b>			
<b>Capacity<sup>1</sup></b>	50 sheets		
<b>Sizes</b>	Custom Sizes: 76 x 127 mm to 216 x 356 mm		
<b>Weights</b>	60 to 220 gsm		
<b>Media Types</b>	Plain paper Envelopes Labels Transparencies Card stock Recycled		
<b>Tray 1</b>			
<b>Capacity<sup>1</sup></b>	250 sheets		
<b>Sizes</b>	Sizes: 105 x 148 mm to 216 x 356 mm		
<b>Weights</b>	60 to 163 gsm		
<b>Media Types</b>	Plain paper Card stock Recycled		

<sup>1</sup> Paper capacities are based on 75 gsm stock; capacities will vary with different weight stocks.

# Xerox® Phaser® 3320 and WorkCentre™ 3315/3325

Additional Tray (Optional)			
Capacity <sup>1</sup>	520 sheets		
Sizes	Sizes: 148 x 210 mm to 216 x 356 mm		
Weights	60 to 163 gsm		
Media Types	Plain paper Card stock Recycled		
Paper Capacity			
Standard Capacity <sup>1</sup>	300 sheets		
Maximum Capacity <sup>1</sup>	820 sheets		
Paper Handling - Output			
Standard Output Capacity <sup>1</sup>	150 sheets		
Automatic Two-sided Printing	Standard		
Print	Phaser 3320	WorkCentre 3315	WorkCentre 3325
First-page-out Time	As fast as 6.5 seconds		
Print Resolution (maximum)	Up to 600 x 600 dpi (1200 x 1200 image quality)		
Page Description Languages	PCL® 5c and 6 emulations PostScript 3 emulation	PCL 5c and 6 emulations PostScript 3 emulation PDF emulation	PCL 5c and 6 emulations PostScript 3 emulation PDF emulation XPS®
Maximum Print Area	4.23 mm from edge of paper		
Printing Features	Watermarks Collation Auto 2-sided prints N-up Poster Booklet print Custom page size Fit to page Scaling Toner Save mode Earth Smart mode	Watermarks Collation Auto 2-sided prints N-up Poster Booklet print Custom page size Fit to page Scaling Toner Save mode Earth Smart mode Print from USB	Watermarks Collation Auto 2-sided prints N-up Poster Booklet print Custom page size Fit to page Scaling Toner Save mode Earth Smart mode Print from USB Job scheduling Print from local drive Save Save and Print
Print Drivers	Windows® XP, 2003 Server, 2008 Server, Vista, 7 Mac OS® 10.5 and higher ORACLE® Solaris 9, 10 Red Hat® Enterprise Linux® 4 Fedora Core SUSE® IBM® AIX 5 HP-UX® Xerox® Global Print Driver® Xerox® Mobile Express Driver®		
Font Capability	PostScript fonts: 136 PCL fonts: 111 scalable, 1 bitmap		

<sup>1</sup> Paper capacities are based on 75 gsm stock; capacities will vary with different weight stocks.

# Xerox® Phaser® 3320 and WorkCentre™ 3315/3325

<b>Xerox® Global Print Driver® (X-GPD)</b>	<p>A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.</p> <ul style="list-style-type: none"> <li>• Printers are automatically discovered</li> <li>• Provides bidirectional feedback for device status, supplies, queue management</li> </ul>		
<b>Copy</b>	<b>Phaser 3320</b>	<b>WorkCentre 3315</b>	<b>WorkCentre 3325</b>
<b>Copy Speed</b> Black-and white	NA	Up to 31 ipm (images per minute) A4 (210 x 297 mm)	Up to 35 ipm (images per minute) A4 (210 x 297 mm)
<b>Document Scanner</b>		Automatic Document Feeder with 50-sheet capacity	Duplex Automatic Document Feeder with 50-sheet capacity
<b>Document Scanner Size</b>		Platen: Up to A4 ADF: Up to 216 x 356 mm	Platen: Up to A4 DADF: Up to 216 x 356 mm
<b>Sides (input:output)</b>		1:1, 1:2	1:1, 1:2, 2:2 and 2:1
<b>Quantity</b>		1 to 999	
<b>Resolution</b>		Up to 600 x 600 dpi	
<b>Concurrency</b>		NA	Concurrent scanning and printing
<b>First-copy-out Time</b>		As fast as 12 seconds	As fast as 10 seconds
<b>Copy Features</b>		Automatic background suppression Darkness control ID Card Copy Margin shift N-up Job build Photo mode Programme Ahead	Automatic background suppression Darkness control ID Card Copy Margin shift N-up Job build Photo mode Programme Ahead Booklet creation Book copying with centre erase Edge erase Job interrupt Poster copying
<b>Fax<sup>2</sup></b>	<b>Phaser 3320</b>	<b>WorkCentre 3315</b>	<b>WorkCentre 3325</b>
<b>Fax Speed</b>	NA	33.6 Kbps	
<b>Memory</b>		4 MB	
<b>Resolution</b>		Up to 300 x 300 dpi (Super Fine / Photo) resolution Up to 203 x 196 dpi (Fine) resolution Up to 203 x 98 dpi (Standard) resolution	
<b>Compression</b>		MH, MR, MMR, JBIG, JPEG	
<b>Fax Features</b>		Address book (up to 200 speed dials, 209 group dials) Auto redial Auto reduction Colour Fax Send Delayed Send Fax Forward to Email/Fax Junk fax protection Memory Receive PC Fax (Windows only) Secure Fax	

<sup>2</sup> Analogue phone line required

# Xerox® Phaser® 3320 and WorkCentre™ 3315/3325

Scan	Phaser 3320	WorkCentre 3315	WorkCentre 3325
<b>Capability</b>	NA	Black and white and colour scanning	
<b>Concurrency</b>		NA	Scan while the system is printing copy or network print jobs, or while it is transferring scan to network or fax jobs
<b>Input Speed</b>		Black and white: Scan up to 20 ipm – A4 (210 x 297 mm) Colour: Scan up to 6 ipm – A4 (210 x 297 mm)	Black and white: Scan up to 24 ipm – A4 (210 x 297 mm) Colour: Scan up to 8 ipm – A4 (210 x 297 mm)
<b>Resolution (maximum)</b>		Black and white: Up to 4800 x 4800 dpi Colour: Up to 600 x 600 dpi	
<b>Bit Depth</b>		24-bit colour, 8-bit grayscale	
<b>Maximum Scan Area</b>		Platen: Up to A4 ADF: Up to 216 x 356 mm	Platen: Up to A4 DADF: Up to 216 x 356 mm
<b>Network Filing Protocol</b>		SMTP	FTP SMTP SMB
<b>File Formats</b>		PDF TIFF (single and multipage) JPEG BMP	
<b>Scan Driver Compatibility</b>		WIA TWAIN	
<b>Supported Scan Destinations</b>		Scan to Email Scan to USB Scan to Local PC Scan to Network PC	Scan to Email Scan to USB Scan to Local PC Scan to Network PC Scan to Folder Scan to FTP Scan to SMB Scan to Local Drive
<b>Scanning Solutions</b>			
<b>Xerox® Scan to PC Desktop Personal Edition</b>	NA	<p>A desktop and server-based offering that provides document imaging, archiving, editing and organisation tools</p> <ul style="list-style-type: none"> <li>• Nuance PaperPort – image viewing and file management software</li> <li>• Nuance OmniPage (for desktop/client installation) – OCR and file format conversion software</li> <li>• Image Retriever – provides fully automated retrieval of scanned images direct from a scan enabled Xerox® WorkCentre to individual desktops.</li> </ul>	
		For a complete list of scanning solutions, visit <a href="http://www.xerox.com">www.xerox.com</a>	

# Xerox® Phaser® 3320 and WorkCentre™ 3315/3325

Security	Phaser 3320	WorkCentre 3315	WorkCentre 3325
<b>Security Features</b>	Secure HTTPS (SSL) IPsec 802.1X SNMPv3 IP Filtering Secure Print Mac Address Filtering	Secure HTTPS (SSL) IPsec Secure LDAP 802.1X SNMPv3 IP Filtering Secure Print (with optional 256 MB memory upgrade) Mac Address Filtering	Secure HTTPS (SSL) IPsec Secure LDAP 802.1X SNMPv3 IP Filtering Secure Print Mac Address Filtering Network Authentication Image Overwrite
<b>Device Management</b>			
<b>Xerox® CentreWare® Web</b>			
	<ul style="list-style-type: none"> <li>• A Web-based server application for network administrators that permits web browser-based device management from any workstation, whether running Windows or UNIX or any other operating system</li> <li>• Works with any SNMP-managed printer from any manufacturer</li> <li>• Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades as well as basic accounting and asset management</li> </ul>		
<b>Xerox® CentreWare® Internet Services - Integrated Device Web Page</b>			
<b>Device Status</b>	Web server embedded <ul style="list-style-type: none"> <li>• Tray status/contents</li> <li>• Consumables status</li> </ul>		
<b>Print Queue Viewing</b>	Complete job print queue management – hold, release, promote and delete		
<b>Job Submission</b>	Print-ready files (PS, PCL, TIFF, PDF) Output feature selection		
<b>Device Administration</b>	Allows simple, remote installation setting of configuration options and management of the device		
<b>Browsers</b>	Microsoft® Internet Explorer 6, 7 Firefox® 2., 3 Safari® 3.0		
<b>Xerox® Mobile Solutions</b>			
<b>Xerox® PrintBack</b>	Ideal for environments where software and solutions are installed by individuals, Xerox® PrintBack enables printing to the default printer you already use with your computer. Plus, it supports the most common office file types (Microsoft® Office documents, PDF, etc.) and delivers uncompromising print quality. For more information, visit <a href="http://www.xerox.com/mobile">www.xerox.com/mobile</a>		
<b>Xerox® Mobile Express Driver®</b>	The Xerox® Mobile Express Driver® is a single, universal printer driver that can be downloaded to a PC and used to print to virtually any PostScript device on the network, including printers made by other manufacturers. Instead of downloading individual printer drivers for each product in each office, users can download the single, simple, Xerox® Mobile Express Driver®, making it easy for mobile users to find, use and manage Xerox® and non-Xerox devices in every new location. Plug into a new network, and X-MED automatically discovers available printers and provides status and capability information. Save a list of “favourite” printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT. <ul style="list-style-type: none"> <li>• Printers are automatically discovered</li> <li>• Printer list can be managed based on location</li> <li>• Provides bidirectional feedback for device status, supplies, queue management</li> </ul>		

# Xerox® Phaser® 3320 and WorkCentre™ 3315/3325

Device Specifications	Phaser 3320	WorkCentre 3315	WorkCentre 3325
<b>Platen Size</b>	NA	Up to A4	
<b>Memory</b> (Standard / maximum)	128 MB / 384 MB		256 MB / 768 MB
<b>Local Drive</b>	NA		2 GB
<b>Processor</b>	600 MHz	360 MHz	600 MHz
<b>Language Support</b>	PCL® 5c and 6 emulations PostScript 3 emulation	PCL 5c and 6 emulations PostScript 3 emulation PDF emulation	PCL 5c and 6 emulations PostScript 3 emulation PDF emulation XPS®
<b>Connectivity</b>	USB 2.0 10/100/1000Base-T Ethernet Wi-Fi <sup>3</sup>	USB 2.0 10/100Base-T Ethernet	USB 2.0 10/100/1000Base-T Ethernet Wi-Fi <sup>3</sup>
<b>Operating Systems</b>	Windows® XP, 2003 Server, 2008 Server, Vista, 7 Mac OS® 10.3 and higher ORACLE® Solaris 9, 10 Linux® Sparc AS400 Citrix Presentation Server SAP Windows Terminal Services IBM® AIX 5 HP-UX®		
<b>Duty Cycle</b>	<b>Phaser 3320</b>	<b>WorkCentre 3315</b>	<b>WorkCentre 3325</b>
	Up to 80,000 pages per month <sup>4</sup>	Up to 50,000 pages per month <sup>4</sup>	Up to 80,000 pages per month <sup>4</sup>
<b>Recommended Monthly Print Volume</b>			
	Up to 6,000 pages per month <sup>5</sup>	Up to 4,000 pages per month <sup>5</sup>	Up to 6,000 pages per month <sup>5</sup>
<b>Sound Pressure Levels</b>			
<b>Printing / Copying</b>	52 dB(A)	52 dB(A)	53 dB(A)
<b>Standby</b>	26 dB(A)	26 dB(A)	26 dB(A)
<b>Sound Power Levels</b>			
<b>Printing / Copying</b>	6.7 B(A)	6.5 B(A)	6.7 B(A)
<b>Standby</b>	0 B(A)	0 B(A)	0 B(A)
<b>Power Consumption</b>			
<b>220-240 VAC, 50/60 Hz, 3.3A</b>			
<b>Printing</b> (average operations)	<420 watts	<600 watts	
<b>Standby</b>	<48 watts	<50 watts	
<b>Sleep</b>	<10 watts	<8 watts	
<b>Warm up</b> From Sleep mode From power on From Power Save mode (UI ready) From Power Save mode (first page)	As fast as 30 seconds As fast as 57 seconds As fast as 15 seconds As fast as 14 seconds	As fast as 35 seconds As fast as 57 seconds As fast as 15 seconds As fast as 14.5 seconds	As fast as 35 seconds As fast as 57 seconds As fast as 15 seconds As fast as 14 seconds

<sup>3</sup> 3320V\_DNI and 3325V\_DNI

<sup>4</sup> Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

<sup>5</sup> Average monthly print volume - expected regular monthly throughput.

# Xerox® Phaser® 3320 and WorkCentre™ 3315/3325

<b>Storage Temperature Range</b>	0° to 40° C
<b>Operating Temperature Range</b>	10° to 32° C
<b>Storage Humidity Range</b> Packed Unpacked	10% to 90% 20% to 80%
<b>Operating Humidity Range</b>	20% to 80%
<b>Optimal Humidity Range</b>	30% to 70%

<b>Dimensions and Weights</b>	<b>Width</b>	<b>Depth</b>	<b>Height</b>	<b>Weight</b>
<b>Phaser 3320</b>	366 mm	368 mm	257 mm	9.89 kg
<b>WorkCentre 3315</b>	424 mm	422 mm	417 mm	14.37 kg
<b>WorkCentre 3325</b>	469 mm	458 mm	447 mm	16.55 kg

<b>Additional Paper Tray</b>	454 mm	366 mm	146 mm	11.6 kg
------------------------------	--------	--------	--------	---------

<b>Packaged Dimensions and Weights</b>	<b>Width</b>	<b>Depth</b>	<b>Height</b>	<b>Weight</b>
<b>Phaser 3320</b>	509 mm	452 mm	373 mm	11.7 kg
<b>WorkCentre 3315</b>	569 mm	551 mm	535 mm	18.2 kg
<b>WorkCentre 3325</b>	594 mm	594 mm	584 mm	20.09 kg
<b>Additional Paper Tray</b>	584 mm	518 mm	297 mm	12.4 kg

<b>Certifications</b>	
	FCC Part 15, Class B FCC Part 68 CE Mark applicable to Low Voltage Directive 2006/95/EC EMC Directive 2004/108/EC and R&TTE Directive 1999/5/EC UL 60950-1/CSA 60950-1-07, 2nd Edition GOST NOM GS Mark Citrix Ready Section 508 (compliant with minor exceptions) Blue Angel (does not include WorkCentre 3315) ENERGY STAR® qualified

<b>What Comes in the Box</b>	
	Phaser 3320, WorkCentre 3315 or WorkCentre 3325 Print cartridge: Phaser 3320 / WorkCentre 3325: 5,000 print capacity <sup>6</sup> ; WorkCentre 3315: 2,300 print capacity <sup>6</sup> ) Documentation and Software CD (with User Manual, Quick Install Guide, Print Drivers, System Administrator Guide and Warranty Statement) Power cord Fax cord (WorkCentre 3315/3325 only)

<sup>6</sup> Average standard pages. Declared Yield in accordance with ISO/IEC 19752. Yield will vary based on image, area coverage and print mode.

# Xerox® Phaser® 3320 and WorkCentre™ 3315/3325

Supplies and Options	Description	Yield	Part Number
High-Capacity Print Cartridges	Phaser 3320	11,000 standard pages <sup>6</sup>	106R02307
	WorkCentre 3315	5,000 standard pages <sup>6</sup>	106R02311
	WorkCentre 3325	11,000 standard pages <sup>6</sup>	106R02313
Standard-Capacity Print Cartridges	Phaser 3320	5,000 standard pages <sup>6</sup>	106R02305
	WorkCentre 3315	2,300 standard pages <sup>6</sup>	106R02309
	WorkCentre 3325	5,000 standard pages <sup>6</sup>	106R02311
Options	Additional 520-sheet Paper Tray		497N01412
	256 MB Memory (Phaser 3320 and WorkCentre 3315)		098N02189
	512 MB Memory (WorkCentre 3325)		098N01878

<sup>6</sup> Average standard pages. Declared Yield in accordance with ISO/IEC 19752. Yield will vary based on image, area coverage and print mode.

For more information, visit us at [www.xerox.com/office](http://www.xerox.com/office)



©2014 Xerox Corporation. All rights reserved. XEROX®, XEROX and Design®, CentreWare®, Phaser® and WorkCentre™ are trademarks of Xerox Corporation in the United States and/or other countries. As an ENERGY STAR® partner, Xerox Corporation has determined that this product meets the ENERGY STAR guidelines for energy efficiency. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. The information in this brochure is subject to change without notice. Updated 6/15 3325S-01EC

