

Xerox[®] Phaser[®] 4600 ISO / IEC 19752 Yield Test Report

Published Yield

Toner Cartridge Yield 30,000 Standard Pages

Declaration of Yield

When Genuine Xerox Phaser 4600 Toner Cartridges are used in a Xerox Phaser 4600 printer:

Toner Cartridge Yield:

Average 31,216 Standard Deviation 1,844 90% Lower Confidence 30,073 90% Upper Confidence 32,359

Date Tested: 11/30/2010 - 12/05/2010

"Customer Report, compliant with ISO/IEC 29142"

For questions concerning testing, contact:

Director of Quality Assurance Xerox Corporation 26600 SW Parkway Ave. Wilsonville, OR 97070

Testing Conditions

Number of cartridges used in testing 9
Number of cartridges used in calculation 9

Type of cartridge Toner only

Shake procedure used No

Print mode Continuous

Number of engines used in testing 3

Media used 75 gsm plain paper

Paper size A4

Paper feed orientation Short Edge Feed

Computer model

Driver version 5.181.4.0N
Operating system Windows® 7

Application software Adobe® Acrobat® version 9

Test Page version Version 4.0

Power on/off every day? Yes

Daily Test break: 8 hours

Use Genuine Xerox Supplies Made for Each Other®

© 2011 Xerox Corporation. All rights reserved. Contents of this publication may not be reproduced in any form without permission of Xerox Corporation. XEROX®, XEROX and Design® and Phaser® are trademarks of Xerox Corporation in the U.S. and/or other countries. 3/11