

# Xerox® AltaLink® Multifunction Printers



B8145/B8155/B8170



AltaLink® B8100 Series Multifunction Printers are built on Xerox® ConnectKey® Technology. For more information, go to [www.connectkey.co.uk](http://www.connectkey.co.uk).

| System Specification  | AltaLink® B8145   | AltaLink® B8155     | AltaLink® B8170     |
|---|---|---------------------|---------------------|
| <b>Speed<sup>1</sup></b>  | Up to 45 ppm  | Up to 55 ppm        | Up to 72 ppm        |
| <b>Monthly Duty Cycle<sup>2</sup></b>                                 | Up to 200,000 pages   | Up to 250,000 pages | Up to 300,000 pages |
| <b>Hard Drive/Processor/Memory</b>                                    | Minimum 128 GB SSD/ <b>Optional:</b> 500 GB HDD/Intel® Atom™ Quad Core 1.91 GHz/4 GB system memory  |                     |                     |
| <b>Connectivity</b>   | Ethernet 10/100/1000 Base-T, High-speed USB 2.0 direct print, NFC; <b>Optional:</b> WiFi/WiFi Direct with Xerox Dual Band Wireless Kit, Bluetooth (iBeacon)   |                     |                     |
| <b>Controller Features</b>  | Unified Address Book, Remote Control Panel, Configuration Cloning, Fleet Orchestrator, Configuration Watchdog   |                     |                     |
| <b>Copy and Print</b>   |   |                     |                     |
| <b>Copy and Print Resolution</b>                                      | <b>Copy:</b> Up to 600 x 600 dpi; <b>Print:</b> Up to 1200 x 2400 dpi   |                     |                     |
| <b>First-Print-Out Time (as fast as)</b>                              | 3.8 seconds   | 3.2 seconds         | 3.0 seconds         |
| <b>First-Copy-Out Time (as fast as) (from platen/warmed-up state)</b> | 4.4 seconds   | 3.7 seconds         | 3.2 seconds         |
| <b>Page Description Language</b>                                      | Adobe® PostScript® 3™, Adobe® PDF, PCL® 5c/PCL® 6   |                     |                     |
| <b>Print Features</b>   | Print from USB, Print from Cloud Repositories (Dropbox, OneDrive and Google Drive), Encrypted Secure Print, Xerox® Earth Smart Driver Settings, Job Identification, Booklet Layout, Store and Recall Driver Settings, Bi-directional Real-time Status, Scaling, Job Monitoring, Application Defaults, Two-sided Printing (as default), Hold All Jobs, Long Sheet (Banner) Printing, Print Around, Print on Alternate Paper, Imaging Security with AltaLink's proprietary marking and infrared detection technology; <b>Optional:</b> Print from and Scan to Xerox® DocuShare® Go content management   |                     |                     |
| <b>Mobile- and Cloud-Ready</b>  |   |                     |                     |
| <b>Mobile Connectivity</b>  | Near Field Communication (NFC); <b>Optional:</b> Wi-Fi Direct, Wi-Fi (802.11 b/g/n/ac), AirPrint (iOS) including iBeacon (Bluetooth)  |                     |                     |
| <b>Mobile Printing</b>  | Mopria® Scan, Apple AirPrint™, Xerox® Print Service (Android), @PrintByXerox App; <b>Optional:</b> Xerox® Workplace Mobile App (iOS/Android)  |                     |                     |
| <b>Mobile Scanning</b>  | Mopria® Scan, Apple AirPrint™, <b>Optional:</b> Xerox® Workplace Mobile App (iOS/Android)   |                     |                     |
| <b>Mobile Apps and Xerox App Gallery</b>                              | Automate everyday processes with apps that translate, redact, eSign, personalise, print, convert, route, collaborate and communicate. Visit <a href="http://www.xerox.co.uk/en-gb/office/print-management-solutions">www.xerox.co.uk/en-gb/office/print-management-solutions</a> to find apps by industry or workflow. Software and services: Xerox® DocuShare® ( <a href="http://xerox.co.uk/ecm">xerox.co.uk/ecm</a> ), XMPie® ( <a href="http://www.xerox.co.uk/en-gb/digital-printing/workflow-software/printing-software/xmpie-personalised-communication-software">www.xerox.co.uk/en-gb/digital-printing/workflow-software/printing-software/xmpie-personalised-communication-software</a> ), Xerox® Workplace Solutions ( <a href="http://www.xerox.co.uk/en-gb/office/print-management-solutions">www.xerox.co.uk/en-gb/office/print-management-solutions</a> ). |                     |                     |
| <b>Xerox® Workplace Central Platform</b>                              | One-platform consistency for seamless productivity across computers, mobile devices and printers. With Workflow Central's ever-expanding suite of cloud-based workflows, you can change documents into audio files for easy listening, convert PDF or image files to popular Microsoft formats for shareability with a wider audience, turn handwriting into legible, editable and shareable text, translate to/from over 40 different languages and automatically redact Personal Identifiable Information using set words or phrases.   |                     |                     |
| <b>Xerox® Workplace Suite and Xerox® Workplace Cloud</b>              | <b>Optional:</b> Xerox® Workplace Suite is a modular set of workflows designed to save customers time and money by providing effective control over their printer fleet, while enabling worker productivity and mobility through a set of robust workflows. Xerox enables ultimate customer flexibility by offering these capabilities in both an on-premises server version (Workplace Suite) and a cloud-based version (Workplace Cloud) of this solution.  |                     |                     |
| <b>Cloud Identity Provider (IdP) Integration</b>                      | Use your desktop, laptop or mobile login credentials to log in to your AltaLink® multifunction printers with direct connections to popular cloud identity providers, Okta, Ping Identity and Microsoft® Azure.  |                     |                     |

# Xerox® AltaLink® B8145/B8155/B8170 Multifunction Printer

| Scan                     |   |
|--------------------------|---|
| <b>Standard Features</b> | <b>Destinations:</b> Scan to USB/Email/Network (FTP/SMB), HTTP, HTTPS, SFTP destinations; <b>File Formats:</b> PDF, PDF/A, JPEG, TIFF; <b>Convenience Features:</b> Scan Preview, Scan to Home, Searchable PDF, Touchless Workflow Accelerators, Single/Multi-Page PDF/TIFF, Password-protected PDF, Unified Address Book, Optical Character Recognition (OCR), Scan to Folder, 1-Touch Apps, TWAIN Support, Imaging Security with AltaLink's proprietary marking and infrared detection technology   |
| <b>Optional Features</b> | Scan to Cloud Repositories (Dropbox, OneDrive and Google Drive). Xerox® Scanning App for DocuShare®, other solutions available through various Xerox® Business Innovation Partners at <a href="http://www.xerox.co.uk/en-gb/office/printer-software">www.xerox.co.uk/en-gb/office/printer-software</a> , Print from and Scan to Xerox® DocuShare® Go content management   |
| Fax                      |   |
| <b>Standard Features</b> | Internet Fax, Network Server Fax Enablement, Fax Build Job  |
| <b>Optional Features</b> | Walk-up Fax (one-line and two-line options available, includes LAN Fax, Direct Fax, Fax Forward to Email or SMB Share)  |
| Security                 |   |
| <b>Standard Features</b> | 802.1x, IPsec, HTTPS, SFTP and Encrypted Email, McAfee® Embedded Control Whitelisting, McAfee® ePolicy Orchestrator®, McAfee Enterprise Security Manager, LogRhythm SIEM, Network Authentication, SNMPv3, SHA-256 Hash Message Authentication, TLS 1.1/1.2/1.3, Security Certificates utilising ECDSA, Automatic Self-signed Certificate, Cisco® Identity Services Engine (ISE) integration, automated threat response through McAfee® DXL/Cisco® pxGrid integration, Local Authentication (Internal Database), FIPS 140-2. User Access and Internal Firewall, Port/IP/Domain Filtering, Audit Log, Access Control, User Permissions, Configuration Watchdog, TPM, Trusted Boot, Encrypted Storage Drive (AES 256-bit, FIPS 140-2), Firmware Verification, Job-Level Encryption via HTTPS and Drivers, Email, Common Criteria Certification (ISO 15408) full system against HCP PP, Encrypted Secure Print, Imaging Security (copy, print, scan, email) with AltaLink's proprietary infrared detection technology |
| <b>Optional Features</b> | McAfee® Integrity Control, Smart Card Enablement Kit (CAC/PIV/.NET) <sup>1</sup> , Xerox® Integrated RFID Card Reader, Encrypted Hard Disk (AES 256-bit, FIPS 140-2) with multi-pass Image optional hard drive, Xerox® Workplace Cloud/Suite Print Management and Content Security; learn more at <a href="http://www.xerox.co.uk/en-gb/office/print-management-solutions">www.xerox.co.uk/en-gb/office/print-management-solutions</a>  |
| Print Management         |   |
| <b>Standard Features</b> | Xerox® Standard Accounting (Copy, Print, Scan, Fax, Email), Network Accounting Enablement   |
| <b>Optional Features</b> | Xerox® Workplace Cloud/Suite, other network accounting solutions available through various Xerox® Business Innovation Partners. Xerox® Virtual Print Management Services; learn more at <a href="http://www.xerox.co.uk/en-gb/office/printer-software#printmanagement">www.xerox.co.uk/en-gb/office/printer-software#printmanagement</a>  |

# Xerox® AltaLink® B8145/B8155/B8170 Multifunction Printer

## Features and Accessories

### Single-Pass Duplex Automatic Document Feeder (DADF)

saves time by simultaneously scanning both sides of a document with up to 270 impressions per minute (ipm).



### USER INTERFACE




**Intuitive Tablet-like 10.1-inch Colour Touchscreen** is customisable and lets you perform tasks in just a few taps. Try it out at [xerox.com/AltaLink8100UI](http://xerox.com/AltaLink8100UI).

### PAPER INPUT<sup>4</sup>

**Two 520-sheet Adjustable Trays** (common with all configurations). Tray 1 handles media sizes up to A3 and Tray 2 handles media sizes up to SRA3.



**Envelope Kit** (optional – replaces Tray 1) provides feeding of up to 60 envelopes.



**High Capacity Tandem Tray Configuration** holds a total paper capacity of up to 3,140 sheets.

**Bypass Tray** handles up to 100 sheets; Custom sizes: 89 x 98 mm to 320 x 1,320 mm.



**High Capacity Feeder** (optional) holds 3,000 sheets of A4 paper, increasing the maximum paper capacity to 6,140 sheets.



### PAPER OUTPUT/FINISHERS<sup>4</sup>



**Office Finisher** (optional) provides advanced finishing functions, optional crease/score and saddle-stitch booklet, capable of 60-page booklets (2 to 15 sheets).



**Business Ready (BR) Finisher** (optional) gives you advanced finishing functions at a great value.



**C-Fold/Z-Fold Unit** (optional) adds C-fold, Z-fold and Z-half-fold capability to the BR Finisher or BR Booklet Maker Finisher.



**BR Booklet Maker Finisher** (optional) creates 64-page saddle-stitched booklets (2 to 16 sheets).

### LONG SHEET PRINTING

**Long Sheet Feed Kit** (optional) provides the ability to print up to 320 x 1,320 mm media.



**Dual Offset Catch Tray** (available when no finishers are installed; Single Offset Catch Tray with finishers).



**Integrated Office Finisher** (optional with B8145/B8155) provides 500-sheet stacking and 50-sheet, 2-position stapling.



**Convenience Stapler** (optional) staples up to 50 sheets of 75 gsm media.

# Xerox® AltaLink® B8145/B8155/B8170 Multifunction Printer

| Device Specification           |   |                 |  |
|--------------------------------|---|-----------------|--|
| <b>Control Panel Languages</b> | US English, International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Turkish, Greek, Russian, Czech, Polish, Hungarian, Romanian, Catalan, Arabic   |                 |  |
| Accessories                    |   |                 |  |
| <b>Optional</b>                | 500GB HDD<br>Bluetooth Kit<br>Booklet Maker for Office Finisher<br>BR (Business Ready) Finisher (requires Horizontal Transport Kit)<br>BR Booklet Maker Finisher (requires Horizontal Transport Kit) C-fold/Z-fold Unit for BR Finisher or BR Booklet Maker<br>Convenience Stapler (includes Work Surface <sup>5</sup> )<br>Finisher<br>Foreign Device Interface (also known as Auxiliary Access Device) Interface for third-party access control devices, such as coin machines and card readers<br>Envelope Tray (Replaces Tray 1)<br>High-Capacity Feeder 3000 A4<br>Hole Punch (2/3, 2/4, Swedish)<br>Horizontal Transport Kit<br>Integrated Office Finisher (Available with AltaLink® B8145, B8155)<br>Long Sheet Feed Kit (banner printing)<br>McAfee® Integrity Control Enablement Kit<br>Multi-feed Detection Kit (AltaLink® B8170 only)<br>Office Finisher<br>Scan To Cloud Enablement Kit<br>Smart Card Enablement Kit <sup>3</sup><br>Walk-up Fax (One- or Two-line options, includes LAN Fax)<br>Wi-Fi/Wi-Fi Direct with Dual Band Wireless Kit<br>Unicode Font Kit<br>USB Keyboard/Shelf Kit<br>Xerox® Integrated RFID Card Reader Kit |                 |  |
| Electrical Requirements        | AltaLink® B8145   | AltaLink® B8155 | AltaLink® B8170  |
| <b>North America</b>           | Voltage: 110-127 VAC +/- 10%<br>Frequency: 50/60 Hz +/- 3%, 15 A  |                 | Voltage: 110-127 VAC +/- 10%<br>Frequency: 50/60 Hz +/- 3%, 20 A |
| <b>Europe</b>                  | Voltage: 220-240 VAC +/- 10%<br>Frequency: 50/60 Hz +/- 3%, 10 A  |                 | Voltage: 220-240 VAC +/- 10%<br>Frequency: 50/60 Hz +/- 3%, 10 A |

# Xerox® AltaLink® B8145/B8155/B8170 Multifunction Printer

| Device Specification (continued)   |   |  |  |
|--|---|--|--|
| Power Consumption  | AltaLink® B8145   | AltaLink® B8155  | AltaLink® B8170  |
| <b>Running (Average)</b>   | 115V: 717 watts<br>230V: 674 watts  | 115V: 806 watts<br>230V: 760 watts   | 115V: 929 watts<br>230V: 908 watts   |
| <b>Standby Mode</b>  | 115V: 71 watts<br>230V: 71 watts  | 115V: 72 watts<br>230V: 70.3 watts   | 115V: 91.1 watts<br>230V: 79 watts   |
| <b>Auto Off/Sleep Mode</b>   | 115V: 0.67 watts<br>230V: 0.71 watts<br>(Default time to sleep mode = 0 minutes)  | 115V: 0.67 watts<br>230V: 0.71 watts<br>(Default time to sleep mode = 0 minutes) | 115V: 0.68 watts<br>230V: 0.75 watts<br>(Default time to sleep mode = 0 minutes) |
| <b>Warm-up (from Off)</b>  | As fast as 8.5 seconds  |  |  |
| <b>Recovery from Sleep</b>   | As fast as 4.5 seconds  |  |  |
| Operating Environment  |   |  |  |
| <b>Required Temperature Range</b>  | 10 to 28° C   |  |  |
| <b>Required Relative Humidity</b>  | 15% to 85%  |  |  |
| <b>Sound Power Levels</b>  | Operating: 63.7/64.2 dB(A)<br>Standby: 4.0/4.0 dB(A)  | Operating: 65.2/67.3 dB(A)<br>Standby: 4.3/4.3 dB(A)                             | Operating: 70.4 dB(A)<br>Standby: 4.3 dB(A)                                      |
| Dimensions and Weight  |   |  |  |
| <b>Base Configuration</b>  | Width: 620 mm<br>Depth: 723 mm<br>Height: 1,130 mm<br>Weight: 129.5 kg  |  | Width: 620 mm<br>Depth: 793 mm<br>Height: 1,169 mm<br>Weight: 144.8 kg           |
| <b>With Office Finisher (with Booklet Maker)</b>   | Width: 1,207 mm<br>Depth: 723 mm<br>Height: 1,130 mm<br>Weight: 168 kg  |  | Width: 1207 mm<br>Depth: 793 mm<br>Height: 1,169 mm<br>Weight: 184.2 kg          |
| <b>Base Configuration with Business Ready (BR) Finisher</b>  | Width: 1,395 mm<br>Depth: 723 mm<br>Height: 1,130 mm<br>Weight: 173.4 kg  |  | Width: 1,395 mm<br>Depth: 723 mm<br>Height: 1,169 mm<br>Weight: 188.4 kg         |
| <b>Base Configuration with BR Booklet Maker Finisher</b>   | Width: 1,496.3 mm<br>Depth: 723 mm<br>Height: 1,130 mm<br>Weight: 190.4 kg  |  | Width: 1,496.3 mm<br>Depth: 723 mm<br>Height: 1,169 mm<br>Weight: 205.6 kg       |
| <b>Base Configuration with BR Booklet Maker Finisher and C-fold/Z-fold Unit</b>                        | Width: 1,632 mm<br>Depth: 723 mm<br>Height: 1,130 mm<br>Weight: 240.7 kg  |  | Width: 1,632 mm<br>Depth: 723 mm<br>Height: 1,169 mm<br>Weight: 255.9 kg         |
| <b>Base Configuration with BR Booklet Maker Finisher, C-fold/Z-fold Unit, and High Capacity Feeder</b> | Width: 2,361 mm<br>Depth: 723 mm<br>Height: 1,130 mm<br>Weight: 271.6 kg  |  | Width: 2,361 mm<br>Depth: 723 mm<br>Height: 1,169 mm<br>Weight: 287 kg           |
| System Certifications/Regulatory Compliances   |   |  |  |
| <b>Certifications</b>  | To view the latest list of certifications, go to <a href="http://xerox.com/OfficeCertifications">xerox.com/OfficeCertifications</a> |  |  |

# Xerox® AltaLink® B8145/B8155/B8170 Multifunction Printer

| Paper Handling   | AltaLink® B8145  | AltaLink® B8155 | AltaLink® B8170   |
|--|--|-----------------|---|
| <b>Single-Pass Duplex Automatic Document Feeder (DADF)</b> |  |                 |   |
| <b>Capacity<sup>4</sup></b>                                | 130 sheets   |                 | 250 sheets  |
| <b>Speed (Up to)</b>                                       | 82 ppm black-and-white (simplex)<br>141 ipm black-and-white (duplex)   |                 | 135 ppm black-and-white (simplex)<br>270 ipm black-and-white (duplex) |
| <b>Paper Sizes Sensed</b>                                  | 85 x 125 mm to 297 x 432 mm  |                 |   |
| <b>Weights</b>   | 60 to 128 gsm  |                 |   |
| <b>Bypass Tray (Standard)</b>                              |  |                 |   |
| <b>Capacity<sup>4</sup></b>                                | 100 sheets   |                 |   |
| <b>Sizes</b>   | <b>Custom Sizes:</b> 89 x 98 mm to 320 x 1320 mm (SEF); <b>Optional:</b> Long Sheet Feed Kit (Banner Printing)   |                 |   |
| <b>Weights</b>   | 52 to 300 gsm, <b>Long sheets/banners (&gt;483 mm):</b> 106 - 220 gsm  |                 |   |
| <b>Media Types</b>   | Bond<br>Card Stock<br>Card Stock Reloaded<br>Custom<br>Envelopes<br>Glossy Card Stock<br>Glossy Card Stock Reloaded<br>Heavyweight Card Stock<br>Heavyweight Card Stock Reloaded<br>Heavyweight Glossy Card Stock<br>Heavyweight Glossy Card Stock Reloaded<br>Hole Punched<br>Labels<br>Letterhead<br>Lightweight<br>Lightweight Card Stock<br>Lightweight Card Stock Reloaded<br>Lightweight Glossy Card Stock<br>Lightweight Glossy Card Stock Reloaded<br>Plain<br>Plain-Reloaded<br>Preprinted<br>Recycled<br>Transparencies<br><br><b>Long Sheets/Banners:</b><br>Card Stock<br>Card Stock Reloaded<br>Lightweight Card Stock<br>Lightweight Card Stock Reloaded |                 |   |
| <b>Trays 1 and 2 (Standard)</b>                            |  |                 |   |
| <b>Capacity<sup>4</sup></b>                                | 520 sheets each  |                 |   |
| <b>Sizes</b>   | <b>Tray 1:</b> Custom Sizes: 140 x 182 mm to 297 x 432 mm (SEF)<br><b>Tray 2:</b> Custom Sizes: 140 x 182 mm to SRA3 (SEF)   |                 |   |
| <b>Weights</b>   | 52 to 300 gsm  |                 |   |
| <b>Media Types</b>   | Bond<br>Card Stock<br>Card Stock Reloaded<br>Custom<br>Envelopes<br>Glossy Card Stock<br>Glossy Card Stock Reloaded<br>Heavyweight Card Stock<br>Heavyweight Card Stock Reloaded<br>Heavyweight Glossy Card Stock<br>Heavyweight Glossy Card Stock Reloaded<br>Hole Punched<br>Labels<br>Letterhead<br>Lightweight<br>Lightweight Card Stock<br>Lightweight Card Stock Reloaded<br>Lightweight Glossy Card Stock<br>Lightweight Glossy Card Stock Reloaded<br>Plain<br>Plain-Reloaded<br>Preprinted<br>Recycled<br>Transparencies  |                 |   |

# Xerox® AltaLink® B8145/B8155/B8170 Multifunction Printer

| Paper Handling (continued)                                   | AltaLink® B8145   | AltaLink® B8155 | AltaLink® B8170 |
|--|---|-----------------|-----------------|
| <b>High Capacity Tandem Tray (Available with all models)</b> |   |                 |                 |
| <b>Capacity<sup>4</sup></b>                                  | <b>Tray 3:</b> 867 sheets<br><b>Tray 4:</b> 1,133 sheets  |                 |                 |
| <b>Sizes</b>   | A4, JIS B5, Executive LEF   |                 |                 |
| <b>Weights</b>   | 52 to 300 gsm   |                 |                 |
| <b>Media Types</b>   | Bond<br>Card Stock<br>Custom<br>Glossy Card Stock<br>Hole Punched<br>Labels<br>Letterhead<br>Lightweight Card Stock<br>Lightweight Glossy Card Stock<br>Plain<br>Preprinted |                 |                 |
| <b>Envelope Tray (Optional – Replaces Tray 1)</b>            |   |                 |                 |
| <b>Capacity<sup>4</sup></b>                                  | Up to 60 envelopes  |                 |                 |
| <b>Sizes</b>   | No. 10 Commercial (235 x 105 mm) / Monarch, DL, C5<br>Custom Sizes: 98 x 148 mm to 162 x 241 mm   |                 |                 |
| <b>Weights</b>   | 75 to 90 gsm  |                 |                 |
| <b>High-Capacity Feeder (HCF) (Optional with all models)</b> |   |                 |                 |
| <b>Capacity<sup>4</sup></b>                                  | 3,000 sheets  |                 |                 |
| <b>Sizes</b>   | Standard Sizes: A4 or B5 LEF  |                 |                 |
| <b>Weights</b>   | 52 to 300 gsm   |                 |                 |
| <b>Total Capacity</b>  |   |                 |                 |
| <b>Device Total Capacity<sup>4</sup></b>                     | High Capacity Tandem Tray Module: 3,140 sheets<br>High-Capacity Tandem Tray Module with High-Capacity Feeder: 6,140 sheets  |                 |                 |

# Xerox® AltaLink® B8145/B8155/B8170 Multifunction Printer

| Finishing   | AltaLink® B8145  | AltaLink® B8155 | AltaLink® B8170 |
|---|--|-----------------|-----------------|
| <b>Output Trays (Standard) (Dual Offset Catch Trays not available with Integrated Office Finisher and limited to one with Office Finisher and BR Finishers)</b> |  |                 |                 |
| <b>Stacking Tray Capacity<sup>4</sup></b>   | Dual Offset Catch Tray: Up to 250 sheets each<br>Left Side Face-up Tray: Up to 100 sheets  |                 |                 |
| <b>Integrated Office Finisher (Optional with AltaLink® B8145/B8155)</b>   |  |                 |                 |
| <b>Stacking Tray Capacity<sup>4</sup></b>   | 500 sheets of 80 gsm – A4 or 250 sheets of 80 gsm – A3   |                 |                 |
| <b>Sizes</b>  | 89 x 98 mm to 297 x 432 mm   |                 |                 |
| <b>Weights</b>  | 52 to 300 gsm  |                 |                 |
| <b>Stapling</b>   | Single/Dual Position<br>Auto-Stapling:<br>50 sheets maximum: A4 / B5 size sheets (less than 90 gsm or (2) 220 gsm covers)<br>30 sheets maximum: Legal/Tabloid/A3/B4 size sheets (less than 90 gsm or (2) 220 gsm covers) |                 |                 |
| <b>Office Finisher (Optional)</b>   |  |                 |                 |
| <b>Stacking Tray Capacity<sup>4</sup></b>   | 2,000 sheets unstapled or 1,000 sheets single-stapled or 750 sheets dual-stapled (A4)  |                 |                 |
| <b>Stacking Tray Sizes</b>  | 210 x 182 mm to 297 x 432 mm   |                 |                 |
| <b>Weights</b>  | 52 to 300 gsm  |                 |                 |
| <b>Multiposition Stapling</b>   | 50 sheets maximum: A4 / B5 size sheets (less than 90 gsm or (2) 220 gsm covers)<br>30 sheets maximum: Legal/Tabloid/A3/B4 size sheets (less than 90 gsm or (2) 220 gsm covers)   |                 |                 |
| <b>Hole Punch (Optional)</b>  | <b>North America:</b> 2/3-hole punch<br><b>Europe:</b> 2/4-hole punch<br><b>Optional:</b> 4-hole "Swedish" punch   |                 |                 |
| <b>Booklet Maker for Office Finisher (Score/Crease, Saddle-stitch Staple) (Optional)</b>  |  |                 |                 |
| <b>Top Tray Capacity<sup>4</sup></b>  | 40 booklets (2-15 sheets per booklet – 80 gsm or less)   |                 |                 |
| <b>Sizes</b>  | Letter – A4 SEF<br>Legal – B4 SEF<br>Tabloid – A3 SEF  |                 |                 |
| <b>Saddle-Stitch Stapling</b>   | 2-15 sheets/8-60 page booklet<br>60 to 256 gsm   |                 |                 |
| <b>Score/Crease</b>   | 1-15 sheets/unstapled<br>60 to 105 gsm   |                 |                 |
| <b>Business Ready (BR) Finisher (Optional) (Requires Horizontal Transport Kit)</b>  |  |                 |                 |
| <b>Capacity<sup>4</sup></b>   | Offsetting Top Tray: 500 sheets<br>Stacking Stapling Tray: 3,000 sheets unstapled or 100 sets (dual or 4-position stapling) A3 or 200 sets (single-position staple) A4   |                 |                 |
| <b>Sizes</b>  | 100 x 148 mm x 320 x 488 mm for top tray<br>182 x 203 mm to 320 x 488 mm for stacking<br>B5 to A3 for stapling   |                 |                 |
| <b>Weights</b>  | 52 to 300 gsm  |                 |                 |
| <b>Stapling</b>   | Single and multiposition stapling<br>Auto stapling (50 sheets maximum) – 90 gsm Letter, Legal, Tabloid, A3, A4, B4 and B5 sizes supported  |                 |                 |
| <b>Hole Punch</b>   | <b>North America:</b> 2/3-hole punch<br><b>Europe:</b> 2/4-hole punch<br><b>Optional:</b> 4-hole "Swedish" punch   |                 |                 |
| <b>BR Booklet Maker Finisher (Optional) (Requires Horizontal Transport Kit)</b>   |  |                 |                 |
| <b>Capacity<sup>4</sup></b>   | Offsetting Top Tray: 500 sheets of A4 unstapled<br>Stacking Stapling Tray: 1,500 sheets of A4/A3 unstapled or 200 stapled sets of A4 (single-position stapling or dual or 4-position stapling) or 100 stapled sets of A3 |                 |                 |
| <b>Sizes</b>  | 100 x 148 mm x 320 x 488 mm for top tray<br>182 x 203 mm to 320 x 488 mm for stacking<br>B5 to A3 for stapling   |                 |                 |
| <b>Weights</b>  | 52 to 300 gsm  |                 |                 |
| <b>Stapling</b>   | Single and multiposition stapling<br>Auto stapling (50 sheets maximum) – 90 gsm Letter, Legal, Tabloid, A3, A4, B4 and B5 sizes supported  |                 |                 |
| <b>Hole Punch</b>   | <b>North America:</b> 2/3-hole punch<br><b>Europe:</b> 2/4-hole punch<br><b>Optional:</b> 4-hole "Swedish" punch   |                 |                 |
| <b>Booklet maker</b>  | Saddle-stitch 2 to 16 sheets (7 sheets at 106 to 176 gsm coated or 5 sheets at 177 to 220 gsm coated)<br>Bi-fold up to 5 sheets<br>Letter, Legal, Tabloid, A3, A4 supported  |                 |                 |



# Xerox® AltaLink® B8145/B8155/B8170 Multifunction Printer

| Finishing (continued)   | AltaLink® B8145  | AltaLink® B8155        | AltaLink® B8170        |
|---|--|------------------------|------------------------|
| <b>C-fold/Z-fold Unit (Optional with BR Finisher and BR Booklet Maker Finisher)</b> |  |                        |                        |
| <b>Types</b>  | C-fold, Z-fold, and Z-half-fold  |                        |                        |
| <b>Capacity<sup>4</sup></b>   | 40 sheets  |                        |                        |
| <b>Sizes</b>  | C-fold and Z-fold: Letter – A4 SEF only<br>Z-half-fold: Tabloid – A3 only  |                        |                        |
| <b>Weights</b>  | 64 to 90 gsm   |                        |                        |
| <b>Output Trays</b>   | Envelope Tray: C-fold, Z-fold, and Tri-fold<br>Stacker Tray or Top Tray: Z-half-fold   |                        |                        |
| <b>Convenience Stapler (Optional - Includes Work Surface<sup>5</sup>)</b>           |  |                        |                        |
| <b>Capacity<sup>4</sup></b>   | 50-sheet stapling<br>5,000 staples<br>Requires separate power outlet   |                        |                        |
| Copy  | AltaLink® B8145  | AltaLink® B8155        | AltaLink® B8170        |
| <b>First-Copy-Out Time (from platen/warmed up)</b>                                  | As fast as 4.4 seconds   | As fast as 3.7 seconds | As fast as 3.2 seconds |
| <b>Sides (input:output)</b>   | 1-1, 1-2, 2-2, 2-1   |                        |                        |
| <b>Quantity</b>   | 1 to 9,999   |                        |                        |
| <b>Resolution (max)</b>   | Up to 600 x 600 dpi  |                        |                        |
| <b>Reduction/Enlargement</b>  | Variable zoom from 25% to 400% in 1% increments  |                        |                        |
| <b>Concurrency</b>  | Program ahead to allow the job to be queued while the initial job is processed (Copy, Print, Fax and Scan)   |                        |                        |
| <b>Copy Features</b>  | Annotation and Bates™ stamping<br>Authentication for Services<br>Auto Paper Select<br>Auto Reduction & Enlargement (to fit the selected paper size)<br>Auto Tray Switching<br>Automatic 2-sided/Duplex Booklet Creation<br>Build Job (Enables page-level programming and also lets you proof each section or delete the last section as the job is built)<br>Collation<br>Covers (front only, front and back, back only, printed inside and out: Blank or Printed)<br>Dividers (blank)<br>Edge Erase<br>Features Help (Intuitive text and graphic descriptions)<br>ID Card Copy<br>Image Quality Adjustments<br>Image Shift (with Auto Center option)<br>Imaging Security<br>Invert Image (negative or mirror image)<br>Large Job Interrupt<br>Multi-up (up to 15 columns by 15 rows)<br>Sample Set<br>Save Job Settings<br>Single Colour<br>Stapling<br>Touchless Workflow Accelerators<br>Transparencies |                        |                        |

# Xerox® AltaLink® B8145/B8155/B8170 Multifunction Printer

| Print   | AltaLink® B8145   | AltaLink® B8155 | AltaLink® B8170 |
|---|---|-----------------|-----------------|
| <b>Resolution (up to)</b>   | 1200 x 2400 dpi   |                 |                 |
| <b>Print Features</b>   | Application Defaults<br>Banner Sheet Enable/Disable<br>Booklet Layout<br>Cover Selection<br>Delay Print (specific time) User Permissions<br>Finishing<br>Fit to New Paper Size<br>Hold All Jobs<br>Image Options (Toner Saver, Resolution (Standard, Enhanced, High))<br>Job Identification (Print ID or Banner, Print ID in margins on the first page only or all pages)<br>LAN Fax (requires optional Fax Kit)<br>Long Sheet/Banner<br>Layout/Watermark<br>N-up (up to 16 pages per sheet)<br>Paper Selection by Attribute Sample Set<br>Print From Cloud Repositories (Dropbox, OneDrive and Google Drive)<br>Saved Job<br>Secure Print with Timed Deletion<br>Special Pages (exception page programming: covers, inserts, exception pages)<br>Store and Recall Driver Settings<br>Sustainability Features (Xerox® Earth Smart Settings, Duplex, N-up, Turn-off Banner and Print ID, Smart Sample Set, Hold All Jobs)<br>Two-sided Printing (as default) |                 |                 |
| <b>Print from USB</b>   | Allows walk-up printing from Type A USB port on the front panel<br>Supports direct printing from a computer via Type B USB port<br>Supported file formats: PDF, JPEG, TIFF, PS, PCL<br>Colour jobs can be printed as black-and-white  |                 |                 |
| <b>Operating Systems</b>  | Windows Server 2008 SP2 (32- and 64-bit)<br>Windows Server 2008 R2 (64-bit)<br>Windows Server 2012 and R2 (64-bit)<br>Windows Server 2016 (64-bit)<br>Windows Server 2019 (64-bit)<br>Windows 7 (32- and 64-bit)<br>Windows 8 (32- and 64-bit)<br>Windows 8.1 (32- and 64-bit)<br>Windows 10 (32- and 64-bit)<br>Mac OS 10.13, 10.14, 10.15<br>Fedora® Core<br>Ubuntu®  |                 |                 |
| <b>Network Protocols</b>  | TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD<br>Microsoft Windows Networking over IP<br>Bonjour®/AirPrint™<br>IPv6<br>Most protocols not in use can be disabled   |                 |                 |
| <b>Font Capability</b>  | PCL: 93 scalable fonts, line printer and bitmap font (including Cyrillic font support) PostScript 3: 173 Type 1 fonts, 2 Multiple Master fonts  |                 |                 |
| <b>Xerox® Global Print Driver®</b>                                      | A truly universal print driver that lets IT administrators install, upgrade and manage non-Xerox and Xerox® Devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls and simplifying print services management. Support for Microsoft Universal Print.   |                 |                 |
| <b>Xerox® Pull Print Driver</b>   | Makes it easy for IT managers to qualify, deploy and manage all print devices using a single driver in a Pull Print environment. Uses a single queue and single driver. The Xerox® Pull Print Driver extends convenience across a broad range of printing assets. IT administrators no longer need to manage and configure multiple drivers. Used in conjunction with Equitrac Office®, Ysoft® SafeQ®, Pharos® and others.  |                 |                 |
| <b>Unified Address Book for Fax, Internet Fax, Email and Scan to...</b> |   |                 |                 |
| <b>Features</b>   | Services supported: Fax, Internet Fax, Email, Scan to<br>Maximum contacts: 5,000<br>Contacts: Supports 1 or more destinations<br>Favourites for quick access of all services supported  |                 |                 |

# Xerox® AltaLink® B8145/B8155/B8170 Multifunction Printer

| Scan   | AltaLink® B8145   | AltaLink® B8155 | AltaLink® B8170   |
|--|---|-----------------|---|
| <b>Concurrency</b>                           | Scan while the system is printing, copying or while it is transferring scan-to-network or fax jobs (priority is for the return of scanned originals and printing concurrent jobs)   |                 |   |
| <b>Input Speed (up to)</b>                   | 82 ppm black-and-white and colour (simplex)<br>141 ipm black-and-white and colour (duplex)  |                 | 135 ppm black-and-white and colour (simplex)<br>270 ipm black-and-white and colour (duplex) |
| <b>Resolution</b>                            | 72 x 72 dpi to 600 x 600 dpi  |                 |   |
| <b>Bit Depth</b>                             | 1-bit (black-and-white), 8-bit (greyscale), 24-bit (colour)   |                 |   |
| <b>Maximum Scan Area</b>                     | A3  |                 |   |
| <b>Scan Template Management</b>              | Support 250 scan templates<br>Create Xerox® CentreWare® IS scan templates and share via device cloning to other multifunction printers' confirmation sheet options  |                 |   |
| <b>Network Protocols</b>                     | SFTP, FTP, SMB, HTTP, HTTPS   |                 |   |
| <b>File Compression</b>                      | Colour TIFF (TIFF 6.0 or TTN2 with JPEG, LZW)<br>Black-and-white TIFF (G3MH, G4 MMR compression – single or multiple pages)<br>Searchable PDF/OCR and PDF/A-1b (MRC, JPEG, G3 MH, G4 MMR, JBIG 2 Huffman, JBIG Arithmetic Compression, Deflate (for black-and-white and within MRC)) Linearised PDF/PDF/A   |                 |   |
| <b>Document Management Fields (Metadata)</b> | Features only available in Network Scan-to-File Templates:<br><ul style="list-style-type: none"> <li>• 1 to 6 user-programmable metadata fields per network scan to file templates and unlimited fields within the template – Metadata field consists of a field name, default value and other configurations</li> <li>• Customised fields viewed on user interface for variable data input</li> </ul>  |                 |   |
| <b>Scan Features</b>                         | Auto Background and Shadow Suppression<br>Bound Originals<br>Compression Quality/File Size Control<br>Edge Erase<br>Imaging Security<br>Mixed Size Originals<br>Original Type (Photo and Text, Photo, Text, Map, Newspaper/Magazine)<br>Reduction/Enlargement<br>Scan Build Job<br>Scan Preview<br>Single Touch Scan buttons (up to 10)<br>Size for Size (for mixed-size originals)<br>Touchless Workflow Accelerators<br>TWAIN Support/WIA 2.0 Support |                 |   |
| <b>Scan to Email (Standard)</b>              |   |                 |   |
| <b>Scan Features</b>                         | <ul style="list-style-type: none"> <li>• Auto send to self</li> <li>• Email signatures (6 lines each of 128 character max), email message body (user configurable), email Embedded Web Server confirmation sheet options</li> <li>• Email signing (requires Smart Card option)</li> <li>• Scan to Email S/MIME Encryption</li> <li>• Touchless Workflow Accelerators</li> </ul>   |                 |   |
| <b>Directory Access</b>                      | Address list via LDAP (Windows Active Directory, Exchange, Notes, Domino), Device Address Book  |                 |   |
| <b>Scan To</b>                               |   |                 |   |
| <b>Standard Features</b>                     | Scan to USB<br>Scan to Network Folder (using Secure FTP/HTTP/HTTPS)<br>Scan to Home<br>Scan to Network (using Secure FTP/HTTP/HTTPS)<br>Scan to Email<br>Scan to PC/Server Client (SMB or FTP)<br>Scan to Mailbox   |                 |   |
| <b>Optional Features</b>                     | Scan to Cloud Repositories (Dropbox, OneDrive and Google Drive)   |                 |   |
| <b>Workflow Scanning (Optional)</b>          |   |                 |   |
| <b>Scanning Software</b>                     | Autostore v7<br>eCopy ShareScan v5.2<br>eCopy ScanStation v5.2  |                 |   |
| <b>Scanning Apps and Xerox App Gallery</b>   | Scan to: Dropbox, Google Drive, Microsoft OneDrive, Microsoft Office 365™, Box®, Xerox® Workplace Mobile App (iOS/Android)<br>See the full list of apps available in the Xerox App Gallery: <a href="http://xerox.com/AppGallery">xerox.com/AppGallery</a>  |                 |   |

# Xerox® AltaLink® B8145/B8155/B8170 Multifunction Printer

| Security   | AltaLink® B8145   | AltaLink® B8155 | AltaLink® B8170 |
|--|---|-----------------|-----------------|
| <b>Features</b>  | <ul style="list-style-type: none"> <li>• Audit Log</li> <li>• Cisco® Identity Services Engine (ISE) compatible</li> <li>• Configuration Watchdog (monitor and remediate 75 security settings in the following areas):               <ul style="list-style-type: none"> <li>- 802.1x</li> <li>- Admin Password Reset</li> <li>- Audit Log</li> <li>- Automatic Software Upgrade</li> <li>- Email Alerts</li> <li>- FIPS 140-2</li> <li>- Hold All Jobs</li> <li>- Immediate Job with optional hard drive</li> <li>- Installation Policies</li> <li>- McAfee® Embedded Control</li> <li>- PII - Login Name</li> <li>- PostScript Passwords</li> <li>- Remote Services Enablement</li> <li>- Remote Start (Mopria® or AirPrint™)</li> <li>- Remote Start (TWAIN)</li> <li>- Reprint Saved Jobs</li> <li>- Scan to Mailbox (Internal storage)</li> <li>- Scheduled Disk with optional hard drive</li> <li>- Secure Passcode Length</li> <li>- Secure Print Device Policies</li> <li>- SIEM</li> <li>- SNMP</li> <li>- System Timeout</li> <li>- USB (Print from USB)</li> <li>- USB (Scan to USB)</li> <li>- USB Port Management</li> <li>- User Data Encryption</li> </ul> </li> <li>• Expanded Authentication               <ul style="list-style-type: none"> <li>- Digitally signed PDF (when using Smart Card authentication)</li> <li>- Encrypted and authentication to SMTP server for Scan to Email</li> <li>- Encrypted/Password-protected PDF (when using Email and Network Scan Templates only)</li> <li>- FIPS 140-2 256 bit Hard Disk Encryption, TLS, IPPS, HTTPS, SFTP, SNMPv3</li> <li>- Immediate Image Overwrite/Securely delete jobs using approved algorithms<sup>9</sup></li> <li>- Local Authentication (internal database)</li> <li>- Network authentication to access device and/or device services via Kerberos (UNIX/Windows Server 2008), SMB (Windows Server 2008, Windows server 2012), NDS, LDAP authentication</li> <li>- On-demand Image Overwrite (Scheduled, Manual), includes sanitation of unused area of disk<sup>9</sup></li> <li>- Secure Data</li> <li>- Secure Print (up to 10 digit PIN or Network Authentication)</li> <li>- Smart Card authentication – 144k CAC/PIV Card Support (2048 bit certificate key)/.NET</li> </ul> </li> <li>• Expanded Authorisation               <ul style="list-style-type: none"> <li>- Authorisation per user per service</li> <li>- SA access based on network credentials</li> <li>- Secure Network Access</li> <li>- User Permissions required to access Print and Print Features (e.g. time restrictions) reflects in the print driver</li> </ul> </li> <li>• Full System Common Criteria certified by NIAP under HD Protection Profile for Hardcopy Devices v1.0 (HCD-PP v1.0)</li> <li>• Hide Print Job Names</li> <li>• Imaging Security</li> <li>• IP Filter, IPsec, IPv6, TLS v1.0, v1.2, v1.3, SNMP v1,v2,v3, HTTPS, 802.1X, SFTP</li> <li>• McAfee® Embedded Control (whitelisting), McAfee® Integrity Control (optional)</li> <li>• Port disablement including USB ports</li> <li>• Security Information and Event Management (SIEM) support for McAfee® Enterprise Security Manager, LogRhythm and Splunk</li> </ul> |                 |                 |
| <b>Xerox® Integrated RFID Card Reader (Optional kit)</b> | Integrated support for most industry security cards providing additional security; with embedded multifunction printer card readers in the multifunction printer panel  |                 |                 |

# Xerox® AltaLink® B8145/B8155/B8170 Multifunction Printer

| Fax  | AltaLink® B8145   | AltaLink® B8155 | AltaLink® B8170 |
|--|---|-----------------|-----------------|
| <b>Network Server Fax Features</b>   |   |                 |                 |
| <b>Compatibility</b>   | ITU (CCITT) group 3; Various Xerox® Business Innovation Partner Solutions   |                 |                 |
| <b>Maximum Scan Area</b>   | A3  |                 |                 |
| <b>Fax Send Features</b>   | One- or Two-sided Scanning (up to A3)<br>Add to Send List (200 numbers maximum)<br>Build Job, Favourites, Delay Send (specific time) Original Type (photo, text or photo and text)  |                 |                 |
| <b>Fax Print Features</b>  | One- or Two-sided Printing, Staple, Secure Print  |                 |                 |
| <b>Transmission Resolution</b>   | Superfine: 400 x 200 dpi (Scan at 600 x 600 dpi)<br>Fine: 200 x 200 dpi<br>Standard: 200 x 100 dpi  |                 |                 |
| <b>Internet Fax Features</b>   |   |                 |                 |
| <b>Compatibility</b>   | Direct print-ready document transmission to remote Internet Fax machines or email clients (SMTP)<br>Reception and automatic printout of documents sent via email from remote Internet Fax machines or email clients   |                 |                 |
| <b>Directory Access</b>  | Utilises the Unified Address Book   |                 |                 |
| <b>Send/Receive</b>  | Send: Multi-page TIFF, PDF, PDF/A<br>Receive: TIFF, MTIFF, PDF, PDF/A, PS, text, PCL, PRN, JPEG   |                 |                 |
| <b>Resolution</b>  | 72 x 72 dpi to 600 x 600 dpi<br>Bit Depth: 1-bit (black-and-white)  |                 |                 |
| <b>Network Protocols</b>   | SMTP (send), POP3 (receive)   |                 |                 |
| <b>Compliance</b>  | ITU-T T.37  |                 |                 |
| <b>Walk-up Fax Features (Optional; Customer-Installable – 1 and 2 lines)</b> |   |                 |                 |
| <b>Compatibility</b>   | ITU (CCITT) Group 3   |                 |                 |
| <b>Speed/Modems</b>  | One or Two V.34 modems: 33,600 bps. Less than 4 seconds per page transmission time  |                 |                 |
| <b>Compression/Speed</b>   | MH/G3, MR/G3, MMR/SG3, JBIG/SG3   |                 |                 |
| <b>Resolution</b>  | <b>Walk-up Send:</b><br>Standard: 200 x 100 dpi<br>Fine: 200 x 200 dpi Superfine: 600 x 600 dpi<br><b>Receive:</b> Accepts all sizes  |                 |                 |
| <b>Fax Send Features</b>   | LAN Fax (fax from print driver)<br>Auto Fax Transmission Reduction<br>Page-by-page Job Status at the Machine<br>Delay Start, Build Job, Favourites<br>Automatic Memory Resend<br>Automatic Cover Sheets<br>PSTN Fax<br>Batch Send (up to memory capacity)<br>Device Address Book (up to 5,000 contacts) |                 |                 |
| <b>Fax Receive Features</b>  | One- or Two-sided Printing<br>Stapled or Unstapled<br>Receive Print Mode – Manual (size, margin, stock, header) / Auto<br>Output Tray Selection<br>Up to 200 Password-Protected Mailboxes<br>Secure Receive<br>Receive Timestamp<br>Auto Answer Delay   |                 |                 |
| <b>Fax forward</b>   | Forward to Email or SMB Location<br>Fax Forward on Receive Only   |                 |                 |
| <b>Fax Reports</b>   | Activity, Dial Directory, Group Directory, Transmission Confirmation, Pending Fax, Options Report, On-Demand with optional hard drive Report, Mailbox Report, Broadcast Report  |                 |                 |
| <b>Directory Access</b>  | Utilises the Unified Address Book<br>Group fax available  |                 |                 |
| <b>Auto Redial</b>   | Up to 14 attempts (per country requirements)<br>1 to 25-minute intervals  |                 |                 |
| <b>Auto Resend</b>   | Up to 5 attempts  |                 |                 |

# Xerox® AltaLink® B8145/B8155/B8170 Multifunction Printer

| Device Management   |  |
|---|--|
| <b>Administrative Protocols</b>   | DHCP, BOOTP, SNMP, SLP® v2, HTTP, HTTPS, DHCP Autonet, TLS, NTP, DNS, SMB, SMTP/POP3, WSD, LDAP, Multicast DNS   |
| <b>Management Support</b>   | SNMP Version 1, SNMP Version 2c and SNMP Version 3 trap over TCP/IP and IP<br>MIB access (IETF-MIBII RFC 1213)<br>Host Resources MIB RFC 2790, Printer MIB RFC 3805, PWG-Imaging-System- Power MIB, Fleet Orchestrator, Configuration Watchdog   |
| <b>Xerox® CentreWare® Web</b>   | A web-based server application for network administrators that permits web browser-based device management from any workstation, whether running on Windows, UNIX or any other operating system:<br>Works with any SNMP-managed printer from any manufacturer <ul style="list-style-type: none"> <li>• Remote configuration of SNMP v3</li> <li>• Provides help with device discovery and installation, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management</li> <li>• Requires Windows 7 and Internet Explorer 6.0 and higher.</li> <li>• Auto-detect Xerox® CentreWare® Web server and download configurations files for touchless remote installation</li> </ul>                                 |
| <b>Xerox® Device Manager</b>  | Xerox® Device Manager collects and manages the data that drives fact-based decisions for your enterprise device management environment. It is a single tool to install print queues and configure, manage, monitor and report on both networked and locally connected devices – regardless of vendor – across your enterprise. Xerox® Device Manager provides: <ul style="list-style-type: none"> <li>• Device monitoring and troubleshooting</li> <li>• Remote configuration of SNMP v3</li> <li>• Extensive reporting and discovery of new devices</li> <li>• Usage collection, chargeback and billing capabilities</li> <li>• Auto-detect Xerox® Device Manager server and download configurations files for touchless remote installation</li> </ul> |
| <b>Xerox® Workplace Cloud</b>   | Remote management to set and audit device configuration data with Xerox® Workplace Cloud, eliminating the need for an on-site server   |
| <b>Fleet Orchestrator</b>   | The Fleet Orchestrator feature offers the ability to create a group of devices that share information with each other via a secure peer-to-peer connection. The following data can be shared: Software update files, clone files and 1-Touch App files. Auto-assembly feature allows a new AltaLink® to automatically set itself on the network and configure.   |
| <b>Novell NDPS/NEPS</b>   | Server gateway application: centralised management tool  |
| <b>Xerox® Device Types for SAP R/3 Intelligent Barcode Utility (optional)</b>   | Provides built-in process intelligence that allows the printing of barcodes on any appropriately configured PostScript printer in specific versions of SAP environment and within Latin-1 (ISO8859-1) SAP system code pages only. Used in conjunction with Xerox® PostScript Device Types for SAP environment and Xerox® Font Centre Barcode Fonts. For more information, visit <a href="http://www.xerox.co.uk/en-gb/office/printer-software">www.xerox.co.uk/en-gb/office/printer-software</a>   |
| <b>Xerox® Device Types for SAP Environment</b>                                  | Xerox, together with SAP through our Gold-level membership in the SAP Printer Vendor Programme, provides seamless connectivity between SAP systems and your Xerox® Printers and Multifunction Printers. As an SAP customer, you benefit from having SAP-certified Xerox® Device types available right from SAP's online delivery model. SAP-certified device types for Xerox® Printers and Multifunction Printers are available to download.<br><a href="http://www.xerox.co.uk/en-gb/office/printer-software">www.xerox.co.uk/en-gb/office/printer-software</a>   |
| Xerox® Embedded Web Server – Integrated Device Web Pages Provided by the Device |  |
| <b>Device Status</b>  | Web server embedded in Network Controller: <ul style="list-style-type: none"> <li>• Tray status/contents</li> <li>• Consumables status</li> <li>• Alerts</li> <li>• Remote Control Panel</li> </ul>  |
| <b>Job Submission</b>   | Print-ready files: PS, PCL, TIFF, PDF, JPG, TXT, PRN<br>Output feature selection (2-sided, collate, orientation, staple, hole punch, folding, output destination) Delivery options (Immediate, sample set, delay and secure, Save job or reprint)  |
| <b>Device Administration</b>  | Allows simple, remote installation setting of configuration options and management of the device, Fleet Orchestrator   |
| <b>Browsers</b>   | Internet Explorer 10.x, 11.x<br>Safari 10.x, 11.x<br>Mozilla Firefox 45.x to 53.x<br>Opera 25.x to 53.x<br>Chrome 48.x to 72.x   |
| <b>Support</b>  | Install print/scan drivers and online support available via <a href="http://www.support.xerox.com/en-gb">www.support.xerox.com/en-gb</a>   |
| <b>Languages Supported</b>  | International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Russian, Simplified Chinese, Korean, Japanese, Arabic   |
| Remote Services   |  |
| <b>Xerox® Automatic Meter Readings (AMR)</b>                                    | Automates the process of collecting and submitting meter reads for the tracking and billing of Xerox® Device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.   |
| <b>Xerox® Automatic Supplies Replenishment (ASR)</b>                            | Automatically orders supplies for Xerox® output devices based on actual usage, eliminating the need to manually manage supplies inventory.   |
| Accounting  |  |
| Xerox® Standard Accounting (Standard)   |  |
| <b>Tracking</b>   | Copy, Print, Fax, Scan and Email usage   |
| <b>Accounting</b>   | Up to 2,497 User Accounts (User ID)<br>Up to 500 General Accounts (Client)<br>Up to 498 Group Accounts (Department)  |
| <b>Features</b>   | <ul style="list-style-type: none"> <li>• Administrator can manage the feature via the Web User Interface or device control panel in tools.</li> <li>• Administrator can import or export User Accounts, Group Accounts, General Accounts and User Limits via an industry-standard CSV file.</li> </ul>   |

# Xerox® AltaLink® B8145/B8155/B8170 Multifunction Printer

| Accounting Options – Network Accounting (Allows central server to manage all accounting) |   |                      |
|--|---|----------------------|
|  | <ul style="list-style-type: none"> <li>Enhanced network accounting with up-to-the-minute data on how the system is being used</li> <li>Comprehensive management and enterprise-scale tracking and reporting of device usage of copy, print, scan and server fax</li> <li>Numerous solutions are available through Xerox Alliance Partners. For details, visit <a href="http://www.xerox.co.uk">www.xerox.co.uk</a></li> <li>Security enhancements with the addition of HTTPS protocol support</li> <li>Device requests account authentication from third-party server enabling larger databases of users and accounts</li> <li>Accept Authentication Login at the control panel and pass to third-party Networking Account</li> <li>Interface with a third-party accounting terminal for accounting user interface</li> </ul> |                      |
| Supplies   | Description   | Yield                |
| <b>Toner Cartridge<sup>6</sup></b>   | Black   | 52,000 pages         |
| <b>Transfer Belt Cleaner</b>   | 1 Assembly  | 160,000 pages        |
| <b>Second Bias Transfer Roll</b>   | 1 Assembly  | 200,000 pages        |
| <b>Staple Cartridges</b>   | For BR Finisher, Integrated Office Finisher, Office Finisher and Convenience Stapler (1 cartridge per carton)   | 5,000 each cartridge |
|  | For BR Booklet Maker (1 cartridge per carton)   | 5,000 each cartridge |
|  | For Office Finisher Booklet Maker (8 cartridges per carton)   | 2,000 each cartridge |
| <b>Staple Refills</b>  | For Integrated Office Finisher, Office Finisher, BR Finisher and Convenience Stapler (3 refills per carton)   | 5,000 each refill    |
| Xerox® Smart Kit®  |   |                      |
| <b>Drum Cartridge<sup>7</sup></b>  | 1 Cartridge   | 200,000 pages        |
| <b>Waste Toner Container w/o Suction Filter<sup>8</sup></b>                              | 1 Cartridge (AltaLink® B8145/8155)  | 121,000 pages        |
| <b>Waste Toner Container with Suction Filter<sup>9</sup></b>                             | 1 Cartridge (AltaLink® B8170)   | 121,000 pages        |

<sup>1</sup> Declared in accordance with ISO/IEC 24734.

<sup>2</sup> Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

<sup>3</sup> Not available in all geographical locations.

<sup>4</sup> Paper capacities are based on 75 gsm stock; capacities will vary with different weight stocks.

<sup>5</sup> Sold separately in some geographical locations.

<sup>6</sup> Average standard pages. Declared in accordance with ISO/IEC 19752. Toner yield can vary due to many factors, including but not limited to, image area coverage, image content, media size, media orientation, run mode, application types, monthly print volumes and image quality set-points.

<sup>7</sup> Average drum yield is based on a run length of 5 pages of A4 LEF pages, with a split of 35% colour/65% black-and-white pages.

<sup>8</sup> Waste Toner Container yield will vary depending on the image type, area coverage % and job run length.

<sup>9</sup> With optional hard drive.

Return spent imaging supplies through the Xerox® Green World Alliance® collection/reuse/recycling programme. For more information, visit [www.xerox.co.uk/recycling](http://www.xerox.co.uk/recycling).

For more information, visit us at [www.xerox.co.uk/office](http://www.xerox.co.uk/office).