# Xerox<sup>®</sup> AltaLink<sup>®</sup> Multifunction Printers



B8145/B8155/B8170



AltaLink® B8100 Series Multifunction Printers are built on Xerox® ConnectKey® Technology. For more information, go to **www.connectkey.co.uk**.

System Specification	AltaLink® B8145	AltaLink® B8155	AltaLink® B8170
Speed <sup>1</sup>	Up to 45 ppm	Up to 55 ppm	Up to 72 ppm
Monthly Duty Cycle <sup>2</sup>	Up to 200,000 pages	Up to 250,000 pages	Up to 300,000 pages
Hard Drive/Processor/ Memory	Minimum 128 GB SSD/ <b>Optional:</b> 500 GB HDD/Int	rel® Atom™ Quad Core 1.91 GHz/4 GB system memo	ory
Connectivity	Ethernet 10/100/1000 Base-T, High-speed USB 2.0	O direct print, NFC; <b>Optional:</b> WiFi/WiFi Direct with A	Kerox Dual Band Wireless Kit, Bluetooth (iBeacon)
Controller Features	Configuration Cloning, Configuration Watchdog, Fl	eet Orchestrator, Remote Control Panel, Unified Add	lress Book
Copy and Print			
Copy and Print Resolution	<b>Copy:</b> Up to 600 x 600 dpi; <b>Print:</b> Up to 1200 x 24	100 dpi	
First-Print-Out Time (as fast as)	3.8 seconds	3.2 seconds	3.0 seconds
First-Copy-Out Time (as fast as) (from platen/ warmed-up state)	4.4 seconds	3.7 seconds	3.2 seconds
Page Description Language	Adobe® PostScript® 3™, Adobe® PDF, PCL® 5c/PCL® 6		
Print Features	Application Defaults, Bi-directional Real-time Status, Booklet Layout, Encrypted Secure Print, Hold All Jobs, Imaging Security with AltaLink's proprietary marking and infrared detection technology, Job Identification, Job Monitoring, Long Sheet (Banner) Printing, Print Around, Print from Cloud Repositories (Dropbox, OneDrive and Google Drive), Print from USB, Print on Alternate Paper, Scaling, Store and Recall Driver Settings, Two-sided Printing (as default), Xerox® Earth Smart Driver Settings; <b>Optional:</b> Print from and Scan to Xerox® DocuShare® Go content management		
Mobile and Cloud Ready			
Mobile Connectivity	Near Field Communication (NFC); <b>Optional:</b> Wi-Fi Direct, Wi-Fi (802.11 b/g/n/ac), AirPrint (iOS) including iBeacon (Bluetooth)		
Mobile Printing	Mopria® Print, Apple AirPrint™, Xerox® Print Service (Android), @PrintByXerox App; <b>Optional:</b> Xerox® Workplace Mobile App (iOS/Android)		
Mobile Scanning	Mopria® Scan, Apple AirPrint™, <b>Optional:</b> Xerox® Workplace Mobile App (iOS/Android)		
Mobile Apps and Xerox App Gallery	Automate everyday processes with apps that translate, redact, eSign, personalise, print, convert, route, collaborate and communicate. Visit www.xerox.co.uk/en-gb/connectkey/workplace-apps to find apps by industry or workflow. Software and services: Xerox® DocuShare® (xerox.co.uk/ecm), XMPie® (www.xerox.co.uk/en-gb/digital-printing/workflow-software/printing-software/xmpie-personalised-communication-software), Xerox® Workplace Solutions (www.xerox.co.uk/en-gb/office/print-management-solutions).		
Xerox® Workplace Central Platform	One-platform consistency for seamless productivity across computers, mobile devices and printers. With Workflow Central's ever-expanding suite of cloud-based workflows, you can change documents into audio files for easy listening, convert PDF or image files to popular Microsoft formats for shareability with a wider audience, turn handwriting into legible, editable and shareable text, translate to/from over 40 different languages and automatically redact Personal Identifiable Information using set words or phrases.		
Xerox® Workplace Suite and Xerox® Workplace Cloud	<b>Optional:</b> Xerox® Workplace Suite is a modular set of workflows designed to save customers time and money by providing effective control over their printer fleet while enabling worker productivity and mobility through a set of robust workflows. Xerox enables ultimate customer flexibility by offering these capabilities in both an on-premises server version (Workplace Suite) and a cloud-based version (Workplace Cloud) of this solution.		
Cloud Identity Provider (IdP) Integration	Use your desktop, laptop or mobile login credentic providers, Okta, Ping Identity and Microsoft® Azur	als to log in to your AltaLink® Multifunction Printers v e.	with direct connections to popular cloud identity

Scan	
Standard Features	Destinations: Scan to USB/PC via USB port/Email/Network (FTP/SMB), HTTP, HTTPS, SFTP destinations; File Formats: PDF, PDF/A, JPEG, TIFF; Convenience Features: 1-Touch Apps, Imaging Security with AltaLink's proprietary marking and infrared detection technology, Optical Character Recognition (OCR), Password-protected PDF, Scan Preview, Scan to Folder, Scan to Home, Searchable PDF, Single/Multi-Page PDF/TIFF, Touchless Workflow Accelerators, TWAIN Support, Unified Address Book
Optional Features	Scan to Cloud Repositories (Dropbox, OneDrive and Google Drive). Xerox® Scanning App for DocuShare®, other solutions available through various Xerox® Business Innovation Partners at <a href="www.xerox.co.uk/en-gb/office/printer-software">www.xerox.co.uk/en-gb/office/printer-software</a> , Print from and Scan to Xerox® DocuShare® Go content management
Fax	
Standard Features	Network Server Fax Enablement, Fax Build Job
Optional Features	Walk-up Fax (one-line and two-line options available, includes LAN Fax, Direct Fax, Fax Forward to Email or SMB Share)
Security	
Standard Features	802.1x, Access Control, Audit Log, Automated threat response through Trellix DXL*/Cisco® pxGrid integration, Automatic Self-signed Certificate, Cisco® Identity Services Engine (ISE) integration, Common Criteria Certification (ISO 15408) full system against HCP PP, Configuration Watchdog, Encrypted Secure Print, Encrypted Storage Drive (AES 256-bit, FIPS 140-3), FIPS 140-3, Firmware Verification, HTTPS, Imaging Security (copy, print, scan, email) with AltaLink's proprietary infrared detection technology, IPsec, Job Level Encryption via HTTPS and Drivers, Local Authentication (Internal Database), Trellix Embedded Control Whitelisting*, Trellix ePolicy Orchestrator®*, Network Authentication, Port/IP/Domain Filtering, Security Certificates utilising ECDSA, Security Dashboard, SFTP and Encrypted Email, SHA-256 Hash Message Authentication, SIEM integration (Splunk, LogRhythm, Trellix ESM*), Signed Email, SNMPv3, TLS 1.1/1.2/1.3, TPM, Trusted Boot, User Access and Internal Firewall, User Permissions
Optional Features	Trellix Integrity Control*, Smart Card Enablement Kit (CAC/PIV/.NET)³, Xerox® Integrated RFID Card Reader, Encrypted Hard Disk (AES 256-bit, FIPS 140-3) with multi-pass Image Overwrite³, Xerox® Workplace Cloud/Suite Print Management and Content Security; WPA2 and WPA3 with Dual Band Wireless Kit; learn more at www.xerox.co.uk/en-gb/office/print-management-solutions
Print Management	
Standard Features	Xerox® Standard Accounting (Copy, Print, Scan, Fax, Email), Network Accounting Enablement
Optional Features	Xerox® Workplace Cloud/Suite, other network accounting solutions available through various Xerox® Business Innovation Partners. Xerox® Virtual Print Management Services; learn more at <a href="https://www.xerox.co.uk/en-gb/office/printer-software#printmanagement">www.xerox.co.uk/en-gb/office/printer-software#printmanagement</a>

#### Features and Accessories

#### Single-Pass Duplex Automatic Document Feeder (DADF) saves time by simultaneously scanning both sides of a document with up to 270 impressions per minute (ipm).



#### **USER INTERFACE**



Intuitive Tablet-like 10.1-inch Colour Touchscreen is customisable and lets you perform tasks in just a few taps. Try it out at xerox.com/AltaLink8100UI.

### PAPER INPUT<sup>4</sup>

Two 520-sheet Adjustable Trays (common with all configurations). Tray 1 handles media sizes up to A3 and Tray 2 handles media sizes up to SRA3.



Envelope Kit (optional – replaces Tray 1) provides feeding of up to 60 envelopes.



#### High Capacity Tandem Tray Configuration

holds a total paper capacity of up to 3,140 sheets.

Bypass Tray handles up to 100 sheets; Custom sizes: 89 x 98 mm to 320 x 1,320 mm.



capacity to 6,140 sheets.



#### (optional) adds card-based

INNOVATIVE TECHNOLOGIES

authentication with support for over 90 access cards. Near Field Communication (NFC)



Tap-to-Pair allows users to tap their mobile devices to the AltaLink® B8100 Series user panel and quickly connect with the multifunction printer.

Xerox® Integrated RFID Card Reader



Smart Proximity Sensor detects when users are nearby. It conserves energy during inactive periods and automatically activates the device when a user approaches.

### PAPER OUTPUT/FINISHERS<sup>4</sup>









#### Office Finisher

(optional) provides advanced finishing functions, optional crease/score and saddle-stitch booklet, capable of 60-page booklets (2 to 15 sheets).

Business Ready (BR) Finisher (optional) gives you advanced finishing functions at a great value.

C-Fold/Z-Fold Unit (optional) adds C-fold, Z-fold and Z-half-fold capability to the BR Finisher or BR Booklet Maker Finisher.

BR Booklet Maker Finisher (optional) creates 64-page saddle-stitched booklets (2 to 16 sheets).

### LONG SHEET PRINTING

Long Sheet Feed Kit (optional) provides the ability to print up to 320 x 1,320 mm media.





Dual Offset Catch Tray (available when no finishers are installed; Single Offset Catch Tray with finishers).



Integrated Office Finisher (optional with B8145/B8155) provides 500-sheet stacking and 50-sheet, 2-position stapling.



Convenience Stapler (optional) staples up to 50 sheets of 75 gsm media.

Device Specification				
Control Panel Languages	US English, International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Turkish, Greek, Russian, Czech, Polish, Hungarian, Romanian, Catalan, Arabic			
Accessories				
Optional	Convenience Stapler (includes Work Surface <sup>5</sup> ) Envelope Tray (Replaces Tray 1)	nsport Kit) C-fold/Z-fold Unit for BR Finisher or BR Bo access Device Interface) for third-party access contro B B8145, B8155)		
Electrical Requirements	AltaLink® B8145	AltaLink® B8155	AltaLink® B8170	
North America	Voltage: 110-127 VAC +/- 10 % Frequency: 50/60 Hz +/- 3 % , 15 A		Voltage: 110-127 VAC +/- 10% Frequency: 50/60 Hz +/- 3%, 20 A	
Europe	Voltage: 220-240 VAC +/- 10 % Frequency: 50/60 Hz +/- 3 %, 10 A		Voltage: 220-240 VAC +/- 10% Frequency: 50/60 Hz +/- 3%, 10 A	

Device Specification (continued)				
Power Consumption	AltaLink® B8145	AltaLink® B8155	AltaLink® B8170	
Running (Average)	115 V: 717 watts 230 V: 674 watts	115 V: 806 watts 230 V: 760 watts	115 V: 929 watts 230 V: 908 watts	
Standby Mode	115 V: 71 watts 230 V: 71 watts	115 V: 72 watts 230 V: 70.3 watts	115 V: 91.1 watts 230 V: 79 watts	
Auto Off/Sleep Mode	115 V: 0.67 watts 230 V: 0.71 watts (Default time to sleep mode = 0 minutes)	115 V: 0.67 watts 230 V: 0.71 watts (Default time to sleep mode = 0 minutes)	115 V: 0.68 watts 230 V: 0.75 watts (Default time to sleep mode = 0 minutes)	
Warm-up (from Off)	As fast as 85 seconds			
Recovery from Sleep	As fast as 4.5 seconds			
Operating Environment				
Required Temperature Range	10 to 28 °C			
Required Relative Humidity	15% to 85%			
Sound Power Levels	Operating: 63.7/64.2 dB(A) Standby: 40.0/40.0 dB(A)	Operating: 65.2/67.3 dB(A) Standby: 43.0/43.0 dB(A)	Operating: 70.4 dB(A) Standby: 43.0 dB(A)	
Dimensions and Weight				
Base Configuration	Width: 620 mm  Depth: 723 mm  Height: 1,130 mm  Weight: 129.5 kg		Width: 620 mm Depth: 793 mm Height: 1,169 mm Weight: 144.8 kg	
With Office Finisher (with Booklet Maker)	Width: 1,207 mm       Width: 1207 mm         Depth: 723 mm       Depth: 793 mm         Height: 1,130 mm       Height: 1,169 mm         Weight: 168 kg       Weight: 184.2 kg		Depth: 793 mm Height: 1,169 mm	
Base Configuration with Business Ready (BR) Finisher	Width: 1,395 mm       Width: 1,395 mm         Depth: 723 mm       Depth: 723 mm         Height: 1,130 mm       Height: 1,169 mm         Weight: 173.4 kg       Weight: 188.4 kg			
Base Configuration with BR Booklet Maker Finisher	Width: 1,496.3 mm       Width: 1,496.3 mm         Depth: 723 mm       Depth: 723 mm         Height: 1,130 mm       Height: 1,169 mm         Weight: 190.4 kg       Weight: 205.6 kg			
Base Configuration with BR Booklet Maker Finisher and C-fold/Z-fold Unit	Width: 1,632 mm       Width: 1,632 mm         Depth: 723 mm       Depth: 723 mm         Height: 1,130 mm       Height: 1,169 mm         Weight: 240.7 kg       Weight: 255.9 kg			
Base Configuration with BR Booklet Maker Finisher, C-fold/Z-fold Unit and High Capacity Feeder	Width: 2,361 mm       Width: 2,361 mm         Depth: 723 mm       Depth: 723 mm         Height: 1,130 mm       Height: 1,169 mm         Weight: 271.6 kg       Weight: 287 kg		Depth: 723 mm Height: 1,169 mm	
System Certifications/Regul	latory Compliances			
Certifications	To view the latest list of certifications, go to <b>xero</b>	x.com/OfficeCertifications		

Paper Handling	AltaLink® B8145	AltaLink® B8155	AltaLink® B8170
Single-Pass Duplex Automo	itic Document Feeder (DADF)		
Capacity <sup>4</sup>	130 sheets		250 sheets
Speed (Up to)	82 ppm black-and-white (simplex) 141 ipm black-and-white (duplex)		135 ppm black-and-white (simplex) 270 ipm black-and-white (duplex)
Paper Sizes Sensed	85 x 125 mm to 297 x 432 mm		
Weights	60 to 128 gsm		
Bypass Tray (Standard)			
Capacity <sup>4</sup>	100 sheets		
Sizes	<b>Custom Sizes:</b> 89 x 98 mm to 320 x 1320 mm (SEF	;); <b>Optional:</b> Long Sheet Feed Kit (Banner Printing)	
Weights	52 to 300 gsm, <b>Long sheets/banners</b> (>483 mm):	106 - 220 gsm	
Media Types	Bond Card Stock Card Stock Reloaded Custom Envelopes Glossy Card Stock Reloaded Heavyweight Card Stock Heavyweight Glossy Card Stock Reloaded Heavyweight Glossy Card Stock Reloaded Heavyweight Glossy Card Stock Reloaded Hole Punched Labels Letterhead Lightweight Card Stock Reloaded Lightweight Glossy Card Stock Reloaded Lightweight Gard Stock Lightweight Glossy Card Stock Reloaded Preprinted Recycled Transparencies  Long Sheets/Banners: Card Stock Card Stock Card Stock Lightweight Card Stock Lightweight Card Stock Lightweight Card Stock Lightweight Card Stock Reloaded		
Trays 1 and 2 (Standard)	3		
Capacity <sup>4</sup>	520 sheets each		
Sizes	<b>Tray 1:</b> Custom Sizes: 140 x 182 mm to 297 x 432 r <b>Tray 2:</b> Custom Sizes: 140 x 182 mm to SRA3 (SEF)	nm (SEF)	
Weights	52 to 300 gsm		
Media Types	Bond Card Stock Card Stock Reloaded Custom Envelopes Glossy Card Stock Glossy Card Stock Glossy Card Stock Reloaded Heavyweight Card Stock Heavyweight Glossy Card Stock Heavyweight Glossy Card Stock Heavyweight Glossy Card Stock Heavyweight Glossy Card Stock Reloaded Hole Punched Labels Letterhead Lightweight Lightweight Card Stock Lightweight Glossy Card Stock Reloaded Plain Plain-Reloaded Preprinted Recycled Transparencies		

Paper Handling (continued)	AltaLink® B8145	AltaLink® B8155	AltaLink® B8170		
High Capacity Tandem Tray	High Capacity Tandem Tray (Available with all models)				
Capacity <sup>4</sup>	<b>Tray 3:</b> 867 sheets <b>Tray 4:</b> 1,133 sheets				
Sizes	A4, JIS B5, Executive (184 x 267 mm) LEF				
Weights	52 to 300 gsm				
Mediα Types	Bond Card Stock Custom Glossy Card Stock Hole Punched Labels Letterhead Lightweight Card Stock Lightweight Glossy Card Stock Plain Preprinted				
Envelope Tray (Optional - R	eplaces Tray 1)				
Capacity <sup>4</sup>	Up to 60 envelopes				
Sizes	No. 10 Commercial (235 x 105 mm) / Monarch, D Custom Sizes: 98 x 148 mm to 162 x 241 mm	L, C5			
Weights	75 to 90 gsm				
High Capacity Feeder (HCF)	(Optional with all models)				
Capacity <sup>4</sup>	3,000 sheets				
Sizes	Standard Sizes: A4 or B5 LEF				
Weights	52 to 300 gsm				
Total Capacity					
Device Total Capacity <sup>4</sup>	High Capacity Tandem Tray Module: 3,140 sheets High Capacity Tandem Tray Module with High Cap				

Finishing	AltaLink® B8145 AltaLink® B8155 AltaLink® B8170
Output Trays (Standard) (D	ual Offset Catch Trays not available with Integrated Office Finisher and limited to one with Office Finisher and BR Finishers)
Stacking Tray Capacity <sup>4</sup>	Dual Offset Catch Tray: Up to 250 sheets each Left Side Face-up Tray: Up to 100 sheets
Integrated Office Finisher (	Optional with AltaLink® B8145/B8155)
Stacking Tray Capacity <sup>4</sup>	500 sheets of 80 gsm – A4 or 250 sheets of 80 gsm – A3
Sizes	89 x 98 mm to 297 x 432 mm
Weights	52 to 300 gsm
Stapling	Single/Dual Position Auto-Stapling: 50 sheets maximum: Letter/A4/B5 size sheets (less than 90 gsm or (2) 220 gsm covers) 30 sheets maximum: Legal/Tabloid/A3/B4 size sheets (less than 90 gsm or (2) 220 gsm covers)
Office Finisher (Optional)	
Stacking Tray Capacity <sup>4</sup>	2,000 sheets unstapled or 1,000 sheets single-stapled or 750 sheets dual-stapled (8.5 x 11 in./A4)
Stacking Tray Sizes	210 x 182 mm to 297 x 432 mm
Weights	52 to 300 gsm
Multiposition Stapling	50 sheets maximum: Letter/A4/B5 size sheets (less than 90 gsm or (2) 220 gsm covers) 30 sheets maximum: Legal/Tabloid/A3/B4 size sheets (less than 90 gsm or (2) 220 gsm covers)
Hole Punch (Optional)	North America: 2/3-hole punch Europe: 2/4-hole punch Optional: 4-hole "Swedish" punch
Booklet Maker for Office Fi	nisher (Score/Crease, Saddle-stitch Staple) (Optional)
Top Tray Capacity <sup>4</sup>	40 booklets (2-15 sheets per booklet – 80 gsm or less)
Sizes	Letter/A4 SEF Legal/B4 SEF Tabloid/A3 SEF
Saddle-Stitch Stapling	2-15 sheets/8-60 page booklet 64 to 220 gsm
Score/Crease	1-15 sheets/unstapled 64 to 105 gsm
Business Ready (BR) Finishe	er (Optional) (Requires Horizontal Transport Kit)
Capacity <sup>4</sup>	Offsetting Top Tray: 500 sheets Stacking Stapling Tray: 3,000 sheets unstapled or 100 sets (dual or 4-position stapling) 279 x 432 mm, A3 or 200 sets (single-position staple) A4
Sizes	100 x 148 mm x 320 x 488 mm for top tray 182 x 203 mm to 320 x 488 mm for stacking B5 to A3 for stapling
Weights	52 to 300 gsm
Stapling	Single and multiposition stapling Auto stapling (50 sheets maximum) – 90 gsm Letter, Legal, Tabloid, A3, A4, B4 and B5 sizes supported
Hole Punch	North America: 2/3-hole punch Europe: 2/4-hole punch Optional: 4-hole "Swedish" punch
BR Booklet Maker Finisher	Optional) (Requires Horizontal Transport Kit)
Capacity <sup>4</sup>	Offsetting Top Tray: 500 sheets of A4 unstapled Stacking Stapling Tray: 1,500 sheets of A4/A3 unstapled or 200 stapled sets of A4 (single-position stapling or dual or 4-position stapling) or 100 stapled sets of A3
Sizes	100 x 148 mm x 320 x 488 mm for top tray 182 x 203 mm to 320 x 488 mm for stacking B5 to A3 for stapling
Weights	52 to 300 gsm
Stapling	Single and multiposition stapling Auto stapling (50 sheets maximum) – 90 gsm Letter, Legal, Tabloid, A3, A4, B4 and B5 sizes supported
Hole Punch	North America: 2/3-hole punch Europe: 2/4-hole punch Optional: 4-hole "Swedish" punch
Booklet maker	Saddle-stitch 2 to 16 sheets (7 sheets at 106 to 176 gsm coated or 5 sheets at 177 to 220 gsm coated) Bi-fold up to 5 sheets Letter, Legal, Tabloid, A3, A4 supported

Finishing (continued)	AltaLink® B8145	AltaLink® B8155	AltaLink® B8170	
C-fold/Z-fold Unit (Optiona	with BR Finisher and BR Booklet Maker Finisher)			
Types	C-fold, Z-fold and Z-half-fold			
Capacity <sup>4</sup>	40 sheets			
Sizes	C-fold and Z-fold: Letter/A4 SEF only Z-half-fold: Tabloid/A3 only	C-fold and Z-fold: Letter/A4 SEF only		
Weights	64 to 90 gsm			
Output Trays	Envelope Tray: C-fold, Z-fold and Tri-fold Stacker Tray or Top Tray: Z-half-fold			
Convenience Stapler (Optio	onal - Includes Work Surface <sup>5</sup> )			
Capacity <sup>4</sup>	50-sheet stapling 5,000 staples Requires separate power outlet			
Сору	AltaLink® B8145	AltaLink® B8155	AltaLink® B8170	
First-Copy-Out Time (from platen/warmed up)	As fast as 4.4 seconds	As fast as 3.7 seconds	As fast as 3.2 seconds	
Sides (input:output)	1-1, 1-2, 2-2, 2-1			
Quantity	1 to 9,999			
Resolution (max)	Up to 600 x 600 dpi	Up to 600 x 600 dpi		
Reduction/Enlargement	Variable zoom from 25% to 400% in 1% increme	ents		
Concurrency	Program ahead to allow the job to be queued whil	e the initial job is processed (Copy, Print, Fax and Sc	an)	
Copy Features	Annotation and Bates* stamping Authentication for Services Auto Paper Select Auto Reduction & Enlargement (to fit selected paper size) Auto Tray Switching Automatic 2-sided/Duplex Booklet Creation Build Job (enables page-level programming and also lets you proof each section or delete the last section as the job is built) Collation Covers (front only, front and back, back only, printed inside and out: blank or printed) Dividers (blank) Edge Erase Features Help (Intuitive text and graphic descriptions) ID Card Copy Image Quality Adjustments Image Shift (with Auto Centre option) Imaging Security Invert Image (negative or mirror image) Large Job Interrupt Multi-up (up to 15 columns by 15 rows) Sample Set Save Job Settings Stapling Touchless Workflow Accelerators Transparencies			

Print	AltaLink® B8145	AltaLink® B8155	AltaLink® B8170		
Resolution (up to)	1200 x 2400 dpi		·		
Print Features	Job Identification (Print ID or Bann LAN Fax (requires optional Fax Kit) Long Sheet/Banner Layout/Watermark N-up (up to 16 pages per sheet) Paper Selection by Attribute Sampl Print From Cloud Repositories (Drog Saved Job Secure Print with Timed Deletion Special Pages (exception page prog Store and Recall Driver Settings	ser Permissions  , Resolution (Standard, Enhanced, High))  or Banner, Print ID in margins on the first page only or all pages)  ax Kit)  eet)  Sample Set  s (Dropbox, OneDrive and Google Drive)  etion  ge programming: covers, inserts, exception pages)  ngs  x® Earth Smart Settings, Duplex, N-up, Turn-off Banner and Print ID, Smart Sample Set, Hold All Jobs)			
Print from USB	Allows walk-up printing from Type A Supports direct printing from a con Supported file formats: PDF, JPEG, Colour jobs can be printed as black	nputer via Type B USB port TIFF, PS, PCL			
Operating Systems	Windows 10 (32 and 64 bit) Windows 11 (32 and 64 bit) MacOS 10.13.x, 10.14.x, 10.15.x, 1 Red Hat Linux 6x, 7.x, 8.x Ubuntu Linux 20.04.x, 22.04.x SuSe Linux Server 12.3-13.x, 15.x  MS Windows 2012 Server (32 and MS Windows 2016 Server (32 and MS Windows 2019 Server (32 and MS Windows 2022 Server (32 and Red Hat Linux Server 7.x, 8.x SuSe Linux Server 12.2-12.4, 15.x	ws 10 (32 and 64 bit) ws 11 (32 and 64 bit) i10.13x, 10.14x, 10.15x, 11.0x, 12.x it Linux 6x, 7x, 8.x u Linux 20.04x, 22.04x nux Server 12.3-13.x, 15.x andows 2012 Server (32 and 64 bit) ndows 2016 Server (32 and 64 bit) ndows 2019 Server (32 and 64 bit) ndows 2022 Server (32 and 64 bit)			
Network Protocols	TCP/IP: HTTP/HTTPS, Internet Print Microsoft Windows Networking ove Bonjour®/AirPrint™ IPv6 Most protocols not in use can be di		9100, IPv4/IPv6, WSD		
Font Capability	PCL: 93 scalable fonts, line printer of	and bitmap font (including Cyrillic font support)	PostScript 3: 173 Type 1 fonts, 2 Multiple Master fonts		
Xerox® Global Print Driver®	A truly universal print driver that lets IT administrators install, upgrade and manage non-Xerox and Xerox® Devices from a single driver. It provides a consistent, easy-to-use interface for end users, reducing the number of support calls and simplifying print services management. Support for Microsoft Universal Print.				
Xerox <sup>®</sup> Pull Print Driver	Makes it easy for IT managers to qualify, deploy and manage all print devices using a single driver in a Pull Print environment. Uses a single queue and single driver. The Xerox® Pull Print Driver extends convenience across a broad range of printing assets. IT administrators no longer need to manage and configure multiple drivers. Used in conjunction with Equitrac Office®, Ysoft® SafeQ®, Pharos® and others.				
Unified Address Book for F	Unified Address Book for Fax, Email and Scan to				
Features	Services supported: Fax, Email, Scar Maximum contacts: 5,000 Contacts: Supports 1 or more destir Favourites for quick access of all ser	nations			

Scan	AltaLink® B8145	AltaLink® B8155	AltaLink® B8170
Concurrency	Scan while the system is printing printing concurrent jobs)	, copying or while it is transferring scan-to-network	c or fax jobs (priority is for the return of scanned originals and
Input Speed (up to)	82 ppm black-and-white and colour (simplex) 141 ipm black-and-white and colour (duplex) 135 ppm black-and-white and colour (simplex) 270 ipm black-and-white and colour (duplex)		
Resolution	150 x 150 dpi to 600 x 600 dpi		
Bit Depth	1-bit (black-and-white), 8-bit (greyscale), 24-bit (colour)		
Maximum Scan Area	A3		
Scan Template Management	Support 250 scan templates Create Xerox® CentreWare® IS sc	can templates and share via device cloning to othe	er multifunction printers' confirmation sheet options
Network Protocols	SFTP, FTP, SMB, HTTP, HTTPS		
File Compression		4 MMR compression – single or multiple pages) -1b (MRC, JPEG, G3 MH, G4 MMR, JBIG 2 Huffmar	n, JBIG Arithmetic Compression, Deflate (for black-and-white and
Document Management Fields (Metadata)	field name, default value and o	tadata fields per network scan to file templates and	d unlimited fields within the template – metadata field consists of a
Scan Features	Auto Background and Shadow Si Bound Originals Compression Quality/File Size Co Edge Erase Imaging Security Mixed Size Originals Original Type (Photo and Text, Ph Reduction/Enlargement Scan Build Job Scan Preview Single Touch Scan buttons (up to Size for Size (for mixed size origin Touchless Workflow Accelerators TWAIN Support/WIA 2.0 Suppor	ontrol noto, Text, Map, Newspaper/Magazine) o 10) nals)	
Scan to Email (Standard)			
Scan Features	Auto send to self     Email signatures (6 lines each o     Email signing (requires Smart C     Scan to Email S/MIME Encrypt     Touchless Workflow Accelerato	Card option) ion	onfigurable), email Embedded Web Server confirmation sheet options
Directory Access	Address list via LDAP (Windows A	Active Directory, Exchange, Notes, Domino), Device	e Address Book
Scan To			
Standard Features	Scan to Email Scan to Home Scan to Mailbox Scan to Network (using Secure FTP/HTTP/HTTPS) Scan to Network Folder (using Secure FTP/HTTP/HTTPS) Scan to Network Folder (using Secure FTP/HTTP/HTTPS) Scan to PC/Server Client (SMB or FTP) Scan to PC via USB port Scan to USB		
Optional Features	Scan to Cloud Repositories (Dropbox, OneDrive and Google Drive)		
Workflow Scanning (Option	nal)		
Scanning Software	Autostore v7 eCopy ShareScan v5.2 eCopy ScanStation v5.2		
Scanning Apps and Xerox App Gallery		Microsoft OneDrive, Microsoft Office 365™, Box®, λ in the Xerox App Gallery: <b>xerox.com/AppGallery</b>	Xerox® Workplace Mobile App (iOS/Android)

Security	AltaLink® B8145	AltaLink® B8155	AltaLink® B8170
Features	Audit Log		
	Cisco® Identity Services Engine (ISE) compatible		
	Configuration Watchdog (Monitor and remediate	e 75 security settings in the following areas):	
	- 802.1x - Admin Password Reset		
	- Audit Log		
	- Automatic Software Upgrade		
	- Email Alerts		
	- FIPS 140-3		
	- Hold All Jobs - Immediate Job Overwrite <sup>9</sup>		
	- Installation Policies		
	- Trellix Embedded Control*		
	- PII - Login Name		
	- PostScript Passwords		
	- Remote Services Enablement - Remote Start (Mopria® or AirPrint™)		
	- Remote Start (TWAIN)		
	- Reprint Saved Jobs		
	- Scan to Mailbox (Internal storage)		
	- Scheduled Disk Overwrite <sup>9</sup>		
	- Secure Passcode Length - Secure Print Device Policies		
	- SEEM		
	- SNMP		
	- System Timeout		
	- USB (Print from USB)		
	- USB (Scan to USB)		
	- USB Port Management - User Data Encryption		
	Expanded Authentication		
	- Digitally signed PDF (when using Smart Card au	ithentication)	
	- Encrypted and authentication to SMTP server fo		
	- Encrypted/Password-protected PDF (when using		
	<ul> <li>FIPS 140-3, 256 bit Hard Disk Encryption, TLS, I</li> <li>Immediate Image Overwrite/Securely delete jol</li> </ul>		
	- Local Authentication (internal database)	ss using approved algorithms	
		device services via Kerberos (UNIX/Windows Serv	ver 2008), SMB (Windows Server 2008, Windows
	server 2012), NDS, LDAP authentication		
	- On-demand Image Overwrite (Scheduled, Manu - Secure Data	ual), includes sanitisation of unused area of disk <sup>9</sup>	
	- Secure Data - Secure Print (up to 10 digit PIN or Network Auth	nentication)	
	- Smart Card authentication – 144k CAC/PIV Car		
	Expanded Authorisation	•	
	- Authorisation per user per service		
	- SA access based on network credentials - Secure Network Access		
		int Features (e.g. time restrictions) reflects in the p	orint driver
	Full System Common Criteria certified by NIAP ur		
	Hide Print Job Names	·	
	• Imaging Security	V4 V2 V2 LITTE: 002 4V CETS	
	<ul> <li>IP Filter, IPsec, IPv6, TLS V1.1, V1.2, V1.3, SNMP \         <ul> <li>Trellix Embedded Control* (whitelisting), Trellix In</li> </ul> </li> </ul>		
	Port disablement including USB ports	acging control (optional)	
	Security Dashboard		
	Security Information and Event Management (S)		er*, LogRhythm and Splunk
	WPA2 and WPA3 are supported by the Dual Band	d Wireless Kit	
Xerox® Integrated RFID	Integrated support for most industry security cards	providing additional security; with embedded mu	ıltifunction printer card readers in the
Card Reader (Optional kit)	multifunction printer panel		

Fax	AltaLink® B8145	AltaLink® B8155	AltaLink® B8170		
Network Server Fax Feature	Network Server Fax Features				
Compatibility	ITU (CCITT) group 3; Various Xerox® Business Innovation Partner Solutions				
Maximum Scan Area	A3				
Fax Send Features	One- or Two-sided Scanning (up to A3) Add to Send List (200 numbers maximum) Build Job, Favourites, Delay Send (specific time) Ori	ginal Type (photo, text or photo and text)			
Fax Print Features	One- or Two-sided Printing, Staple, Secure Print				
Transmission Resolution	Superfine: 400 x 200 dpi (Scan at 600 x 600 dpi) Fine: 200 x 200 dpi Standard: 200 x 100 dpi				
Walk-up Fax Features (Opti	onal; Customer-Installable – 1 and 2 lines)				
Compatibility	ITU (CCITT) Group 3				
Speed/Modems	One or Two V.34 modems: 33,600 bps. Less than 4	seconds per page transmission time			
Compression/Speed	MH/G3, MR/G3, MMR/SG3, JBIG/SG3				
Resolution	Walk-up Send: Standard: 200 x 100 dpi Fine: 200 x 200 dpi Superfine: 600 x 600 dpi Receive: Accepts all sizes				
Fax Send Features	Auto Fax Transmission Reduction Automatic Cover Sheets Automatic Memory Resend Batch Send (up to memory capacity) Delay Start, Build Job, Favourites Device Address Book (up to 5,000 contacts) LAN Fax (fax from print driver) Page-by-page Job Status at the Machine PSTN Fax				
Fax Receive Features	Auto Answer Delay One- or Two-sided Printing Output Tray Selection Receive Print Mode – Manual (size, margin, stock, h Receive Timestamp Secure Receive Stapled or Unstapled Up to 200 Password-Protected Mailboxes	eader)/Auto			
Fax forward	Forward to Email or SMB Location Fax Forward on Receive Only				
Fax Reports	Activity, Dial Directory, Group Directory, Transmissi Broadcast Report	on Confirmation, Pending Fax, Options Report, On-d	emand Overwrite <sup>9</sup> Report, Mailbox Report,		
Directory Access	Utilises the Unified Address Book Group fax available				
Auto Redial	Up to 14 attempts (per country requirements) 1 to 25-minute intervals				
Auto Resend	Up to 5 attempts				

Device Management	
Administrative Protocols	DHCP, BOOTP, SNMP, SLP® v2, HTTP, HTTPS, DHCP Autonet, TLS, NTP, DNS, SMB, SMTP/POP3, WSD, LDAP, Multicast DNS
Management Support	SNMP Version 1. SNMP Version 2c and SNMP Version 3 trap over TCP/IP and IP MIB access (IETF-MIBII RFC 1213) Host Resources MIB RFC 2790, Printer MIB RFC 3805, PWG-Imaging-System- Power MIB, Fleet Orchestrator, Configuration Watchdog, Xerox® Easy Assist App
Xerox® CentreWare® Web	A Web-based server application for network administrators that permits Web-browser-based device management from any workstation, whether running on Windows, UNIX or any other operating system:  • Works with any SNMP-managed printer from any manufacturer  • Remote configuration of SNMP v3  • Provides help with device discovery and installation, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management  • Requires Windows 7 and Internet Explorer 6.0 and higher  • Auto-detect Xerox® CentreWare® Web server and download configurations files for touchless remote installation
Xerox® Device Manager	Xerox® Device Manager collects and manages the data that drives fact-based decisions for your enterprise device management environment. It is a single tool to install print queues and configure, manage, monitor and report on both networked and locally connected devices – regardless of vendor – across your enterprise. Xerox® Device Manager provides:  • Device monitoring and troubleshooting  • Remote configuration of SNMP v3  • Extensive reporting and discovery of new devices  • Usage collection, chargeback and billing capabilities  • Auto-detect Xerox® Device Manager server and download configurations files for touchless remote installation
Xerox® Workplace Cloud	Remote management to set and audit device configuration data with Xerox® Workplace Cloud, eliminating the need for an on-site server
Fleet Orchestrator	Fleet Orchestrator feature offers the ability to create a group of devices that share information with each other via a secure peer-to-peer connection. The following data can be shared: Software update files, clone files and 1-Touch App files. Auto-assembly feature allows a new AltaLink® to automatically set itself on the network and configure.
Novell NDPS/NEPS	Server gateway application: centralised management tool
Xerox® Device Types for SAP R/3 Intelligent Barcode Utility (optional)	Provides built-in process intelligence that allows the printing of barcodes on any appropriately configured PostScript printer in specific versions of SAP environment and within Latin-1 (ISO8859-1) SAP system code pages only. Used in conjunction with Xerox® PostScript Device Types for SAP environment and Xerox® Font Centre Barcode Fonts. For more information, visit <a href="https://www.xerox.co.uk/en-gb/office/printer-software">www.xerox.co.uk/en-gb/office/printer-software</a>
Xerox® Device Types for SAP Environment	Xerox, together with SAP through our Gold-level membership in the SAP Printer Vendor Programme, provides seamless connectivity between SAP systems and your Xerox® Printers and Multifunction Printers. As an SAP customer, you benefit from having SAP-certified Xerox® Device types available right from SAP's online delivery model. SAP-certified device types for Xerox® Printers and Multifunction Printers are available to download. www.xerox.co.uk/en-gb/office/printer-software
Xerox® Embedded Web Ser	ver – Integrated Device Web Pages Provided by the Device
Device Status	Web server embedded in Network Controller:  Tray status/contents  Consumables status  Alerts  Remote Control Panel
Job Submission	Print-ready files: PS, PCL, TIFF, PDF, JPG, TXT, PRN Output feature selection (2-sided, collate, orientation, staple, hole punch, folding, output destination) Delivery options (Immediate, sample set, delay and secure, Save job or reprint)
Device Administration	Allows simple, remote installation setting of configuration options and management of the device, Fleet Orchestrator, Security Dashboard
Browsers	Microsoft Edge version 88+ Microsoft Chromium Edge version 79+ Mozilla Firefox 91.9.0, 100.0 Safari 13.1.2, 14.1.2, 15.4 Opera 2020, 2021 Google Chrome version 80.0.x+
Support	Install print/scan drivers and online support available via www.support.xerox.com/en-gb
Languages Supported	International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Russian, Simplified Chinese, Korean, Japanese, Arabic
Remote Services	
Xerox® Automatic Meter Readings (AMR)	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® Device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.
Xerox® Automatic Supplies Replenishment (ASR)	Automatically orders supplies for output devices from Xerox based on actual usage, eliminating the need to manually manage supplies inventory.
Accounting	
Xerox® Standard Accounting (Standard)	
Tracking	Copy, Print, Fax, Scan and Email usage
Accounting	Up to 2,497 User Accounts (User ID) Up to 500 General Accounts (Client) Up to 498 Group Accounts (Department)
Features	Administrator can manage the feature via the Web User Interface or device control panel in tools.     Administrator can import or export User Accounts, Group Accounts, General Accounts and User Limits via an industry-standard CSV file.

#### Accounting Options – Network Accounting (Allows central server to manage all accounting) $\bullet$ Enhanced network accounting with up-to-the-minute data on how the system is being used Comprehensive management and enterprise-scale tracking and reporting of device usage of copy, print, scan and server fax • Numerous solutions are available through Xerox Alliance Partners. For details, visit www.xerox.co.uk • Security enhancements with the addition of HTTPS protocol support • Device requests account authentication from third-party server enabling larger databases of users and accounts • Accept Authentication Login at the control panel and pass to third-party Networking Account • Interface with third-party accounting terminal for accounting user interface Supplies Yield Toner Cartridge<sup>6</sup> 52,000 pages Black Transfer Belt Cleaner 160,000 pages 1 Assembly Second Bias Transfer Roll 1 Assembly 200,000 pages Staple Cartridges For BR Finisher, Integrated Office Finisher, Office Finisher and Convenience Stapler (1 cartridge per carton) 5,000 each cartridge For BR Booklet Maker (1 cartridge per carton) 5,000 each cartridge For Office Finisher Booklet Maker (8 cartridges per carton) 2,000 each cartridge Staple Refills For Integrated Office Finisher, Office Finisher, BR Finisher and Convenience Stapler (3 refills per carton) 5,000 each refill Xerox® Smart Kit® Drum Cartridge 1 Cartridge 200,000 pages Waste Toner Container 1 Cartridge (AltaLink® B8145/8155) 121,000 pages w/o Suction Filter Waste Toner Container 1 Cartridge (AltaLink® B8170) 121.000 pages with Suction Filter9

Return spent imaging supplies through the Xerox® Green World Alliance® collection/reuse/recycling programme. For more information, visit www.xerox.co.uk/recycling.

For more information, visit us at www.xerox.co.uk/office.



Declared in accordance with ISO/IEC 24734.

Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

<sup>&</sup>lt;sup>3</sup> Not available in all geographical locations.

Paper capacities are based on 75 gsm stock; capacities will vary with different weight stocks

<sup>&</sup>lt;sup>5</sup> Sold separately in some geographical locations.

<sup>6</sup> Average standard pages. Declared in accordance with ISO/IEC 19752. Toner yield can vary due to many factors, including but not limited to image area coverage, image content, media size, media orientation, run mode, application types, monthly print volumes and image quality set-points.

<sup>&</sup>lt;sup>7</sup> Average drum yield is based on a run length of 5 pages of A4 LEF pages, with a split of 35% colour/65% black-and-white pages <sup>8</sup> Waste Toner Container yield will vary depending on the image type, area coverage % and job run length.

<sup>&</sup>lt;sup>9</sup> With optional hard drive.

\* Trellix DXL formerly known as McAfee® DXL, Trellix Embedded Control Whitelisting formerly known as McAfee® Embedded Control Whitelisting, Trellix ePolicy Orchestrator\* formerly known as McAfee® ePolicy Orchestrator\*, Trellix Folicy Or Security Manager. Trellix brand name will be reflected in future firmware releases.