Xerox[®] AltaLink[®] Multifunction Printers

Xerox[™]

B8145/B8155/B8170



AltaLink® B8100 Series Multifunction Printers are built on Xerox® ConnectKey® Technology. For more information, go to **www.ConnectKey.com**.

System Specification	AltaLink® B8145	AltaLink® B8155	AltaLink® B8170	
Speed ¹	Up to 45 ppm	Up to 55 ppm	Up to 72 ppm	
Monthly Duty Cycle ²	Up to 200,000 pages	Up to 250,000 pages	Up to 300,000 pages	
Hard Drive/ Processor/Memory	Minimum 128 GB SSD/ Optional : 500 GB HDD/Intel	[®] Atom™ Quad Core 1.91 GHz/4 GB system memory		
Connectivity	Ethernet 10/100/1000 Base-T, High-speed USB 2.0	direct print, NFC; Optional: WiFi/WiFi Direct with Xero	ox Dual Band Wireless Kit, Bluetooth (iBeacon)	
Controller Features	Configuration Cloning, Configuration Watchdog, Flee	et Orchestrator, Remote Control Panel, Unified Address	s Book	
Copy and Print				
Copy and Print Resolution	Copy: Up to 600 x 600 dpi; Print: Up to 1200 x 240	0 dpi		
First-Print-Out Time (as fast as)	3.8 seconds	3.2 seconds	3.0 seconds	
First-Copy-Out Time (as fast as) (from platen/ warmed-up state)	4.4 seconds	3.7 seconds	3.2 seconds	
Page Description Language	Adobe® PostScript® 3™, Adobe® PDF, PCL® 5c/PCL® 6			
Print Features	Application Defaults, Bi-directional Real-time Status, Booklet Layout, Encrypted Secure Print, Hold All Jobs, Imaging Security with AltaLink's proprietary marking and infrared detection technology, Job Identification, Job Monitoring, Long Sheet (Banner) Printing, Print Around, Print from Cloud Repositories (Dropbox, OneDrive, and Google Drive), Print from USB, Print on Alternate Paper, Scaling, Store and Recall Driver Settings, Two-sided Printing (as default), Xerox® Earth Smart Driver Settings; Optional: Print from and Scan to Xerox® DocuShare® Go content management			
Mobile- and Cloud-Ready				
Mobile Connectivity	Near Field Communication (NFC); Optional: Wi-Fi D	irect, Wi-Fi (802.11 b/g/n/ac), AirPrint (iOS) including	iBeacon (Bluetooth)	
Mobile Printing	Mopria® Print, Apple AirPrint™, Xerox® Print Service (Α	Mopria® Print, Apple AirPrint™, Xerox® Print Service (Android), @PrintByXerox App; Optional: Xerox® Workplace Mobile App (iOS/Android)		
Mobile Scanning	Mopria® Scan, Apple AirPrint™, Optional: Xerox® Wo	orkplace Mobile App (iOS/Android)		
Mobile Apps and Xerox App Gallery	Automate everyday processes with apps that translate, redact, eSign, personalize, print, convert, route, collaborate, and communicate. Visit xerox.com/WorkplaceApps to find apps by industry or workflow. Software and services: Xerox® DocuShare® (xerox.com/ecm), XMPie® (xerox.com/XMPie), Xerox® Workplace Solutions (xerox.com/WorkplaceSolutions).			
Xerox® Workplace Central Platform	One-platform consistency for seamless productivity across computers, mobile devices and printers. With Workflow Central's ever-expanding suite of cloud-based workflows, you can change documents into audio files for easy listening, convert PDF or image files to popular Microsoft formats for shareability with a wider audience, turn handwriting into legible, editable and shareable text, translate to/from over 40 different languages, and automatically redact Personal Identifiable Information using set words or phrases.			
Xerox® Workplace Suite and Xerox® Workplace Cloud	Optional: Xerox® Workplace Suite is a modular set of workflows designed to save customers time and money by providing effective control over their printer fleet while enabling worker productivity and mobility through a set of robust workflows. Xerox enables ultimate customer flexibility by offering these capabilities in both an on-premises server version (Workplace Suite) and with a cloud-based version (Workplace Cloud) of this solution.			
Cloud Identity Provider (IdP) Integration	Use your desktop, laptop, or mobile login credentials to log in to your AltaLink® MFPs with direct connections to popular cloud identity providers, Okta, Ping Identity, and Microsoft® Azure.			

Scan	
Standard Features	Destinations: Scan to USB/PC via USB port/Email/Network (FTP/SMB), HTTP, HTTPS, SFTP destinations; File Formats: PDF, PDF/A, JPEG, TIFF; Convenience Features: 1-Touch Apps, Imaging Security with AltaLink's proprietary marking and infrared detection technology, Optical Character Recognition (OCR), Password-protected PDF, Scan Preview, Scan to Folder, Scan to Home, Searchable PDF, Single/Multi-Page PDF/TIFF, Touchless Workflow Accelerators, TWAIN Support, Unified Address Book
Optional Features	Scan to Cloud Repositories (Dropbox, OneDrive, and Google Drive). Xerox® Scanning App for DocuShare®, other solutions available through various Xerox® Business Innovation Partners at xerox.com/Software-Solutions, Print from and Scan to Xerox® DocuShare® Go content management
Fax	
Standard Features	Network Server Fax Enablement, Fax Build Job
Optional Features	Walk-up Fax (one-line and two-line options available, includes LAN Fax, Direct Fax, Fax Forward to Email or SMB Share)
Security	
Standard Features	802.1x, Access Control, Audit Log, Automated threat response through Trellix DXL*/Cisco® pxGrid integration, Automatic Self-signed Certificate, Cisco® Identity Services Engine (ISE) integration, Common Criteria Certification (ISO 15408) full system against HCP PP, Configuration Watchdog, Encrypted Secure Print, Encrypted Storage Drive (AES 256-bit, FIPS 140-3), FIPS 140-3, Firmware Verification, HTTPS, Imaging Security (copy, print, scan, email) with AltaLink's proprietary infrared detection technology, IPsec, Job Level Encryption via HTTPS and Drivers, Local Authentication (Internal Database), Trellix Embedded Control Whitelisting*, Trellix ePolicy Orchestrator®*, Network Authentication, Port/IP/Domain Filtering, Security Certificates utilizing ECDSA, Security Dashboard, SFTP and Encrypted Email, SHA-256 Hash Message Authentication, SIEM integration (Splunk, LogRhythm, Trellix ESM*), Signed Email, SNMPv3, TLS 1.1/1.2/1.3, TPM, Trusted Boot, User Access and Internal Firewall, User Permissions
Optional Features	Trellix Integrity Control*, Smart Card Enablement Kit (CAC/PIV/.NET)³, Xerox® Integrated RFID Card Reader, Encrypted Hard Disk (AES 256-bit, FIPS 140-3) with multi-pass Image Overwrite®, Xerox® Workplace Cloud/Suite Print Management and Content Security; WPA2 and WPA3 with Dual Band Wireless Kit; learn more at xerox.com/WorkplaceSolutions
Print Management	
Standard Features	Xerox® Standard Accounting (Copy, Print, Scan, Fax, Email), Network Accounting Enablement
Optional Features	Xerox® Workplace Cloud/Suite, other network accounting solutions available through various Xerox® Business Innovation Partners. Xerox® Virtual Print Management Services; learn more at xerox.com/PrintManagement

Features and Accessories

Single-Pass Duplex Automatic Document Feeder (DADF)

saves time by simultaneously scanning both sides of a document with up to 270 impressions per minute (ipm).



USER INTERFACE



INNOVATIVE TECHNOLOGIES

Intuitive Tablet-like 10.1-inch
Color Touchscreen is customizable
and lets you perform tasks in just a
few taps. Try it out at
xerox.com/AltaLink8100UI.

Xerox® Integrated RFID Card

90 access cards.

with the MFP.

Reader (optional) adds card-based authentication with support for over

Near Field Communication (NFC)

Tap-to-Pair allows users to tap their mobile devices to the AltaLink® B8100 Series user panel and quickly connect

Smart Proximity Sensor detects

when users are nearby. It conserves

energy during inactive periods and automatically activates the device when a user approaches.

PAPER INPUT⁴

Two 520-sheet Adjustable Trays (common with all configurations). Tray 1 handles media sizes up to 11.7 x 17 in./A3 and Tray 2 handles media sizes up to 12 x 18 in./SRA3.



Envelope Kit (optional — replaces Tray 1) provides feeding of up to 60 envelopes.



High Capacity Tandem Tray Configuration holds a total paper capacity of up to 3,140 sheets.

Bypass Tray handles up to 100 sheets; Custom sizes: 3.5 x 3.9 in. to 12.6 x 52 in./89 x 98 mm to 320 x 1,320 mm.



Feeder (optional) holds 3,000 sheets of letter/A4 paper, increasing the maximum paper capacity to 6,140 sheets.





Office Finisher (optional) provides

(optional) provides advanced finishing functions, optional crease/score, and saddle-stitch booklet, capable of 60-page booklets (2 to 15 sheets).



Business Ready (BR) Finisher (optional)

gives you advanced finishing functions at a great value.



C-Fold/Z-Fold Unit

(optional) adds C-fold, Z-fold, and Z-half-fold capability to the BR Finisher or BR Booklet Maker Finisher.



BR Booklet Maker

Finisher (optional) creates 64-page saddle-stitched booklets (2 to 16 sheets).



Long Sheet Feed Kit (optional) provides the ability to print up to 12.6 x 52 in./ 320 x 1,320 mm media.





Dual Offset Catch Tray (available when no finishers are installed; Single Offset

Catch Tray with finishers).



Integrated Office Finisher (optional with B8145/B8155) provides 500-sheet stacking and 50-sheet, 2-position stapling.



Convenience Stapler (optional) staples up to 50 sheets of 20 lb./75 gsm media.

Device Specification	
Control Panel Languages	US English, International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Turkish, Greek, Russian, Czech, Polish, Hungarian, Romanian, Catalan, Arabic
Accessories	
Optional	SOOGB HDD Bluetooth Kit Booklet Maker for Office Finisher BR (Business Ready) Finisher (requires Horizontal Transport Kit) BR Booklet Maker Finisher (requires Horizontal Transport Kit) BR Booklet Maker Finisher (requires Horizontal Transport Kit) C-fold/Z-fold Unit for BR Finisher or BR Booklet Maker Finisher Convenience Stapler (includes Work Surface5) Envelope Tray (Replaces Tray 1) Foreign Device Interface (Also known as Auxiliary Access Device Interface) for third-party access control devices, such as coin machines and card readers High Capacity Feeder 3000 A4/Letter Hole Punch (2/3, 2/4, Swedish) Horizontal Transport Kit Integrated Office Finisher (Available with AltaLink® B8145, B8155) Long Sheet Feed Kit (banner printing) Trellix Integrity Control Enablement Kit* Multi-feed Detection Kit (AltaLink® B8170 only) Office Finisher Scan To Cloud Enablement Kit Smart Card Enablement Kit USB Keyboard/Shelf Kit Walk-up Fax (One- or Two-line options, includes LAN Fax) Wi-Fi/Wi-Fi Direct with Dual Band Wireless Kit Xerox® Integrated RFID Card Reader Kit
Electrical Requirements	AltaLink® B8145 AltaLink® B8155 AltaLink® B8170
North America	Voltage: 110-127 VAC +/- 10% Voltage: 110-127 VAC +/- 10% Frequency: 50/60 Hz +/- 3%, 15 A Frequency: 50/60 Hz +/- 3%, 20 A
Europe	Voltage: 220-240 VAC +/- 10% Voltage: 220-240 VAC +/- 10% Frequency: 50/60 Hz +/- 3%, 10 A Frequency: 50/60 Hz +/- 3%, 10 A

Device Specification (continued)				
Power Consumption	AltaLink® B8145 AltaLink® B8155 AltaLink® B8170			
Running (Average)	115V: 717 watts 230V: 674 watts	115V: 806 watts 230V: 760 watts	115V: 929 watts 230V: 908 watts	
Standby Mode	115V: 71 watts 230V: 71 watts	115V: 72 watts 230V: 70.3 watts	115V: 91.1 watts 230V: 79 watts	
Auto Off/Sleep Mode	115V: 0.67 watts 230V: 0.71 watts (Default time to sleep mode = 0 minutes)	115V: 0.67 watts 230V: 0.71 watts (Default time to sleep mode = 0 minutes)	115V: 0.68 watts 230V: 0.75 watts (Default time to sleep mode = 0 minutes)	
Warm-up (from Off)	As fast as 85 seconds			
Recovery from Sleep	As fast as 4.5 seconds			
Operating Environment				
Required Temperature Range	50 to 82° F/10 to 28° C			
Required Relative Humidity	15% to 85%			
Sound Power Levels	Operating: 63.7/64.2 dB(A) Operating: 65.2/67.3 dB(A) Operating: 70.4 dB(A) Standby: 40.0/40.0 dB(A) Standby: 43.0/43.0 dB(A) Standby: 43.0 dB(A)			
Dimensions and Weight				
Base Configuration	Width: 24.4 in./620 mm Depth: 28.5 in./723 mm Height: 44.5 in./1,130 mm Weight: 286 lb./129.5 kg		Width: 24.4 in./620 mm Depth: 31.2 in./793 mm Height: 46 in./1,169 mm Weight: 319.2 lb./144.8 kg	
With Office Finisher (with Booklet Mαker)	Width: 47.5 in./1,207 mm Width: 47.5 in./1207 mm Depth: 28.5 in./723 mm Depth: 31.2 in./793 mm Height: 44.5 in./1,130 mm Height: 46 in./1,169 mm Weight: 370.3 lb./168 kg Weight: 406 lb./184.2 kg		Depth: 31.2 in./793 mm	
Base Configuration with Business Ready (BR) Finisher	Width: 55 in./1,395 mm Width: 55 in./1,395 mm Depth: 28.5 in./723 mm Depth: 31.2 in./723 mm Height: 44.5 in./1,130 mm Height: 46 in./1,169 mm Weight: 382.3 lb./173.4 kg Weight: 415.4 lb./188.4 kg		Depth: 31.2 in./723 mm Height: 46 in./1,169 mm	
Base Configuration with BR Booklet Maker Finisher	Width: 59 in./1,496.3 mm Width: 59 in./1,496.3 mm Depth: 28.5 in./723 mm Depth: 31.2 in./723 mm Height: 44.5 in./1,130 mm Height: 46 in./1,169 mm Weight: 419.7 lb./190.4 kg Weight: 453.3 lb./205.6 kg		Depth: 31.2 in./723 mm Height: 46 in./1,169 mm	
Base Configuration with BR Booklet Maker Finisher and C-fold/Z-fold Unit	Width: 64.3 in./1,632 mm Width: 64.3 in./1,632 mm Depth: 28.5 in./723 mm Depth: 31.2 in./723 mm Height: 44.5 in./1,130 mm Height: 46 in./1,169 mm Weight: 530.6 lb./240.7 kg Weight: 564.2 lb./255.9 kg		Depth: 31.2 in./723 mm Height: 46 in./1,169 mm	
Base Configuration with BR Booklet Maker Finisher, C-fold/Z-fold Unit, and High Capacity Feeder	Width: 93 in./2,361 mm Depth: 28.5 in./723 mm Height: 44.5 in./1,130 mm Weight: 598.8 lb./271.6 kg		Width: 93 in./2,361 mm Depth: 31.2 in./723 mm Height: 46 in./1,169 mm Weight: 632.8 lb./287 kg	
System Certifications/Regulo	atory Compliances			
Certifications	To view the latest list of certifications, go to xerox .	com/OfficeCertifications		

Paper Handling	AltaLink® B8145	AltaLink® B8155	AltaLink® B8170
Single-Pass Duplex Automat	ic Document Feeder (DADF)		
Capacity ⁴	130 sheets		250 sheets
Speed (Up to)	82 ppm black-and-white (simplex) 141 ipm black-and-white (duplex)		135 ppm black-and-white (simplex) 270 ipm black-and-white (duplex)
Paper Sizes Sensed	3.4 x 4.9 in. to 11.7 x 17 in./85 x 125 mm to 297 x 43	32 mm	
Weights	16 lb. to 32 lb. bond/60 to 128 gsm		
Bypass Tray (Standard)			
Capacity ⁴	100 sheets		
Sizes	Custom Sizes: 3.5 x 3.9 in. to 12.6 x 52 in./89 x 98 m	nm to 320 x 1320 mm (SEF); Optional: Long Sheet F	eed Kit (Banner Printing)
Weights	16 lb. bond to 110 lb. cover/52 to 300 gsm, Long sh	eets/banners (>19 in./483 mm): 28lb Bond - 120lb I	ndex/106 - 220 gsm
Media Types	Bond Card Stock Card Stock Reloaded Custom Envelopes Glossy Card Stock Reloaded Heavyweight Card Stock Reloaded Heavyweight Glossy Card Stock Reloaded Heavyweight Glossy Card Stock Reloaded Heavyweight Glossy Card Stock Reloaded Hole Punched Labels Letterhead Lightweight Card Stock Reloaded Lightweight Glossy Card Stock Reloaded Lightweight Glossy Card Stock Reloaded Lightweight Glossy Card Stock Lightweight Card Stock Card Stock Card Stock Card Stock Card Stock Lightweight Card Stock		
Trays 1 and 2 (Standard)			
Capacity ⁴	520 sheets each		
Sizes	Tray 1: Custom Sizes: 5.5 x 7.2 in. to 11.7 x 17 in./14 Tray 2: Custom Sizes: 5.5 x 7.2 in. to 12 x 18 in./140		
Weights	16 lb. bond to 110 lb. cover/52 to 300 gsm		
Mediα Types	Bond Card Stock Card Stock Reloaded Custom Envelopes Glossy Card Stock Glossy Card Stock Reloaded Heavyweight Card Stock Reloaded Heavyweight Gard Stock Reloaded Heavyweight Glossy Card Stock Reloaded Heavyweight Glossy Card Stock Heavyweight Glossy Card Stock Reloaded Hole Punched Labels Letterhead Lightweight Lightweight Card Stock Lightweight Glossy Card Stock Reloaded Plain Plain-Reloaded Preprinted Recycled Transparencies		

Paper Handling (continued)	AltaLink® B8145	AltaLink® B8155	AltaLink® B8170
High Capacity Tandem Tray	(Available with all models)	·	
Capacity ⁴	Tray 3: 867 sheets Tray 4: 1,133 sheets		
Sizes	8.5 x 11 in./A4, JIS B5, Executive (7.25 x 10.5 in) LEF		
Weights	16 lb. bond to 110 lb. cover/52 to 300 gsm		
Media Types	Bond Card Stock Custom Glossy Card Stock Hole Punched Labels Letterhead Lightweight Card Stock Lightweight Glossy Card Stock Plain Preprinted		
Envelope Tray (Optional - Re	places Tray 1)		
Capacity ⁴	Up to 60 envelopes		
Sizes	#10 Commercial (9.25 x 4.125 in.)/Monarch, DL, C5 Custom Sizes: 3.9 x 5.8 in. to 6.4 x 9.5 in./98 x 148 mm to 162 x 241 mm		
Weights	20 lb. to 24 lb. bond/75 to 90 gsm		
High Capacity Feeder (HCF)	(Optional with all models)		
Capacity ⁴	3,000 sheets		
Sizes	Standard Sizes: 8.5 x 11 in. or 7.25 x 10.5 in./A4 or B5 LEF		
Weights	16 lb. bond to 110 lb. cover/52 to 300 gsm		
Total Capacity			
Device Total Capacity ⁴	High Capacity Tandem Tray Module: 3,140 sheets High Capacity Tandem Tray Module with High Capa	city Feeder: 6,140 sheets	

Finishing	AltaLink® B8145	taLink® B8155	AltaLink® B8170
Output Trays (Standard) (Du	ıal Offset Catch Trays not available with Integrated O	Office Finisher and limited to one with Office	Finisher and BR Finishers)
Stacking Tray Capacity ⁴	Dual Offset Catch Tray: Up to 250 sheets each Left Side Face-up Tray: Up to 100 sheets		
Integrated Office Finisher (C	Optional with AltaLink® B8145/B8155)		
Stacking Tray Capacity ⁴	500 sheets of 20 lb. bond/80 gsm – 8.5 x 11 in./A4 or 25	50 sheets of 20 lb. bond/80 gsm $- 11 \times 17$ in./A3	
Sizes	3.5 x 3.9 in. to 11.7 x 17 in./89 x 98 mm to 297 x 432 m	m	
Weights	16 lb. bond to 110 lb. cover/52 to 300 gsm		
Stapling	Single/Dual Position Auto-Stapling: 50 sheets maximum: Letter/A4/B5 size sheets (less than 30 sheets maximum: Legal/Tabloid/A3/B4 size sheets (le		
Office Finisher (Optional)			
Stacking Tray Capacity ⁴	2,000 sheets unstapled or 1,000 sheets single stapled or	750 sheets dual stapled (8.5 x 11 in./A4)	
Stacking Tray Sizes	8.3 x 7.2 in. to 11.7 x 17 in./210 x 182 mm to 297 x 432	mm	
Weights	16 lb. bond to 110 lb. cover/52 to 300 gsm		
Multiposition Stapling	50 sheets maximum: Letter/A4/B5 size sheets (less than 30 sheets maximum: Legal/Tabloid/A3/B4 size sheets (le		
Hole Punch (Optional)	North America: 2/3-hole punch Europe: 2/4-hole punch Optional: 4-hole "Swedish" punch		
Booklet Maker for Office Fin	isher (Score/Crease, Saddle-stitch Staple) (Optional)		
Top Tray Capacity ⁴	40 booklets (2-15 sheets per booklet – 20 lb./80 gsm or l	less)	
Sizes	Letter – 8.5 x 11 in./A4 SEF Legal – 8.5 x 14 in./B4 SEF Tabloid – 11 x 17 in./A3 SEF		
Saddle-Stitch Stapling	2-15 sheets/8-60 page booklet 16 lb. bond to 80 lb. cover/64 to 220 gsm		
Score/Crease	1-15 sheets/unstapled 16 lb. bond to 28 lb. bond/64 to 105 gsm		
Business Ready (BR) Finishe	r (Optional) (Requires Horizontal Transport Kit)		
Capacity ⁴	Offsetting Top Tray: 500 sheets Stacking Stapling Tray: 3,000 sheets unstapled or 100 sets (dual or 4-position stapling) 11 x 17 in., 8.5 x 14	4 in./A3 or 200 sets (single-position staple) 8.5 x	11 in./A4
Sizes	3.9 x 5.8 in to 12.6 x 19.2 in/100 x 148 mm x 320 x 488 7.25 x 10.5 in. to 12.6 x 19 in./182 x 203 mm to 320 x 4 7.25 x 10.5 in. to 11 x 17 in./B5 to A3 for stapling	, ,	
Weights	16 lb. bond to 110 lb. cover/52 to 300 gsm		
Stapling	Single and multiposition stapling Auto stapling (50 sheets maximum) – 24 lb./90 gsm Letter, Legal, Tabloid, A3, A4, B4, and B5 sizes supported		
Hole Punch	North America: 2/3-hole punch Europe: 2/4-hole punch Optional: 4-hole "Swedish" punch		
BR Booklet Maker Finisher (Optional) (Requires Horizontal Transport Kit)		
Capacity ⁴	Offsetting Top Tray: 500 sheets of 8.5 x 11 in./A4 unstag Stacking Stapling Tray: 1,500 sheets of 8.5 x 11 in./11 x 17 in./A4/A3 unstapled 200 stapled sets of 8.5 x 11 in./A4 (single-position stapli dual or 4-position stapling) or 100 stapled sets of 11 x 1	or ng or	
Sizes	3.9 x 5.8 in to 12.6 x 19.2 in/100 x 148 mm x 320 x 488 7.25 x 10.5 in. to 12.6 x 19 in./182 x 203 mm to 320 x 4 7.25 x 10.5 in. to 11 x 17 in./B5 to A3 for stapling		
Weights	16 lb. bond to 110 lb. cover/52 to 300 gsm		
Stapling	Single and multiposition stapling Auto stapling (50 sheets maximum) – 24 lb./90 gsm Letter, Legal, Tabloid, A3, A4, B4, and B5 sizes supported		
Hole Punch	North America: 2/3-hole punch Europe: 2/4-hole punch Optional: 4-hole "Swedish" punch		
Booklet Maker	Saddle-stitch 2 to 16 sheets (7 sheets at 106 to 176 gsm Bi-fold up to 5 sheets Letter, Legal, Tabloid, A3, A4 supported	n coated or 5 sheets at 177 to 220 gsm coated)	

Finishing (continued)	AltaLink® B8145	AltaLink® B8155	AltaLink® B8170
C-fold/Z-fold Unit (Optional	with BR Finisher and BR Booklet Maker Finisher)		
Types	C-fold, Z-fold, and Z-half-fold		
Capacity ⁴	40 sheets		
Sizes	C-fold and Z-fold: Letter – 8.5 x 11 in./A4 SEF only Z-half-fold: Tabloid – 11 x 17 in./A3 only		
Weights	16 lb. to 24 lb. bond/64 to 90 gsm		
Output Trays	Envelope Tray: C-fold, Z-fold, and Tri-fold Stacker Tray or Top Tray: Z-half-fold		
Convenience Stapler (Option	nal - Includes Work Surface ^s)		
Capacity ⁴	50-sheet stapling 5,000 staples Requires separate power outlet		
Сору	AltaLink® B8145	AltaLink® B8155	AltaLink® B8170
First-Copy-Out Time (from platen/warmed up)	As fast as 4.4 seconds	As fast as 3.7 seconds	As fast as 3.2 seconds
Sides (input:output)	1-1, 1-2, 2-2, 2-1		
Quantity	1 to 9,999		
Resolution (max)	Up to 600 x 600 dpi		
Reduction/Enlargement	Variable zoom from 25% to 400% in 1% increment	ts	
Concurrency	Program-ahead to allow the job to be queued while	the initial job is processed (Copy, Print, Fax, and Scan))
Copy Features	Annotation and Bates [™] stamping Authentication for Services Auto Paper Select Auto Reduction & Enlargement (To fit selected paper size) Auto Tray Switching Automatic 2-sided/Duplex Booklet Creation Build Job (Enables page-level programming and also lets you proof each section or delete the last section as the job is built) Collation Covers (Front only, front and back, back only, printed inside and out: Blank or Printed) Dividers (blank) Edge Erase Features Help (Intuitive text and graphic descriptions) ID Card Copy Image Quality Adjustments Image Shift (with Auto Center option) Imaging Security Invert Image (negative or mirror image) Large Job Interrupt Multi-up (up to 15 columns by 15 rows) Sample Set Save Job Settings Stapling Touchless Workflow Accelerators Transparencies		

Print	AltaLink® B8145	AltaLink® B8155	AltaLink® B8170
Resolution (up to)	1200 x 2400 dpi		
Print Features	LAN Fax (requires optional Fax Kit) Long Sheet/Banner Layout/Watermark N-up (up to 16 pages per sheet) Paper Selection by Attribute Sample Print From Cloud Repositories (Dropl Saved Job Secure Print with Timed Deletion Special Pages (exception page progr Store and Recall Driver Settings	tion (Standard, Enhanced, High)) or, Print ID in margins on the first page only or all p Set	
Print from USB	Allows walk-up printing from Type A USB port on the front panel Supports direct printing from a computer via Type B USB port Supported file formats: PDF, JPEG, TIFF, PS, PCL Color jobs can be printed as black-and-white		
Operating Systems	Windows 10 (32 and 64 bit) Windows 11 (32 and 64 bit) MacOS 10.13.x, 10.14.x, 10.15.x, 11. Red Hat Linux 6.x, 7.x, 8.x Ubuntu Linux 20.04.x, 22.04.x SuSe Linux Server 12.3-13.x, 15.x MS Windows 2012 Server (32 and 6 MS Windows 2016 Server (32 and 6 MS Windows 2019 Server (32 and 6 MS Windows 2022 Server (32 and 6 RS Windows 2022 Server (32 and 6 RS Windows 2022 Server 7.x, 8.x SuSe Linux Server 7.x, 8.x	4 bit) 4 bit) 4 bit)	
Network Protocols	·		00, IPv4/IPv6, WSD
Font Capability	PCL: 93 scalable fonts, line printer, a	nd bitmap font (including Cyrillic font support) Po	stScript 3: 173 Type 1 fonts, 2 Multiple Master fonts
Xerox® Global Print Driver®	A truly universal print driver that lets IT administrators install, upgrade, and manage non-Xerox and Xerox® Devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls and simplifying print services management. Support for Microsoft Universal Print.		
Xerox® Pull Print Driver	driver. The Xerox® Pull Print Driver ex		a single driver in a Pull Print environment. Uses a single queue and single ng assets. IT administrators no longer need to manage and configure d others.
Unified Address Book for Fax	ess Book for Fax, Email, and Scan to		
Features	Services supported: Fax, Email, Scan Maximum contacts: 5,000 Contacts: Supports 1 or more destin Favorites for quick access of all servic	ations	

Scan	AltaLink® B8145	AltaLink® B8155	AltaLink® B8170
Concurrency	Scan while the system is printing, concurrent jobs)	, copying, or while it is transferring scan to network	or fax jobs (priority is for return of scanned originals and printing
Input Speed (up to)	82 ppm black-and-white and cold 141 ipm black-and-white and col		135 ppm black-and-white and color (simplex) 270 ipm black-and-white and color (duplex)
Resolution	150 x 150 dpi to 600 x 600 dpi		
Bit Depth	1-bit (black-and-white), 8-bit (gra	yscale), 24-bit (color)	
Maximum Scan Area	11 x 17 in./A3		
Scan Template Management	Support 250 scan templates Create Xerox® CentreWare® IS sc	an templates and share via device cloning to other	multifunction printers' confirmation sheet options
Network Protocols	SFTP, FTP, SMB, HTTP, HTTPS		
File Compression		MMR compression – single or multiple pages)	JBIG Arithmetic Compression, Deflate (for black-and-white and within
Document Management Fields (Metadata)	Metadata field consists of a fiel	rk Scan to File Templates: adata fields per network scan to file templates and d name, default value, and other configurations er interface for variable data input	unlimited fields within the template –
Scan Features	Auto Background and Shadow Su Bound Originals Compression Quality/File Size Cor Edge Erase Imaging Security Mixed Size Originals Original Type (Photo and Text, Ph Reduction/Enlargement Scan Build Job Scan Preview Single Touch Scan buttons (up to Size for Size (for mixed size origin Touchless Workflow Accelerators TWAIN Support/WIA 2.0 Support	ntrol noto, Text, Map, Newspaper/Magazine) 10) als)	
Scan to Email (Standard)			
Scan Features	Auto send to self Email signatures (6 lines each c Email signing (requires Smart C Scan to Email S/MIME Encrypti Touchless Workflow Accelerator	Card option) on	onfigurable), email Embedded Web Server confirmation sheet options
Directory Access	Address list via LDAP (Windows A	active Directory, Exchange, Notes, Domino), Device	Address Book
Scan To			
Standard Features	Scan to Email Scan to Home Scan to Mailbox Scan to Network (using Secure FI Scan to Network Folder (using Se Scan to PC/Server Client (SMB or Scan to PC via USB port Scan to USB	cure FTP/HTTP/HTTPS)	
Optional Features	Scan to Cloud Repositories (Drop	box, OneDrive, and Google Drive)	
Workflow Scanning (Option	al)		
Scanning Software	Autostore v7 eCopy ShareScan v5.2 eCopy ScanStation v5.2		
Scanning Apps and Xerox App Gallery		Microsoft OneDrive, Microsoft Office 365™, Box®, Xo in the Xerox App Gallery: xerox.com/AppGallery	erox® Workplace Mobile App (iOS/Android)

Security	AltaLink® B8145	AltaLink® B8155	AltaLink® B8170
Features	Audit Log		
-	 Audit Log Cisco® Identity Services Engine (ISE) compatible Configuration Watchdog (Monitor and remediate 802.1x Admin Password Reset Audit Log Automatic Software Upgrade Email Alerts FIPS 140-3 Hold All Jobs Immediate Job Overwrite® Installation Policies Trellix Embedded Control* PII - Login Name PostScript Passwords Remote Services Enablement Remote Start (Mopria® or AirPrint™) Remote Start (TWAIN) Reprint Saved Jobs Scan to Mailbox (Internal storage) Scheduled Disk Overwrite® Secure Passcode Length Secure Print Device Policies SIEM SNMP System Timeout USB (Print from USB) USB (Scan to USB) USB Port Management User Data Encryption Expanded Authentication Digitally signed PDF (when using Smart Card au Encrypted and authentication to SMTP server fo Encrypted Password-protected PDF (when using FIPS 140-3, 256 bit Hard Disk Encryption, TLS, II Immediate Image Overwrite/Securely delete jot Local Authentication (internal database) Network authentication to access device and/or Windows server 2012), NDS, LDAP authentication Secure Data Secure Print (up to 10 digit PIN or Network Auth Smart Card authentication – 144k CAC/PIV Card Expanded Authorization 	thentication) r Scan to Email Email and Network Scan Templates only) PS, HTTPS, SFTP, SNMPv3 ss using approved algorithms9 device services via Kerberos (UNIX/Windows Serve on al), includes sanitation of unused area of disk9 entication)	
	Secure Data Secure Print (up to 10 digit PIN or Network Auth Smart Card authentication – 144k CAC/PIV Card Expanded Authorization	entication)	
	Authorization per user per service SA access based on network credentials Secure Network Access User Permissions required to access Print and Pri Full System Common Criteria certified by NIAP un Hide Print Job Names		
	Imaging Security IP Filter, IPsec, IPv6, TLS V1.1, V1.2, V1.3, SNMP V Trellix Embedded Control* (whitelisting), Trellix Int Port disablement including USB ports Security Dashboard Security Information and Event Management (SII WPA2 and WPA3 are supported by the Dual Band	egrity Control" (optional) EM) support for Trellix Enterprise Security Manager	*, LogRhythm, and Splunk
Xerox® Integrated RFID Card Reader (Optional kit)	Integrated support for most industry security cards the multifunction printer panel		ifunction printer card readers in

AltaLink® B8145

Compatibility ITU (CCTT) group 3; Various Xerox® Business Innovation Partner Solutions Maximum Scon Area Tax 5 End Fectures One or Two-sided Sconning (up to 11 x 17 in/A3) Add to Send Ibit (200 numbers maximum) Build dobt (nortines, Debty Send Experient time) Driginal Type (photo, text or photo and text) Fax Print Features One or Two-sided Printing, Staple, Secure Print Transmission Resolution Fine: 200 x 200 dpi Standard: 200 x 100 dpi Wall-up Fax Features (Optionals Customer-Installable – 1 and 2 lines) Compatibility ITU (CCTT) Group 3 Speed/Moderns One or Two V-34 moderns: 33,600 bps, Less than 4 seconds per page transmission time Compression/Speed Mil/G3, Mil/G3, Mil/RSG3, Mil/RSG3, Bil/GSG3 Resolution Wall-up Send. Wall-up Send. Wall-up Send. Wall-up Send. Standard: 200 x 100 dpi Fine: 200 x 200 dpi Superfine: 600 x 600 dpi Fine: 200 x 200 d	rux	Attubility Bo 143 Attubility Bo 173 Attubility Bo 170		
Maximum Scan Area 11 x 17 In A3 One or Two-sided Scanning (up to 11 x 17 in A3) Add to Send I str (200 numbers maximum) Build Job, Fowrites, Deby Send (specific time) Original Type (photo, text or photo and text) Fax Print Features One- or Two-sided Printing, Stople, Secure Print Transmission Resolution Superfine: 400 x 200 dpi (Scan at 600 x 600 dpi) Fine: 200 x 200 dpi (Scan at 600 x 600 dpi) Standard: 200 x 100 dpi Fine: 200 x 200 dpi Superfine: 600 x 600 dpi) Fine: 200 x 200 dpi Superfine: 600 x 600 dpi Fine: 200 x 200 dpi Superfine: 600 x 600 dpi Fine: 200 x 200 dpi Superfine: 600 x 600 dpi Fine: 200 x 200 dpi Superfine: 600 x 600 dpi Fine: 200 x 200 dpi Superfine: 600 x 600 dpi Fine: 200 x 200 dpi Superfine: 600 x 600 dpi Fine: 200 x 200 dpi Superfine: 600 x 600 dpi Fine: 200 x 200 dpi Superfine: 600 x 600 dpi Receive: Accepts all sizes Fax Send Features Auto-fax Transmission Reduction Automatic Amenny Recend Batch Send (up to memory capacity) Deloy Start, Bulld Job, Foxorites Device Address Book (up to 5000 contacts) LAN Fax (fax from print driver) Page-by-page Job Status at the Mochine PSTN Fax Fax Receive Features And Answer Delay One- or Two-sided Printing Output Transfer Secure Receive Stapled or Unstapled Up to 200 Texsword Foetced Moliboxes Fax Forward Forward to Femilia of SMB Location Fax Forward to Femilia of SMB Location Fax Forward to Femilia of SMB Location Fax Reports Automatic Memory Report, Molibox Report, Molibox Report, Molibox Report, Molibox Report, Molibox Report, Driectory Access Up to 24 attempts (per country requirements) 1 to 25 minute intervals 1 to 25 minute intervals	letwork Server Fax Features			
Fax Send Features One- or Two-sided Scanning (up to 11 x 17 in./A3) Add to Send Lat 1200 numbers maximum? Build Job Franchise, Deby Send (Specific Lime) Original Type (photo, text or photo and text) Fax Print Features One- or Two-sided Printing, Staple, Secure Print Transmission Resolution Superfine: 400 x 200 dpi (Scan at 600 x 600 dpi) Fine: 200 x 200 dpi (Scan at 600 x 600 dpi) Fine: 200 x 200 dpi (Scan at 600 x 600 dpi) Fine: 200 x 200 dpi (Scan at 600 x 600 dpi) Fine: 200 x 200 dpi (Scan at 600 x 600 dpi) Fine: 200 x 200 dpi (Scan at 600 x 600 dpi) Speed/Modems One or Two V34 modems: 33 600 bps. Less than 4 seconds per page transmission time Compression/Speed MH/I/G3, MR/I/G3, MR	Compatibility	ITU (CCITT) group 3; Various Xerox® Business Innovation Partner Solutions		
Add to Send List (200 numbers maximum) Bull do No, Franches, Deby Send (Specific time) Original Type (photo, text or photo and text) Fax Print Features One- or Two-sided Printing, Staple, Secure Print Transmission Resolution Fine: 200 x 200 dpi (Scan at 600 x 600 dpi) Standard, 200 x 100 dpi Walkup Fax Features (Optional; Customer-Installable – 1 and 2 lines) Compatibility ITU (CCITT) Group 3 Speed/Modems One- or Two V.34 modems: 33,600 bps. Less than 4 seconds per page transmission time Compression/Speed MiH/G3, MR/G3, MMR/SG3, JBEG/SG3 Resolution Walkup Send: Standard: 200 x 100 dpi Fine: 200 x 200 dpi Receiver: Accepts all states Standard: 200 x 100 dpi Fine: 200 x 200 dpi Receiver: Accepts all states Automatic Cover Sheets Automatic Cover Sheets Automatic Cover Sheets Automatic Memory Resend Batch Send (up to memory capacity) Deby State Julid Joh Franches Device Address Book (up to 5,000 contacts) LAN Fax (fax from print driver) Page-by-page Job Status at the Machine PSTN Fox Fax Receive Features Auto Answer Deby One- or Two-sided Printing Output Tray Selection Receiver Printint Mode – Manual (size, margin, stock, header)/Auto Receiver Timestamp Secure Receive Stapled or Unstappled Up to 200 Passward Protected Mailboxes Fax Reports Activity, Diel Directory, Group Directory, Transmission Confirmation, Pending Fax. Options Report, On-demand Overwrite* Report, Mailbox Report, Broadcast Report United the Confirmation of Page Post Mail Contacts Standard Report One- or Two-sided Printing Output Tray Selection Fax Forward Fox Reports Activity, Diel Directory, Group Directory, Transmission Confirmation, Pending Fax. Options Report, On-demand Overwrite* Report, Mailbox Report, Broadcast Report United the Up to 14 attempts (per country requirements) 3 to 25-minute intervols	Maximum Scan Area	11 x 17 in./A3		
Transmission Resolution Superfine: 400 x 200 dpi Scan at 600 x 600 dpi Fine: 200 x 200 dpi Standard: 200 x 100 dpi Fine: 200 x 200 dpi Standard: 200 x 100 dpi Fine: 200 x 200 dpi Standard: 200 x 100 dpi Fine: 200 x 200 dpi Standard: 200 x 100 dpi Fine: 200 x 200 dpi Standard: 200 x 100 dpi Fine: 200 x 200 dpi Standard: 200 x 100 dpi Fine: 200 x 200 dpi Standard: 200 x 100 dpi Fine: 200 x 200 dpi Standard: 200 x 100 dpi Fine: 200 x 200 dpi Standard: 200 x 100 dpi Fine: 200 x 200 dpi Standard: 200 x 100	Fax Send Features	Add to Send List (200 numbers maximum)		
Fine: 200 x 200 dpi Standard: 200 x 100 dpi Walk-up Fax Features (Optional); Customer-Installable – 1 and 2 lines) Compatibility	Fax Print Features	One- or Two-sided Printing, Staple, Secure Print		
Speed/Modems	Transmission Resolution	Fine: 200 x 200 dpi		
Speed/Modems	Walk-up Fax Features (Optio	nal; Customer-Installable – 1 and 2 lines)		
Compression/Speed MH/G3, MR/G3, MB/G5, JBIG/SG3 Resolution Walk-up Send: Standard: 200 x 100 dp! Fine: 200 x 200 dp! Superfine: 600 x 600 dp! Receive: Accepts all sizes Fax Send Features Auto Fax Transmission Reduction Automatic Cower Sheets Automatic Memory Resend Batch Send (up to memory capacity) Deleys Start, Build Job, Favorites Device Address Book (up to 5,000 contacts) LAN Fax (Kax from print driver) Page-by-page Job Status at the Machine PSTN Fax Fax Receive Features Auto Answer Delay One- or Two-sided Printing Output Tray Selection Receive Print Mode – Manual (size, margin, stock, header)/Auto Receive Print Mode – Manual (size, margin, stock, header)/Auto Receive Timestamp Secure Receive Stapled or Unstapled Up to 200 Password Protected Mailboxes Fax Forward Forward to Email or SMB Location Fax Forward on Receive Only Activity, Dial Directory, Group Directory, Transmission Confirmation, Pending Fax, Options Report, On-demand Overwrite® Report, Mailbox Report, Broadcast Report Utilizes the Unified Address Book Group fax available Up to 14 attempts (per country requirements) 1 to 25-minute intervals	Compatibility	ITU (CCITT) Group 3		
Resolution Walk-up Send: Standard: 200 x 100 dpl Fine: 200 x 200 dpl Superfine: 600 x 600 dpl Receive: Accepts all sizes Automatic Cover Sheets Automatic Cover Sheets Automatic Memory Resend Batch Send (up to memory capacity) Delay Start, Build Job, Fowrites Device Address Book (up to 5,000 contacts) LAN Fax (fax from print driver) Page-by-page Job Status at the Machine PSTN Fox	Speed/Modems	One or Two V.34 modems: 33,600 bps. Less than 4 seconds per page transmission time		
Standard: 200 x 200 dpi Superfine: 600 x 600 dpi Fine: 200 x 200 dpi Superfine: 600 x 600 dpi Receive: Accepts all sizes	Compression/Speed	MH/G3, MR/G3, MMR/SG3, JBIG/SG3		
Automatic Cover Sheets Automotic Memory Resend Batch Send (up to memory capacity) Delay Start, Build Job, Favorites Device Address Book (up to 5,000 contacts) LAN Fax (fax from print driver) Page-by-page Job Status at the Machine PSTN Fax Fax Receive Features Auto Answer Delay One- or Two-sided Printing Output Tray Selection Receive Print Mode – Manual (size, margin, stock, header)/Auto Receive Print Mode – Manual (size, margin, stock, header)/Auto Receive Timestamp Secure Receive Stapled or Unstapled Up to 200 Password Protected Mailboxes Fax Forward Forward to Email or SMB Location Fax Forward on Receive Only Fax Reports Activity, Dial Directory, Group Directory, Transmission Confirmation, Pending Fax, Options Report, On-demand Overwrite® Report, Mailbox Report, Broadcast Report Directory Access Utilizes the Unified Address Book Group fox available Up to 14 attempts (per country requirements) 1 to 25-minute intervals	Resolution	Standard: 200 x 100 dpi Fine: 200 x 200 dpi Superfine: 600 x 600 dpi		
One- or Two-sided Printing Output Tray Selection Receive Print Mode – Manual (size, margin, stock, header)/Auto Receive Timestamp Secure Receive Stapled or Unstapled Up to 200 Password Protected Mailboxes Fax Forward Forward to Email or SMB Location Fax Forward on Receive Only Fax Reports Activity, Dial Directory, Group Directory, Transmission Confirmation, Pending Fax, Options Report, On-demand Overwrite ⁹ Report, Mailbox Report, Broadcast Report Utilizes the Unified Address Book Group fax available Auto Redial Up to 14 attempts (per country requirements) 1 to 25-minute intervals	Fax Send Features	Automatic Cover Sheets Automatic Memory Resend Batch Send (up to memory capacity) Delay Start, Build Job, Favorites Device Address Book (up to 5,000 contacts) LAN Fax (fax from print driver) Page-by-page Job Status at the Machine		
Fax Forward on Receive Only Fax Reports Activity, Dial Directory, Group Directory, Transmission Confirmation, Pending Fax, Options Report, On-demand Overwrite® Report, Mailbox Report, Broadcast Report Utilizes the Unified Address Book Group fax available Auto Redial Up to 14 attempts (per country requirements) 1 to 25-minute intervals	Fax Receive Features	One- or Two-sided Printing Output Tray Selection Receive Print Mode – Manual (size, margin, stock, header)/Auto Receive Timestamp Secure Receive Stapled or Unstapled		
Broadcast Report Directory Access Utilizes the Unified Address Book Group fax available Auto Redial Up to 14 attempts (per country requirements) 1 to 25-minute intervals	Fax Forward			
Group fax available Auto Redial Up to 14 attempts (per country requirements) 1 to 25-minute intervals	Fax Reports			
1 to 25-minute intervals	Directory Access			
Auto Resend Up to 5 attempts	Auto Redial			
	Auto Resend	Up to 5 attempts		

AltaLink® B8155

AltaLink® B8170

Device Management	
Administrative Protocols	DHCP, BOOTP, SNMP, SLP® v2, HTTP, HTTPS, DHCP Autonet, TLS, NTP, DNS, SMB, SMTP/POP3, WSD, LDAP, Multicast DNS
Management Support	SNMP Version 1. SNMP Version 2c and SNMP Version 3 trap over TCP/IP and IP
	MIB access (IETF-MIBII RFC 1213) Host Resources MIB RFC 2790, Printer MIB RFC 3805, PWG-Imaging-System- Power MIB, Fleet Orchestrator, Configuration Watchdog, Xerox® Easy Assist App
Xerox® CentreWare® Web	A Web-based server application for network administrators that permits Web browser-based device management from any workstation, whether running on Windows, UNIX, or any other operating system:
	Works with any SNMP-managed printer from any manufacturer
	Remote configuration of SNMP v3 Provides help with device discovery and installation, health checks and troubleshooting, and device upgrades, as well as basic accounting and
	asset management • Requires Windows 7 and Internet Explorer 6.0 and higher
	Auto-detect Xerox® CentreWare® Web server and download configurations files for touchless remote installation
Xerox® Device Manager	Xerox® Device Manager collects and manages the data that drives fact-based decisions for your enterprise device management environment. It is a single tool to install print queues and configure, manage, monitor, and report on both networked and locally connected devices – regardless of vendor – across your enterprise. Xerox® Device Manager provides: • Device monitoring and troubleshooting • Remote configuration of SNMP v3 • Extensive reporting and discovery of new devices
	Usage collection, chargeback, and billing capabilities Auto-detect Xerox® Device Manager server and download configurations files for touchless remote installation
Xerox® Workplace Cloud	Remote management to set and audit device configuration data with Xerox® Workplace Cloud, eliminating the need for an on-site server
Fleet Orchestrator	Fleet Orchestrator feature offers the ability to create a group of devices that share information with each other via a secure peer-to-peer connection.
	The following data can be shared: Software update files, clone files, and 1-Touch App files. Auto-assembly feature allows a new AltaLink® to automatically set itself on the network and configure.
Novell NDPS/NEPS	Server gateway application: centralized management tool
Xerox® Device Types	Provides built-in process intelligence that allows the printing of barcodes on any appropriately configured PostScript printer in specific versions of SAP
for SAP R/3 Intelligent Barcode Utility (optional)	environment and within Latin-1 (ISO8859-1) SAP system code pages only. Used in conjunction with Xerox® PostScript Device Types for SAP environment and Xerox® Font Center Barcode Fonts. For more information, visit office.xerox.com/Software-Solutions
Xerox® Device Types for SAP Environment	Xerox, together with SAP through our Gold-level membership in the SAP Printer Vendor Program, provides seamless connectivity between SAP systems and your Xerox® Printers and Multifunction Printers. As an SAP customer, you benefit from having SAP-certified Xerox® Device types available right from SAP's online delivery model. SAP-certified device types for Xerox® Printers and Multifunction Printers are available to download. office.xerox.com/Software-Solutions
Xerox® Embedded Web Server – Integrated Device Web Pages Provided by the Device	
Device Status	Web server embedded in Network Controller: • Tray status/contents • Consumables status
	Alerts Remote Control Panel
Job Submission	Print-ready files: PS, PCL, TIFF, PDF, JPG, TXT, PRN
Jub Subminission	Output feature selection (2-sided, collate, orientation, staple, hole punch, folding, output destination) Delivery options (Immediate, sample set, delay and secure, Save job or reprint)
Device Administration	Allows simple, remote installation setting of configuration options and management of the device, Fleet Orchestrator, Security Dashboard
Browsers	Microsoft Edge version 88+ Microsoft Chromium Edge version 79+ Mozilla Firefox 91.9.0, 100.0 Safari 13.1.2, 14.1.2, 15.4 Opera 2020, 2021 Google Chrome version 80.0.x+
Support	Install print/scan drivers and online support available via support.xerox.com
Languages Supported	International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Russian, Simplified Chinese, Korean, Japanese, Arabic
Remote Services	
Xerox® Automatic Meter Readings (AMR)	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® Device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.
Xerox [®] Automαtic Supplies Replenishment (ASR)	Automatically orders supplies for output devices from Xerox based on actual usage, eliminating the need to manually manage supplies inventory.
Accounting	
Xerox® Standard Accounting	
Tracking	Copy, Print, Fax, Scan, and Email usage
Accounting	Up to 2,497 User Accounts (User ID) Up to 500 General Accounts (Client) Up to 498 Group Accounts (Department)
Features	 Administrator can manage the feature via the Web User Interface or device control panel in tools. Administrator can import or export User Accounts, Group Accounts, General Accounts, and User Limits via an industry-standard CSV file.

Accounting Options – Network Accounting (Allows central server to manage all accounting) • Enhanced network accounting with up-to-the-minute data on how the system is being used • Comprehensive management and enterprise-scale tracking and reporting of device usage of copy, print, scan, and server fax • Numerous solutions are available through Xerox Alliance Partners. For details, visit www.xerox.com • Security enhancements with the addition of HTTPS protocol support • Device requests account authentication from third-party server enabling larger databases of users and accounts • Accept Authentication Login at the control panel and pass to third-party Networking Account • Interface with third-party accounting terminal for accounting user interface **Supplies** Description Yield Toner Cartridge⁶ Black 52,000 pages Transfer Belt Cleaner 1 Assembly 160,000 pages Second Bias Transfer Roll 200,000 pages 1 Assembly Staple Cartridges For BR Finisher, Integrated Office Finisher, Office Finisher, and Convenience Stapler (1 cartridge per carton) 5,000 each cartridge For BR Booklet Maker (1 cartridge per carton) 5,000 each cartridge For Office Finisher Booklet Maker (8 cartridges per carton) 2,000 each cartridge For Integrated Office Finisher, Office Finisher, BR Finisher, and Convenience Stapler (3 refills per carton) Staple Refills 5,000 each refill Xerox® Smart Kit® Drum Cartridge7 1 Cartridge 200,000 pages **Waste Toner Container** 1 Cartridge (AltaLink® B8145/8155) 121,000 pages w/o Suction Filter Waste Toner Container 1 Cartridge (AltaLink® B8170) 121,000 pages with Suction Filter9

Return spent imaging supplies through the Xerox® Green World Alliance® collection/reuse/recycling program. For more information, visit www.xerox.com/About-Xerox/Recycling.

For more information, visit us at www.xerox.com/Office



¹ Declared in accordance with ISO/IEC 24734.

 $^{^{2}}$ Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis

³ Not available in all geographies.

⁴ Paper capacities are based on 20 lb./75 gsm stock; capacities will vary with different weight stocks.

⁵ Sold separately in some geographies.

⁶ Average standard pages. Declared in accordance with ISO/IEC 19752. Toner yield can vary due to many factors, including but not limited to image area coverage, image content, media size, media orientation, run mode, application types, monthly print volumes, and image quality set-points.

 $^{^{7}}$ Average drum yield is based on a run length of 5 pages of 8.5 x 11 in./A4 LEF pages, with a split of 35% color/65% black-and-white pages.

⁸ Waste Toner Container yield will vary depending on the image type, area coverage %, and job run length.

⁹ With optional hard drive.

^{*} Trellix DXL formerly known as McAfee® DXL, Trellix Embedded Control Whitelisting formerly known as McAfee® Embedded Control Whitelisting,
Trellix ePolicy Orchestrator® formerly known as McAfee® ePolicy Orchestrator®, Trellix ESM formerly known as McAfee® ESM, Trellix Integrity Control formerly
known as McAfee® Integrity Control, Trellix Enterprise Security Manager formerly known as McAfee® Enterprise Security Manager. Trellix brand name will be
reflected in future firmware releases.