XEROX

ISO/IEC 19752 Yield Test Report

USE GENUINE XEROX SUPPLIES MADE FOR EACH OTHER

Phaser 3450 Toner Cartridge

Declaration of Yield:

Published Cartridge Yield: 5,000 standard pages
Declared yield value in accordance with ISO/IEC 19752

Average:	5,365
Standard Deviation:	342
90% Lower Confidence:	5,153

"Customer Report, compliant with ISO/IEC 29142"

	Start	End
Date Tested:	21-Jul-2005	22-Jul-2005

Number of Cartridges used in testing:	9
Number of Cartridges used in calculations:	9
Type of Cartridge:	All-in-ine
Shake Procedure Used?	Yes
Print mode:	Continuous (500pages/job)
Number of engines used in testing:	3
Media Used:	Kyesung paper
Paper Weight:	75gsm
Paper Size:	A4
Paper feed orientation:	Short edge feed (SEF)
Computer Model:	M5950 (Samsung)
Driver Version:	OS 0.99.1, Engine 0.5.5/OS 0.99.4, Engine 0.5.6
Operating System:	Windows XP
Application Software:	Adobe Acrobat Professional 6.01
Test Page Version:	Version 3.2
Power (off/on) everyday?	Yes

Cartridge	Printer	Temperature (°C)			Humidity (%RH)			Cartridge	Included
Serial Number	Serial Number	Avg.	Max	Min	Avg.	Max	Min	Yield	in calc.
Not recorded	Not recorded	24.5	25.0	24.0	46.0	49.0	43.0	5,912	y
Not recorded	Not recorded	24.5	25.0	24.0	46.0	49.0	43.0	5,735	y
Not recorded	Not recorded	24.5	25.0	24.0	46.0	49.0	43.0	5,735	y
KRE1JC9602640JSH45Y7C0570	BE27B1EY500016V	24.5	25.0	24.0	46.0	49.0	43.0	5,109	y
KRE1JC9602640JSH45Y7C0575	BE27B1EY500020X	24.5	25.0	24.0	46.0	49.0	43.0	5,281	y
KRE1JC9602640JSH45Y7C0564	BE27B1EY500018T	24.5	25.0	24.0	46.0	49.0	43.0	4,951	y
KRE1JC9602640JSH45Y7C0578	BE27B1EY500015W	24.5	25.0	24.0	46.0	49.0	43.0	5,122	y
KRE1JC9602640JSH45Y7C0296	BE27B1EY500017L	24.5	25.0	24.0	46.0	49.0	43.0	5,309	y
KRE1JC9602640JSH45Y7C0584	BE27B1EY500021N	24.5	25.0	24.0	46.0	49.0	43.0	5,130	y

Comments: