



# ISO/IEC 19752 Yield Test Report



## Phaser 3450 Toner Cartridge

Declaration of Yield:

**Published Cartridge Yield: 5,000 standard pages**  
**Declared yield value in accordance with ISO/IEC 19752**

Average: 5,365  
 Standard Deviation: 342  
 90% Lower Confidence: 5,153

**Date Tested:**                      **Start**              **End**  
    21-Jul-2005    22-Jul-2005

Number of Cartridges used in testing: 9  
 Number of Cartridges used in calculations: 9  
 Type of Cartridge: All-in-one  
 Shake Procedure Used? Yes  
 Print mode: Continuous (500pages/job)  
 Number of engines used in testing: 3  
 Media Used: Kyesung paper  
 Paper Weight: 75gsm  
 Paper Size: A4  
 Paper feed orientation: Short edge feed (SEF)  
 Computer Model: M5950 (Samsung)  
 Driver Version: OS 0.99.1, Engine 0.5.5/OS 0.99.4, Engine 0.5.6  
 Operating System: Windows XP  
 Application Software: Adobe Acrobat Professional 6.01  
 Test Page Version: Version 3.2  
 Power (off/on) everyday? Yes

Cartridge Serial Number	Printer Serial Number	Temperature (°C)			Humidity (%RH)			Cartridge Yield	Included in calc.
		Avg.	Max	Min	Avg.	Max	Min		
Not recorded	Not recorded	24.5	25.0	24.0	46.0	49.0	43.0	5,912	y
Not recorded	Not recorded	24.5	25.0	24.0	46.0	49.0	43.0	5,735	y
Not recorded	Not recorded	24.5	25.0	24.0	46.0	49.0	43.0	5,735	y
KRE1JC9602640JSH45Y7C0570	BE27B1EY500016V	24.5	25.0	24.0	46.0	49.0	43.0	5,109	y
KRE1JC9602640JSH45Y7C0575	BE27B1EY500020X	24.5	25.0	24.0	46.0	49.0	43.0	5,281	y
KRE1JC9602640JSH45Y7C0564	BE27B1EY500018T	24.5	25.0	24.0	46.0	49.0	43.0	4,951	y
KRE1JC9602640JSH45Y7C0578	BE27B1EY500015W	24.5	25.0	24.0	46.0	49.0	43.0	5,122	y
KRE1JC9602640JSH45Y7C0296	BE27B1EY500017L	24.5	25.0	24.0	46.0	49.0	43.0	5,309	y
KRE1JC9602640JSH45Y7C0584	BE27B1EY500021N	24.5	25.0	24.0	46.0	49.0	43.0	5,130	y

Comments: