



ISO/IEC 19752 Yield Test Report



Phaser 3500 Toner Cartridge (Standard Capacity)

Declaration of Yield:

Published Cartridge Yield: 6,000 standard pages
Declared yield value in accordance with ISO/IEC 19752

Average: 6,499
Standard Deviation: 4
90% Lower Confidence: 6,497

Date Tested: Start End
25-May-2005 5-Aug-2005

Number of Cartridges used in testing: 9
Number of Cartridges used in calculations: 9
Type of Cartridge: All-in-one
Shake Procedure Used? Yes
Print mode: Continuous (500pages/job)
Number of engines used in testing: 3
Media Used: Samsung Premium (75gsm)
Paper Weight: 75gsm
Paper Size: A4
Paper feed orientation: Short edge feed (SEF)
Computer Model: M5950 (Samsung)
Driver Version: 0.61 (PCL6. Phaser 3500)
Operating System: Win_XP
Application Software: Adobe Acrobat Professional 6.01
Test Page Version: Version 4.0
Power (off/on) everyday? Yes

Cartridge Serial Number	Printer Serial Number	Temperature (°C)			Humidity (%RH)			Cartridge Yield	Included in calc.
		Avg.	Max	Min	Avg.	Max	Min		
520010	PRS-LV-012	24.5	25.0	24.0	45	47	42	6,500	y
520008	PRS-LV-014	24.5	25.0	24.0	45	47	42	6,500	y
520001	PRS-HV-008	24.5	25.0	24.0	48	50	45	6,500	y
KRE1JC9603398FDJ78Y6UO003	PRS-LV-012	25.0	26.0	24.0	45	47	42	6,501	y
KRE1JC9603398FDJ78Y7PS005	PRS-LV-014	25.0	26.0	23.0	45	47	42	6,501	y
KRE1JC9603398FDJ78Y7PS003	PRS-HV-008	25.0	26.0	23.0	45	47	42	6,501	y
KRE1JC9603398FDJ78Y7PS004	PRS-LV-012	24.5	25.0	23.0	48	50	45	6,501	y
KRE1JC9603398FDJ78Y7PS001	PRS-LV-014	24.5	25.0	23.0	48	50	45	6,501	y
KRE1JC9603398FDJ78Y7PS002	PRS-HV-008	24.5	25.0	23.0	48	50	45	6,490	y

Comments: