



ISO/IEC 19752 Yield Test Report



Phaser 4400 Toner Cartridge (High Capacity)

Declaration of Yield:

Published Cartridge Yield: 15,000 standard pages
Declared yield value in accordance with ISO/IEC 19752

Average: 15,804
 Standard Deviation: 300
 90% Lower Confidence: 15,618

"Customer Report, compliant with ISO/IEC 29142"

	<u>Start</u>	<u>End</u>
Date Tested:	9-Mar-2007	9-Apr-2007
Number of Cartridges used in testing:	9	
Number of Cartridges used in calculations:	9	
Type of Cartridge:	High Capacity Cartridge	
Shake Procedure Used?	No	
Print mode:	Continuous (500pages/job)	
Number of engines used in testing:	3	
Media Used:	Xerox 4200	
Paper Weight:	20lb	
Paper Size:	A4	
Paper feed orientation:	Long Edge Feed (LEF)	
Computer Model:	Dell PC 1.2GHz	
Driver Version:	Xerox	
Operating System:	Windows XP	
Application Software:	Adobe Acrobat Professional 7.0.1	
Test Page Version:	ISO/IEC 19752:2004	
Power (off/on) everyday?	No	

Cartridge Serial Number	Printer Serial Number	Temperature (°C)			Humidity (%RH)			Cartridge Yield	Included in calc.
		Avg.	Max	Min	Avg.	Max	Min		
CT350135FA107736Z26	XWO3563	22.6	25.0	22.0	50.0	51.0	49.0	15,941	y
CT350135FA108246Z26	XWO3563	22.5	22.8	22.3	50.0	51.0	49.0	15,875	y
CT350135FA108376Z26	XWO3563	22.6	22.8	22.4	50.0	51.0	50.0	15,404	y
CT350135FA107756Z26	XW03458	22.5	22.8	22.0	50.0	50.0	50.0	15,778	y
CT350135FA108186Z26	XW03458	22.7	22.8	22.5	50.0	50.0	50.0	15,349	y
CT350135FA107886Z26	XW03458	22.6	22.8	22.4	50.0	50.0	50.0	15,637	y
CT350135FA108006Z26	XW03533	22.5	22.8	22.0	50.0	50.0	49.0	16,097	y
CT350135FA107766Z26	XW03533	22.7	22.8	22.5	50.0	51.0	49.0	15,898	y
CT350135FA108206Z26	XW03533	22.6	22.8	22.4	50.0	51.0	49.0	16,258	y

Comments: