XEROX

ISO/IEC 19752 Yield Test Report

USE GENUINE XEROX SUPPLIES MADE FOR EACH OTHER®

Phaser 4500 Toner Cartridge (Standard Capacity)

Declaration of Yield:

Published Cartridge Yield: 10,000 standard pages
Declared yield value in accordance with ISO/IEC 19752

Average:	10,313
Standard Deviation:	365
90% Lower Confidence:	10,087

	Start	**End**
Date Tested:	18-May-2007	1-Jun-2007

Number of Cartridges used in testing:	9
Number of Cartridges used in calculations:	9
Type of Cartridge:	Standard Capacity Cartridge
Shake Procedure Used?	yes
Print mode:	Continuous (500pages/job)
Number of engines used in testing:	3
Media Used:	Xerox 4200
Paper Weight:	20lb
Paper Size:	A4
Paper feed orientation:	Long Edge Feed (LEF)
Computer Model:	Dell PC 1.2GHz
Driver Version:	Xerox
Operating System:	Windows XP
Application Software:	Adobe Acrobat Professional 7.0.1
Test Page Version:	ISO/IEC 19752:2004
Power (off/on) everyday?	No

Cartridge	Printer	Temperature (°C)			Humidity (%RH)			Cartridge	Included
Serial Number	Serial Number	Avg.	Max	Min	Avg.	Max	Min	Yield	in calc.
CN-084K-10799-71R 2000000131	XWO3541	22.6	25.0	22.0	50.0	51.0	50.0	10,215	y
CN-084K-10799-71R 2000000108	XWO3541	22.5	22.8	22.3	50.0	51.0	49.0	10,640	y
CN-084K-10799-71R 2000000135	XWO3541	22.6	22.8	22.4	50.0	51.0	50.0	10,303	y
CN-084K-10799-71R 2000000119	XW03751	22.5	22.8	22.0	50.0	50.0	50.0	10,482	y
CN-084K-10799-71R 2000000146	XW03751	22.7	22.8	22.5	50.0	50.0	50.0	10,625	y
CN-084K-10799-71R 2000000147	XW03751	22.6	22.8	22.4	50.0	50.0	50.0	10,131	y
CN-084K-10799-71R 2000000137	XW03613	22.5	22.8	22.0	50.0	50.0	49.0	10,457	y
CN-084K-10799-71R 2000000138	XW03613	22.7	22.8	22.5	50.0	51.0	49.0	10,504	y
CN-084K-10799-71R 2000000139	XW03613	22.6	22.8	22.4	50.0	51.0	50.0	9,458	y

Comments: