



# ISO/IEC 19752 Yield Test Report



## Phaser 5400 Toner Cartridge

Declaration of Yield:

**Published Cartridge Yield: 20,000 standard pages**  
**Declared yield value in accordance with ISO/IEC 19752**

Average: 20,588  
 Standard Deviation: 735  
 90% Lower Confidence: 20,132

### "Customer Report, compliant with ISO/IEC 29142"

	<u>Start</u>	<u>End</u>
<b>Date Tested:</b>	9-Mar-2007	4-Apr-2007
Number of Cartridges used in testing:	9	
Number of Cartridges used in calculations:	9	
Type of Cartridge:	Print Cartridge Phaser 5400	
Shake Procedure Used?	No shake	
Print mode:	Continuous (500pages/job)	
Number of engines used in testing:	3	
Media Used:	Xerox 4200	
Paper Weight:	20lb	
Paper Size:	Letter	
Paper feed orientation:	Long Edge Feed (LEF)	
Computer Model:	Dell PC 1.2GHz	
Driver Version:	Xerox	
Operating System:	Windows XP	
Application Software:	Adobe Acrobat Professional 7.0.1	
Test Page Version:	ISO/IEC 19752:2004	
Power (off/on) everyday?	No	

Cartridge Serial Number	Printer Serial Number	Temperature (°C)			Humidity (%RH)			Cartridge Yield	Included in calc.
		Avg.	Max	Min	Avg.	Max	Min		
CT350050 SC 30250 6810	XW02700	22.6	25.0	22.0	50.0	51.0	49.0	21,547	y
CT350050 SC 30269 6Z19	XW02700	22.6	22.8	22.4	50.0	50.0	50.0	20,514	y
CT350050 SC 30273 6Z19	XW02700	22.4	22.8	22.0	50.0	51.0	49.0	19,814	y
CT350050 SC 30272 6Z19	XW01579	22.4	22.8	22.0	50.0	50.0	49.0	20,875	y
CT350050 SC 30278 6Z19	XW01579	22.6	22.8	22.4	50.0	51.0	49.0	20,894	y
CT350050 SC 30268 6Z19	XW01579	22.5	22.8	22.3	50.0	51.0	49.0	21,739	y
CT350050 SC 30291 6Z19	XW01575	22.4	22.8	22.0	50.0	50.0	49.0	19,823	y
CT350050 SC 30270 6Z19	XW01575	22.7	22.8	22.5	50.0	51.0	49.0	20,290	y
CT350050 SC 30261 6Z19	XW01575	22.5	22.8	22.3	50.0	51.0	49.0	19,796	y

Comments: