



ISO/IEC 19752 Yield Test Report



Phaser 5400 Toner Cartridge

Declaration of Yield:

Published Cartridge Yield: 20,000 standard pages
Declared yield value in accordance with ISO/IEC 19752

Average: 20,588
Standard Deviation: 735
90% Lower Confidence: 20,132

Date Tested: Start End
 9-Mar-2007 4-Apr-2007

Number of Cartridges used in testing: 9
Number of Cartridges used in calculations: 9
Type of Cartridge: Print Cartridge Phaser 5400
Shake Procedure Used? No shake
Print mode: Continuous (500pages/job)
Number of engines used in testing: 3
Media Used: Xerox 4200
Paper Weight: 20lb
Paper Size: Letter
Paper feed orientation: Long Edge Feed (LEF)
Computer Model: Dell PC 1.2GHz
Driver Version: Xerox
Operating System: Windows XP
Application Software: Adobe Acrobat Professional 7.0.1
Test Page Version: ISO/IEC 19752:2004
Power (off/on) everyday? No

Cartridge Serial Number	Printer Serial Number	Temperature (°C)			Humidity (%RH)			Cartridge Yield	Included in calc.
		Avg.	Max	Min	Avg.	Max	Min		
CT350050 SC 30250 6810	XW02700	22.6	25.0	22.0	50.0	51.0	49.0	21,547	y
CT350050 SC 30269 6Z19	XW02700	22.6	22.8	22.4	50.0	50.0	50.0	20,514	y
CT350050 SC 30273 6Z19	XW02700	22.4	22.8	22.0	50.0	51.0	49.0	19,814	y
CT350050 SC 30272 6Z19	XW01579	22.4	22.8	22.0	50.0	50.0	49.0	20,875	y
CT350050 SC 30278 6Z19	XW01579	22.6	22.8	22.4	50.0	51.0	49.0	20,894	y
CT350050 SC 30268 6Z19	XW01579	22.5	22.8	22.3	50.0	51.0	49.0	21,739	y
CT350050 SC 30291 6Z19	XW01575	22.4	22.8	22.0	50.0	50.0	49.0	19,823	y
CT350050 SC 30270 6Z19	XW01575	22.7	22.8	22.5	50.0	51.0	49.0	20,290	y
CT350050 SC 30261 6Z19	XW01575	22.5	22.8	22.3	50.0	51.0	49.0	19,796	y

Comments: