ISO/IEC 19752 Yield Test Report

USE GENUINE XEROX SUPPLIES
MADE FOR EACH OTHER®

Phaser 5500 Toner Cartridge

Declaration of Yield:

Published Cartridge Yield: 30,000 standard pages
Declared yield value in accordance with ISO/IEC 19752

Average:	32,466
Standard Deviation:	1,082
90% Lower Confidence:	31,795

	Start	**End**
Date Tested:	4-Jul-2005	13-Jul-2015

Number of Cartridges used in testing:	9
Number of Cartridges used in calculations:	9
Type of Cartridge:	Only toner
Shake Procedure Used?	No shake
Print mode:	Continuous (500pages/job)
Number of engines used in testing:	3
Media Used:	Xerox 4024DP & Xerox 4200DP
Paper Weight:	20lb
Paper Size:	Letter
Paper feed orientation:	Long Edge Feed (LEF)
Computer Model:	Toshiba DynaBook Satellite J10
Driver Version:	5500w2kpx1.0.0.4
Operating System:	Windows 2000
Application Software:	Adobe Acrobat Professional 6.0.0
Test Page Version:	Version 4.0
Power (off/on) everyday?	Yes

Cartridge	Printer	Temperature (°C)			Humidity (%RH)			Cartridge	Included
Serial Number	Serial Number	Avg.	Max	Min	Avg.	Max	Min	Yield	in calc.
562-1001000344	100116	22.0	22.2	21.7	56.6	57.3	55.8	30,757	y
562-1001000339	100116	21.9	22.2	21.6	56.4	57.8	55.0	32,631	y
562-1001000343	100116	22.1	22.2	22.0	55.8	56.8	54.3	31,716	y
562-1001000341	100126	21.9	22.2	21.7	56.6	57.3	55.8	33,343	y
562-1001000353	100126	22.0	22.2	21.6	56.2	57.5	55.0	33,963	y
562-1001000338	100126	22.1	22.2	21.9	55.8	56.8	54.3	33,037	y
562-1001000340	100136	22.0	22.2	21.7	56.6	57.3	55.8	31,888	y
562-1001000342	100136	21.9	22.2	21.6	56.3	57.8	55.0	33,473	y
562-1001000345	100136	22.1	22.2	22.0	55.7	56.8	54.3	31,382	y

Comments: