

**Xerox Phaser 8560W Solid Ink Yield**

Declaration of Yield:

<b>Published CMY Ink Stick Yield:</b>	<b>1,300 standard pages</b>
<b>Published K Ink Stick Yield:</b>	<b>1,300 standard pages</b>
Average Composite CMY Ink Yield:	1,317 standard pages
Average K Ink Yield:	1,331 standard pages
<b>Declared yield value in accordance with ISO/IEC 24711</b>	

<b>Published Ink Yield:</b>	
3 Pack Yield (CMY)	3,900 standard pages
3 Pack Yield (K)	3,900 standard pages
<b>Declared yield value in accordance with ISO/IEC 24711</b>	

90% Lower Confidence  
 Cyan: 1,331 Standard Pages  
 Magenta: 1,384 Standard Pages  
 Yellow: 1,244 Standard Pages  
 Black: 1,331 Standard Pages

**Date Tested:**                      **Start**                                      **End**  
 21-Feb-2007                                      23-Feb-2007

Number of Ink Sticks used in testing:                      C=9, M=9, Y=9, K=9  
 Number of Ink Sticks used in calculations:                      C=9, M=9, Y=9, K=9  
 Type of Ink:                                      Phaser 8560W Solid Ink  
 Print mode:                                      Continuous (500pages/job)  
 Number of engines used in testing:                      3  
 Media Used:                                      Xerox 4200  
 Paper Weight:                                      20lb  
 Paper Size:                                      Letter  
 Paper feed orientation:                      Short Edge Feed (SEF)  
 Computer Model:                                      Dell Latitude C640 4M 2.0GHz  
 Driver Version:                                      Walk Up Driver 2.0  
 Operating System:                                      Windows XP  
 Application Software:                                      Adobe Acrobat Professional 7.0.7  
 Test Page Version:                                      ISO/IEC 24712 FCD Test Suite  
 Power (off/on) everyday?                                      No

Printer #1: PP2-20

	Ink	Serial Number	Temperature (°C)			Humidity (%RH)			Ink Yield	Included in calc.
			Avg.	Max	Min	Avg.	Max	Min		
1st Set	C	na	22.0	23.0	22.0	46.0	47.0	45.0	1451	y
	M	na	22.0	23.0	22.0	46.0	47.0	45.0	1435	y
	Y	na	22.0	23.0	22.0	46.0	47.0	45.0	1300	y
	K	na	22.0	23.0	22.0	46.0	47.0	45.0	1420	y
2nd Set	C	na	22.0	22.0	22.0	46.0	48.0	46.0	1285	y
	M	na	22.0	22.0	22.0	46.0	48.0	46.0	1415	y
	Y	na	22.0	22.0	22.0	46.0	48.0	46.0	1265	y
	K	na	22.0	22.0	22.0	46.0	48.0	46.0	1372	y
3rd Set	C	na	22.0	23.0	22.0	47.0	48.0	45.0	1426	y
	M	na	22.0	23.0	22.0	47.0	48.0	45.0	1410	y
	Y	na	22.0	23.0	22.0	47.0	48.0	45.0	1200	y
	K	na	22.0	23.0	22.0	47.0	48.0	45.0	1339	y

Printer #2: PP2-14

	Ink	Serial Number	Temperature (°C)			Humidity (%RH)			Ink Yield	Included in calc.
			Avg.	Max	Min	Avg.	Max	Min		
1st Set	C	na	22.0	23.0	22.0	46.0	47.0	45.0	1392	y
	M	na	22.0	23.0	22.0	46.0	47.0	45.0	1298	y
	Y	na	22.0	23.0	22.0	46.0	47.0	45.0	1270	y
	K	na	22.0	23.0	22.0	46.0	47.0	45.0	1335	y
2nd Set	C	na	22.0	22.0	22.0	46.0	48.0	46.0	1361	y
	M	na	22.0	22.0	22.0	46.0	48.0	46.0	1463	y
	Y	na	22.0	22.0	22.0	46.0	48.0	46.0	1265	y
	K	na	22.0	22.0	22.0	46.0	48.0	46.0	1340	y
3rd Set	C	na	22.0	23.0	22.0	47.0	48.0	45.0	1360	y
	M	na	22.0	23.0	22.0	47.0	48.0	45.0	1424	y
	Y	na	22.0	23.0	22.0	47.0	48.0	45.0	1270	y
	K	na	22.0	23.0	22.0	47.0	48.0	45.0	1378	y

Printer #3: PP2-13

	Ink	Serial Number	Temperature (°C)			Humidity (%RH)			Ink Yield	Included in calc.
			Avg.	Max	Min	Avg.	Max	Min		
1st Set	C	na	22.0	23.0	22.0	46.0	47.0	45.0	1425	y
	M	na	22.0	23.0	22.0	46.0	47.0	45.0	1515	y
	Y	na	22.0	23.0	22.0	46.0	47.0	45.0	1257	y
	K	na	22.0	23.0	22.0	46.0	47.0	45.0	1453	y
2nd Set	C	na	22.0	22.0	22.0	46.0	48.0	46.0	1238	y
	M	na	22.0	22.0	22.0	46.0	48.0	46.0	1372	y
	Y	na	22.0	22.0	22.0	46.0	48.0	46.0	1253	y
	K	na	22.0	22.0	22.0	46.0	48.0	46.0	1252	y
3rd Set	C	na	22.0	23.0	22.0	47.0	48.0	45.0	1486	y
	M	na	22.0	23.0	22.0	47.0	48.0	45.0	1475	y
	Y	na	22.0	23.0	22.0	47.0	48.0	45.0	1266	y
	K	na	22.0	23.0	22.0	47.0	48.0	45.0	1430	y