



ISO/IEC 19752 Yield Test Report



DocuPrint N2125 Print Cartridge

Declaration of Yield:

Published Cartridge Yield: 10,000 standard pages
Declared yield value in accordance with ISO/IEC 19752

Average: 10,671
 Standard Deviation: 329
 90% Lower Confidence: 10,468

Date Tested: **Start** **End**
 15-Nov-2006 29-Nov-2006

"Customer Report, compliant with ISO/IEC 29142"

Number of Cartridges used in testing: 9- Part Number 113R00445
 Number of Cartridges used in calculations: 9
 Type of Cartridge: Print cartridge DP N2125
 Shake Procedure Used? No
 Print mode: Continuous (500pages/job)
 Number of engines used in testing: 3
 Media Used: Xerox 4200 20#
 Paper Weight: 20#
 Paper Size: 8.5" x 11"
 Paper feed orientation: Long Edge Feed
 Computer Model: Dell PC 1.2GHz
 Driver Version: Xerox
 Operating System: Windows XP
 Application Software: Adobe Acrobat version 7.0.1
 Test Page Version: Available at <http://www.iso.org/jtc1/sc28> 19752:2004
 Power (off/on) everyday? No

| Cartridge Serial Number | Printer Serial Number | Temperature (°C) | | | Humidity (%RH) | | | Cartridge Yield | Included in calc. |
|----------------------------|--------------------------|------------------|------|------|----------------|------|------|--------------------|----------------------|
| | | Avg. | Max | Min | Avg. | Max | Min | | |
| C9102126X26 | DPN2125_1 | 22.0 | 22.0 | 22.0 | 50.0 | 50.0 | 50.0 | 10651 | y |
| C9102006X26 | DPN2125_1 | 22.0 | 22.0 | 22.0 | 50.0 | 50.0 | 50.0 | 10820 | y |
| C9101986X26 | DPN2125_1 | 22.0 | 22.0 | 22.0 | 50.0 | 50.0 | 50.0 | 10054 | y |
| C9102016X26 | DPN2125_2 | 22.0 | 22.0 | 22.0 | 50.0 | 50.0 | 50.0 | 10832 | y |
| C9102146X26 | DPN2125_2 | 22.0 | 22.0 | 22.0 | 50.0 | 50.0 | 50.0 | 10941 | y |
| C9102066X26 | DPN2125_2 | 22.0 | 22.0 | 22.0 | 50.0 | 50.0 | 50.0 | 10165 | y |
| C9102156X26 | DPN2125_3 | 22.0 | 22.0 | 22.0 | 50.0 | 50.0 | 50.0 | 10872 | y |
| C9102036X26 | DPN2125_3 | 22.0 | 22.0 | 22.0 | 50.0 | 50.0 | 50.0 | 10837 | y |
| C9101976X26 | DPN2125_3 | 22.0 | 22.0 | 22.0 | 50.0 | 50.0 | 50.0 | 10870 | y |

Comments: