



ISO/IEC 19752 Yield Test Report



DocuPrint N4525 Print Cartridge

Declaration of Yield:

Published Cartridge Yield: 30,000 standard pages
Declared yield value in accordance with ISO/IEC 19752

Average: 31,712
 Standard Deviation: 930
 90% Lower Confidence: 31,135

Date Tested: Start 12-Jan-2007 End 2-Feb-2007

Number of Cartridges used in testing: 9- Part Number 113R00195
 Number of Cartridges used in calculations: 9
 Type of Cartridge: Print cartridge DP N4525
 Shake Procedure Used? No
 Print mode: Continuous (500pages/job)
 Number of engines used in testing: 3
 Media Used: Xerox 4200 20#
 Paper Weight: 20#
 Paper Size: 8.5" x 11"
 Paper feed orientation: Long Edge Feed
 Computer Model: Dell PC 1.2GHz
 Driver Version: Xerox
 Operating System: Windows XP
 Application Software: Adobe Acrobat version 7.0.1
 Test Page Version: Available at http://www.iso.org/jtc1/sc28_19752:2004
 Power (off/on) everyday? No

Cartridge Serial Number	Printer Serial Number	Temperature (°C)			Humidity (%RH)			Cartridge Yield	Included in calc.
		Avg.	Max	Min	Avg.	Max	Min		
DP N4525_1	XW03383	22.6	25.0	22.0	50.0	51.0	49.0	31,014	y
DP N4525_2	XW03383	22.6	22.8	22.4	50.0	50.0	50.0	31,176	y
DP N4525_3	XW03383	22.4	22.8	22.0	50.0	51.0	49.0	31,000	y
DP N4525_4	XW03384	22.4	22.8	22.0	50.0	50.0	49.0	32,696	y
DP N4525_5	XW03384	22.6	22.8	22.4	50.0	51.0	49.0	33,050	y
DP N4525_6	XW03384	22.5	22.8	22.3	50.0	51.0	49.0	33,063	y
DP N4525_7	XW03386	22.4	22.8	22.0	50.0	50.0	49.0	31,241	y
DP N4525_8	XW03386	22.7	22.8	22.5	50.0	51.0	49.0	30,915	y
DP N4525_9	XW03386	22.5	22.8	22.3	50.0	51.0	49.0	31,251	y

Comments: