

Xerox® ColorQube® 9300 Series Colour Multifunction Printer

The ColorQube 9302/9303 Colour Multifunction Printer is built on Xerox® ConnectKey® Technology. For more information, go to www.connectkey.com.



| System Specifications | ColorQube 9302 | ColorQube 9303 |
|--|---|--|
| Speed Colour | High Resolution / Photo Mode: 35 ppm Enhanced Mode (Default): 45 ppm Standard Mode: 60 ppm Fast Colour Mode: 70 ppm | High Resolution / Photo Mode: 38 ppm Enhanced Mode (Default): 55 ppm Standard Mode: 70 ppm Fast Colour Mode: 85 ppm |
| Black and white | High Resolution / Photo Mode: 36 ppm High Speed Mode: 55 ppm Standard Mode: 70 ppm Fast Colour Mode: 95 ppm | High Resolution / Photo Mode: 38 ppm High Speed Mode: 60 ppm Standard Mode: 70 ppm Fast Colour Mode: 95 ppm |
| Flexible Print Speeds Colour / Black and white | From 35-70 / 36-95 ppm | From 38-85 / 38-95 ppm |
| Monthly Duty Cycle ² | Up to 225,000 pages | Up to 300,000 pages |
| Recommended Average Monthly Print Volume ³ | 15,000 to 75,000 pages | |
| Hard Drive / Processor / Memory | Minimum 160 GB / 1.5 GHz Dual-core / 1 GB system plus 1 GB page memory | |
| Connectivity | 10/100/1000Base-T Ethernet, High-Speed USB 2.0 Direct Print, Optional Wi-Fi Adapter | |
| Controller Features | Unified Address Book, Remote Control Panel, Online Support (accessed from the user interface and print driver), Configuration Cloning | |
| Copy and Print | | |
| Copy and Print Resolution | Up to 600 x 600 dpi | |
| First-print-out Time | As fast as 7.2 seconds colour | |
| Page Description Languages | Adobe® PostScript® 3™, PDF, PCL® 5c / PCL 6, XML Paper Specification (XPS®) | |
| Print Features | Print from USB, Earth Smart Driver Settings, Job Identification, Booklet Creation, Store and Recall Driver Settings, Bidirectional Status, Scaling, Job Monitoring, Colour By Words | |
| Mobile Printing | Apple® AirPrint, Xerox® PrintBack, Xerox® Mobile Print (Optional), Xerox® Mobile Print Cloud (Optional), Mopria™ certified | |
| Scan | | |
| Standard Features | Destinations: Scan to Mailbox, Scan to USB, Scan to Email, Scan to Network; File Formats: PDF, PDF/A, XPS, JPEG, TIFF; Convenience Features: Scan to Home, Single Touch Scan, Searchable PDF, Single/Multi-Page PDF / XPS / TIFF, Encrypted / Password Protected PDF, Linearised PDF / PDF/A | |
| Optional Features | Software Packages: ConnectKey® for SharePoint®, ConnectKey® for DocuShare®, ConnectKey® Share to Cloud, Xerox® Scan to PC Desktop® SE and Professional, other solutions available through various Xerox Alliance Partners | |
| Fax | | |
| Standard Features | Internet Fax, Fax Build Job, Network Server Fax Enablement | |
| Optional Features | Fax Forward to Email or SMB, Walk-up Fax (one-line and two-line options, includes LAN Fax), | |
| Security | | |
| Standard Features | McAfee® Embedded, McAfee ePolicy (ePO) Compatible, Hard Drive Image Overwrite, 256-bit Encryption (FIPS 140-2 compliant), Common Criteria Certification (ISO 15408), Secure Print, Secure Fax, Secure Scan, Secure Email, Cisco® TrustSec Identity Services Engine (ISE) Integration, Network Authentication, SSL, SNMPv3, Audit Log, Access Controls, User Permissions | |
| Optional Features | McAfee Integrity Control, Xerox Secure Access Unified ID System®, Smart Card Enablement Kit (CAC/PIV/.NET) | |
| Accounting | | |
| Standard Features | Xerox® Standard Accounting (Copy, Print, Scan, Fax, Email), Network Accounting Enablement | |
| Optional Features | Equitrac Express®, Equitrac Office®, Equitrac Professional®, YSoft® SafeQ®, other network accounting solutions available through various Xerox Alliance Partners | |

| Device Specifications | | | | |
|---|---|-------------------|---------------------|---------------------|
| Control Panel Languages | US English, International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Turkish, Greek, Russian, Czech, Polish, Hungarian, Romanian, Catalan | | | |
| Accessories | | | | |
| Optional | High Capacity Feeder HCF Letter / A4 SEF Kit HCF Tabloid / A3 Kit Offset Catch Tray Office Finisher High Volume Finisher (HVF) High Volume Finisher with Booklet Maker Z Fold / C Fold Unit with HVF with Booklet Maker Post Process Inserter with HVF and HVF with Booklet Maker Convenience Stapler Smart Card Enablement Kit Xerox Secure Access Unified ID System® Walk up Fax (One- or Two-line options, includes LAN Fax) Xerox® USB Wireless Adapter McAfee Integrity Control Enablement Kit | | | |
| Foreign Device Interface (FDI) (Optional) | Also known as Auxiliary Access Device, this is an interface to third party access control devices, such as coin machines and card readers. | | | |
| Electrical Requirements | | | | |
| North America | Voltage : 110-127 VAC, -10% / +6% (99-135 VAC) Frequency: 60 Hz, + /-3, 15 A | | | |
| Europe | Voltage : 220-240 VAC, -10% / +6% (198-254 VAC) Frequency: 50 Hz, + /-3, 10 A | | | |
| Power Consumption | | | | |
| Printing (Max) | 120V: 1800 watts (15A) 230V: 2300 watts (10A) | | | |
| Printing (Average) | 610 watts | | | |
| Standby Mode | 338 watts | | | |
| Low Power Mode | 221 watts | | | |
| Auto Off / Sleep Mode | 91 watts | | | |
| Warm-up (Ready to Mark) | From Low Power: As fast as 47 sec. (Dependent on the number of services registered) From Sleep: As fast as 3 min 30 sec. (Dependent on the number of services registered) The Intelligent Ready power management feature learns the unique print usage patterns of an office so the device will be in ready mode when needed and automatically go into lower power modes when not needed. This feature maximises energy efficiency and results in pages being generated in as fast as 7.2 seconds | | | |
| Operating Environment | | | | |
| Required Temperature Range | 50° to 90° F (10° to 32° C) | | | |
| Required Relative Humidity | 5% to 85% | | | |
| Sound | Run Continuous | Impulse | Standby | |
| Sound Power Levels | 7.8 B(A) | 8.6 B(A) | 5.5 B(A) | |
| Sound Pressure Levels | 63 dB(A) | 71 dB(A) | 40 dB(A) | |
| Dimensions and Weight | Width | Depth | Height | Weight |
| IOT with Offset Catch Tray (OCT) | 55 in. / 1,398 mm | 28.4 in. / 722 mm | 45.5 in. / 1,156 mm | 501 lbs. / 227 kg |
| IOT with Office Finisher | 65 in. / 1,651 mm | 28.4 in. / 722 mm | 45.5 in. / 1,156 mm | 562.2 lbs. / 255 kg |
| IOT with High Volume Finisher | 81.7 in. / 2,075 mm | 28.4 in. / 722 mm | 45.5 in. / 1,156 mm | 687 lbs. / 311.5 kg |
| IOT with High Volume Finisher with Booklet Maker, Post Process Inserter and Z-Fold / C-Fold Unit | 96.2 in. / 2,443 mm | 28.4 in. / 722 mm | 45.5 in. / 1,156 mm | 813 lbs. / 368.8 kg |
| IOT with OCT and High Capacity Feeder | 63.6 in. / 1,607 mm | 28.4 in. / 722 mm | 45.5 in. / 1,156 mm | 567 lbs. / 257 kg |

| Certifications | |
|--|---|
| | FCC Class A Compliant (U.S.); DOC Class A Compliant (Canada) CB Certified (IEC 60950/EN 60950) 2004/108/EC 2006/95/EC 99/5/EC Full System Common Criteria (ISO 15408) certification ENERGY STAR® EPEAT (United States) ECOLOGO® Citrix® Certified Cerner MEDITECH To view the latest list of certifications, go to www.xerox.com/OfficeCertifications . |
| Paper Handling | |
| Duplex Automatic Document Feeder | |
| Capacity ^a | 100 sheets |
| Speed | 84 images per minute (ipm) black and white, 60 ipm colour |
| Paper Sizes Sensed | 5.5 x 8.5 in. to 11 x 17 in. SEF or 5.5 x 8.5 in. to 8.5 x 11 in. LEF (A5 / 148 x 210 mm to A3 / 297 x 420 mm SEF or A5 / 148 x 210 mm to A4 / 210 x 297 mm) LEF |
| Weights | 13 lb. bond to 43 lb. bond (50 to 160 gsm) |
| Bypass Tray | |
| Capacity ^a | 100 sheets of 20 lb. bond (75 gsm) |
| Sizes | A5 / 8.5 x 5.5 in. / #10 Envelope SEF to SRA3 / 12 x 18 in. SEF |
| Weights | 16 lb. bond to 80 lb. cover (60 to 220 gsm) |
| Types | Plain Heavy weight Extra heavy weight Labels Transparencies (paper backed not supported) Envelopes Punched paper Recycled |
| Three Front Loading Paper Trays – Paper Trays 1, 2 and 3 | |
| Capacity ^a | Trays 1-2: 550 sheets of 20 lb. bond (75 gsm) each tray Tray 3: 2,100 sheets of 20 lb. bond (75 gsm) |
| Sizes | Trays 1-2: 5.5 x 8.5 in. SEF to 11 x 17 in. SEF (A5 / 148 x 210 mm to A3 / 297 x 420 mm) Tray 3: 8.5 x 11 in. LEF (A4 / 210 x 297 mm) |
| Weights | 16 lb. bond to 57 lb. bond / 80 lb. cover (60 to 220 gsm) |
| Types | Plain Labels (Trays 1-2 only) Punched paper (Trays 1-2 only) |
| High Capacity Feeder (Optional) | |
| Capacity ^a | Up to 4,000 sheets of 20 lb. bond (75 gsm) |
| Sizes | 8.5 x 11 in. (A4 / 210 x 297 mm) LEF Optional 8.5 x 11 in. / 8.5 x 14 in. Short Edge Kit – 8.5 x 14 in. (A4 / 210 x 297 mm) SEF with 2,000 sheet capacity Optional 11 x 17 in. Short Edge Kit – 11 x 17 in. (A3 / 297 x 420 mm) SEF with 2,000 sheet capacity |
| Weights | 16 lb. bond to 57 lb. bond / 80 lb. cover (60 to 220 gsm) |
| Total Capacity | |
| Standard Capacity ^a | 3,300 sheets |
| Device Total Capacity ^a | 7,300 sheets |
| Paper Output / Finishing | |
| Offset Catch Tray (OCT) (Optional) | |
| Capacity ^a | 500 sheets of 20 lb. bond (75 gsm) |
| Office Finisher (Optional) | |
| Capacity ^a | Top Tray – 250 sheets Stacking Tray – 2,000 sheets |
| Sizes | 5.5 x 8.5 in. (A5 / 148 x 210 mm) to 11 x 17 in. (A3 / 297 x 420 mm) |
| Weights | 16 lb. to 57 lb. bond / 80 lb. cover (60 to 220 gsm) |

| | |
|---|--|
| Stapling⁴ | 50 sheets Single and dual |
| Hole Punch (Optional) North America: Europe: | 3-hole punch, 2-hole Legal punch 2-hole punch, 4-hole punch, 4-hole "Swedish" punch |
| High Volume Finisher (Optional) | |
| Capacity⁴ | Top Tray – 250 sheets Stacking Tray – 3,000 sheets |
| Sizes | 5.5 x 8.5 in. (A5 / 148 x 210 mm) to 11 x 17 in. (A3 / 297 x 420 mm) |
| Weights | 13 lb. to 57 lb. bond / 80 lb. cover (60 to 220 gsm) |
| Stapling⁴ | 100 sheets Front single (landscape), rear single (portrait), dual staples, multiple staples |
| Hole Punch (Optional) North America: Europe: | 3-hole punch, 2-hole Legal punch 2-hole punch, 4-hole punch and 4-hole "Swedish" punch |
| High Volume Finisher with Booklet Maker (Optional) | |
| Capacity⁴ | Top Tray – 250 sheets Stacking Tray – 3,000 sheets (2,000 sheets with Z-Fold / C-Fold) |
| Sizes | 5.5 x 8.5 in. (A5 / 148 x 210 mm) to 11 x 17 in. (A3 / 297 x 420 mm) |
| Weights | 16 lb. to 57 lb. bond / 80 lb. cover (60 to 220 gsm) |
| Stapling⁴ | 100 sheets Front single (landscape), rear single (portrait), dual staples, multiple staples |
| Hole Punch (Optional) North America: Europe: | 3-hole punch, 2-hole Legal punch 2-hole punch, 4-hole punch and 4-hole "Swedish" punch |
| Booklet Maker Capacity⁴ | Tray stop up: 25 booklets (1-15 sheets per booklet) Tray stop down: Unlimited |
| Sizes | Letter – 8.5 x 11 in. (A4 / 210 x 297 mm) Legal – 8.5 x 14 in. (216 x 356 mm) Ledger – 11 x 17 in. (A3 / 297 x 420 mm) |
| Weights | 16 lb. to 57 lb. bond / 80 lb. cover (60 to 220 gsm) |
| Stapling⁴ | Saddle-stitch (2-15 sheets / 8-60 page booklet) |
| Folding | V-folding (1-5 sheets / unstapled) |
| Z-Fold / C-Fold Unit with HVF with Booklet Maker (Optional) | |
| Capacity⁴ | 50 sheets or unlimited capacity with tray stop in the down position |
| Sizes | Letter – 8.5 x 11 in. (A4 / 210 x 297 mm) |
| Weights | 16 lb. to 32 lb. bond (60 to 120 gsm) |
| Post Process Inserter (Optional with HVF and HVF with Booklet Maker) | |
| Capacity⁴ | 250 sheets Tray stop down: unlimited |
| Sizes | Letter – 8.5 x 11 in. (A4 / 210 x 297 mm) Legal – 8.5 x 14 in. (216 x 356 mm) Ledger – 11 x 17 in. (A3 / 297 x 420 mm) |
| Weights | 16 lb. to 57 lb. bond / 80 lb. cover (60 to 220 gsm) |
| Convenience Stapler (Optional) | |
| Capacity⁴ | 50 sheets 5,000 staples Requires a separate outlet |
| Copy | |
| First-copy-out Time (Letter / A4-size, from Platen to Centre Tray) | As fast as 8.2 seconds colour |
| Sides (input:output) | 1-1, 1-2, 2-2, 2-1 |
| Quantity | 1 to 9,999 |
| Resolution (max.) | Up to 600 x 600 dpi |
| Reduction / Enlargement | Variable zoom from 25% to 400% in 1% increments |
| Concurrency | Programme-ahead to allow job to be initiated while initial job is processed (Copy, Print, Fax and Scan) |

| | |
|--------------------------|---|
| Copy Features | <p>Annotation and Bates™ stamping (with colour capability and font size adjustment) Authentication for Services (i.e. Colour Copy) Auto Paper Select Auto Reduction & Enlargement to fit selected paper size Auto Tray Switching Automatic 2-sided / Duplex Booklet Creation Build Job: (Enables page-level programming and also lets you proof each section or delete last section as the job is built) Collation Covers (Front only, front and back, back only, printed inside and out: Blank or Printed) Dividers (blank) Edge Erase Features Help (Intuitive text and graphic descriptions) ID Card Copy Image Quality Adjustments Image Shift (with Auto Centre option) Invert Image (negative or mirror image) Large Job Interrupt Multi-up (up to 15 columns by 15 rows) Sample Set Save Job Settings Single Colour Stapling Transparencies</p> |
| Accessibility | <p>Xerox® Copier Assistant® Software provides a PC-based alternative to the user interface touch screen. Used in conjunction with a customer-supplied PC attached via the USB port, this software supports text-to-speech, screen magnification and easy PC keyboard access to basic and advanced copy features. Section 508 compliant. For more information or to download Xerox® Copier Assistant for free, visit www.xerox.com</p> |
| Print | |
| Print Resolution | <p>Fast Colour: 225 x 450 dpi Standard: 300 x 500 dpi Enhanced / High Speed: 450 x 567 dpi High Resolution: 600 x 600 dpi</p> |
| Print Features | <p>Application Defaults Banner Sheet Enable / Disable Bidirectional Status Custom Colour Options (Colour By Words) Cover Selection Delay Print (specific time) User Permissions Image Options (Toner Saver, Resolution (Standard, Enhanced, High)) Job Identification (Print ID or Banner, Print ID in margins on first page only or all pages) Layout / Watermark (N-up (up to 16 pages per sheet), Multi-up, Booklet layout / finishing, Fit to new paper size) Overlays Paper Selection by Attribute LAN Fax (requires optional Fax Kit) Sample Set Saved Job (colour jobs can be printed as monochrome) Secure Print with Timed Deletion Special Pages (exception page programming: covers, inserts, exception pages) Store and Recall Driver Settings Sustainability Features (Xerox® Earth Smart Settings, Duplex, N-up, Turn-off Banner and Print ID, Smart Sample Set, Hold All Jobs)</p> |
| Print from USB | <p>Allows walk-up printing from Type A USB port on front panel Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TIFF, PS, XPS, PCL Colour jobs can be printed as monochrome</p> |
| Operating Systems | <p>Microsoft® Windows® XP SP3 (32- and 64-bit) Windows Server 2003 (32- and 64-bit) Windows Server 2008 and R2 (32- and 64-bit) Windows Server 2012 and R2 Windows Vista SP2 (32- and 64-bit) Windows 7 (32- and 64-bit) Windows 8 (32- and 64-bit) Windows 8.1 (32- and 64-bit) Mac OS 10.7, 10.8, 10.9 Linux® Redhat® Fedora® Core 19 x86 Ubuntu® 13.10 x64 openSUSE® 13.1 x64</p> |

| | |
|---|--|
| Network Protocols | TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6,WSD NetWare: Bindery and NDS IPX/SPX, NDPS®/NEPS (with Server Gateway) AppleTalk®: EtherTalk® Microsoft Windows Networking over IP Apple Bonjour® IPv6 Secure FTP Most protocols not in use can be disabled |
| Administrative Protocols | DHCP, BOOTP, SNMP, WINS, SLP® v2, HTTP, HTTPS, DHCP Autonet, SSL, NTP, DNS, SSDP |
| Fonts | PCL: 93 scalable fonts, line printer and bitmap font (including Cyrillic font support) PostScript 3: 173 Type 1 fonts, 2 Multiple Master fonts |
| Xerox® Mobile Express Driver® | Makes it easy for mobile users to find, use and manage Xerox® and non-Xerox devices in every new location. Plug into a new network, and Mobile Express Driver automatically discovers available printers and provides status and capability information. Save a list of “favourite” printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT. |
| Xerox® Global Print Driver® | A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management. |
| Print Solutions | |
| Xerox® Mobile Print Cloud (Optional) | Xerox® Mobile Print Cloud addresses the needs of businesses with a mobile workforce and puts you ahead of the evolving mobile print need, but without burdening staff, budget or infrastructure. Getting started takes only a few minutes via the cloud. Print from any mobile device to nearly any brand of printer. Get accurate printing with true Microsoft® Office® rendering and more. Print what you need, when, where and how you need it. |
| Xerox® Mobile Print Solution (Optional) | Xerox® Mobile Print Solution is an ideal choice for sites that have additional requirements for control and security with an onsite server. Xerox® Mobile Print Solution allows users to print from most mobile devices to nearly any brand of printer or multifunction printer without drivers or added complexity. Simply enter a release code (PIN) at the device and get accurate printing with true Microsoft Office rendering and more to use with your server for private, onsite deployment. |
| Xerox® Pull Print Driver | Makes it easy for IT managers to qualify, deploy and manage all print devices using a single driver in a Pull Print environment. Uses a single queue and single driver. The Xerox® Pull Print Driver extends convenience across a broad range of printing assets. IT administrators no longer need to manage and configure multiple drivers. Used in conjunction with Xerox Secure Access Unified ID System®, Equitrac Office®, Ysoft® SafeQ®, Pharos® and others. |
| Unified Address Book for Fax, Internet Fax, Email and Scan to... | |
| Features | Services supported: Fax, Internet Fax, Email, Scan to Maximum contacts: 5,000 Contacts: Supports 1 or more destinations Favourites for quick access of fax numbers, emails, etc. |
| Scan | |
| Concurrency | Scan while the system is printing, copying, or while it is transferring scan to network or fax jobs (priority is for return of scanned originals and printing concurrent jobs) |
| Input Speed | Scan at up to 60 ipm colour scanning, up to 84 ipm black and white – 8.5 x 11 in. / A4 LEF |
| Resolution | 72 x 72 dpi to 600 x 600 dpi Bit Depth: 1-bit (black and white), 8-bit (greyscale), 24-bit (colour) |
| Maximum Scan Area | 11 x 17 in. / A3 |
| Scan Template Management | Support 250 scan templates Create Xerox® CentreWare® IS scan templates and share via device cloning to other multifunction printers Confirmation sheet options |
| Network Protocols | sFTP, FTP, SMB, NetWare, HTTP, HTTPS |
| File Compression | Color TIFF (TIFF 6.0 or TTN2 with JPEG, LZW) Black-and-white TIFF (G3MH, G4 MMR compression - single or multiple pages) Searchable PDF and PDF/A (MRC, JPEG, G3 MH, G4 MMR, JBIG 2 Huffman, JBIG Arithmetic Compression, Deflate (for Black-and-white and within MRC)) Linearized PDF / PDF/A |
| Document Management Fields (Meta Data) | Features only available in Network Scan to File Templates: <ul style="list-style-type: none"> • 1 to 6 user programmable metadata fields per network scan to file templates and unlimited fields within the template – Metadata field consists of field name, default value and other configurations • Customised fields viewed on user interface for variable data input |
| Scan Features | Mixed Size Originals Scan Build Job Compression Quality / File Size Control Original Type (Photo and Text, Photo, Text, Map, Newspaper / Magazine) Auto Background and Shadow Suppression Size for Size (for mixed size originals) TWAIN Support / WIA Support Bound Originals Edge Erase Reduction / Enlargement Single Touch Scan buttons (up to 10) |

| | |
|---|---|
| Scan to Email (Standard) | |
| Scan Features | <ul style="list-style-type: none"> • Email signatures (6 lines each of 128 character max), email message body (user configurable), email CentreWare IS confirmation sheet options • Scan to Email S/MIME Encryption • Email signing (requires Smart Card option) • Auto send to self |
| Directory Access | Address list via LDAP (Windows Active Directory, Exchange, Notes, Domino) Downloaded address list (comma-separated file format) |
| Scan to... (Standard) | |
| Features | Scan to USB Scan to Network Folder (uses Unified Address Book entries) |
| Network Scanning – Software Solutions | |
| Xerox® Scan to PC Desktop® Professional (Optional) | <p>A desktop offering that provides advanced document imaging, archiving, editing and organisation tools:</p> <ul style="list-style-type: none"> • PaperPort Professional image viewing and file management software <ul style="list-style-type: none"> – Complete PDF functionality – Secure PDF workflow of all scanning applications • OmniPage Pro Office (for desktop / client installation) – Professional OCR software for digital archiving and document conversion • Image Retriever – provides fully automated retrieval of scanned images direct from a scan enabled Xerox® ColorQube to individual desktops. Also includes email inbox polling capability |
| Xerox® ConnectKey® for SharePoint® (Optional) | Xerox® ConnectKey for SharePoint simplifies and streamlines the way you scan, capture and store your paper-based documents. Using your Xerox® multifunction printer, you can route documents directly into the precise document repository folder, just like you would from your PC. At the multifunction printer, you can browse to the folder, name the document, and add any key indexing information before you scan. With the flexibility to capture and route to SharePoint as well as Windows folders, ConnectKey is the right solution for any office that needs to archive and share paper-based documents. |
| Xerox® ConnectKey® Share to Cloud (Optional) | ConnectKey Share to Cloud provides organisations with powerful, easy and secure document scanning capabilities that connect your Xerox® multifunction printer to popular cloud services and email, such as Google Docs™, Salesforce.com, Office 365 and Dropbox™ and gives employees anytime, anywhere access to their most important documents using mobile devices. |
| Xerox® ConnectKey® for DocuShare® (Optional) | Xerox® ConnectKey for DocuShare, a one-step scan-to-workflow solution, simplifies the process of incorporating hard copy content into enterprise document flows. Users can easily scan documents directly into a DocuShare collection or Windows folder via a multifunction printer. |
| Security | |
| Features | <ul style="list-style-type: none"> • Expanded Authentication <ul style="list-style-type: none"> – Network authentication to access device and / or device services via- Kerberos (UNIX / Windows Server 2003 / Windows Server 2008), SMB (Windows Server 2003 / Windows Server 2008), NDS, LDAP – Xerox Secure Access Unified ID System® – Local Authentication (internal database) – Smart Card authentication -144k CAC / PIV Card Support (2048 bit certificate key) / .NET • Secure Data <ul style="list-style-type: none"> – Digitally signed PDF (when using Smart Card authentication) – Encrypted Scan to Email – Encrypted Password Protected PDF (Email and Network Scan Templates only) – Secure Print (up to 10 digit PIN or Network Authentication) – Immediate Image Overwrite – On Demand Image Overwrite (Scheduled, Manual), includes sanitation of unused area of disk – FIPS 140-2 256 bit Hard Disk Encryption • Expanded Authorisation <ul style="list-style-type: none"> – SA access based on network credentials – Authorisation per user per service – User Permissions required to access Print and Print Features (e.g. colour access, or time restrictions) reflects in the print driver • Secure Network Access • IP Filter, IPsec, IPv6, SSL v3.0, SNMPv3, HTTPs, 802.1X, Cisco® TrustSec integration, Device Security <ul style="list-style-type: none"> – McAfee® Embedded Security, Port disablement including USB ports, Audit Log, Hide Print Job Names, McAfee Integrity Control (optional) • Common Criteria Certification ISO 15408 |
| Xerox Secure Access Unified ID System® (Optional) | <p>Xerox Secure Access Unified ID System integrates your Xerox® multifunction systems with your existing employee / student ID PIN or badge providing a flexible and convenient authentication system. Allow your staff, employees or students to send documents to a centralised print server. Then, at any multifunction printer on the network, they'll simply log in with a swipe of their magnetic or proximity ID card or their PIN to securely print their job.</p> <p>For more information, go to www.office.xerox.com/software-solutions</p> |
| Fax | |
| Network Server Fax Features | |
| Compatibility | ITU (CCITT) group 3 Various Xerox Alliance Partner Solutions |
| Maximum Scan Area | 11 x 17 in. / A3 |
| Fax Send Features | One- or Two-sided Scanning (up to 11 x 17 in. / A3) Add to Send List (50 numbers maximum) Build Job, Favourites, Delay Send (specific time) Original Type (photo, text or photo and text) |
| Fax Print Features | One- or Two-sided Printing, Staple, Secure Print |

| | |
|---|--|
| Transmission Resolution | Superfine: 400 x 200 dpi (Scan at 600 x 600 dpi) Fine: 200 x 200 dpi Standard: 200 x 100 dpi |
| Internet Fax Features | |
| Capability | Direct print-ready document transmission to remote Internet Fax machines or email clients (SMTP) Reception and automatic printout of documents sent via email from remote Internet Fax machines or email clients |
| Directory Access | Utilises the Unified Address Book |
| Send / Receive | Multi-page TIFF, Image only PDF |
| Resolution | 72 x 72 dpi to 600 x 600 dpi Bit Depth: 1-bit (black and white) |
| Network Protocols | SMTP (send), POP3 (receive) |
| Compliance | ITU-T T.37 compliant |
| Walk-up Fax Features (Optional (Customer-installable) – 1 and 2 lines) | |
| Compatibility | ITU (CCITT) Group 3 |
| Speed / Modems | One or Two V.34 modems: 33,600 bps. Less than 4 seconds per page transmission time ATA analog terminal adapter utilising T38 (optional) |
| Compression / Speed | MH/G3, MMR/SG3 |
| Resolution | Walkup Send: Standard: 200 x 100 dpi Fine: 200 x 200 dpi Superfine: 600 x 600 dpi Receive: Accepts all sizes |
| Fax Send Features | LAN Fax (fax from print driver) Auto Fax Transmission Reduction Page-by-page Job Status at the Machine Delay Start, Build Job, Favourites Automatic Memory Resend Automatic Cover Sheets PSTN Fax Batch Send (up to memory capacity) |
| Fax Receive Features | One- or Two-sided Printing Stapled or Unstapled Receive Print Mode – Manual (size, margin, stock, header) / Auto Output Tray Selection Up to 200 Password Protected Mailboxes Secure Receive Receive Timestamp Auto Answer Delay |
| Fax Forward | Forward to Email or SMB Location Fax Forward on Receive Only |
| Fax Reports | Activity, Dial Directory, Group Directory, Transmission Confirmation, Pending Fax, Options Report, On Demand Overwrite Report, Mailbox Report, Broadcast Report |
| Directory Access | Utilises the Unified Address Book Group fax available |
| Auto Redial | Up to 14 attempts (per country requirements) • 1 to 25 minute intervals |
| Auto Resend | Up to 5 attempts |
| Device Management | |
| Management Support | SNMP Version 1, SNMP Version 2c and SNMP Version 3 trap over TCP/IP and IP MIB access (IETF-MIBII RFC 1213), Host Resources MIB RFC 2790, Printer MIB RFC 1759 v.2 |
| Xerox® CentreWare® Web | A Web-based server application for network administrators that permits Web browser-based device management from any workstation, whether running Windows, UNIX or any other operating system: <ul style="list-style-type: none"> • Works with any SNMP-managed printer from any manufacturer. • Provides help with device discovery and installation, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management. • Requires Windows XP, Vista or Windows 7 and Internet Explorer 6.0 and higher. • CentreWare Integration available for Tivoli® NetView®, Unicentre TNG®, Microsoft Management Console (MMC), HP® OpenView® |
| Novell NDPS/NEPS | Server gateway application: centralised management tool. |

| | |
|---|--|
| Xerox® Device Manager | Xerox® Device Manager collects and manages the data that drives fact-based decisions for your enterprise device management environment. It is a single tool to install print queues and configure, manage, monitor and report on both networked and locally connected devices – regardless of vendor – across your enterprise. Xerox® Device Manager provides: <ul style="list-style-type: none"> • Device monitoring and troubleshooting • Extensive reporting and discovery of new devices • Usage collection, chargeback and billing capabilities |
| Xerox® Device Types for SAP Environment | Xerox, together with SAP through our Gold-level membership in the SAP Printer Vendor Programme, provides seamless connectivity between SAP systems and your Xerox® printers and multifunction printers. And as an SAP customer you benefit from having SAP-certified Xerox® device types available right from SAP's online delivery model. SAP-certified device types for Xerox® printers and multifunction printers are available to download. www.office.xerox.com/software-solutions |
| Xerox® Device Types for SAP R/3 Intelligent Barcode Utility (optional) | Provides built-in process intelligence that allows the printing of barcodes on any appropriately configured PostScript printer in specific versions of SAP environment and within Latin-1 (ISO8859-1) SAP system code pages only. Used in conjunction with Xerox® PostScript Device Types for SAP environment and Xerox® Font Centre Barcode Fonts. Information available at www.office.xerox.com/software-solutions |
| Xerox® Barcode Pro PS (optional) | Enables intelligent PostScript printing on Xerox® multifunction systems by storing Xerox® software, as well as, the barcode fonts on the printer hard disk. Enables the printing of barcodes from any application (SAP client or mainframe) that supports PostScript printing. Information available at www.office.xerox.com/software-solutions |
| CentreWare Internet Services – Integrated Web Pages Provided by the Device | |
| Device Status | Web server embedded in Network Controller: <ul style="list-style-type: none"> • Tray status/contents • Consumables status • Alerts Remote Control Panel |
| Job Submission | Print ready files: PS, PCL, TIFF, PDF, JPG, XPS, TXT, RRN Output feature selection (2-sided, output colour, collate, orientation, staple, hole punch, folding, output destination) Delivery options (Immediate, sample set, delay and secure, Save job or reprint) |
| Device Administration | Allows simple, remote installation setting of configuration options and management of the device |
| Browsers | Internet Explorer 7.x, 8.x, 9.x Safari 5.x Mozilla Firefox 4.x, 5.x, 6.x, 7.x, 8.x, 9.x, 10.x, 11.x Opera 11.x Chrome 12 |
| Support | Install print / scan drivers and online support available via web page |
| Languages Supported | International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish or Russian, Simplified Chinese, Korean, Japanese |
| Remote Print Services | |
| Automatic Meter Reading (AMR) | Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time. |
| Automatic Supplies Replacement (ASR) | Automatically orders supplies for Xerox® output devices based on actual usage, eliminating the need to manually manage supplies inventory (may not be available in all countries). |
| Accounting | |
| Xerox® Standard Accounting (Standard) | |
| Tracking | Copy, Print, Fax, Scan and Email usage |
| Accounting | Up to 2,497 User accounts (User ID) Up to 500 General accounts (Client) Up to 498 Group accounts (Department) |
| Features | <ul style="list-style-type: none"> • Administrator can manage the feature via the Web User Interface or device control panel in tools • Administrator has the ability to import or export user accounts, Group Accounts, General Accounts and User limits via an industry standard CSV file |
| Accounting Options – Network Accounting – Third Party Enablement | |
| | <ul style="list-style-type: none"> • Enhanced network accounting with up to the minute data on how the system is being used • Comprehensive management and enterprise scale tracking and reporting of device usage of copy, print, scan and server fax • Numerous solutions are available through Xerox Alliance Partners. For details visit www.xerox.com • Security enhancements with the addition of HTTPS protocol support • Device requests account authentication from third party server enabling larger databases of users and accounts • Accept Authentication Login at control panel and pass to third party Networking Account • Interface with third party accounting terminal for accounting user interface |

Xerox® ColorQube® 9302/9303

| Supplies | | |
|--|-------------------------|------------------------|
| Cartridge-free Solid Ink Sticks⁵ | 4 sticks Black (Sold) | 108R00840 |
| | 4 sticks Cyan (Sold) | 108R00837 |
| | 4 sticks Magenta (Sold) | 108R00838 |
| | 4 sticks Yellow (Sold) | 108R00839 |
| Staple Cartridge Staple Refills | Office Finisher | 008R12964 008R12941 |
| 50 sheet Cartridge Staple Refills | High Volume Finisher | 008R12919 008R12920 |
| 100 sheet Cartridge Staple Refills | High Volume Finisher | 008R12912 008R12898 |
| Staple Refills | Booklet Maker (for HVF) | 008R12897 |
| Staple Refills | Convenience Stapler | 008R12941 |
| Xerox® Smart Kit® | | |
| Cleaning Unit | | 108R00989 |

¹ Standard and Fast Colour speeds are available for printing in PostScript only. Copy settings are limited to High Resolution / Photo and Enhanced Mode speeds.

² Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

³ Expected regular monthly throughput.

⁴ Paper capacities are based on 20 lb. / 75 gsm stock; capacities will vary with different weight stocks.

⁵ Average standard pages. Declared Yield in accordance with ISO/IEC 24711. Yield will vary based on image, area coverage and print mode.

Return spent imaging supplies through the Xerox Green World Alliance collection/reuse/recycling programme.
For more information, visit www.xerox.com/about-xerox/recycling.

For more information, visit us at www.xerox.com/office.

